THE WELCH LABS

Illustrated GUIDE TO AI



A deep dive into modern AI

VOLUME I

Copyright © Welch Labs LLC 2025
Revision: V12

QUESTIONS, COMMENTS, OR FEEDBACK?

If you have any issues, concerns, or questions about this book, please reach out to Welch Labs at:

`www.welchlabs.com/contact`

We appreciate your feedback!

Welch Labs

Written by: *Stephen Welch*

Illustrations: *Sam Baskin, Pranav Gundu, Stephen Welch*

Special thanks to: *Alison Young, Charles Young, Joan Young, Varun Reddy, Grant Sanderson, Jonathan Ho, Preetum Nakkiran, Chenyang Yuan, Emily Zhang, Juan Benet, Ross Hanson, Yan Babitski, AJ Englehardt, Alvin Khaled, Eduardo Barraza, Hitoshi Yamauchi, Jaewon Jung, Mrgoodlight, Shinichi Hayashi, Sid Sarasvati, Dominic Beaumont, Shannon Prater, Ubiquity Ventures, Matias Forti, Brian Henry, Tim Palade, Petar Vecutin, Nicolas baumann, Jason Singh, Robert Riley, vornska, Barry Silverman, Jake Ehrlich, Mitch Jacobs, Lauren Steely, Jeff Eastman, Rodolfo Ibarra, Clark Barrus, Rob Napier, Andrew White, Richard B Johnston, abhiteja mandava, Burt Humburg, Kevin Mitchell, Daniel Sanchez, Ferdie Wang, Tripp Hill, Richard Harbaugh Jr, Prasad Raje, Kalle Aaltonen, Midori Switch Hound, Zach Wilson, Chris Seltzer, Ven Popov, Hunter Nelson, Amit Bueno, Scott Olsen, Johan Rimez, Shehryar Saroya, Tyler Christensen, Beckett Madden-Woods, Darrell Thomas, Javier Soto, U007D, Caleb Begly, Rick Rubenstein, Brent Hunsaker, Dan Patterson, Tchsurvives, Alex Adai, Walter Reade, Zyansheep, Walter Reade, Duncan Stannett, Reginald Carey, Jean-Manuel Izaret, dh71633, Adrian Rodriguez, Dimitar Stojanovski, Michael Harder, Peter Maldonado, Emily Pesce, David Johnston, Insang Song, FaeTheWolf, Stephen Taylor, KittenKaboodle, EMatter, Patrick McCormack, John Beahan, Cameron, Cole Jones, Garrett Thornburg, Jeroen W, Rohit Sharma, GlennB, Emmanuel Cortes, Katie Quinn, Karina C, Cakra WW, Mike Ton, Eric Gometz, MacCallister Higgins, Niko Drossos, David Eraso, Tom Zehle, Steve, Brian Lineburg, rjbl, Michael Loh, Perry Vais, Bengal0, Farhad Manjoo, Sara Chipps, Ellis Driscoll, William Taysom, Will Harmon, CK, Abdullah, Peter Cho, Leo Nikora, Griffin Smith, Ash Katnoria, Alex, Markus Hays Nielsen*

Welch Labs

"Study hard what interests you the most in the most undisciplined, irreverent and original manner possible."

Richard Feynman

"With four parameters I can fit an elephant, and with five I can make him wiggle his trunk."

John Von Neumann

"The purpose of computing is insight, not numbers"

Richard Hamming

"At the moment, none whatsoever. Someday we may find it useful to send into space to take impressions for us."

Frank Rosenblatt, creator of the perceptron—the precursor to neural networks—when asked what use his algorithm might have

"It reminded me just how much of reality slips through the net of our words, and that time working directly with the flesh of the world is the best antidote for abstraction."

Michael Pollan in "A Place Of My Own"

"Programming is just gluing things together that nobody understands."

George Hotz (youtube.com/watch?v=7Hlb8YX2-W8 8:30:45)

PREFACE

It's a wild time to study artificial intelligence. Ever since deep learning started really picking up steam around 2014, every year I've thought to myself "ok, progress will certainly stall soon, there's no way this just keeps working, the bubble is about to burst." And year after year, I've been proven wrong. The story of deep learning and AI continues to unfold.

AI has certainly become overhyped, an annoying buzzword, and has run into well-deserved backlash. But behind the hype and companies and products, there is deep, beautiful, and compelling science and engineering happening. That is what this book is about.

In the summer of 2014, I needed to learn neural networks for a startup I was working on. It took some time, but I eventually found a nice Stanford course, got my head around the math, and wrote my own little Python library. When I finally made it "to the bottom", I was floored. There was no witchcraft, just some matrix math coming together in surprisingly effective fashion. It was incredibly empowering. That fall I made my first YouTube series walking through what I had learned.

My hope for this book is that it can help readers "find the bottom" of the core algorithms, ideas, and math that make this generation of AI work. This is an ambitious goal. The field is advancing at a blistering pace, but has also become murky—frontier labs don't publish much anymore. The saving grace here, I believe, is that the core ideas that make even the largest, most advanced models work are not that complicated, and have been around for a while.

This book begins by exploring these core ideas and their histories—artificial neurons, gradient descent, backpropagation, multilayer models. From there we build into modern topics including scaling laws, mechanistic interpretability, attention, and diffusion models.

There's an embarrassingly large amount of AI material we don't cover in this book. I'm a big believer in depth over breadth—I've found over the years that knowing a few important things really well gets me further than knowing a little about a lot. This bias is reflected in this book.[1]

I feel incredibly lucky to have had enough time and resources to get really deep into the beautiful and fascinating topics we cover in this book—I hope that this comes through in the writing and many, many figures. Happy reading.

Stephen Welch
Winston-Salem, North Carolina
November 2025

1 And hey, there's always volume 2, right?

ABOUT THIS BOOK

VIDEOS

Each chapter of this book goes along with a Welch Labs video, and follows the same path through the material. You'll find each video linked at the beginning of each chapter. There are many different ways to use the books and videos together; your approach will likely depend on your goals and learning style. The book can stand completely alone, or complement the videos nicely.

CODE

You'll find supporting code for each chapter at `github.com/stephencwelch/ai_book`. The most relevant supporting code is also included in the book itself at the end of each chapter—depending on your background and learning style, it can be really nice to "just see the code."

EXERCISES AND SOLUTIONS

Each chapter includes exercises—we've put a bunch of thought into these, especially in the earlier chapters when it's possible to walk through all the details "by hand." Solutions are in the back of the book. Note that exercise difficulty does vary.

WRITING IN THIS BOOK

Do it! I write in all my books in annoying colored Flair pens—but I know this drives some people crazy! History is full of mathematicians and scientists writing in their books, these notes have made for some amazing stories.[1] This book is designed with wide margins for you to write in it, if you want to! That said, I understand this isn't for everyone—we have a printable pdf of just the exercise pages at `welchlabs.com/ai_book` if you would like to keep your book pristine.

1 Fermat's last theorem margin note!

CONTENTS

1. THE PERCEPTRON **13**
Build Your Own Perceptron *40*
Supporting Code *42*
Exercises *52*

ChatGPT is made from 100 million of these

2. GRADIENT DESCENT **67**
Supporting Code *84*
Exercises *99*

The misconception that almost stopped AI

3. BACKPROPAGATION **107**
Supporting Code *131*
Exercises *137*

The F=ma of artificial intelligence

4. DEEP LEARNING **147**
Supporting Code *172*
Exercises *177*

The geometry of depth

5. ALEXNET **182**
Supporting Code *208*
Exercises *213*

The moment we stopped understanding AI

6. NEURAL SCALING LAWS **217**
Exercises *239*

AI can't cross this line and we don't know why

7. MECHANISTIC INTERPRETABILITY **245**
Exercises *265*

The dark matter of AI

8. ATTENTION **269**
Supporting Code *288*
Exercises *290*

How DeepSeek rewrote the transformer

9. VIDEO AND IMAGE GENERATION **295**
Supporting Code *334*
Exercises *345*

AI videos are brownian motion backwards

References *353*
Index *359*
Solutions to Exercises *362*

Figure 1.1 | A Perceptron. Many early AI systems were built using physical circuits like this. Each switch is connected to an indicator LED and knob. The switches can be used to create various patterns. The perceptron adds together the values of all the "switched on" dials and subtracts the values of the "switched off" dials. Here, two of the "switched on" knobs in the T shape are set to ~10, resulting in an output value of 10+10=20. See the end of this chapter for more information on this machine and a guide to building your own.

1. THE PERCEPTRON

ChatGPT is made from 100 million of these

This is a perceptron (Figure 1.1). The machine shocked the world in the 1950s by learning to recognize patterns completely automatically, and incredibly, the algorithm it implements has become the core building block of modern AI systems like ChatGPT. But why is this the atomic unit of the intelligent systems we have today, and why has it taken us 70 years to arrive here?

The perceptron works by processing patterns we input using the switches on the far left of the machine. Switches in the up position output a positive voltage, and switches in the down position output a negative voltage. Each switch connects to an indicator LED and one of the machine's center knobs. Rotating a knob multiplies the switch's output by the number shown on the knob. The meter shows the result of adding the signals from all the knobs together—two of the "switched on" knobs on the machine pictured in Figure 1.1 are set to 10, and the rest are set to zero, resulting in an output meter value of 10+10=20.

Now, is there a way to configure our dials such that the perceptron always outputs a positive signal for T shapes while outputting a negative value for other types of shapes, like the J shapes shown in Figure 1.3? Note that our shapes won't be in the same position each time.

Remarkably, it turns out that if a configuration of dials that solves our problem exists, there is a simple procedure we can follow that is guaranteed to find it—every time. See Figures 1.4 and 1.5 on the following pages.



Figure 1.3 | Can the Perceptron Read? Can the perceptron machine in Figure 1.1 learn to tell apart these T and J patterns? More specifically, is there a configuration of dials that results in the machine outputting a positive signal when shown a T shape and a negative signal when shown a J shape?



NEW NAVY DEVICE LEARNS BY DOING

Psychologist Shows Embryo of Computer Designed to Read and Grow Wiser

WASHINGTON, July. 7 (UPI) —The Navy revealed the embryo of an electronic computer today that it expects will be able to walk, talk, see, write, reproduce itself and be conscious of its existence.

The embryo—the Weather Bureau's $2,000,000 "704" computer—learned to differentiate between right and left after fifty attempts in the Navy's demonstration for newsmen.

The service said it would use this principle to build the first of its Perceptron thinking machines that will be able to read and write. It is expected to be finished in about a year at a cost of $100,000.

Dr. Frank Rosenblatt, designer of the Perceptron, conducted the demonstration. He said the machine would be the first device to think as the human brain. As do human beings, Perceptron will make mistakes at first, but will grow wiser as it gains experience, he said.

Dr. Rosenblatt, a research psychologist at the Cornell Aeronautical Laboratory, Buffalo, said Perceptrons might be fired to the planets as mechanical space explorers.

Figure 1.2 | The New York Times, July 7, 1958. The perceptron shocked the world in the 1950s by learning to recognize patterns completely automatically. The claims made by Rosenblatt and the press were grandiose but are slowly coming true. The perceptron was first implemented by Rosenblatt on an IBM 704 computer and then built as a special-purpose machine, similar to the machine shown in Figure 1. Used with permission.

Chapter 1 Video

Figure 1.4 | Training the Perceptron

The perceptron learning rule is simple and powerful. If our target output is positive, but our machine's output is negative (Case 1), we turn up all the dials that are switched on, and turn down the dials that are switched off (switched on dials in this case follow the T shape below). We turn each knob by a predetermined fixed amount called the learning rate. If our target output is negative, but our actual output is positive (Case 2), we turn down all our knobs that are switched on, and turn up all our knobs that are switched off by our learning rate. If the Perceptron gets the answer right (Cases 3 and 4), we do not adjust our knobs. Note that we're leaving out the bottom 17th dial; this is known as "bias", we'll cover bias later in the Chapter.



---

1. Setup

All dials are initially set to zero, and initial output is zero. We'll train our machine on these examples and target outputs:





2. Training Example 1

Let's switch on the first T-shape pattern. Our machine output is still zero, because our zero dial values are multiplying all of our input voltages by zero.





3. Training Step 1

Our output in step 2 is zero but we want it to be positive, which falls under Case 1 above, so we turn up all dials that are switched on and turn down all dials that are switched off. This makes our output positive.









4. Training Example 2

Let's move to our next training example, this J shape. Our perceptron outputs a positive voltage, but we want it to be negative for J shapes!





5. Training Step 2

Since our target output is negative, but our machine's output in step 4 is positive (Case 2), we turn down all our knobs that are switched on and turn up all our knobs that are switched off.





6. Example 3

Moving to our next J shape, our perceptron outputs a positive value, but again we want it to be negative.





7. Training Step 3

Since our target output is negative, but our machine's output in step 6 is positive (Case 2 again), we turn down all our knobs that are switched on and turn up all our knobs that are switched off.





8. Training Example 4

Our final example is this T shape, which our machine correctly outputs a positive value for. No adjustments needed. See the next page for testing our learned configuration of knobs on all four patterns.

See Supporting Code 1.1 and 1.2 at the end of this chapter for a full walkthrough of this process in Python.



Figure 1.5 | Testing Our Trained Perceptron. We can now test the perceptron we trained in Figure 1.4 on our four T and J shapes. Switching through our patterns, we see that by following the Perceptron Learning Rule, we were able to find a configuration of dials that results in positive outputs for our T shapes and negative outputs for our J shapes!





Figure 1.6 | The Mark I Perceptron. Frank Rosenblatt's perceptron machine included a video camera for input connected to a 20 by 20 grid of photoresistors and multiple output neurons and used motors to turn the machine's potentiometers, making learning automatic. The Mark 1 Perceptron was technically a two-layer neural network, but the weights in the first layer were fixed and connected randomly to mimic the connection between the photoreceptor cells in the human eye and the visual cortex. Images used with permission.

This procedure was discovered in 1957 by the psychologist Frank Rosenblatt and is known as the Perceptron Learning Rule. Rosenblatt unveiled the approach to the public in a press conference on July 7, 1958. The next day the New York Times reported that the machine was expected to be able to walk, talk, see, write, reproduce itself, and be conscious of its own existence. [New Navy device learns by doing, 1958]

Rosenblatt's perceptron was in some ways more sophisticated than our machine—its input grid was 20 by 20 instead of 4 by 4, it had multiple artificial neurons instead of just one, and it used motors to turn the dials, so learning was automatic—but the learning algorithm and operating principles are the same. [Hay et al. 1960] Rosenblatt's claims were grandiose but are slowly becoming true, and before his untimely death in 1971, Rosenblatt was even working on multilayer architectures that closely resemble modern neural networks. [Olazaran 1993]

But there was a problem with Rosenblatt's design, and in fact all neural networks from this era, that nearly completely halted our modern neural-network-driven approach to AI.

We've seen that our perceptron machine can quickly learn to tell apart certain patterns—but what exactly can the perceptron do and not do?

In 1962 Albert Novikoff proved mathematically that if a configuration of dials exists that cleanly separates a given set of examples, the perceptron learning rule is guaranteed to find it. [Novikoff 1962] But do cleanly separating configurations of dials exist for *all types* of input patterns?



Figure 1.7 | We, of course, don't know exactly what Rosenblatt meant, but I think it's fair to say that modern neural networks can walk, talk, see, and write very much like humans. "Reproduce itself" is a bit subjective—modern models can certainly make copies of their own weights.

Task 1* | Figure 1.10

Perceptron output should be positive when one or both switches are on.



Step	*Input*	*Target*	*Initial Dials*	*Initial Output*	*Correct?*	*Update*
1	●○				✗	
2	●○				✗	
3	●●				✓	
4	○○				✗	
5	●●				✓	
6	●○				✓	
7	●●				✓	
8	○○				✓	

* See Supporting Code 1.3 and 1.4 at the end of this chapter for a walkthrough of these processes in Python.



Figure 1.8 | Baby Perceptron so cute :). This two-input perceptron machine is going to help us figure out exactly what the perceptron learning rule can and cannot do.

Task 2

Perceptron output should be positive when either switch is on, and negative when both switches are on or off.



Step	*Input*	*Target*	*Initial Dials*	*Initial Output*	*Correct?*	*Update*
1					✗	
2					✗	
3					✗	
4					✗	
5					✗	
6					✗	
7					✗	
8					✗	

To get to the bottom of this, let's build an even simpler version of the perceptron, with just two inputs, as shown in Figure 1.8. We now have only four possible input patterns—both switches off, one or the other on, or both switches on. Note that although we only have two inputs, we have three dials—the extra dial is called "bias" and is not connected to any of our switches but is effectively always switched on. The bias dial allows us to directly add or subtract from the final value that goes to our meter regardless of the current switch configuration, giving us an extra parameter that doesn't depend on our input and helps our perceptron learn. This is also why our full machine in Figure 1.1 has 17 dials instead of 16.

Figure 1.9 | All input possibilities. Our baby two-input perceptron only has 4 possible input paaterns—here they are!

Now, let's say that we want our perceptron to output a positive value when either one or both of our switches are on and a negative value when both switches are off, as shown in Task 1 above. Following our perceptron learning rule, our machine is able to successfully learn these patterns after just four steps.

But what about other output assignments for our four examples? What if we want our output to be positive when one or the other input switch is on and negative when both switches are on or off, as shown in the Task 2 targets? Following our same perceptron learning rule, we now get stuck in a loop, where the machine never settles down on a viable solution. *Why is the perceptron able to learn the first grouping of patterns but not the second?*





Figure 1.11 | Let's Get Mathematical. A nice way to see why the baby perceptron can learn Task 1 but not Task 2 in Figure 1.10 starts by visualizing the inputs to our machine on a 2D grid like this, where the first switch on our machine corresponds to the x-axis, and the second switch corresponds to the y-axis. "On" switches correspond to values of +1, and "off" switches correspond to values of -1.

We can make sense of what's going on visually by plotting each input configuration on a 2D grid, where the x-axis represents our first input value, and our y-axis represents our second input value. A switch in the on position creates an input of +1 volt[1], so the configuration with both switches on is represented as a point at (1, 1) on our grid, as shown in Figure 1.11. An off switch represents an input of minus one volt, so the configuration with both switches off would show up at (-1, -1) on our grid, and configurations with one switch on show up at (1, -1), and (-1, 1).

Now, how does the mathematics of our perceptron show up on our 2D grid? As shown in Figure 1.12, each dial on our machine is effectively multiplying each input value by a configurable weight, so our machine's output is equal to the weight value of our first dial times x plus the weight value of our second dial times y, plus the output of our bias dial—which doesn't depend on x or y—we'll call this value b.

When our output value is greater than zero, our perceptron will classify our input (x, y) as positive. Now, for what regions on our grid will the output of our perceptron be greater than zero? Setting our output greater than zero in our equation and solving for y, we get an equation for a straight line with a slope of $-w_1/w_2$ and a y-intercept of $-b/w_2$. So our perceptron will classify all points on our grid above this line as positive.

We can see this behavior in action on the two tasks we considered earlier in Figure 1.10—see Figure 1.14 on the following page.

1 Our machine uses AA batteries, which have voltages closer to 1.5V, but the math works out the same.

Figure 1.13 | Tuning Our Decision Boundary. Using our equations from Figure 1.12, we can see how turning our knobs changes our decision boundary. Figure 1.14 on the following pages shows how our decision boundary moves when our knobs are guided by the Perceptron Learning Rule.





$$output = w_1x+w_2y+b$$

$$0 < w_1x+w_2y+b$$

Set output>0 to capture when perceptron's output is positive.

$$w_2y = -w_1x-b$$

Solve for y

$$y > -\frac{w_1}{w_2}x-\frac{b}{w_2}$$

It's a line! Slope = $-w_1/w_2$, y-intercept = $-b/w_2$



Figure 1.12 | Perceptrons Think in Lines! What regions of the xy-plane in Figure 1.11 result in positive output values from our perceptron machine? Turning our machine into an equation, we can set its output > 0 and solve for y. The result is a nice linear inequality, meaning our perceptron is learning a linear decision boundary on our xy-plane!



Figure 1.14 | A Closer Look at Tasks 1 & 2 From Earlier. Now that we've seen that our perceptron machine "thinks in lines," we can make sense of what went wrong with Task 2 in Figure 1.10. As our perceptron learns Task 1, our line moves and quickly lands in a configuration where all of our positive examples are on the positive side of our decision boundary. In Task 2, however, our decision boundary jumps around without being able to settle in a location that cleanly separates out examples. This is because there's actually no way to use a single line to separate this pattern—we'll always miss at least one example!

Task 2

Perceptron output should be positive when either switch is on, and negative when both switches are on or off.



Step	*Input*	*Target*	*Initial Dials*	*Initial Output*	*Correct?*	*Update*	*Decision Boundary*
1					✗		
2					✗		
3					✗		
4					✗		
5					✗		
6					✗		
7					✗		
8					✗		



Figure 1.16 | Sort of, but no, not really. Like many AI researchers before and after him, Rosenblatt overestimated what an AI algorithm was capable of, claiming the Perceptron could tell apart cats and dogs. Here we have a large dataset of cat and dog faces (kaggle.com/datasets/andrewmvd/animal-faces) and apply the same perceptron learning algorithm we used with our physical machine. Our images are 64 × 64 pixels, meaning we have 64 × 64+1=4097 learnable weights, and the physical machine we would need to solve this problem would require 4097 knobs. We can visualize our weight knobs as images themselves; here we're showing knobs that are turned to high positive values in yellow and knobs that are turned down in purple. Unlike our physical machine, where the inputs are boolean, here our inputs are pixels that can take on any value between 0 and 255. The perceptron learning rule still works, but instead of turning up/down all the dials by our fixed learning rate, we add/subtract our learning rate times the entire example from our weights. See Exercise 1.6 for why these operations are equivalent. In Step 1, our model predicts Dog (0), but our label is Cat (1), so we add our cat image to our weights. This is why our weights just look like our training image after our first step. In Step 2, the Perceptron gets the answer right, so we do not update our weights. In Step 3, our model predicts Cat (1), but the correct label is Dog (0). Following the perceptron learning rule, we subtract our dog image from our weights, resulting in our weights containing a "positive cat" and "inverted dog" image. Following our rule, our error rate does come down a little but is erratic and never beats 20%. Our weights after 2500 steps are interesting—you can see glowing cat eyes and noses; these features result in high outputs for cat images, allowing the Perceptron to perform better than chance.

As we can see in Figure 1.14, the reason the perceptron can solve Task 1 but not Task 2 is because the data in Task 2 is not linearly separable—there's no way to use a single line to separate this pattern!

This example is known as the exclusive OR problem, because the mapping from inputs to outputs follows the logical exclusive OR function and is one of the simplest examples of a non-linearly separable pattern.

This inability to learn a simple exclusive OR function was a major criticism of Rosenblatt's perceptron and other early neural networks. The example may feel a bit contrived, but linear separability is a significant concern in real data—in Rosenblatt's 1958 press conference, he showed an example of the perceptron learning to tell apart examples with markings on the left vs. the right side of an image—these patterns are linearly separable.

However, later that year in an interview with the New Yorker, Rosenblatt claimed that the perceptron could tell apart images of cats and dogs [Mason and Gill 1958]. He likely meant in principle, but if we try this out in Python on images of cat and dog faces[2] as shown in Figure 1.16, the perceptron learning rule is able to learn some basic patterns but is unstable and unable to beat a 20% error rate, meaning this cat and dog dataset is not linearly separable.[3]

x_0	x_1	y
0	0	0
0	1	1
1	0	1
1	1	0

Figure 1.15 | Exclusive OR. The boolean exclusive or function returns 1 when either input is 1 and 0 when both inputs are 0 or both are 1. Our perceptron mathematics assumes -1/1 instead of the standard boolean 0/1, but the underlying structure is the same.

Figure 1.17 | Rosenblatt's Learning Rule 70 years later. Rosenblatt wasn't able to test his cats and dogs prediction, but today we can easily with a few dozen lines of Python. See Supporting Code 1.5 for the full implementation.

```
def neuron(x, w):
    '''Simple McCulloch-Pitts Neuron model, x and w and are numpy arrays of the same shape'''
    return np.dot(x, w) > 0

def update_neuron(w, x, label):
    '''
    Update McCulloch + Pitts Neuron using Rosenblatt's Perceptron Algorithms
    w = neuron weights, x = (n dimensional numpy array example), label = binary label
    '''
    is_correct = False
    prediction=neuron(x, w)
    if prediction == 0 and label == 1:
        w = w + x
    elif prediction == 1 and label == 0:
        w = w - x
    else:
        is_correct = True
    return w, is_correct, prediction
```

2 See Supporting Code 1.5

3 There are a few notable distinctions here. First, we're using grayscale instead of binary inputs; the Perceptron Learning Rule still holds in this case. Second, the perceptron has a VC-dimension of the dimension of the input data plus one—what this means for us is that the perceptron can find a hyperplane that perfectly divides any set of examples, as long as we have fewer examples than the dimension of the input data plus one. Here, we're using images of size 64 × 64, so the input dimension of our data is 4096. So if we use fewer than 4097 examples, our perceptron will be able to perfectly divide our cats from dogs, given enough iterations, possibly without necessarily "learning anything." Here we're choosing N = 5000 > 4096. I would like to see a demonstration of this fact on a dataset like this—please send me one if you have it—welchlabs.com/contact. For a great intro to the VC dimension, see [Abu-Mostafa et al. 2012].

Now, as Rosenblatt himself pointed out, there is a solution to the linear separability problem, but it comes with a catch.

Our perceptron machine implements a single artificial neuron (Figure 1.18), which is limited to creating a single linear decision boundary to recognize patterns. If we expand to a *network* of these artificial neurons, we can combine multiple linear decision boundaries to learn more complex patterns.

It turns out that a very simple network with just three neurons across two layers can solve the exclusive OR problem—it works by creating two decision boundaries in the first layer and then combining these boundaries in the second layer into a band on our grid that captures (-1, 1), and (1, -1), while rejecting (-1, -1), and (1, 1) (Figure 1.19).

However, while it was well known in the 1960s that multilayer neural networks could solve nonlinearly separable problems like this in principle—no one could find a suitable algorithm capable of learning the weights. The perceptron learning rule that works so well for a single neuron does not generalize to multilayer networks, and while it's easy to manually figure out weights to solve toy problems like exclusive OR—real problems like telling apart cats and dogs with multilayer neural networks require a learning algorithm that can simultaneously update all neuron weights based on real data.

Neural networks had hit a dead end.

Figure 1.20 | Shots Fired. Minsky and Papert throw some serious shade on perceptrons in their 1969 book—the cover itself shows two patterns that Rosenblatt's perceptron cannot tell apart. The top shape is a single connected purple line, while the bottom shape is composed of two separate lines.

In the mid-1960s, two leaders in AI, Marvin Minsky and Seymour Papert, began circulating preprints of a book called *Perceptrons*. Despite its title, the book takes a negative view, rigorously showing mathematically what perceptrons could not do. The cover shows two figures the perceptron cannot tell apart—the shapes in Figure 1.20 look similar but have different connectivities: the top shape is made from a single purple line, and the bottom from two. Like the exclusive OR problem, Rosenblatt's perceptron cannot separate these patterns—although modern neural networks can.[4]

This apparent dead end contributed to the rise of completely different, symbolic approaches to AI in the 1960s and 70s and a significant decline in neural network research. [Crevier 1993, Olazaran 1993, Nets 1999]

While Rosenblatt's Perceptron received the most attention at the time, there were a number of other groups working on systems of

4 Minsky and Papert's proof for the example on the cover depends on Rosenblatt's decision to wire up his perceptron using locally connected regions. This local connection design is not part of all perceptrons. Within the book, Minsky and Paper explore many shortcoming of perceptrons, including the famous XOR example.



Figure 1.18 | Perceptrons are Artificial Neurons. Each of our perceptron machines is equivalent to a single artificial neuron, just with a different number of inputs. There is one important component missing from this picture. The outputs of real neurons are more binary—the neurons in our brain fire or don't (sortof), while our perceptron machine's output is continuous. As we'll see shortly and in following chapters, this distinction will become critical when we consider networks of artificial neurons. We'll address this issue by adding one more small piece of math to our artificial neurons, known as an activation function.



Figure 1.19 | Networks of Neurons are Powerful. If we connect three of our baby perceptrons together, we can solve the XOR problem! Each perceptron in our first layer learns a single decision boundary, and the perceptron in our second layer puts these boundaries together. As discussed in Figure 1.8, we're also not showing activation functions; we'll get to these shortly! Throughout this book, and especially in Chapter 4, we'll unpack how multiple layers of neurons are able to work together to solve incredibly complex problems. Before we can do that though, we need a way to train networks of neurons—the Perceptron Learning Rule only works for a single layer of neurons. Note that we're using superscripts to indicate which layer a given variable is in.



Figure 1.21 | Same Problem Different Strategy. Let's use one of the same examples we solved earlier with the Perceptron Learning Rule, but try a new approach.



Figure 1.22 | Different Names for the Same Thing. Switching to these variable names will help us scale to bigger models in this chapter and the remainder of the book.

artificial neurons. At Stanford, Bernard Widrow's group came incredibly close to solving the problem of training multilayer neural networks and discovering our modern approach to AI.

On a Friday afternoon in the fall of 1959, Widrow had his first meeting with a new graduate student, Ted Hoff [Widrow 2005].

As Widrow explained, his group had been working on gradient-based methods for learning the weights in artificial neurons. The idea was that instead of following an ad hoc method like the Perceptron Learning Rule, it was possible to measure and minimize the machine's error mathematically.

In the first two-input example (Figure 1.21, Figure 1.10 Task 1), where we wanted our perceptron to learn to classify inputs where either one or both switches are on as positive, we can measure our system's error by comparing the machine's outputs to our target outputs. Let's make a small notation change that will help us scale up to larger networks. Instead of calling our inputs x and y, let's call our inputs x_1 and x_2; otherwise we'll run out of letters pretty quickly! We'll also rename our output to $\hat{y}$, which is a common variable choice in machine learning for a model's predictions—the idea is that $\hat{y}$ is an estimate of our model's targets y.

Let's take a single switch pattern and machine configuration and measure our system's error. Starting with both switches off (x_1=-1, x_2=-1), we know we want the output of our machine to be negative (Figures 1.21 and 1.23). To use Widrow's method, we need to choose a specific target value Let's say that instead of asking our machine to output any negative value, let's ask it to output a value of y=-1.

Now, let's begin with an initial machine configuration of w_1=-1, w_2=1, and b=1 (Figure 1.23). From here we can compute our perceptron's outputs for this configuration and input, $\hat{y} = w_1x_1+w_2x_2+b$=(-1)(-1)+(1)(-1)+1=1. However, our target value is y=-1, so the difference or error between our target and our output is y-$\hat{y}$=-1-1=-2. From here Widrow's group would square this error value; this ensured the value was always positive and made it easier to minimize. So our squared error is $(-2)^2$=4.

How does our squared error change as we turn our dials? If we move our first dial from w_1=-1 to w_1=-0.9, our overall output is now $\hat{y}$=0.9, reducing our error to 1.9 and our squared error to 3.61.

Now, how will our squared error change as we keep turning our w_1 knob?



Figure 1.23 | Measuring Error. Taking a single input from learning task 1 in Figure 1.10, we can measure the error of the perceptron machine as we adjust our knobs. For a starting knob configuration of w_1=-1, w_2=1, and b=1, and input values of x_1=-1 and x_2=-1, we can compute our machine's output $\hat{y}$=1. For this method to work, we need to pick specific target values y (instead of just asking our machine to output a positive or negative value), here we're choosing targets of y=1 and y=-1. Given the target y=-1 for our inputs x_1=-1, x_2=-1, we can measure our system's error. Widrow's group used the squared error; this ensures that our error is always positive, making our system easier to optimize. As we'll see throughout this book, the idea of using a model to make a prediction $\hat{y}$, comparing this prediction to a target y, measuring error, and then minimizing this error is the core of how virtually all modern models learn. Now what will happen to our error if we keep turning up our w_1 knob?

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
x_1	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0
w_1	-0.9	-0.7	-0.5	-0.3	-0.1	0.1	0.3	0.5	0.7	0.9	1.1	1.3	1.5	1.7	1.9
x_2	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0
w_2	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
b	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
$\hat{y}$	0.9	0.7	0.5	0.3	0.1	-0.1	-0.3	-0.5	-0.7	-0.9	-1.1	-1.3	-1.5	-1.7	-1.9
y	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0
E	3.61	2.89	2.25	1.69	1.21	0.81	0.49	0.25	0.09	0.01	0.01	0.09	0.25	0.49	0.81



Figure 1.24 | Minimizing Error. Tuning our w_1 knob, we can compute and visualize our errors, resulting in a nice parabola with a minimum around w_1 =1. Of course, we want to find an optimal configuration for all knobs, not just one. Tuning w_1 and w_2 together, we end up with a parabolic bowl shape, where the best configuration of these two knobs will be at the bottom. Note that in the 3D version, we've switched to averaging our error across all 4 examples; see supporting code 1.6 at the end of this chapter.

Moving our w_1 knob step by step and plotting the results, we see that our error value makes a smooth parabolic shape, as shown in Figure 1.24. Our error reaches a minimum around $w_1=1$, so for the w_1 knob, the perceptron's error will be minimized around this value.

Of course we want to find the best overall configuration of all knobs, not just w_1. If we vary w_1 and w_2 at the same time across a range of values, and plot our errors as the height of a surface, we end up with a nice bowl shape, where the best configuration of dials is nicely located at the bottom of the bowl. (Figure 1.24)

Now, as we move to machines with more dials, it becomes intractable to test all configurations like this. In the 3D bowl of Figure 1.24, we tested 16 values for each knob, meaning we had to perform (16)(16)=256 computations. If we add the third knob of our baby perceptron, this brings our number of required computations to (16)(16)(16)=16^3=4,096. Visually this would look like testing every point in a cube with 16 points along each side. We really run into trouble when we consider larger machines; our full-size 17-dial perceptron machine would require an enormous 16^{17} = 295,147,905,179,352,825,856 computations to test all configurations of dials.[5]

What's interesting here, though, is that we don't need to know what our entire error landscape looks like to find the best solution—given a starting configuration of dials, if we just know which way is downhill in our error landscape, also known as the gradient, we can take incremental steps in this direction to reach the bottom of our bowl.[6]



Figure 1.25 | A Better Way. Instead of testing every point in our error landscape, if we just know which way is downhill, we can take iterative steps in that direction to reach the bottom of the bowl. This is known as gradient descent and is at the core of how virtually all modern AI models learn.

5 This known as the curse of dimensionality.

6 Assuming we don't get stuck in a local minimum/our surface is convex—we'll have much more to say about this in Chapter 2!



Figure 1.26 | Numerical Gradient Estimation. Up until this point, Widrow's group at Stanford had used numerical estimates of the gradient. Testing two values around our start point of w_1 =-1, we can estimate the slope $\Delta E/\Delta w_1$ of our error curve. If we repeat this process for all the knobs on our perceptron, we'll have a set of slopes (the gradient) that tell us "which way is downhill" on our error surface.



Figure 1.27 | The Gradient Points to the Answer. Repeating the slope estimation approach in Figure 1.26 for each weight in our model, we end up with one slope for each weight. In the language of calculus, we write these slopes as $\partial E/\partial w$, although technically at this point Widrow's team was estimating this gradient numerically, so the more appropriate terminology is $\Delta E/\Delta w$. Putting these slopes together into a vector, we obtain the gradient—which points us downhill towards lower error solutions. Note that technically the gradient points uphill, and we move in the exact opposite direction of the gradient to move downhill—we'll see why this is the case in Chapter 3.

"Then when you work out the gradient of that error with respect to the weights, it's really simple. You get an algebraic expression and you realize that you don't have to square anything; you don't have to average anything to get mean square error. You don't have to differentiate to get gradient. You get this all directly in one step. Not only that, but you get all components of the gradient simultaneously instead of having to make measurements to get one gradient component at a time. The power of that, compared to the earlier method, is just fantastic."

- Bernhard Widrow [Talking Nets p53]

Up until this point, Widrow's group estimated the gradient numerically. Given our starting point w_1=-1, w_2=1, and b=1, they would compute error at points in the neighborhood around each weight. For the w_1 weight, for example, we can compute the error at w_1=-1.1 and w_1=-0.9 to compute the slope of the error curve, as shown in Figure 1.26.

Widrow's group would then estimate the slope in this way for each of the weights in their models—the resulting collection of slopes is known as the gradient. These slopes tell us "which way is downhill" in our model's error landscape, as shown in Figure 1.27—we'll cover the mechanics of computing and using gradients in detail in Chapter 3.

As Widrow walked through this mathematics at his office blackboard with Hoff, they came across a powerful new approach that is incredibly close to how we train networks of artificial neurons today, but with one critical exception.

Instead of estimating the gradient by computing the error around each weight value, what if we instead use calculus to take the derivatives of the error function directly?[7] Starting with our two-input perceptron equation and error expression, we can compute the rate of change of our squared error with respect to our first weight, w_1:

$$\hat{y} = w_1 x_1 + w_2 x_2 + b$$ Two input Perceptron equation

$$E = Error^2 = (y - \hat{y})^2$$ Squared error

$$\frac{\partial E}{\partial w_1} = -2(y - \hat{y})\frac{\partial \hat{y}}{\partial w_1}$$ How does our error change with our weight w_1? Drop down power of 2, then chain rule

$$\frac{\partial E}{\partial w_1} = -2(y - \hat{y})\frac{\partial [w_1 x_1 + w_2 x_2 + b]}{\partial w_1}$$ Plug in preceptron equation, second two terms do not depend on w_1

$$\frac{\partial E}{\partial w_1} = -2(y - \hat{y})x_1$$



Our input x_1 is contant, $w_1 x_1$ is the equation of a line with a slope of x_1

We're left with a simple expression for our derivative, and we can compute similar expressions for our remaining weights. Putting these pieces together, we're left with three simple equations that give us the full gradient—telling us exactly which way is downhill from a given starting point on our error landscape. As Widrow would later explain, you don't even have to square anything or compute the actual error; "the power of that, compared to earlier methods, is just fantastic." [Talking Nets 1999]

$$\frac{\partial E}{\partial w_1} = -2(y - \hat{y})x_1$$
$$\frac{\partial E}{\partial w_2} = -2(y - \hat{y})x_2$$
$$\frac{\partial E}{\partial b} = -2(y - \hat{y})$$

GRADIENT

7 If you're fuzzy or not familiar with calculus, in Chapter 3 we'll do a more in depth walkthrough of gradient computation, and following the calculus steps here is not critical to understanding the majority of the material.

Widrow and Hoff had found a method that appeared to be incredibly efficient, but would it actually work?

They had to find out.

They quickly worked out a circuit design, but the university stockroom was closed by the end of their Friday afternoon meeting and would not reopen until Monday. The next morning, Widrow and Hoff rushed to an electronics supply store and over the weekend pieced together an artificial neuron circuit very similar to ours, and by Sunday evening were testing out their new learning algorithm on various input patterns. [Talking Nets 1999]

Their new learning algorithm worked incredibly well.

Interestingly, despite being derived in a completely different way, Widrow and Hoff's algorithm updates the machine's weights in a very similar way to the perceptron learning rule. The only real difference is that Widrow and Hoff's algorithm, which they later called LMS, includes multiplying the weight update by the current error value. So instead of turning the knobs by the same fixed learning rate at each step, we turn them proportionally to the error between the target and current output values.

The LMS algorithm can quickly solve the T and J classification problem we solved earlier with the perceptron learning rule. It was later shown that although the LMS algorithm is not guaranteed to find a solution if one exists, it performs better in the all-too-common cases where our examples are not linearly separable.

Now, as impressive as the LMS algorithm is, Widrow and Hoff were not able to use it to address the core issue that halted 1960s neural network research. As Widrow would later explain, despite their best efforts, they were never able to adapt LMS to train networks with multiple layers.

What's wild here is how close the algorithm they wrote on the blackboard that day is to the back-propagation algorithm we use today to train AI systems like ChatGPT.

Let's revisit the three-neuron, two-layer neural network we considered earlier that could solve the exclusive OR problem (Figures 1.19, 1.30). When we first saw this network earlier, we omitted an important detail. For this network to actually be able to solve the exclusive OR problem, we need to add one more small component called an activation function.[8] Mathematically, this looks like passing the output of each perceptron equation $w_1x_1+w_2x_2+b$, into a function before passing the neuron's output to the following layer of the network, as shown in Figure 1.30.[9]

PERCEPTRON LEARNING RULE

$$w^{(t+1)} \leftarrow w^{(t)} \pm \alpha x$$

LEAST MEAN SQUARES (LMS)

$$w^{(t+1)} \leftarrow w^{(t)} + \alpha x(y - \hat{y})$$

Error Term

Figure 1.29 | Different Approaches but Similar Results. Interestingly, Widrow and Hoff's LMS algorithm ends up working in a very similar way to Rosenblatt's Perceptron Learning Rule Here w^{t+1} refers to our machine's updated weights, w^t is our original weights, α is our learning rate, and x is our data. Note that the factor of 2 from the computed partial derivatives is missing, this term is effectively absorbed into the learning rate and omitted here for clarity. See Exercises 1.6 and 1.10 for a detailed walkthrough.

"But we never succeeded in developing an algorithm for adapting both layers, so that the second layer is not fixed and both layers are adaptive. It wasn't that we didn't try. I mean we would have given our eye teeth [sic] to come up with something like backprop."

- Bernhard Widrow [Talking Nets p60]

8 See Chapter 4 for a detailed explanation of why activation functions are essential for multilayer networks.

9 Up until this point, we've considered activation functions indirectly—for example by having our Perceptron Machine classify T's when it's output is greater than 0, we're saying that if $w_1x_1+w_2x_2+b>0$, then our input is a T. This a type of activation function, but we need to make this more explicit.



Figure 1.28 | KNOBBY ADALINE Widrow and Hoff's ADALINE machine works in the same way as our perceptron (Figure 1.1), and can be trained using Widrow and Hoff's LMS algorithm, or Rosenblatt's Perceptron Learning Rule. Widrow and Hoff would later make a version that learned automatically as Rosenblatt's Perceptron did, but using a clever electrochemical design.



Figure 1.30 | Activation Functions Matter. The three-neuron network we saw earlier (Figure 1.19) was missing a small but critical detail. To actually be able to solve the XOR problem, we need to pass the output of our perceptron's equation into a non-linear function called an activation function. If we omit the activation function, our network effectively collapses back down into a single neuron, leaving us with a single decision boundary (see Chapter 4 for a detailed explanation). Including an activation function allows our model to fit multiple decision boundaries. As we'll see in later Chapters, there are many effective choices for activation functions, but in the early days of neural network research, many investigators used binary step-function activation functions (i.e. McCulloch and Pitts Neurons) to roughly approximate the fact that real neurons either fire or don't. These activation functions return a value of +1 if $w_1 x_1 + w_2 x_2 + b > 0$, and 0 or -1 otherwise. Finally note that we're using superscripts to indicate which layer a given variable is in. See Exercise 1.15 for a detailed walkthrough.



$$\hat{y} = w_1^{(2)}\begin{bmatrix}\begin{cases}1 & w_{11}^{(1)}x_1 + w_{12}^{(1)}x_2 + b_1^{(1)} > 0\\ 0 & \text{otherwise}\end{cases}\end{bmatrix} + w_2^{(2)}\begin{bmatrix}\begin{cases}1 & w_{21}^{(1)}x_1 + w_{22}^{(1)}x_2 + b_2^{(1)} > 0\\ 0 & \text{otherwise}\end{cases}\end{bmatrix} + b_1^{(2)}$$

Full Network Equation

$$E = Error^2 = (y - \hat{y})^2$$

$$\frac{\partial E}{\partial w_{11}^{(1)}} = -2(y-\hat{y})\frac{\partial \hat{y}}{\partial w_{11}^{(1)}}$$

No dependence on w_{11}

$$= -2(y-\hat{y})\frac{\partial}{\partial w_{11}^{(1)}}\left[w_1^{(2)}\begin{bmatrix}\begin{cases}1 & w_{11}^{(1)}x_1 + w_{12}^{(1)}x_2 + b_1^{(1)} > 0\\ 0 & \text{otherwise}\end{cases}\end{bmatrix} + w_2^{(2)}\begin{bmatrix}\begin{cases}1 & w_{21}^{(1)}x_1 + w_{22}^{(1)}x_2 + b_2^{(1)} > 0\\ 0 & \text{otherwise}\end{cases}\end{bmatrix} + b_1^{(2)}\right]$$

$$= -2(y-\hat{y})\frac{\partial}{\partial w_{11}^{(1)}}\left[w_1^{(2)}\begin{bmatrix}\begin{cases}1 & w_{11}^{(1)}x_1 + w_{12}^{(1)}x_2 + b_1^{(1)} > 0\\ 0 & \text{otherwise}\end{cases}\end{bmatrix}\right]$$



Slope is 0 or undefined!

Figure 1.32 | You Can't Differentiate Through a Brick Wall. Like Rosenblatt's Perceptron Learning Rule, Widrow and Hoff's LMS approach fails to generalize to multilayer neural networks, but gets incredibly close. The problem is not the LMS algorithm itself, but the step function activations they used in their models. When we try to differentiate across the step functions, we get stuck—the slopes of our step functions are zero or undefined, meaning we can't complete our calculus.

McCulloch–Pitts Neuron Activation



$$f(x) = \begin{cases}1 & \text{if } x \geq 0,\\ 0 & \text{if } x < 0\end{cases}$$

Sigmoid Activation



$$f(x) = \frac{1}{1+e^{-x}}$$





Figure 1.33 | The Fix is Surprisingly Simple. If we simply swap out our all-or-nothing activation function for something smoother, Widrow and Hoff's LMS algorithm works!

The artificial neuron model used by most researchers in the 1950s and 1960s, originally developed by Walter Pitts and Warren McCulloch in the 1940s, assumes an all-or-nothing output. Each neuron either fires or doesn't. If the sum of our weights times our inputs is greater than zero, our artificial neuron fires and outputs a one, otherwise the neuron outputs 0 or -1.

In our three-neuron, two-layer network, we can write a set of equations that map our inputs x to our outputs $\hat{y}$, (Figure 1.32) just as Widrow and Hoff did for a single neuron. (Figures 1.22, 1.23) Following Widrow and Hoff's approach of differentiating our error equation directly (Figure 1.23), we can differentiate our error equation with respect to our weights, and follow the chain rule. However, when we reach the boundary between our first and second layers, our calculus hits a brick wall.

The slope of the binary step activation function is zero everywhere and undefined at zero, so when we reach this function in our chain rule calculus, we get stuck—this function effectively snaps our gradient to zero.

Visually, the binary step activation function turns our error landscape into flat plateaus and infinitely steep cliffs—Figure 1.33 shows our error as a function of the weights in our first layer—these flat landscapes give gradient based methods like LMS no hope of incrementally working their way downhill.

The solution to the problem, in hindsight, is surprisingly simple—all we have to do is replace the all-or-nothing step activation function with something less flat. Swapping our step function for a sigmoid function as shown in Figure 1.33, we still have somewhat flat regions, but there's enough of a slope in these regions to guide our solution downhill. Figure 1.33 shows a continuation of the LMS algorithm extended through both layers of the network working its way downhill to find a solution to the exclusive OR problem.[10]

In 1986, 27 years after Widrow and Hoff discovered the LMS algorithm, David Rumelhart, Geoff Hinton, and Ronald Williams published [Rumelhart 1987], where they present the backpropagation algorithm that we use today. Their derivation cites the LMS algorithm, which they call the delta rule, and they proceed with deriving backpropagation as a generalization of this rule—using the chain rule with sigmoid activation functions to continue the gradient computation started by Widrow and Hoff almost three decades before.

10 See supporting code for more details.

McCulloch–Pitts Neuron



$$f(x_1, x_2) = \begin{cases} 1 & w_{11}^{(1)} x_1 + w_{12}^{(1)} x_2 + b_1^{(1)} > 0 \\ 0 & \text{otherwise} \end{cases}$$



Figure 1.31 | The McCulloch-Pitts Neuron. The McCulloch-Pitts neuron was introduced way back in the 1940s by the neurophysiologist and philosopher Warren McCulloch and the mathematical prodigy Walter Pitts.

In 2020, OpenAI used back-propagation to train GPT-3, the largest neural network ever created at the time, with a staggering 175 billion learnable weights. [Brown 2020]

These weights are spread across 96 layers, each made from two compute blocks. The second compute block in each layer is still called by the name Frank Rosenblatt gave it almost 70 years ago—a multilayer perceptron. Each multilayer perceptron block in GPT-3 has two layers, just like our two-layer network that solved the exclusive OR problem, but with way more neurons—around 50 thousand in the first layer, and 12 thousand in the second layer.

The first compute block in each layer implements a relatively recent idea called attention, and arguably still uses artificial neurons, but in a more complex way. One way to think about the attention block is as a specialized multilayer perceptron where the weights are controlled by other perceptrons, allowing the data itself to control the weights as it moves through the model. Each attention block in GPT-3 effectively uses around 50,000 artificial neurons.

This makes for around 10 million artificial neurons across GPT-3's 96 layers, so we would need 10 million of our perceptron machines, each with over 10,000 dials, to implement GPT-3. Today GPT-3 fits on around 10 GPUs.[11] GPT-4 is reportedly around 10 times larger than GPT-3, bringing our neuron count to something in the neighborhood of 100 million.

Like our simple perceptron machine, GPT-3 is in many ways a pattern recognizer—it's enormous network of neurons allows it to learn very complex patterns in language, and use these patterns to predict what text should come next.

It's incredible that this atomic unit, the perceptron, connected in giant networks and trained with an extension of the LMS algorithm, would result in the most intelligent systems we've been able to build so far.

It's been almost seventy years now since Frank Rosenblatt claimed that the perceptron would be able to walk, talk, see, write, reproduce itself, and be conscious of its own existence. He clearly was missing key details, but time has only proven Rosenblatt more right about what the humble perceptron can do.

We'll have to wait and see if he was right about everything.

Assuming FP16, for inference, not training



Figure 1.34 | Yep, we actually drew all 96 GPT-3 layers. It's hard to make sense of just how large Large Language Models (LLMs) are. GPT-3 is made of 96 transformer blocks, each with an attention and multilayer perceptron (MLP) compute block. The MLP blocks are remarkably similar to our XOR network, just way bigger and with different activation functions (ReLU vs Step function). We'll cover LLM architecture in much more detail in the coming chapters.



Figure 1.35 | That's a lot of neurons. It's hard to imagine 10 million of our perceptron machines hooked together, but this exactly what GPT-3 is!

12 There are some notable caveats here, with less neurons being used at inference, and OpenAI has not shared this information directly. Method for counting neurons in ChatGPT: Starting with Andrej Karpathy's build-nanogpt GPT-2 implementation here- keys, queries, and values are implemented in Linear layers with n_embd inputs and 3*n_embd outputs, where n_embd is the embedding dimension. Output projection layer has n_embd and n_embd outputs. So a single attention layer will have ~4*n_embd neurons. GPT-3 has an embedding dimension of 12,288, so each attention layer has ~49,152 neurons. Each MLP block has n_embd inputs, 4*n_embd hidden units, and n_embd outputs, so ~5*n_embd total neurons, or ~61,440. Total neuron count for GPT-3 is then 96*(49,152+61,440)=10,616,832, ignoring initial embedding and final unembedding. Finally, GPT-4 reportedly has ~1.8 Trillion parameters [Patel and Wong 2023] making it ~10x larger than GPT-3. Note that GPT-4 is reportedly a mixture of experts, and not all experts are used for each inference, so it appears that not all 1.8 trillion parameters are used for a given inference call. Assuming that ~10x the parameters means 10x the neurons, then GPT-4 should have ~100M neurons.



SWITCHES
SPDT toggle switches on painted alluminum plate.



LEDS
Connected in series with a restistor to match battery voltage.

POTENTIOMETERS
10 kΩ Potentiometers, numbers made with vinyl cutting machine.



SUMMING CIRCUIT
Solderable breadboards help with connecting everything together.



Figure 1.36 | The Circuit Behind the Machine. The perceptrons we show in this chapter and corresponding video are based on a circuit design shared by Bernard Widrow in 2005. There's nothing quite like playing with the machine yourself!

BUILD YOUR OWN PERCEPTRON

There's nothing quite like playing with the Perceptron machine yourself—it's really satisfying. Unfortunately, it's not an easy build, especially if you want it to look polished, but it is doable![1] Bernard Widrow eventually published a circuit diagram [Widrow 2005], but didn't include any resistor values. For this project, we had to experiment with different component values, and add a simple LED circuit for the display. Our final circuit is shown in Figure 1.36.

Our construction style required a bunch of soldering, although we prototyped on breadboards first. The switch and knob panels are cut from aluminum plates using a jigsaw, and the backing board is simple 1/2" plywood. The knob ticks and numbers are cutout using a Cricut® cutting machine, you'll find the files we used in the github repo linked below.

The machine is not perfect—the tolerances of components mean you'll need to adjust exactly how the potentiometers are oriented for things to "line up". Finally, the machine is "not linear"—the ratio between the dial numbers and the meter outputs depends on how many switches are on. This doesn't affect the ability of the Perceptron Learning Rule to converge, but means the machine is not truly "adding the dial values together."[2]

Happy building—and send us a picture of your machine![3]

PART	QUANTITY	NOTES / DETAILS
10k Ohm Resistor	36	For summing circuit
68 Ohm Resistor	16	For wiring up LEDs
Switch	16	SPDT Mini Toggle Switch 3-Pin 2 Position
LED	17	ON/ON
10K Ohm Potentiometer & knob	17	5mm
Wires	~50'	22-26 Gauge
AA Battery	2	
Battery Holder	1	2 AA Battery holder with leads
Microamp Current Meter	1	Used on Ebay - a little tricky
Solderable Breadboard 1	1	2.75"x2" - for LED panel
Solderable Breadboard 2	1	2.05"x3.5" - for summing circuit
Sheet Metal 1	1	4x4" - plate for switches
Sheet Metal 2	1	6x6" - plate for knobs
Wood Backing Board	1	8.5"x19"
Carraige Bolts - 3" & Nuts	8	
Standoffs	8	To hold up solder boards

Parts list with purchase links, and vinyl cutouts file at:
`github.com/stephencwelch/ai_book`



Figure 1.37 | Building the Machine. Top to bottom: Yeah, it's like a lot of wires. Be sure to label them! I used little pieces of painter's tape, and tested a bunch as I went. | It's important to have helpers | Laying out the machine with sheet metal cutouts and breadboards | "Oh my God nothing is working this was a huge mistake!"

1 It would be fun make a kit at some point!

2 We couldn't find any mention of this from Widrow—there's likely better choices of resistor values or a different design that would behave more linearly—if you're aware of a better design—please let us know at welchlabs.com/contact.

3 welchlabs.com/contact

1.1 Perceptron Learning Ts vs Js - Step Through Manually

Manually walk through the training procedure of Figure 1.4

[1]:
```
import numpy as np
import matplotlib.pyplot as plt
```

[2]:
```
#Manually Code up examples
examples=np.array([[[1,1,1,-1], #T Shifted Left
                    [-1,1,-1,-1],
                    [-1,1,-1,-1],
                    [-1,1,-1,-1]],
                   [[-1,1,1,1], #T Shifted Right
                    [-1,-1,1,-1],
                    [-1,-1,1,-1],
                    [-1,-1,1,-1]],
                   [[-1,-1,1,-1], #J Shifted Left
                    [-1,-1,1,-1],
                    [1,-1,1,-1],
                    [1,1,1,-1]],
                   [[-1,-1,-1,1], #J Shifted Right
                    [-1,-1,-1,1],
                    [-1,1,-1,1],
                    [-1,1,1,1]]])
```

[3]:
```
fig=plt.figure(0,(6,6))
for i in range(len(examples)):
    fig.add_subplot(2,2,i+1)
    plt.imshow(examples[i])
```

[3]:
```
<Figure size 600x600 with 4 Axes>
```



[4]:
```
# Setup labels - we want our machine to output positive voltage to T shapes,
# our first 2 examples are Ts - so we'll set these values to +1, our second to
# examples are Js - so we'll set these to -1s
y=np.array([1,1,-1,-1])

# Reshape each example into a row, and add a 17th column for the bias term
# Bias term is a like a switch that is "always on", an extra parameter that doesn't depend the input
X=np.hstack((examples.reshape(-1, 16), np.ones((len(y),1))))
```

[5]:
```
X.shape, y.shape
```

[5]:
```
((4, 17), (4,))
```

SUPPORTING CODE

This sections contains supporting code for the key results presented in this chapter. This code and more are available at:

github.com/stephencwelch/ai_book

[6]:
```
X #1 row for each example
```

[6]:
```
array([[ 1., 1., 1., -1., -1., 1., -1., -1., -1., 1., -1., -1., -1.,
1., -1., -1., 1.],
[-1., 1., 1., 1., -1., -1., 1., -1., -1., -1., 1., -1., -1.,
-1., 1., -1., 1.],
[-1., -1., 1., -1., -1., -1., 1., -1., 1., -1., 1., -1., 1.,
1., 1., -1., 1.],
[-1., -1., -1., 1., -1., -1., -1., 1., -1., 1., -1., 1., -1.,
1., 1., 1., 1.]])
```

[7]:
```
#Initialized weights to zeros, this is equivalent to turning each knob to 12 o'clock
w = np.zeros(17)
lr=1.0 #Learning rate
```

[8]:
```
i=1 #Start with index 1, converges a little faster than starting at index 0
yhat=np.dot(X[i],w) #Compute perceptron output by taking dot product of example X and weights.
```

[9]:
```
yhat, y[i] #machine outputs 0, but we want it to output +1
```

[9]:
```
(0.0, 1)
```

[10]:
```
# Update weight following perceptron learning rule
# adding our learning rate times our example is equivalent
# to turning up all our dials that are switched on, and turning
# down all our dails that are switched off
w=w+lr*X[i]
```

[11]:
```
#Adding our learning rate times our example now makes our weights look like our first example.
w[:16].reshape(4,4)
```

[11]:
```
array([[-1., 1., 1., 1.],
[-1., -1., 1., -1.],
[-1., -1., 1., -1.],
[-1., -1., 1., -1.]])
```

[12]:
```
i+=1 #Increment our counter i
i
```

[12]:
```
2
```

[13]:
```
yhat=np.dot(X[i],w) #Compute perceptron output
```

[14]:
```
yhat, y[i] #machine outputs +, but we want it to output -
```

[14]:
```
(7.0, -1)
```

[15]:
```
w=w-lr*X[i] #Machine output a +, but we wanted -, so subract learning rate time examples
```

[16]:
```
w[:16].reshape(4,4)
```

[16]:
```
array([[ 0., 2., 0., 2.],
[ 0., 0., 0., 0.],
[-2., 0., 0., 0.],
[-2., -2., 0., 0.]])
```

[17]:
```
i+=1 #Increment our counter i
i
```

[17]:
```
3
```

[18]:
```
yhat=np.dot(X[i],w) #Compute perceptron output
```

[19]:
```
yhat, y[i] #machine outputs +, but we want it to output -
```

[19]:
```
(2.0, -1)
```

[20]:
```
w=w-lr*X[i] #Machine output a +, but we wanted -, so subract learning rate time examples
```

[21]:
```
w[:16].reshape(4,4)
```

[21]:
```
array([[ 1., 3., 1., 1.],
[ 1., 1., 1., -1.],
[-1., -1., 1., -1.],
[-1., -3., -1., -1.]])
```

[22]:
```
i=0 #We've reached the end our our examples (index 3, so start over)
```

[23]:
```
yhat=np.dot(X[i],w) #Compute perceptron output
```

[24]:
```
yhat, y[i] #machine outputs +, and we want a +, so do not update weights.
```

[24]:
```
(3.0, 1)
```

[25]:
```
#Cycle back through examples, print machine output and target output for each
for i in range(4):
    yhat=np.dot(X[i],w) #Compute perceptron output
    print(yhat, y[i])
```

[25]:
```
3.0 1
11.0 1
-7.0 -1
-15.0 -1
```

Signs match in each case! Our perceptron is correctly classifying all examples.

1.2 Percpeptron Learning Ts vs Js - Step through in automated loop

[26]:
```
#Manually Code up examples
examples=np.array([[[1,1,1,-1], #T Shifted Left
                    [-1,1,-1,-1],
                    [-1,1,-1,-1],
                    [-1,1,-1,-1]],
                   [[-1,1,1,1], #T Shifted Right
                    [-1,-1,1,-1],
                    [-1,-1,1,-1],
                    [-1,-1,1,-1]],
                   [[-1,-1,1,-1], #J Shifted Left
                    [-1,-1,1,-1],
                    [1,-1,1,-1],
                    [1,1,1,-1]],
                   [[-1,-1,-1,1], #J Shifted Right
                    [-1,-1,-1,1],
                    [-1,1,-1,1],
                    [-1,1,1,1]]])
```

[27]:
```
fig=plt.figure(0,(6,6))
for i in range(len(examples)):
    fig.add_subplot(2,2,i+1)
    plt.imshow(examples[i])
```

[27]:
```
<Figure size 600x600 with 4 Axes>
```



[28]:
```
# Setup labels - we want our machine to output positive voltage to T shapes,
# our first 2 examples are Ts - so we'll set these values to +1, our second to
# examples are Js - so we'll set these to -1s
y=np.array([1,1,-1,-1])

#Reshape each example into a row, and add a 17th column for the bias term
X=np.hstack((examples.reshape(-1, 16), np.ones((len(y),1))))

#Initialized weights to zeros, this is equivalent to turning each knob to 12 o'clock
w = np.zeros(17)
lr=1.0 #Learning rate
```

[29]:
```
for i in range(1,10):
    yhat=np.dot(X[i%len(y)],w)
    if yhat<=0 and y[i%len(y)]>0:
        print(f"output is {yhat} but we want it to be {y[i%len(y)]}, updating weights.")
        w=w+lr*X[i%len(y)]
    elif yhat>0 and y[i%len(y)]<=0:
        print(f"output is {yhat} but we want it to be {y[i%len(y)]}, updating weights.")
        w=w-lr*X[i%len(y)]
    else:
        print(f"output is {yhat}, which has the same sign as our target {y[i%len(y)]},"
              f"machine is correct, not updating weights.")
```

[29]:
```
output is 0.0 but we want it to be 1, updating weights.
output is 7.0 but we want it to be -1, updating weights.
output is 2.0 but we want it to be -1, updating weights.
output is 3.0, which has the same sign as our target 1,machine is correct, not updating weights.
output is 11.0, which has the same sign as our target 1,machine is correct, not updating weights.
output is -7.0, which has the same sign as our target -1,machine is correct, not updating weights.
output is -15.0, which has the same sign as our target -1,machine is correct, not updating weights.
output is 3.0, which has the same sign as our target 1,machine is correct, not updating weights.
output is 11.0, which has the same sign as our target 1,machine is correct, not updating weights.
```

1.3 Two input perceptron - solvable case

Replicates Results of Figure 1.10, Task 1

[30]:
```
examples=np.array([[[-1,-1]],
                   [[-1,1]],
                   [[1,-1]],
                   [[1,1]]])

y=np.array([-1,1,1,1]) #we want our machine to output + when either or both switches are on

#Reshape each example into a row, and add a 3rd column for the bias term
X=np.hstack((examples.reshape(-1, 2), np.ones((len(y),1))))

#Initialized weights to zeros, this is equivalent to turning each knob to 12 o'clock
w = np.zeros(3)
lr=1.0 #Learning rate
```

[31]:
```
X
```

[31]:
```
array([[-1., -1., 1.],
[-1., 1., 1.],
[ 1., -1., 1.],
[ 1., 1., 1.]])
```

[32]:
```
w, y
```

[32]:
```
(array([0., 0., 0.]), array([-1, 1, 1, 1]))
```

[33]:
```
for i in range(1, 12): #Starting at index 1 instead of 0 results are a little more clear this way.
    yhat=np.dot(X[i%len(y)],w)
    print(f"step: {i}, current example: {X[i%len(y)][:2]}, current weights = {w}")
    if yhat<=0 and y[i%len(y)]>0:
        print(f"output is {yhat} but we want it to be {y[i%len(y)]}, updating weights.")
        w=w+lr*X[i%len(y)]
    elif yhat>0 and y[i%len(y)]<=0:
        print(f"output is {yhat} but we want it to be {y[i%len(y)]}, updating weights.")
        w=w-lr*X[i%len(y)]
    else:
        print(f"output is {yhat}, which has the same sign as our target {y[i%len(y)]},"
              f"machine is correct, not updating weights.")
```

[33]:
```
step: 1, current example: [-1. 1.], current weights = [0. 0. 0.]
output is 0.0 but we want it to be 1, updating weights.
step: 2, current example: [ 1. -1.], current weights = [-1. 1. 1.]
output is -1.0 but we want it to be 1, updating weights.
step: 3, current example: [1. 1.], current weights = [0. 0. 2.]
output is 2.0, which has the same sign as our target 1,machine is correct, not updating weights.
step: 4, current example: [-1. -1.], current weights = [0. 0. 2.]
output is 2.0 but we want it to be -1, updating weights.
step: 5, current example: [-1. 1.], current weights = [1. 1. 1.]
output is 1.0, which has the same sign as our target 1,machine is correct, not updating weights.
step: 6, current example: [ 1. -1.], current weights = [1. 1. 1.]
output is 1.0, which has the same sign as our target 1,machine is correct, not updating weights.
step: 7, current example: [1. 1.], current weights = [1. 1. 1.]
output is 3.0, which has the same sign as our target 1,machine is correct, not updating weights.
step: 8, current example: [-1. -1.], current weights = [1. 1. 1.]
output is -1.0, which has the same sign as our target -1,machine is correct, not updating weights.
step: 9, current example: [-1. 1.], current weights = [1. 1. 1.]
output is 1.0, which has the same sign as our target 1,machine is correct, not updating weights.
step: 10, current example: [ 1. -1.], current weights = [1. 1. 1.]
output is 1.0, which has the same sign as our target 1,machine is correct, not updating weights.
step: 11, current example: [1. 1.], current weights = [1. 1. 1.]
output is 3.0, which has the same sign as our target 1,machine is correct, not updating weights.
```

1.4 - Two input perceptron - unsolvable XOR case.

Replicates Results of Figure 1.10, Task 2

[34]:
```
examples=np.array([[[-1,-1]],
                   [[-1,1]],
                   [[1,-1]],
                   [[1,1]]])

y=np.array([-1,1,1,-1]) #machine should output + when either one, but not both switches are on

#Reshape each example into a row, and add a 3rd column for the bias term
X=np.hstack((examples.reshape(-1, 2), np.ones((len(y),1))))

#Initialized weights to zeros, this is equivalent to turning each knob to 12 o'clock
w = np.zeros(3)
lr=1.0 #Learning rate
```

[35]:
```
X
```

[35]:
```
array([[-1., -1., 1.],
[-1., 1., 1.],
[ 1., -1., 1.],
[ 1., 1., 1.]])
```

[36]:
```
w, y
```

[36]:
```
(array([0., 0., 0.]), array([-1, 1, 1, -1]))
```

[37]:
```
for i in range(1, 14): #Starting at index 1, instead of 0, results are a little more clear this way.
    yhat=np.dot(X[i%len(y)],w)
    print(f"step: {i}, current example: {X[i%len(y)][:2]}, current weights = {w}")
    if yhat<=0 and y[i%len(y)]>0:
        print(f"output is {yhat} but we want it to be {y[i%len(y)]}, updating weights.")
        w=w+lr*X[i%len(y)]
    elif yhat>0 and y[i%len(y)]<=0:
        print(f"output is {yhat} but we want it to be {y[i%len(y)]}, updating weights.")
        w=w-lr*X[i%len(y)]
    else:
        print(f"output is {yhat}, which has the same sign as our target {y[i%len(y)]}, \
              machine is correct, not updating weights.")
```

[37]:
```
step: 1, current example: [-1. 1.], current weights = [0. 0. 0.]
output is 0.0 but we want it to be 1, updating weights.
step: 2, current example: [ 1. -1.], current weights = [-1. 1. 1.]
output is -1.0 but we want it to be 1, updating weights.
step: 3, current example: [1. 1.], current weights = [0. 0. 2.]
output is 2.0 but we want it to be -1, updating weights.
step: 4, current example: [-1. -1.], current weights = [-1. -1. 1.]
output is 3.0 but we want it to be -1, updating weights.
step: 5, current example: [-1. 1.], current weights = [0. 0. 0.]
output is 0.0 but we want it to be 1, updating weights.
step: 6, current example: [ 1. -1.], current weights = [-1. 1. 1.]
output is -1.0 but we want it to be 1, updating weights.
step: 7, current example: [1. 1.], current weights = [0. 0. 2.]
output is 2.0 but we want it to be -1, updating weights.
step: 8, current example: [-1. -1.], current weights = [-1. -1. 1.]
output is 3.0 but we want it to be -1, updating weights.
step: 9, current example: [-1. 1.], current weights = [0. 0. 0.]
output is 0.0 but we want it to be 1, updating weights.
step: 10, current example: [ 1. -1.], current weights = [-1. 1. 1.]
output is -1.0 but we want it to be 1, updating weights.
step: 11, current example: [1. 1.], current weights = [0. 0. 2.]
output is 2.0 but we want it to be -1, updating weights.
step: 12, current example: [-1. -1.], current weights = [-1. -1. 1.]
output is 3.0 but we want it to be -1, updating weights.
step: 13, current example: [-1. 1.], current weights = [0. 0. 0.]
output is 0.0 but we want it to be 1, updating weights.
```

Note that our weights are stuck in a loop!

1.6 Compute Perceptron Error Across a Range of Values

Reproduces bowl shaped error surface in Figure 1.24

[38]:
```
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

# Linearly Separable case
X = np.array([[-1, -1], [-1, 1], [1, -1], [1, 1]])
y = np.array([[-1], [1], [1], [1]])
w0_range = np.arange(-1.9, 2.0, 0.2)
w1_range = np.arange(-1.9, 2.0, 0.2)
b = 1   # Bias term

# Initialize lists to store results
w0_points = []
w1_points = []
error_points = []

# Compute error for each weight combination
for w0 in w0_range:
    for w1 in w1_range:
        yhat = X[:,0]*w0 + X[:,1]*w1 + b  # Compute all 4 yhats at once
        error = np.mean((y.ravel() - yhat)**2)  # Mean squared error

        # Store the results
        w0_points.append(w0)
        w1_points.append(w1)
        error_points.append(error)

# Convert to numpy arrays
w0_points = np.array(w0_points)
w1_points = np.array(w1_points)
error_points = np.array(error_points)

# Create 3D scatter plot
fig = plt.figure(figsize=(12, 8))
ax = fig.add_subplot(111, projection='3d')

# Create scatter plot with color mapping
scatter = ax.scatter(w0_points, w1_points, error_points,
                     c=error_points, cmap='viridis',
                     alpha=0.6, s=20)

# Add labels and title
ax.set_xlabel('Weight w0')
ax.set_ylabel('Weight w1')
ax.set_zlabel('Mean Squared Error')
ax.set_title('Perceptron Error Surface\n(Linearly Separable Case)')
```

[38]:
```
Text(0.5, 0.92, 'Perceptron Error Surface\n(Linearly Separable Case)')
```



1.7 Train Small Network to Solve XOR Using LMS

[108]:
```
import torch
import torch.nn as nn
import torch.optim as optim

# XOR dataset
X = torch.tensor([[0, 0], [0, 1], [1, 0], [1, 1]], dtype=torch.float32)
y = torch.tensor([[0], [1], [1], [0]], dtype=torch.float32)

# Simple 2-layer network: 2 inputs -> 2 hidden -> 1 output
class XORNet(nn.Module):
    def __init__(self):
        super(XORNet, self).__init__()
        self.hidden = nn.Linear(2, 2)  # Hidden layer with 2 neurons
        self.output = nn.Linear(2, 1)  # Output layer
        self.sigmoid = nn.Sigmoid()

    def forward(self, x):
        x = self.sigmoid(self.hidden(x))
        x = self.sigmoid(self.output(x))
        return x

# Initialize network, loss, and optimizer
# Weights are chosen randomly, does not always converge - networks with more
# hidden units will converge more often
model = XORNet()

# Same squared error that Widrow and Hoff used, just taking the average across all 4 examples
# This is known as "batch" or "minibatch" gradient descent.
criterion = nn.MSELoss()

#Using the Adam optimizer here instead of vanilla SGD, SGD gets stuck when model is small.
optimizer = optim.Adam(model.parameters(), lr=0.1)

# Training loop
for epoch in range(1000):
    optimizer.zero_grad()
    outputs = model(X)
    loss = criterion(outputs, y)
    loss.backward()
    optimizer.step()

    if epoch % 1000 == 0:
        print(f'Epoch {epoch}, Loss: {loss.item():.4f}')

# Test the network
print("\nResults:")
with torch.no_grad():
    for i in range(len(X)):
        output = model(X[i:i+1])
        print(f"Input: {X[i].numpy()}, Target: {y[i].item()}, Output: {output.item():.4f}")
```

[108]:
```
Epoch 0, Loss: 0.2504

Results:
Input: [0. 0.], Target: 0.0, Output: 0.0097
Input: [0. 1.], Target: 1.0, Output: 0.9925
Input: [1. 0.], Target: 1.0, Output: 0.9899
Input: [1. 1.], Target: 0.0, Output: 0.0093
```



Figure 1.7 | We, of course, don't know exactly what Rosenblatt meant, but I think it's fair to say that modern neural networks can walk, talk, see, and write very much like humans. "Reproduce itself" is a bit subjective—modern models can certainly make copies of their own weights.

1. PERCEPTRON | EXERCISES

1.1 What do you think of Rosenblatt's predictions (Figure 1.7)? Wildly optimistic or incredible foresight? Do you think that all of Rosenblatt's predictions will eventually come true? If his predictions do come true, do you think that the enabling AI systems will still be based on these simple neuron models?

1.2 Why were the activation functions used in the 1950s and 1960s "all or nothing" binary step functions?

1.3 It's wild how close Widrow and Hoff were to modern gradient descent and backpropagation. In hindsight, switching from binary activation functions to a differentiable function like sigmoid seems pretty obvious—why do you think Widrow and Hoff didn't try this?



Targets for exercise 1.4



Figure 1.4 The perceptron learning rule is simple and powerful. If our target output is positive, but our machine's output is negative (Case 1), we turn up all the dials that are switched on, and turn down on the dials that are switched off (switched on dials in this case follow the T shape "Example Input"). We turn each knob by a predetermined fixed amount called the learning rate. If our target output is negative, but our actual output is positive (Case 2), we turn down all our knobs that are switched on, and turn up all our knobs that are switched off by our learning rate. If the Perceptron gets the answer right (Cases 3 and 4), we do not adjust our knobs.

1.4. Consider the target perceptron machine outputs on the previous page, where inputs of (-1, -1) and (-1,1) result in a negative output, and (1, -1) and (1,1) result in a positive output. Complete the missing rows in the table below, training a two-input perceptron to learn these targets, using the Perceptron Learning Rule. The Perceptron Learning Rule is summarized in Figure 1.4; here our machine has two inputs and includes a bias knob. The bias is "always switched on", so in Case 1 we turn up the bias knob by the learning rate, and in Case 2 we turn down the bias knob by the learning rate. To figure out the machine's output, we're using the equation $\hat{y} = w_1x_1+w_2x_2+b$, where x_1 and x_2 are input switch values, an on switch sets x=1, and an off switch sets x=-1. Assume a learning rate of α=1, and track the knob's values numerically. Step 1 in the table below falls under Case 2, so we turn down all the knobs that are switched on (just the bias knob, since it's always on), and turn up all the knobs that are switched off (w_1 and w_2) by our learning rate α=1, resulting in updated parameters of w_1=1, w_2=1, b=-1. Does the machine converge? Are these examples linearly separable?

Step	*Input* $x_1\ x_2$	*Target*	*Parameters* w_1	w_2	b	*Output Value* $\hat{y} = w_1x_1 + w_2x_2 + b$	*Correct?*	*Updated Parameters* w_1	w_2	b
1			0	0	0	$(0)(-1) + (0)(-1) + 0 = 0$	✗	1	1	-1
2			1	1	-1	$(1)(-1) + (1)(1) - 1 = -1$	✓	1	1	-1
3			1	1	-1					
4										
5										
6										
7										
8										

Step	*Input* $x_1\ x_2$	*Target*	*Parameters* w_1	w_2	b	*Output Value* $\hat{y} = w_1x_1 + w_2x_2 + b$	*Correct?*	*Updated Parameters* w_1	w_2	b
1	●●		0	0	0	$(0)(-1) + (0)(-1) + 0 = 0$	✗	1	1	-1
2	●●		1	1	-1					
3	●●									
4	●●									
5	●●									
6	●●									
7	●●									
8	●●									

1.5. Consider the target perceptron machine outputs below, where inputs of (-1, -1) and (1,-1) result in a negative output, and (-1, 1) and (1,1) result in a positive output. Complete the missing rows in the table above, training a two-input perceptron to learn these targets, using the Perceptron Learning Rule. The Perceptron Learning Rule is summarized in Figure 1.4; here our machine has two inputs and includes a bias knob. The bias is "always switched on", so in Case 1 we turn up the bias knob by the learning rate, and in Case 2 we turn down the bias knob by the learning rate. To figure out the machine's output, we're using the equation $\hat{y} = w_1x_1+w_2x_2+b$, where x_1 and x_2 are input switch values, an on switch sets x=1, and an off switch sets x=-1. Assume a learning rate of α=1, and track the knobs' values numerically. Step 1 in the table above falls under Case 2, so we turn down all the knobs that are switched on (just the bias knob, since it's always on), and turn up all the knobs that are switched off (w_1 and w_2) by our learning rate α=1, resulting in updated parameters of w_1=1, w_2=1, b=-1. Does the machine converge? Are these examples linearly separable?



Targets for exercise 1.5

	Input x			Target	Parameters $w^{(t)}$			Output Value		Updated Parameters $w^{(t+1)}$		
Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y} = w_1x_1 + w_2x_2 + b$	Correct?	w_1	w_2	b
1	-1	-1	1	-1	0	0	0	$(0)(-1) + (0)(-1) + 0 = 0$	✗	1	1	-1
2	1	-1	1	-1	1	1	-1					
3	-1	1	1	1								
4	1	1	1	1								
5	-1	-1	1	-1								
6	1	-1	1	-1								
7	-1	1	1	1								
8	1	1	1	1								

1.6. Let's repeat the problem we solved in Exercise 1.5, but streamline our computations. We showed a compact mathematical expression for the perceptron learning rule in Figure 1.29, but didn't explain how we arrived at this equation. Let's first write all three of our model's parameters as a vector w=[w_1, w_2, b]. Let's also write our input data as a vector, but add a third term x_b: x=[x_1, x_2, x_b],where x_b is always 1. Note that our model parameter vector w and input data vector x are now of the same length. Now, consider Step 1 in the table above, our machine's output $\hat{y}$ is 0, but our target is y=-1. Applying Case 2 of our Perceptron Learning Rule, we turn down all the dials that are switched on (b), and turn up all the dials that are switched off (x_1, x_2) by the learning rate α=1, resulting in new weights of w=[1, 1, -1]. Turning our knobs in this way is equivalent to subtracting: w-αx=[0, 0, 0]-[-1, -1, 1]=[1, 1, -1]. So instead of thinking about turning knobs, we can just add or subtract our learning rate times our data from our weights at each step (Figure 1.37). This approach is much easier to reason over and code up, especially when you don't have a real machine in front of you! Complete the table above using this approach.



Figure 1.37 | Perceptron Learning Rule written using Algebra. After some shuffling around, we can express the Perceptron Learning Rule using simple equations. Note that x_b is a "fake input" that's always set to 1, that makes our math easier.

	Input x			Target	Parameters $w^{(t)}$			Output Value		Updated Parameters $w^{(t+1)}$		
Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y} = w_1x_1 + w_2x_2 + b$	*Correct?*	w_1	w_2	b
1	1	-1	1	-1	0	0	0	$(0)(1) + (0)(-1) + 0 = 0$	✗	-1	1	-1
2	-1	1	1	-1	-1	1	-1					
3	-1	-1	1	1								
4	1	1	1	1								
5	1	-1	1	-1								
6	-1	1	1	-1								
7	-1	-1	1	1								
8	1	1	1	1								

1.7. Consider the target perceptron machine outputs below, where inputs of (1, -1) and (-1,1) result in a negative output, and (-1, -1) and (1,1) result in a positive output. Complete the table above, training a two-input perceptron to learn these targets, using the numerical approach to the Perceptron Learning Rule presented in Exercise 1.6. Assume a learning rate of α=1. Does the machine converge? Are these examples linearly separable?



Targets for exercise 1.7

1.8. Now that we've seen that the Perceptron Learning Rule is equivalent to iteratively adding or subtracting a scaled version of our examples to our model's parameters—this can help us begin to understand why the rule works. In our first learning step, we start from $w=[0,\ 0,\ 0]$, and add/subtract a scaled version of our first example $x=[x_1,\ x_2,\ x_b]$. Show algebraically that doing this is guaranteed to produce the output $\hat{y}$ we want for both Case 1 and Case 2 of the Perceptron Learning Rule.

	Input x			*Target*	*Parameters* $w^{(t)}$			*Output Value*		*Updated Parameters* $w^{(t+1)}$		
Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y} = w_1x_1 + w_2x_2 + b$	*Correct?*	w_1	w_2	b
1	-1	-1	1	-1	0	0	0	$(0)(-1) + (0)(-1) + 0 = 0$	✗	1	1	-1
2	-1	1	1	-1	1	1	-1					
3	1	-1	1	1								
4	1	1	1	1								
5	-1	-1	1	-1								
6	-1	1	1	-1								
7	1	-1	1	1								
8	1	1	1	1								

1.9 In Exercise 1.4, we trained a perceptron to match these targets, where inputs of (-1, -1) and (-1,1) result in a negative output, and (1, -1) and (1,1) result in a positive output. Let's now see how Rosenblatt's Perceptron Learning Rule compares to Widrow and Hoff's LMS algorithm. First, complete the table above to train a perceptron using The Perceptron Learning Rule. Assume a learning rate of α=1.



1.10 Let's solve the same problem from part 1.9, but using Widrow and Hoff's LMS algorithm. Remember that the LMS algorithm depends on having a measure of the system's error, which we defined as $E=(y\text{-}\hat{y})^2$. The LMS approach uses the same neuron model as Rosenblatt's Perceptron: $\hat{y} = w_1x_1+w_2x_2+b$. Complete the missing entries in the table on the following page, using the LMS update rule. Use a learning rate of α=0.2 (a learning rate of α=1.0 is too large and will "blow up"). Note that the quantities in the last three columns include dividing by two—this is just a book keeping step that allows us to keep our LMS formula simple (another way to think about this is that we're absorbing the factor of 2 from our calculus steps into the learning rate). These last three terms tell us how much to update each model parameter (e.g. to compute the new w_1 value in step 3, take the w_1 value from step 2 and subtract your computed value for $(\alpha/2)\partial E/\partial w_1$).

PERCEPTRON LEARNING RULE

$$w^{(t+1)} \leftarrow w^{(t)} \pm \alpha x$$

LEAST MEAN SQUARES (LMS)

$$w^{(t+1)} \leftarrow w^{(t)} + \alpha x(y - \hat{y})$$

Error Term

$$\frac{\partial E}{\partial w_1} = -2(y - \hat{y})x_1$$
$$\frac{\partial E}{\partial w_2} = -2(y - \hat{y})x_2$$
$$\frac{\partial E}{\partial b} = -2(y - \hat{y})$$

GRADIENT

Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y}$	$y-\hat{y}$	$E=(y-\hat{y})^2$	$\frac{\partial E}{\partial w_1}$	$\frac{\partial E}{\partial w_2}$	$\frac{\partial E}{\partial b}$	$\frac{\alpha}{2}\frac{\partial E}{\partial w_1}$	$\frac{\alpha}{2}\frac{\partial E}{\partial w_2}$	$\frac{\alpha}{2}\frac{\partial E}{\partial b}$
1	-1	-1	1	-1	0	0	0	0	-1	1	-2	-2	2	-0.2	-0.2	0.2
2	-1	1	1	-1	0.2	0.2	-0.2	-0.2								
3	1	-1	1	1					1.04	1.08	-2.08	2.08	-2.08	-0.21	0.21	-0.21
4	1	1	1	1	0.57	-0.17	-0.15	0.25	0.75	0.57	-1.5	-1.5	-1.5	-0.15	-0.15	-0.15
5	-1	-1	1	-1	0.72	-0.02	0	-0.7	-0.3	0.09	-0.6	-0.6	0.6	-0.06	-0.06	0.06
6	-1	1	1	-1	0.78	0.04	-0.06	-0.8	-0.2	0.04	-0.41	0.41	0.41	-0.04	0.04	0.04
7	1	-1	1	1	0.82	0	-0.1	0.72	0.28	0.08	-0.57	0.57	-0.57	-0.06	0.06	-0.06
8	1	1	1	1	0.88	-0.06	-0.04	0.78	0.22	0.05	-0.45	-0.45	-0.45	-0.04	-0.04	-0.04
9	-1	-1	1	-1	0.92	-0.01	0				-0.18	-0.18	0.18	-0.02	-0.02	0.02
10	-1	1	1	-1	0.94	0.01	-0.02	-0.95	-0.05	0	-0.1	0.1	0.1	-0.01	0.01	0.01
11	1	-1	1	1	0.95	0	-0.03	0.92	0.08	0.01	-0.15	0.15	-0.15	-0.02	0.02	-0.02
12	1	1	1	1	0.96	-0.02	-0.01	0.93	0.07	0	-0.13	-0.13	-0.13	-0.01	-0.01	-0.01

1.11 How does the LMS algorithm perform relative to the Perceptron Learning Rule? If we just consider the sign of $\hat{y}$ as we do in the Perceptron Learning Rule, does the LMS algorithm converge? How long does it take?

1.12 The Perceptron Learning Rule requires us to independently consider four different cases, but the LMS method just involves a single equation. How does the LMS "get away with a single equation"? Consider all four cases in your answer.

Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y}$	$y-\hat{y}$	$E=(y-\hat{y})^2$	$\frac{\partial E}{\partial w_1}$	$\frac{\partial E}{\partial w_2}$	$\frac{\partial E}{\partial b}$	$\frac{\alpha}{2}\frac{\partial E}{\partial w_1}$	$\frac{\alpha}{2}\frac{\partial E}{\partial w_2}$	$\frac{\alpha}{2}\frac{\partial E}{\partial b}$
1	-1	-1	1	-1	0	0	0	0	-1	1	-2	-2	2	-0.2	-0.2	0.2
2	1	-1	1	-1	0.2	0.2	-0.2									
3	-1	1	1	1				-0.04	1.04	1.08	2.08	-2.08	-2.08	0.21	-0.21	-0.21
4	1	1	1	1	-0.17	0.57	-0.15	0.25	0.75	0.57	-1.5	-1.5	-1.5	-0.15	-0.15	-0.15
5	-1	-1	1	-1	-0.02	0.72	0	-0.7	-0.3	0.09	-0.6	-0.6	0.6	-0.06	-0.06	0.06
6	1	-1	1	-1	0.04	0.78	-0.06	-0.8	-0.2	0.04	0.41	-0.41	0.41	0.04	-0.04	0.04
7	-1	1	1	1	0	0.82	-0.1	0.72	0.28	0.08	0.57	-0.57	-0.57	0.06	-0.06	-0.06
8	1	1	1	1	-0.06	0.88	-0.04	0.78	0.22	0.05	-0.45	-0.45	-0.45	-0.04	-0.04	-0.04
9	-1	-1	1	-1	-0.01	0.92	0	-0.91	-0.09	0.01	-0.18	-0.18	0.18	-0.02	-0.02	0.02
10	1	-1	1	-1	0.01	0.94	-0.02	-0.95	-0.05	0	0.1	-0.1	0.1	0.01	-0.01	0.01
11	-1	1	1	1	0	0.95	-0.03	0.92	0.08	0.01	0.15	-0.15	-0.15	0.02	-0.02	-0.02
12	1	1	1	1	-0.02	0.96	-0.01	0.93	0.07	0	-0.13	-0.13	-0.13	-0.01	-0.01	-0.01

1.13 The table above shows the LMS algorithm learning to match the targets shown to the right with a learning rate of α=0.2. Complete the missing entries. Does the LMS algorithm progressively make better predictions as it learns?



Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y}$	$y-\hat{y}$	$E=(y-\hat{y})^2$	$\frac{\partial E}{\partial w_1}$	$\frac{\partial E}{\partial w_2}$	$\frac{\partial E}{\partial b}$	$\frac{\alpha}{2}\frac{\partial E}{\partial w_1}$	$\frac{\alpha}{2}\frac{\partial E}{\partial w_2}$	$\frac{\alpha}{2}\frac{\partial E}{\partial b}$
1	1	-1	1	-1	0	0	0	0	-1	1	2	-2	2	0.2	-0.2	0.2
2	-1	1	1	-1	-0.2	0.2	-0.2									
3	-1	-1	1	1				-0.44	1.44	2.07	2.88	2.88	-2.88	0.29	0.29	-0.29
4	1	1	1	1	-0.25	-0.33	-0.15	-0.73	1.73	2.99	-3.46	-3.46	-3.46	-0.35	-0.35	-0.35
5	1	-1	1	-1	0.1	0.02	0.19	0.27	-1.27	1.62	2.55	-2.55	2.55	0.25	-0.25	0.25
6	-1	1	1	-1	-0.16	0.27	-0.06	0.37	-1.37	1.87	-2.74	2.74	2.74	-0.27	0.27	0.27
7	-1	-1	1	1	0.12	0	-0.33	-0.45	1.45	2.1	2.9	2.9	-2.9	0.29	0.29	-0.29
8	1	1	1	1	-0.17	-0.29	-0.04	-0.51	1.51	2.28	-3.02	-3.02	-3.02	-0.3	-0.3	-0.3
9	1	-1	1	-1	0.13	0.01	0.26	0.38	-1.38	1.89	2.75	-2.75	2.75	0.28	-0.28	0.28
10	-1	1	1	-1	-0.15	0.29	-0.02	0.41	-1.41	2	-2.83	2.83	2.83	-0.28	0.28	0.28
11	-1	-1	1	1	0.14	0	-0.3	-0.44	1.44	2.07	2.88	2.88	-2.88	0.29	0.29	-0.29
12	1	1	1	1	-0.15	-0.29	-0.01	-0.45	1.45	2.1	-2.9	-2.9	-2.9	-0.29	-0.29	-0.29

1.14 The table above shows the LMS algorithm learning to match the targets shown to the right with a learning rate of α=0.2. Complete the missing entries. Does the LMS algorithm progressively make better predictions as it learns?





Figure 1.30 Excerpt | But How Does it Work? How exactly does our simple network of three neurons solve XOR?

$$f(x_1, x_2) = \begin{cases} 1 & w_{21}^{(1)} x_1 + w_{22}^{(1)} + b_2^{(1)} > 0 \\ 0 & \text{otherwise} \end{cases}$$

1.15 In Figure 1.30 we claimed that a network of three neurons with binary step function activations can solve the exclusive or (XOR) problem, but we didn't explain exactly how. Consider the three neuron network on the following page. The network has nine total parameters, and the first six have been filled in for you. Can you find the three missing values that correctly solve XOR? A valid solution will produce $\hat{y}$>0 for x=[-1, 1] and x=[1, -1], and $\hat{y}$<0 for x=[-1, -1] and x=[1, 1]. Complete the missing $\hat{y}$ values using your solution.



$$f_1(x_1, x_2) = \begin{cases} 1 & w_{11}^{(1)} x_1 + w_{12}^{(1)} x_2 + b_1^{(1)} > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$f_2(x_1, x_2) = \begin{cases} 1 & w_{21}^{(1)} x_1 + w_{22}^{(1)} + b_2^{(1)} > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\hat{y} = w_1^{(2)} f_1 + w_2^{(2)} f_2 + b_1^{(2)}$$

$$w_{11}^{(1)} = 1$$
$$w_{12}^{(1)} = 1$$
$$b_1^{(1)} = 0.5$$
$$w_{21}^{(1)} = 1$$
$$w_{22}^{(1)} = 1$$
$$b_1^{(2)} = \text{-}1.5$$
$$w_1^{(2)} =$$
$$w_2^{(2)} =$$
$$b_2^{(1)} =$$

x_1	x_2	y	$w_{11}^{(1)} x_1 + w_{12}^{(1)} x_2 + b_1^{(1)}$	$w_{21}^{(1)} x_1 + w_{22}^{(1)} + b_2^{(1)}$	f_1	f_2	$\hat{y}$
-1	-1	-1	(1)(-1)+(1)(-1)+0.5=-1.5	(1)(-1)+(1)(-1)-1.5=-3.5	0	0	
-1	1	1	(1)(-1)+(1)(1)+0.5=0.5	(1)(-1)+(1)(1)-1.5=-1.5	1	0	
1	-1	1	(1)(1)+(1)(-1)+0.5=0.5	(1)(1)+(1)(-1)-1.5=-1.5	1	0	
1	1	-1	(1)(1)+(1)(1)+0.5=2.5	(1)(1)+(1)(1)-1.5=0.5	1	1	

1.16 Implement the Perceptron Learning Rule in your programming language of your choice. Test on the example in Exercise 1.4.

1.17 Implement the LMS algorithm in your programming language of your choice. Test on the example in Exercise 1.10.



"There was no guarantee you'd find a global optimum. Since you're bound to get stuck in local minima, it wasn't really worth investigating"

Geoffrey Hinton, future Nobel laureate, circa 1982
[Talking Nets p.376]

2. GRADIENT DESCENT

The misconception that almost stopped AI

This is the loss landscape of Meta's Llama 3.2 large language model (Figure 2.1).

Virtually all modern AI models learn by gradient descent. Visually, this looks like starting at a random location in our landscape and working our way downhill towards lower loss, higher performance solutions.

But how does our model avoid getting stuck in local valleys, like the one shown in Figure 2.2?

This question stopped many early AI pioneers in their tracks. Geoff Hinton, who would go on to win the Nobel Prize in 2024 for his work in AI, initially entirely dismissed training neural networks like Llama with gradient descent for exactly this reason.

Of course, as we now know, gradient descent actually works unbelievably well—what understanding was Hinton missing back in 1982, and what's wrong with the picture of gradient descent shown below in Figure 2.2?

In this chapter, we'll take a fresh look at how AI models learn with a visual-first approach.[1] We'll dig into exactly how our Llama model learns from real training examples, what our loss landscape can and can't show us, and ultimately see why gradient descent for large models looks more like falling into a wormhole than it does simply heading downhill. In Chapter 3, we'll build on this visual understanding with some hands-on mathematics.

Chapter 2 Video

Figure 2.1 | (Previous Page) Loss Landscape. Two views of the loss landscape of Meta's Llama 3.2-1B large language model. As we'll see in this chapter, loss landscapes give us a fascinating but limited view into how models learn. The upper surface uses a colormap to show the values of the loss surface, where blue/purple regions correspond to lower loss, higher-performing combinations of model parameters, and yellow regions correspond to poor-performing combinations of parameters. The lower figure shows the same surface in wireframe and highlights the two slices of the loss landscape we show in Figure 1.2.

Figure 2.2 | (Below) Gradient Descent. A closer look at the two slices of the loss landscape shown in Figure 2.1. The α and β values control the amount we update our model's weights in two randomly chosen directions in the model's parameter space (more on this later). The vertical axis corresponds to cross entropy loss; lower points on these curves correspond to higher-performing combinations of model parameters. When our model learns, it starts in a random spot on our landscape and works its way downhill. But how do we avoid getting stuck in local minima?



1 We'll dive in pretty quickly to cutting-edge "frontier models" in this chapter. We think this works better than building up slowly to the modern cutting-edge stuff at the end of the book, but this approach can be a little overwhelming if you're new to the field. We'll fill in gaps as we go, and the exercises and the supporting code are also a great way to get additional context & understanding!



Figure 2.3 | LLMs are Next Token Predictors. Given the input, "Llama is a large language", this text is broken into six tokens, which are passed into the model. The model predicts the next token, in this case token 1646, which corresponds to the word "model". Figure 2.4 goes more deeply into how exactly LLMs make predictions.

0	!	1620	final	12350	razy
1	"	1621	""	12351	aser
2	#	1622	Key	12352	\Database
3	$	1623	LO	12353	alendar
4	%	1624	del	12354	_ass
5	&	1625	pty	12355	;}
6	'	1626	thing	12356	vertex
7	(	1627	26	12357	inecraft
8	)	1628	And	12358	Warning
9	*	1629	run	12359	argo
10	+	1630	X	12360	actor
11	,	1631	ym	12361	Instead
12	-	1632	.app	12362	Using
13	.	1633	very	12363	Self
14	/	1634	ces	12364	@interface
15	0	1635	_N	12365	speaking
16	1	1636	ared	12366	Paris
17	2	1637	ward	12367	LICENSE
18	3	1638	list	12368	.node
19	4	1639	ited	12369	Food
20	5	1640	olog	12370	EIF
21	6	1641	itch	12371	Bi
22	7	1642	Box	12372	.Start
23	8	1643	ife	12373	IB
24	9	1644	33	12374	university
25	:	1645	ac	12375	254
26	;	1646	model	12376	Header
27	<	1647	mon	12377	.product
28	=	1648	way	12378	409

Figure 2.4 | Some Tokens. Here are some of the 128,256 tokens in Llama's vocabulary. Token indices are in brown. Yeah, they can be kind of random. Most tokenizers are learned and roughly based on the most frequent combinations of characters found in training texts.

Let's begin by experimenting with a real Large Language Model (LLM): Meta's Llama 3.2 1.2 billion parameter model. Given a sequence of text, models like Llama and ChatGPT are trained to predict the word or word fragment, known as a token, that comes next. When we pass in the text "*The capital of France is*" into Llama, this text is first tokenized into five tokens, each represented by a single number. For each input token, our Llama model returns a prediction of what token will come next in the form of a vector of probabilities (Figure 2.5). So when we pass in the five tokens for "*The capital of France is*", our model returns five vectors, each of length 128,256, with one predicted probability value for each of the 128,256 tokens in Llama's vocabulary. Our fifth vector has a maximum probability of 0.39 at index 12,366, which corresponds to the token for Paris—so our model is assigning a 39% probability to Paris as the token that follows "*The capital of France is*". The next most likely token according to the model is the word "*a*" with a probability of 8.4%; this could lead to sentences like "*The capital of France is a beautiful place to visit*". Note that when generating new text, we only make use of Llama's final output vector.

Now, to actually train Llama to make predictions, we need some way to measure how well the model is predicting the correct next token in the training text. Let's assume that the next word in our training text is "*Paris*", and we want to train Llama to predict this token. Given that, according to the training text, the correct next token is "*Paris*", a perfect model would return a probability of 1.0 for the "*Paris*" token and a probability of 0.0 for all other tokens. This line of thought leads to a simple error metric—we could just set:

$$Error = 1 - P_i \qquad \text{L1 Loss}$$

where P_i is the model's predicted probability of the correct next token. This error measure is known as the L1 loss. As shown in Figure 2.5, our model's final output vector contains $P_{12,366} = P(\text{Paris}) = 0.39$, making our L1 loss=1-0.39=0.61 in this example. As shown in Figure 2.6, L1 loss reaches 0 when our model is 100% confident in the correct next token.

L1 loss plays a critical role in learning. However, it turns out that models are able to learn more effectively if we instead use a function called cross-entropy loss:

$$Error = -\ln(P_i) \qquad \text{CROSS-ENTROPY LOSS}$$

This ends up looking similar to the L1 loss (Figure 2.6)—the key difference here is that as our model becomes less and less confident in the right answer, cross-entropy loss shoots up, penalizing our model more.

Large Language Model training is entirely driven by reducing this cross-entropy loss.



Figure 2.5 | A Large Language Model Generating Text. Given the input text "*The capital of France is*", we first break this phrase into individual tokens. In this case, each word corresponds to a single token; however, this will not always be the case (e.g. in Figure 2.3, "*Llama*" is broken into one token for "*L*" and one for "*lama*"). Each token is then passed into our Llama model, which returns a vector of length 128,256 for each input token. Each vector contains Llama's estimated probabilities for what token will come next. The fifth output vector (purple) has a maximum value of 0.39 in position 12,366, meaning Llama is assigning a probability of 39% to the next token of "*Paris*", following "*The capital of France is*". The next most likely token is "*a*" with a probability of 8%; this could lead to completions like "*The capital of France is a beautiful place to visit.*" Interestingly, modern LLMs do not always go with the most probable next token—these can lead to unoriginal responses—but instead sample their outputs probabilistically.

Model's Probability of Correct Next Token	P_i	1.0	0.9	0.8	0.7	0.6	0.5	0.4	0.3	0.2	0.1	0.0
L1 Loss	$1-P_i$	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Cross-Entropy Loss	$-\ln(P_i)$	0.0	0.11	0.22	0.36	0.51	0.69	0.92	1.20	1.61	2.30	∞

Figure 2.6 | Cross-entropy loss is not so different from L1 loss, unless you're really wrong. L1 loss and cross-entropy loss give us different ways of measuring our model's performance and guiding the learning process. Both metrics are 0 when our model is 100% confident in the correct next token. As our model's confidence in the correct answer approaches 0, L1 loss linearly moves to its maximum value of 1.0, while cross-entropy gets a little angrier.



Figure 2.7 | But how do we train it? Most large language models are trained using the cross-entropy loss. When training, we can simultaneously train Llama to predict the next token given each subsequence of inputs. We can train Llama to predict "*capital*" given "*The*", "*of*" given "*The capital*", "*France*" given "*The capital of*", and "*is*" given "*The capital of France*". Typically we would compute the cross-entropy with respect to each target and average the results, but here we will just focus on training our model to predict the single next token of "*Paris*". Note that at each position, Llama uses all previous tokens to make a prediction, but not future tokens. For example, to generate the orange third output vector in Figure 2.5, the model does not make use of the inputs "of", "*France*", or "*is*".



Figure 2.8 | Deep Learning Models are Big Functions. In this chapter we won't worry too much about exactly how our model works; instead, we'll think of the model mostly as a function that takes in some input text X and uses its parameters θ to predict what text comes next. The learning process is all about adjusting θ so $f(X,\theta)$ returns the output we want.

Now, how do we actually use this loss to make our model better, and how can we visualize the process?

Our model's current parameters give a probability of 0.39 for a next token of "*Paris*", leading to a cross-entropy loss of $-\ln(0.39)=0.94$ (Figure 2.7). Note that we would typically compute our loss at each token position and average the results across our training text, but for now let's focus exclusively on training our model to be more confident in a text token on "*Paris*" at the fifth position. So our total cross-entropy loss is 0.94. Now how do we adjust our model parameters to increase the model's confidence in Paris, and bring down this loss?

Our Llama model follows a fairly standard transformer architecture—it's composed of 16 layers, each containing an attention and multilayer perceptron compute block. In this chapter, we won't be too concerned with how these layers work—a helpful (and increasingly true) mental model here is to think of our whole transformer as a single function f that takes in our input text X, and uses its parameters, θ, to compute the next token probabilities. We'll explore how our model's output changes as we change our model's parameters, and as we'll see, doing this in a structured way is precisely how these models learn.

Let's begin by visualizing the impact of just one of our 1.2 billion model parameters on our model's output. The multilayer perceptron compute block in the model's final layer has around 50 million total parameters, we'll pick out one of these parameters, and see how it impacts our model's final output.[2]

2 The exact parameter is layers.mlp.down_proj.weight[395, 1788], chosen due to the high gradient. See supporting code 2.2 for a detailed walkthrough. Not all parameters will have this large of an impact on our model's output for this input!



Figure 2.9 | Testing Parameter Values. Modifying a single parameter changes our model's confidence in a next token of *"Paris"*, given the input text *"The capital of France is"*. Our parameter's initial value (in our trained Llama model) is -0.007. Increasing our parameter increases our model's confidence in a next token of *"Paris"*. Plotting a range of values, we see a nice parabolic curve. Note that all parameters will not impact our model's confidence in *"Paris"* in the same way.

Our parameter's current value is -0.007 (Figure 2.9). Let's decrease this parameter's value by 0.01, rerun our input text through our model, and see how our predictions and loss change. Our model's predicted probability of a final token of Paris moves down a little from 0.3916 to 0.3901. Testing a change in the other direction, increasing our parameter's value by 0.01, moves up our model's confidence a little to 0.3930. So for this single parameter and for this example text, we now know that we can make our model more confident in the right answer by *increasing* this parameter's value.

But by how much should we increase it? Can we make our model more confident in the right answer by further increasing this parameter? Extending and visualizing this idea, we can test more values and plot our model's output probability for a range of values of our parameter and see a nice parabola-ish looking curve as a function of the value of this single parameter (Figure 2.9).

As we've seen, our cross-entropy loss is just the negative logarithm of these output probability values. Computing and visualizing these loss values, we get a flipped version of our parabola. These results suggest that we can maximize our model's predicted probability of the correct answer and minimize our loss by setting our parameter to around 1.59. We could then walk through each parameter one at a time, applying the same analysis, and setting each parameter to minimize our output loss.



Figure 2.10 | Eh? If 1.59 is the best value for θ_1 (Figure 2.9), can we just step through our parameters one at a time and find the best value for each?



Figure 2.11 | Can we learn one parameter at a time? One way we can try to train our Llama model to be more confident in a next token of *"Paris"* is by tuning one parameter at a time. However, after we update our second parameter θ_2, when we return to our first parameter θ_1, the shape and minimum of our curve change! This means there is a new, better minimum value for θ_1, and to train our model we would have to jump back and forth between parameters again and again.



Figure 2.12 | The Full Picture (For two parameters). We can make sense of the behavior we saw in Figure 2.11 by plotting our cross-entropy loss across a range of θ_1 and θ_2 values. The curve in Step 1 of Figure 2.11 is just one slice of our surface, and when we update θ_2 in Step 2, we move to a new slice of our surface, changing the optimal θ_1 solution. So training our model one parameter at a time isn't going to work.

Let's see visually why this doesn't work. After setting our first parameter, θ_1, to a value of 1.59 to maximize our model's confidence in the Paris token and minimize our loss, if we move to a second parameter, we can again test a range of values and set this second parameter, θ_2, to the value that minimizes our loss—in this case 1.76.

Now, here's the problem—if we return to our first parameter, which we already tested and set to a value of 1.59 to minimize loss, and run the same analysis, the shape of our curve changes! Now it looks like a value of 1.11 will actually minimize our loss.

The impacts of each parameter on our model's outputs are not independent.[3]

Changing the value of our second parameter changes the shape of our first loss curve, and vice versa—so we aren't really going to be able to learn effectively by tuning one parameter at a time like this. We can see this visually by testing how our loss changes as we vary our parameter values together, testing a grid of values and plotting our loss for each combination of parameters as the height of a surface, as shown in Figure 2.12.

It's now straightforward to see what went wrong in Figure 2.11—if we only consider our first parameter, θ_1, we're effectively looking at a slice shown in curve A, moving to the bottom of this curve, and then tuning our second parameter, we're moving along our blue curve B. When we move to the bottom of this second curve, we reach a new location on our loss landscape, where we're no longer at the bottom of a valley in the direction θ_1. And since the loss curve for each of our parameters depends on the values of the other 1.2 billion parameters, this is not an effective way to learn! In this two-parameter visualization, it is easy to see which combination of parameter values minimizes overall loss, we just need to set our two parameters to the values at the bottom of the bowl—we now have an optimal solution in both directions, with respect to these two parameters (Figure 2.13).

Of course, it's not just these two parameters that are coupled—effectively all 1.2 billion parameters of the model are, meaning our loss landscape is 1.2 billion-dimensional, and it's computationally impossible to probe all combinations of parameters as we did with our two test parameters. If we test 10 values for each parameter, testing how two parameters vary together as we just did requires 10^2=100 evaluations, testing three parameters together is equivalent to testing all 10^3=1,000 values in a $10 \times 10 \times 10$ cube, and testing all 1.2 billion model parameters like this would require an unfathomable $10^{1,200,000,000}$ calculations!

We need a far more scalable approach. Returning to our two-dimensional loss landscape of Figure 2.12, is there a way to find the bottom of the bowl without computing the height of every point in the landscape?

3 If the impacts of each paratemeter were independent, our model would actually not be very powerful!



Figure 2.13 | Isn't this actually easy? If we only need to worry about finding the best values for θ_1 and θ_2, we can just pick the lowest point on our bowl. But how will this method of testing all combinations of parameter values scale?



Figure 2.14 | This is not going well. Sure, we can easily pick out the bottom of our bowl in Figure 2.13, but this is just for 2 out of 1.2 billion parameters! The size of our search space explodes as we add parameters.

Figure 2.15 | The Concept of Gradient Descent. If you are lost in a forest on a mountain, trying to find your way to the valley below without a map, a pretty reasonable thing to do is just keep heading downhill, even if you can't see the valley. This image was generated with a transformer model not too different from the Llama model we're covering in this chapter. See Chapter 9 for more on image and video generation.



Figure 2.16 | Gradient Descent. Instead of computing the height of every point in our bowl, it turns out we can efficiently compute the steepness or slope in the direction of each of our model's parameters and put these slopes together into a vector called the gradient (yellow) that can guide us to the bottom of our bowl, step by step. Note that we need to recompute our components (red and blue arrows) at each step, and that technically our gradient points exactly uphill, and we move in the opposite direction—we'll see why this is the case in Chapter 3. Now, what does this process look like in the 1.2 billion-dimensional space that our Llama model learns in?

If you were lost in a forest on a mountain, trying to find your way to the valley below without a map, a pretty reasonable thing to do is just keep heading downhill, even if you can't see the valley.

We can effectively do this mathematically. For each parameter, instead of computing the loss across a range of values, we can compute the slope of the loss curve—telling us which way is downhill in each direction and how steep the descent is. As we'll see in Chapter 3, it turns out we can compute these slopes very efficiently—we won't even need to compute the actual values on our loss curve.

From here, we can put our slopes together into a single vector called the gradient, which acts like a little compass that points us downhill. Note that technically the gradient points uphill, and we move in the opposite direction to go downhill—we'll see why this is the case in Chapter 3. The idea now is to take small iterative steps downhill, where after each step we recompute the gradient to guide our next step—this is known as gradient descent and is how virtually all modern AI models learn.

By taking small steps downhill, in practice we're often able to find very good solutions, even in very high-dimensional loss landscapes that we could never fully explore computationally.



Figure 2.17 | Here's the plan. We can't see 1.2 billion-dimensional space, but we can probe it. Given a vector of starting parameters θ_0, we can generate a vector of random numbers R of the same length (1.2 billion values). From here we can add small multiples of our random vector R to our original parameters to take small steps in this random direction in parameter space and measure our error at each step.



Figure 2.19 | The math that makes our landscape. The 3D loss landscapes in Figure 2.18 are created by taking steps in two randomly chosen directions. Here α and β are scalars, and θ_{mod}, θ_0, R_1, and R_2 are vectors of length 1.2 billion. To generate our landscape, we sweep over a range of α and β values, recomputing our loss for each combination of values.

It's of course a little difficult to visualize the 1.2 billion-dimensional loss landscape of our large language model and what going downhill really looks like in this high-dimensional space.

One approach we can try here is to choose a random direction in our high-dimensional space, and measure our loss as we take small steps in this direction.[4] Note that here, choosing a random direction is equivalent to generating 1.2 billion random numbers, one for each model parameter, and taking a small step in this direction means multiplying these 1.2 billion random numbers by a small scaling factor and adding these scaled random numbers to our weights and then recomputing our loss (Figure 2.17). As we move further in our random direction by increasing our scaling factor, we can recompute our loss at each step and see how this combination of model weights impacts our loss.

Note that this is almost exactly what we do when training our model with gradient descent, except here we're choosing our direction randomly, instead of using the downhill direction from our gradient computation. Choosing a random direction like this will hopefully give us a broader feel for what our loss landscape looks like.

The two "Before Training" line plots at the top of Figure 2.18 show the loss landscape of our Llama model before training for two randomly chosen directions. Exploring our high-dimensional loss landscape in this way reveals interesting structures—with hills, valleys, cliffs, and plateaus. The second column of plots shows the loss landscape for our model after training. With our trained model, we can clearly see the lower loss valley the model has found through training at α=0 and β=0.[5] Finally, it can be interesting to confine our random directions to certain layers; the final pair of plots shows what our loss landscape looks like as we explore two random directions in the first 8 layers of our trained model's total 16 layers.

We can take this approach one step further by putting two of these random directions together on a 2D grid and computing our loss for combinations of steps in our two random directions. We can now visualize our loss landscape as we explore these two random directions together, as shown in the three bottom panels of Figure 2.18. Now imagine navigating this loss landscape from the perspective of our gradient descent algorithm. Before training, our model's parameters are randomly initialized, meaning we're effectively dropped into a random location in this landscape. From here, our job is to navigate our way to the bottom of our valley—ideally the global minimum around α=0 and β=0, but our only guide is the gradient, which only tells us which way is downhill on the tiny local part of the landscape we're currently on!

4 The idea for this approach comes from a great 2018 paper "Visualizing the loss landscape of neural nets" see [Li et. al. 2018]

5 We're using positive and negative values for α and β, moving us forward and backwards in our randomly chosen directions





Figure 2.18 | Building the landscape. The top row of plots shows different ways to explore our loss landscape. The input text to our model is "The capital of France is" as we set up in Figure 2.9. We're measuring the model's cross-entropy loss when predicting a next token of "Paris"—so lower loss values mean our model is more confident in "Paris". Note that α=0 and β=0 correspond to unmodified model parameters. We're bringing together the two final plots to create our 3D landscape; these layers are created by modifying the first 8/16 layers in our model. The choice of these layers is mainly aesthetic; we could generate landscapes by modifying all 16 layers (middle column of plots), but these landscapes become so noisy that it's difficult to see what's going on. The contour plot to the right shows an overhead view of our landscape, where each continuous white line corresponds to a constant value for the loss function, meaning anywhere you see a closed empty loop is a local minimum (at this resolution). How does gradient descent avoid getting stuck in all these valleys?

Figure 2.20 | What we might expect to happen. Since our 2D loss landscape is just a projection of a much higher-dimensional space, maybe when we trained our model we were able to just "glide" over local minima nicely? The dotted red "slice" in the overhead view above is shown in profile to the right, and a hypothetical path for our gradient descent algorithm to take is shown in the overhead view, in profile to the right, and in 3D below. But this is not what actually happens when we train our model!





A baffling fact about modern AI, and one of the reasons many early AI researchers dismissed this approach[6], is that there's no guarantee that gradient descent will find the best or even a good solution in these high-dimensional loss landscapes—our Llama loss landscape has many local minima where gradient descent potentially could get stuck.

But remember, even with our clever random direction probing trick, we're still looking at a two-dimensional shadow of a 1.2 billion-dimensional landscape. If we actually run gradient descent and train our model on our example text, we might imagine that learning looks like a point representing our parameters working its way downhill in the landscape, and maybe the fact that the real optimization process is higher dimensional means that gradient descent can avoid getting stuck in a local minimum (Figure 2.20).

6 Including Hinton! [Talking Nets 1999 p. 376]





Figure 2.21 | What actually happens. Instead of "gliding over local minima" as we hypothesized in Figure 2.20, when we actually train our model starting from the location of the red dot, a new low-loss "wormhole" appears out of nowhere! The profile plot to the left shows profiles of our loss landscape (red dotted line in the overhead view) as our model learns. So instead of working its way over to the global minimum, gradient descent just seems to pull its own solution out of thin air. What's going on here?

This was roughly the image I had in my head when I started working on this topic—but after some experimentation I realized that this is really not what happens as our model learns. The reason is that as soon as we take even a small step in the full high-dimensional space of our model's parameters, our two-dimensional visualization of the landscape changes dramatically.

Visually, as we run gradient descent, it almost looks like a wormhole opens up in our landscape, quickly landing our parameters in a very low loss valley that basically comes out of nowhere. And this happens before our little dot really even has a chance to go anywhere on our landscape—it does move a little towards our global minimum—but not enough to really notice in our visualization.

What exactly is going on here?





Training Example 1
The Lords continued to suggest amendments to money bills over which it had no right of veto and in several instances these were accepted by the Commons. These included the China Bill 1925 and the Inshore Industry Bill 1947. The use of the Lords' now temporary veto remains a

During the over, another rising Larwood delivery knocked the bat out of Woodfull's hands. He battled it out for 89 minutes, collecting more before Allen bowled him for 22. Later in the day, the English team manager Pelham Warner visited the Australian dressing room to express his

The common starling is a highly gregarious species, especially in autumn and winter. Although flock size is highly variable, huge, noisy flocks—may form near roosts. These dense concentrations of birds are thought to be a defence against attacks by birds of prey such as pere

In 1995, England topped their pool and defeated Australia 25 – 22 at the quarter final stage before being beaten by the All Blacks in the semi final. Their third fourth place play off match against France was lost 19 – 9.

Figure 2.22 | What happens to our landscape when we train on batches of text? In Figure 2.21, we trained on a single short phrase. In this figure we're taking two gradient descent steps on the wikitext dataset and updating our loss landscape as we go. The leftmost contour plot shows Llama's loss landscape when evaluated on the text shown in "Training Example 1". We're now evaluating our model on its ability to predict each token based on the tokens that come before (within each batch of 4 examples). Since our overall loss is averaged across all tokens in the example, our landscape is much smoother than the landscape we saw in Figure 2.21. The magenta line on the leftmost contour plot is visualized from a side view below. The magenta dot shows where we begin our optimizer; this starting point is also shown as a brown line in the lower plot. After one gradient descent step on this training example, our loss landscape moves down around our starting point, showing our model learning to increase its confidence (on average) in the tokens in the training example, as shown in the second loss landscape panel and dotted magenta line. In the figures on the following page, we move to a second training example. Our loss landscape changes (before we even take a training step), because we're now evaluating our model on new input text. The value of our loss at our starting point goes up a bit (solid blue curve) when we switch to Example 2 and then comes down after taking a training step on this example (dashed blue curve). So when we train on longer examples (that are closer to how modern LLMs are trained), we still see our loss landscape shifting and moving down around our starting point, but not as dramatically as the "wormhole" we saw with our single short training phrase.

Training Example 2
The evacuation by train from Romani was carried out in a manner which caused much suffering and shock to the wounded. It was not effected till the night of August 6 – the transport of prisoners of war being given precedence over that of the wounded – and only open trucks without straw were available. The military

The situation in Europe remained volatile into 1794. Off Northern France, the French Atlantic Fleet had mutinied due to errors in provisions and pay. In consequence, the French Navy officer corps suffered greatly from the effects of the Reign of Terror, with many experienced sailors being executed, imprisoned or dismissed from the service

In the general election, Nixon emphasized " law and order, " positioning himself as the champion of what he called the " silent majority. " Running well ahead of his opponent, incumbent Vice President Hubert Humphrey, his support slipped in the polls following his refusal to in presidential debates, and following an

Gold did not again circulate in most of the nation until 1879 ; once it did, the gold dollar did not regain its place. In its final years, it was struck in small numbers, causing speculation by. It was also in demand to be mounted in jewelry. The regular issue gold



To create the "wormhole" visualization in Figure 2.21, we're only training on the single phrase *"The capital of France is Paris"*[7]—the newly learned parameters quickly boost our model's probability for a next token of "*Paris*" to a max value approaching 1.0 and drop our loss to essentially zero. Of course, just training a large language model on a single short phrase is not how these models are trained in practice. Let's look at the same visualization, but where our model is instead trained on examples from the Wikitext dataset (Figure 2.22)—we'll use a batch size of four, meaning we're learning from four different text examples at once; this is much closer to how Large Language Models are trained in practice.[8] Our loss landscapes become smoother—this makes some sense because our loss is averaged across all the tokens in our batch. When we take a gradient descent step, we see our loss landscape move down around our starting point, just as we saw in our Paris example—this shows our model reducing the loss and performing better on the examples in this batch. When we switch to the next batch of data, the shape of our loss landscape changes, and some of the gains we made from the last batch disappear. Step by step like this, our gradient descent algorithm will work its way to a good solution, and our landscape visualization shifts as our model learns.

7 And only measuring our model's error on predicting *"Paris"*.
8 Batch size = 4, max token length = 64, wikitext-2-v1 dataset

In both the Paris and Wikitext examples, our visualized loss landscape changes as we learn, because we're effectively looking in our randomly chosen directions from a new vantage point in high-dimensional space.

This is analogous to our exploration of our model's loss earlier as we varied a single parameter and then varied two parameters together (Figure 2.11). Let's imagine for a moment that we're only able to visualize our loss with respect to one of our two parameters. Our loss may look something like the red "A" curve in Figure 2.23 with respect to our first parameter θ_1. Now if we run gradient descent, we're moving in the full 2D space of both parameters, so our entire curve with respect to our first parameter changes—we're moving to a different slice of our full 2D loss surface.

If there happens to be a nice valley close to us, but the only way to get there is to move in the direction of our second parameter θ_2, we won't see it at all in our initial 1D visualization with respect to our first parameter, and when we find it with gradient descent, it will appear to come out of nowhere in our 1D visualization, very much like our wormhole that came out of nowhere in our full visualization.

The wormhole example is a bit extreme because we're only training on a single short phrase, but it does tell us something interesting about the high-dimensional loss landscapes we're trying to visualize and understand—in this example there are very good solutions very close to us in high-dimensional space—we just can't see them until we compute our full high-dimensional gradient and move in that direction.

"Anyway, after over a year of fiddling around with such things to try to make them work properly, I finally decided they [Boltzmann Machines] really weren't going to work. In despair, I thought, 'Well, maybe, why don't I just program up that old idea of Rumelhart's and see how well it works on some of the problems we've been trying?'"

Geoffrey Hinton
[Talking Nets p. 377]

When Geoff Hinton did eventually try out gradient descent, after getting stuck with another approach called Boltzmann machines, he tested it on a model with around 50 parameters—and was shocked by how well it worked. For gradient descent to become fully stuck in a local minimum, it would have to get stuck in every dimension at once—and the chances of this happening become smaller and smaller as we add more and more parameters.

For simple two-parameter models, as we see in problems like linear regression, loss landscapes give us a complete picture and can provide helpful intuition for how these models learn. However, as our models become more and more complex with more and more parameters, our loss landscape visualizations become a more and more distant shadow of the model's true learning process.

In Chapter 3, we'll see how, although our ability to visualize these landscapes becomes more and more limited as we add more and more dimensions, our mathematics has no problem operating in these incredibly high-dimensional landscapes.



Figure 2.23 | Wormholes Explained. The top two plots are repeated from Figures 2.21 and 2.22. Our full loss landscapes in Figures 2.21 and 2.22 are 2D visualizations of a 1.2 billion-dimensional object. Let's consider a one-dimensional visualization of a two-dimensional loss landscape. Here, curves A, B, C, and D show slices of our full two-dimensional landscape, just as our full loss landscapes in Figures 2.21 and 2.22 are "slices" of our full 1.2 billion-dimensional landscape. If we were only able to visualize the loss landscape in one of our two dimensions (θ_1), and there happens to be a nearby minimum, but the only way to get to this minimum is to move in the θ_2 direction, this minimum will appear to "come out of nowhere" in our θ_1 plot. Analogously, there are often good solutions close to us in the high-dimensional space of our model's parameters; we just can't see them until we follow our gradient toward these solutions.

2.1 Load Llama and Pass Sample Text Through

[1]:
```
import torch
from torch.nn import functional as F
from transformers import AutoModelForCausalLM, AutoTokenizer
import numpy as np
import matplotlib.pyplot as plt
from tqdm import tqdm
```

[2]:
```
device='cuda'
model_id = "meta-llama/Llama-3.2-1B"
```

[3]:
```
model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
model.eval();
```

[4]:
```
text = "The capital of France is"
inputs = tokenizer(text, return_tensors="pt").to(device)
```

[5]:
```
inputs
```

[5]:
```
{'input_ids': tensor([[128000, 791, 6864, 315, 9822, 374]], device='cuda:0'), 'attention_mask':
tensor([[1, 1, 1, 1, 1, 1]], device='cuda:0')}
```

[6]:
```
#Tokenizer prepends a speical <|begin_of_text|> token
for input_token_index in inputs['input_ids'].view(-1):
    print(input_token_index.item(), tokenizer.decode(input_token_index))
```

[6]:
```
128000 <|begin_of_text|>
791 The
6864 capital
315 of
9822 France
374 is
```

[7]:
```
#Pass inputs into model
with torch.no_grad():
    outputs=model(inputs["input_ids"])
```

[8]:
```
#One output vector for each input token, 128256 token vocabulary
outputs.logits.shape
```

[8]:
```
torch.Size([1, 6, 128256])
```

[9]:
```
probabilities=F.softmax(outputs.logits, dim=-1) #Convert to probs (more on this in Ch. 3)
probabilities.shape
```

[9]:
```
torch.Size([1, 6, 128256])
```

[10]:
```
#Just look at final vector to see what text the model predicts next
top_probs, top_indices = torch.topk(probabilities[0, -1, :], 10)
for i, (prob, idx) in enumerate(zip(top_probs, top_indices), 1):
    print(idx.item(), round(probabilities[0, -1, idx].item(),5), tokenizer.decode([idx]))
```

[10]:
```
12366 0.39153 Paris
264 0.08419 a
279 0.0704 the
832 0.03096 one
1101 0.03061 also
2162 0.02528 home
3967 0.02462 known
539 0.01659 not
459 0.01241 an
7559 0.01172 located
```

[11]:
```
# For comparison, here's the top results for the 4th position,
# these are the models predictions after "The Capital of"
top_probs, top_indices = torch.topk(probabilities[0, 3, :], 10)
for i, (prob, idx) in enumerate(zip(top_probs, top_indices), 1):
    print(idx.item(), round(probabilities[0, 3, idx].item(),5), tokenizer.decode([idx]))
```

[11]:
```
279 0.20471 the
1561 0.01653 New
6890 0.01426 India
4987 0.01425 South
9822 0.01127 France
5734 0.00979 China
8524 0.0095 Russia
18157 0.00935 Spain
12550 0.00887 Mexico
16272 0.00872 Georgia
```

SUPPORTING CODE

This part of the chapter contains supporting code for the key results presented in this chapter. All code shown here is also available at:

`github.com/stephencwelch/ai_book`

2.2 How does our model's confidence in Paris change as we modify a specific weight?

[12]:
```
param_dict = {name: param for name, param in model.named_parameters()}
len(param_dict) #Our llama model contains 146 separate parameter tensors
```

[12]:
```
146
```

[13]:
```
#Quick look at the sizes of the first tensors
for k, v in list(param_dict.items())[:16]:
    print(k, v.shape)
```

[13]:
```
model.embed_tokens.weight torch.Size([128256, 2048])
model.layers.0.self_attn.q_proj.weight torch.Size([2048, 2048])
model.layers.0.self_attn.k_proj.weight torch.Size([512, 2048])
model.layers.0.self_attn.v_proj.weight torch.Size([512, 2048])
model.layers.0.self_attn.o_proj.weight torch.Size([2048, 2048])
model.layers.0.mlp.gate_proj.weight torch.Size([8192, 2048])
model.layers.0.mlp.up_proj.weight torch.Size([8192, 2048])
model.layers.0.mlp.down_proj.weight torch.Size([2048, 8192])
model.layers.0.input_layernorm.weight torch.Size([2048])
model.layers.0.post_attention_layernorm.weight torch.Size([2048])
model.layers.1.self_attn.q_proj.weight torch.Size([2048, 2048])
model.layers.1.self_attn.k_proj.weight torch.Size([512, 2048])
model.layers.1.self_attn.v_proj.weight torch.Size([512, 2048])
model.layers.1.self_attn.o_proj.weight torch.Size([2048, 2048])
model.layers.1.mlp.gate_proj.weight torch.Size([8192, 2048])
model.layers.1.mlp.up_proj.weight torch.Size([8192, 2048])
```

[14]:
```
#We're going to modify a parameter in the final MLP layer
param_dict['model.layers.15.mlp.down_proj.weight'].shape
```

[14]:
```
torch.Size([2048, 8192])
```

[15]:
```
#Print this parameters current value.
initial_value=param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788].item()
initial_value
```

[15]:
```
-0.007080078125
```

[16]:
```
text = "The capital of France is"
inputs = tokenizer(text, return_tensors="pt").to(device)
```

[17]:
```
#Sanity check that if replace our parameter with it's current value we get the same answer
with torch.no_grad():
    param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788]=initial_value
    with torch.no_grad():
        outputs=model(inputs["input_ids"])
    probs=F.softmax(outputs.logits.detach().cpu(), dim=-1)
    loss=-np.log(probs[0, -1, 12366].item()) #12366 is Paris token index
    print(param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788].item(),
          probs[0, 5, 12366].item(), loss)
```

[17]:
```
-0.007080078125 0.391557902097702 0.9376218764087003
```

[18]:
```
#Decrease our parameter, how does our models prediction change?
with torch.no_grad():
    param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788]=initial_value-0.01
    with torch.no_grad():
        outputs = model(inputs["input_ids"])
    probs=F.softmax(outputs.logits.detach().cpu(), dim=-1)
    loss=-np.log(probs[0, -1, 12366].item())
    print(param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788].item(),
          probs[0, 5, 12366].item(), loss)
```

[18]:
```
-0.017080077901482582 0.39008358120918274 0.9413942520269462
```

[19]:
```
#Increase our parameter, how does our models prediction change?
with torch.no_grad():
    param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788]=initial_value+0.01
    with torch.no_grad():
        outputs = model(inputs["input_ids"])
    probs = F.softmax(outputs.logits.detach().cpu(), dim=-1)
    loss=-np.log(probs[0, -1, 12366].item())
    print(param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788].item(),
          probs[0, 5, 12366].item(), loss)
```

[19]:
```
0.0029199218843132257 0.3930262625217438 0.9338788435905439
```

[20]:
```
# Now test range of values for our parameter
xs=np.arange(-1, 4, 0.01)
model.eval()
losses=[]; all_probs=[]
with torch.no_grad():
    for x in tqdm(xs):
        param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788]=x
        outputs = model(inputs["input_ids"])
        probs = F.softmax(outputs.logits.detach().cpu(), dim=-1)
        my_loss=-np.log(probs[0, -1, 12366])
        losses.append(my_loss.item())
        all_probs.append(probs[0, -1, 12366].item())
```

[20]:
```
0%| | 0/500 [00:00<?,
100%|████████████████████████████████████| 500/500 [00:12<00:00, 41.17it/s]
```

[21]:
```
plt.plot(xs, all_probs, color='red'); plt.plot(xs, losses, color='blue')
plt.legend(['Model confidence in "Paris"', 'Cross-entropy loss'])
plt.xlabel('Parameter Value (model.layers.15.mlp.down_proj.weight [395, 1788])')
```

[21]:
```
Text(0.5, 0, 'Parameter Value (model.layers.15.mlp.down_proj.weight [395, 1788])')

<Figure size 640x480 with 1 Axes>
```



[22]:
```
#What paramter value minimizes our loss?
xs[np.argmin(losses).item()]
```

[22]:
```
np.float64(1.5900000000000025)
```

2.3 Let's Try Learning One Parameter At a Time

[24]:
```
#Set our first parameter to the optimal value we found in 2.2
with torch.no_grad():
    param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788]=1.59
```

[25]:
```
# Now test range of values for a second parameter
xs=np.arange(-1, 4, 0.01)
model.eval()
losses_2=[]; all_probs_2=[]
with torch.no_grad():
    for x in tqdm(xs):
        param_dict['model.layers.15.mlp.down_proj.weight'][1671, 1788]=x
        outputs = model(inputs["input_ids"])
        probs = F.softmax(outputs.logits.detach().cpu(), dim=-1)
        my_loss=-np.log(probs[0, -1, 12366])
        losses_2.append(my_loss.item())
        all_probs_2.append(probs[0, -1, 12366].item())
```

[25]:
```
100%|██████████████████████████████████████| 500/500 [00:11<00:00, 44.64it/s]
```

[26]:
```
plt.plot(xs, all_probs_2, color='red'); plt.plot(xs, losses_2, color='blue')
plt.legend(['Model confidence in "Paris"', 'Cross-entropy loss'])
plt.xlabel('Parameter Value (model.layers.15.mlp.down_proj.weight [1671, 1788])')
```

[26]:
```
Text(0.5, 0, 'Parameter Value (model.layers.15.mlp.down_proj.weight [1671, 1788])')

<Figure size 640x480 with 1 Axes>
```



[27]:
```
#What paramter value minimizes our loss?
xs[np.argmin(losses_2).item()]
```

[27]:
```
np.float64(1.7500000000000027)
```

[28]:
```
#Set our second parameter to it's optimal value
with torch.no_grad():
    param_dict['model.layers.15.mlp.down_proj.weight'][1671, 1788]=1.75
```

[29]:
```
# Now we get into a pickle, let's test our first parameter again
xs=np.arange(-1, 4, 0.01)
model.eval()
losses_b=[]; all_probs_b=[]
with torch.no_grad():
    for x in tqdm(xs):
        param_dict['model.layers.15.mlp.down_proj.weight'][395, 1788]=x
        outputs = model(inputs["input_ids"])
        probs = F.softmax(outputs.logits.detach().cpu(), dim=-1)
        my_loss=-np.log(probs[0, -1, 12366])
        losses_b.append(my_loss.item())
        all_probs_b.append(probs[0, -1, 12366].item())
```

[29]:
```
100%|██████████████████████████████████████| 500/500 [00:11<00:00, 45.17it/s]
```

[30]:
```
plt.plot(xs, all_probs, color='red'); plt.plot(xs, losses, color='blue')
plt.plot(xs, all_probs_b, 'r--'); plt.plot(xs, losses_b, 'b--')
plt.legend(['Model confidence in "Paris"', 'Cross-entropy loss',
            'After updating second parameter', 'After updating second parameter'])
plt.xlabel('Parameter Value (model.layers.15.mlp.down_proj.weight [395, 1788])')
```

[30]:
```
Text(0.5, 0, 'Parameter Value (model.layers.15.mlp.down_proj.weight [395, 1788])')
```

```
<Figure size 640x480 with 1 Axes>
```



2.4 Explore Loss Landscape For Randomly Initialized Model

[32]:
```python
def get_random_directions(params, seed=None):
    """
    Generate random direction vectors for each parameter tensor.

    Args:
        params: List of (name, parameter) tuples from model.named_parameters()
        seed: Random seed for reproducibility

    Returns:
        direction: OrderedDict mapping parameter names to random direction tensors
    """
    if seed is not None:
        torch.manual_seed(seed)
        np.random.seed(seed)

    direction = OrderedDict()
    for name, param in params:
        if param.requires_grad:
            direction[name] = torch.randn_like(param.data)

    return direction

def normalize_direction(direction, params):
    """
    Normalize the direction tensors to match the norm of each parameter tensor.

    Args:
        direction: OrderedDict mapping parameter names to direction tensors
        params: List of (name, parameter) tuples from model.named_parameters()

    Returns:
        normalized_direction: OrderedDict with normalized direction tensors
    """
    param_dict = OrderedDict(params)
    normalized_direction = OrderedDict()

    for name, dir_tensor in direction.items():
        param_norm = torch.norm(param_dict[name].data)
        dir_norm = torch.norm(dir_tensor)

        # Avoid division by zero
        if dir_norm > 0:
            normalized_direction[name] = dir_tensor * (param_norm / dir_norm)
        else:
            normalized_direction[name] = dir_tensor

    return normalized_direction
```

[33]:
```python
import torch
from torch.nn import functional as F
from transformers import LlamaForCausalLM, PreTrainedTokenizerFast, LlamaConfig
from transformers import AutoModelForCausalLM, AutoTokenizer
import numpy as np
import matplotlib.pyplot as plt
from tqdm import tqdm
from collections import OrderedDict
```

[34]:
```
#Only needed for llama random initialization
config_dict = {
  "_attn_implementation_autoset": True,
  "architectures": [
    "LlamaForCausalLM"
  ],
  "attention_bias": False,
  "attention_dropout": 0.0,
  "bos_token_id": 128000,
  "eos_token_id": 128001,
  "head_dim": 64,
  "hidden_act": "silu",
  "hidden_size": 2048,
  "initializer_range": 0.02,
  "intermediate_size": 8192,
  "max_position_embeddings": 131072,
  "mlp_bias": False,
  "model_type": "llama",
  "num_attention_heads": 32,
  "num_hidden_layers": 16,
  "num_key_value_heads": 8,
  "pretraining_tp": 1,
  "rms_norm_eps": 1e-05,
  "rope_scaling": {
    "factor": 32.0,
    "high_freq_factor": 4.0,
    "low_freq_factor": 1.0,
    "original_max_position_embeddings": 8192,
    "rope_type": "llama3"
  },
  "rope_theta": 500000.0,
  "tie_word_embeddings": True,
  "torch_dtype": "float32",
  "transformers_version": "4.50.3",
  "use_cache": True,
  "vocab_size": 128256
}
```

[35]:
```
device='cuda'
model_id = "meta-llama/Llama-3.2-1B"

torch.manual_seed(42)
np.random.seed(42)

model_config  = LlamaConfig.from_dict(config_dict)
model = LlamaForCausalLM(model_config).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
model.eval();
```

[36]:
```
text = "The capital of France is Paris"
inputs = tokenizer(text, return_tensors="pt").to(device)
input_ids = inputs["input_ids"]
```

[37]:
```
fig=plt.figure(0, (10, 3.5))
for fig_count, random_seed in enumerate([64, 51]):
    filtered_params = [(name, p) for name, p in model.named_parameters() if p.requires_grad]
    filtered_params = filtered_params[1:] #Leave off embedding layer

    direction1 = get_random_directions(filtered_params, seed=random_seed)
    direction1 = normalize_direction(direction1, filtered_params)

    original_params = OrderedDict()
    for name, param in filtered_params:
        original_params[name] = param.data.clone()

    num_points=512 #use 4096 for video and book, probably overkill
    alphas=np.linspace(-2.5, 2.5, num_points)

    losses=[]
    with torch.no_grad():
        for i, alpha in enumerate(tqdm(alphas)):
            for name, param in model.named_parameters():
                if name in direction1:
                    param.data = original_params[name] + alpha * direction1[name]

            outputs = model(input_ids, labels=input_ids)
            my_probs=F.softmax(outputs.logits, dim=-1)
            paris_only_loss=-np.log(my_probs[0, 5, 12366].item())
            losses.append(paris_only_loss)

        for name, param in model.named_parameters(): # Restore original parameters
            if name in original_params:
                param.data.copy_(original_params[name])

    fig.add_subplot(1,2,fig_count+1)
    plt.plot(alphas, losses)
    plt.xlabel('alpha'); plt.ylabel('Loss')
```

[37]:
```
100%|██████████████████████████████████████| 512/512 [00:16<00:00, 30.52it/s]
100%|██████████████████████████████████████| 512/512 [00:16<00:00, 30.51it/s]

<Figure size 1000x350 with 2 Axes>
```



2.5 Explore Loss Landscape for Trained Model

[38]:
```
import torch
from torch.nn import functional as F
from transformers import LlamaForCausalLM, PreTrainedTokenizerFast, LlamaConfig
from transformers import AutoModelForCausalLM, AutoTokenizer
import numpy as np
import matplotlib.pyplot as plt
from tqdm import tqdm
from collections import OrderedDict
```

[39]:
```
device='cuda'
model_id = "meta-llama/Llama-3.2-1B"
```

[40]:
```
#Pretrained
model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
model.eval();
```

[41]:
```
text = "The capital of France is Paris"
inputs = tokenizer(text, return_tensors="pt").to(device)
input_ids = inputs["input_ids"]
```

[42]:
```
fig=plt.figure(0, (10, 3.5))
for fig_count, random_seed in enumerate([19, 27]):
    filtered_params = [(name, p) for name, p in model.named_parameters() if p.requires_grad]
    filtered_params = filtered_params[1:] #Leave off embedding layer

    direction1 = get_random_directions(filtered_params, seed=random_seed)
    direction1 = normalize_direction(direction1, filtered_params)

    original_params = OrderedDict()
    for name, param in filtered_params:
        original_params[name] = param.data.clone()

    num_points=512 #4096
    alphas=np.linspace(-2.5, 2.5, num_points)

    losses=[]
    with torch.no_grad():
        for i, alpha in enumerate(tqdm(alphas)):
            for name, param in model.named_parameters():
                if name in direction1:
                    param.data = original_params[name] + alpha * direction1[name]

            outputs = model(input_ids, labels=input_ids)
            my_probs=F.softmax(outputs.logits, dim=-1)
            paris_only_loss=-np.log(my_probs[0, 5, 12366].item())
            losses.append(paris_only_loss)

        for name, param in model.named_parameters(): # Restore original parameters
            if name in original_params:
                param.data.copy_(original_params[name])

    fig.add_subplot(1,2,fig_count+1)
    plt.plot(alphas, losses)
    plt.xlabel('alpha'); plt.ylabel('Loss')
```

[42]:
```
100%|████████████████████████████████████| 512/512 [00:16<00:00, 30.45it/s]
100%|████████████████████████████████████| 512/512 [00:16<00:00, 30.22it/s]
```



2.6 Explore full 2D Landsacpe

[43]:
```
import torch
from torch.nn import functional as F
from transformers import LlamaForCausalLM, PreTrainedTokenizerFast, LlamaConfig
from transformers import AutoModelForCausalLM, AutoTokenizer
import numpy as np
import matplotlib.pyplot as plt
from tqdm import tqdm
from collections import OrderedDict
from matplotlib.colors import Normalize
from matplotlib.cm import ScalarMappable
```

[44]:
```
device='cuda'
model_id = "meta-llama/Llama-3.2-1B"
```

[45]:
```
#Pretrained
model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
model.eval();
```

[46]:
```
text = "The capital of France is Paris"
inputs = tokenizer(text, return_tensors="pt").to(device)
input_ids = inputs["input_ids"]
```

[47]:
```
prefix='pretrained_'
filtered_params = [(name, p) for name, p in model.named_parameters() if p.requires_grad]

layers_name='first_8'
filtered_params = filtered_params[1:73] #First 8 layers - I like this - facorite so far

num_points=32 #Video uses 512, takes a few hours to compute
random_seed_1 = 11
random_seed_2 = 111

# Generate and normalize random directions
direction1 = get_random_directions(filtered_params, seed=random_seed_1)
direction2 = get_random_directions(filtered_params, seed=random_seed_2)

direction1 = normalize_direction(direction1, filtered_params)
direction2 = normalize_direction(direction2, filtered_params)

original_params = OrderedDict()
for name, param in filtered_params:
    original_params[name] = param.data.clone()

alphas=np.linspace(-2.5, 2.5, num_points)
betas=np.linspace(-2.5, 2.5, num_points)
losses=[]
with torch.no_grad():
    for i, alpha in enumerate(tqdm(alphas)):
        losses.append([])
        for j, beta in enumerate(betas):
            for name, param in model.named_parameters():
                if name in direction1:
                    param.data = original_params[name] + alpha * direction1[name] + beta*direction2[name]

            outputs = model(input_ids, labels=input_ids)
            my_probs=F.softmax(outputs.logits, dim=-1)
            paris_only_loss=-np.log(my_probs[0, 5, 12366].item())
            losses[-1].append(paris_only_loss)

    for name, param in model.named_parameters(): # Restore original parameters
        if name in original_params:
            param.data.copy_(original_params[name])

losses=np.array(losses)

plt.clf()
fig, ax = plt.subplots(figsize=(10, 8))
contourf = ax.contourf(alphas, betas, losses, 20, cmap='viridis', alpha=0.8)
contour = ax.contour(alphas, betas, losses, 30, colors='white', linewidths=0.5)
```

[47]:
```
100%|██████████| 32/32 [00:34<00:00, 1.09s/it]
```



[48]:
```
#Alternatively, load up saved hig res (512x512) version
alphas_1=np.linspace(-2.5, 2.5, 512)
betas_1=np.linspace(-2.5, 2.5, 512)
loss_2d_1=np.load('data/loss_landscape.npy')
# plt.imshow(loss_2d_1)
```

[49]:
```
#Take middle slices in each direction of landscape
slice_1=loss_2d_1[255, :]
slice_2=loss_2d_1[:, 255]
```

[50]:
```
fig=plt.figure(0, (10, 3.5))

fig.add_subplot(1,2,1)
plt.plot(alphas_1, slice_1)
plt.xlabel('alpha'); plt.ylabel('Loss')

fig.add_subplot(1,2,2)
plt.plot(betas_1, slice_2)
plt.xlabel('alpha'); plt.ylabel('Loss')
```

[50]:
```
Text(0, 0.5, 'Loss')
```



[51]:
```
#Loss landscape contour plot
plt.clf()
fig, ax = plt.subplots(figsize=(12, 10))
contourf = ax.contourf(alphas_1, betas_1, loss_2d_1, 30, cmap='viridis', alpha=0.8)
contour = ax.contour(alphas_1, betas_1, loss_2d_1, 30, colors='white', linewidths=0.5)
plt.colorbar(contourf, ax=ax)
```

[51]:



2. GRADIENT DESCENT | EXERCISES

2.1 What is a local minimum, and why were early AI pioneers like Geoffrey Hinton worried about them?

2.2 Why are local minima less of a concern for modern neural networks than once thought?

2.3 How does cross-entropy penalize our model differently than the L1 loss?

2.4 In Figure 2.11, we tried training our Llama model one parameter at a time. What went wrong with this approach?

2.5 Why can't we just train Llama by testing all combinations of parameter values?

2.6 When training on short texts, why does it look like a wormhole opens up in our loss landscape (Figure 2.21)?

[1]:
```
import torch
from torch.nn import functional as F
from transformers import AutoModelForCausalLM, AutoTokenizer
import numpy as np
import matplotlib.pyplot as plt
from tqdm import tqdm

device='cuda'
model_id = "meta-llama/Llama-3.2-1B"

model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
```

[2]:
```
text = "The capital of France is Paris"
inputs = tokenizer(text, return_tensors="pt").to(device)

with torch.no_grad():
    outputs = model(**inputs, labels=inputs["input_ids"])

outputs.loss  # This is the average cross-entropy loss
```

[2]:
```
tensor(3.3752, device='cuda:0')
```

INPUT TEXT	MODEL'S MOST PROBABLE NEXT TOKEN	MODEL'S MOST PROBABLE NEXT TOKEN PROBABILITY	CORRECT NEXT TOKEN	MODEL'S PROBABILITY OF CORRECT NEXT TOKEN (P_i)	$-\ln(P_i)$
<|begin_of_text|>	Question	0.301258	The	0.026724	3.6222
<|begin_of_text|>The		0.0244	capital	0.000169	
<|begin_of_text|>The capital	of	0.568659	of	0.568659	
<|begin_of_text|>The capital of	the	0.204712	France	0.011272	
<|begin_of_text|>The capital of France	,	0.508131	is	0.141121	
<|begin_of_text|>The capital of France is	Paris	0.391531	Paris	0.391531	0.9377

2.7 The code snippet to the left shows the process of computing the loss value for a pre-trained Llama large language model given the input text *"The capital of France is Paris"*. According to PyTorch, our model's loss is 3.3752. Let's reproduce this value. First, fill in the missing values in the final column of the table on the previous page. These are the values of the cross-entropy loss of each prediction our model makes on our training text.

2.8 When training, the loss at each token position is averaged to compute a final loss for each example. Take the average of your computed cross-entropy values. Do your results match what PyTorch reports?

2.9 Which predicted tokens (i.e. which rows in the table you completed in 2.7) have the highest loss values? Why?

2.10 Which predicted tokens (i.e. which rows in the table you completed in 2.7) have the lowest loss values? Why?

2.11 If our model instead used L1 Loss, what would our L1 loss be for this example? How would switching to L1 Loss change the relative contributions of each token to the final loss value?

[7]:
```
import torch
from torch.nn import functional as F
from transformers import AutoModelForCausalLM, AutoTokenizer
import numpy as np
import matplotlib.pyplot as plt
from tqdm import tqdm

device='cuda'
model_id = "meta-llama/Llama-3.2-1B"

model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
```

[8]:
```
text = "An apple a day keeps the doctor away"
inputs = tokenizer(text, return_tensors="pt").to(device)

with torch.no_grad():
    outputs = model(**inputs, labels=inputs["input_ids"])

outputs.loss  # This is the average cross-entropy loss
```

[8]:
```
tensor(1.9323, device='cuda:0')
```

INPUT TEXT	MODEL'S MOST PROBABLE NEXT TOKEN	MODEL'S MOST PROBABLE NEXT TOKEN PROBABILITY	CORRECT NEXT TOKEN	MODEL'S PROBABILITY OF CORRECT NEXT TOKEN (P_i)	$-\ln(P_i)$
<|begin_of_text|>	Question	0.301258	An	0.001692	6.3816
<|begin_of_text|>An		0.022775	apple	0.000615	7.3936
<|begin_of_text|>An apple	a	0.649742	a	0.649742	0.4312
<|begin_of_text|>An apple a	day	0.986583	day	0.986583	
<|begin_of_text|>An apple a day	keeps	0.483511	keeps	0.483511	
<|begin_of_text|>An apple a day keeps	the	0.850819	the	0.850819	
<|begin_of_text|>An apple a day keeps the	doctor	0.738021	doctor	0.738021	0.3038
<|begin_of_text|>An apple a day keeps the doctor	away	0.954824	away	0.954824	0.0462

2.12 The code snippet to the left shows the process of computing the loss value for a pre-trained Llama large language model given the input text *"An apple a day keeps the doctor away"* According to PyTorch, our model's loss is 1.9323. Let's reproduce this value. First, fill in the missing values in the final column of the table on the previous page. These are the values of the cross-entropy loss of each prediction our model makes on our training text.

2.13 When training, the loss at each token position is averaged to compute a final loss for each example. Take the average of your computed cross-entropy values. Do your results match what PyTorch reports?

2.14 Which predicted tokens (i.e. which rows in the table you completed in 2.12) have the highest loss values? Why?

2.15 Which predicted tokens (i.e. which rows in the table you completed in 2.12) have the lowest loss values? Why?

2.16 How would switching to L1 loss change the relative contributions of each token to the final loss value?

INPUT TEXT	MODEL'S MOST PROBABLE NEXT TOKEN	MODEL'S MOST PROBABLE NEXT TOKEN PROBABILITY	CORRECT NEXT TOKEN	MODEL'S PROBABILITY OF CORRECT NEXT TOKEN (P_i)	$-\ln(P_i)$
<|begin_of_text|>	Question	0.301258	I	0.006885	4.9784
<|begin_of_text|>I	have	0.093446	've	0.029747	3.515
<|begin_of_text|>I've	been	0.3544	had	0.049489	3.006
<|begin_of_text|>I've had	a	0.302687	a	0.302687	1.1951
<|begin_of_text|>I've had a	few	0.143885	perfectly	0.000096	9.252
<|begin_of_text|>I've had a perfectly	good	0.174156	wonderful	0.038335	3.2614
<|begin_of_text|>I've had a perfectly wonderful	life	0.158798	evening	0.009312	4.6765
<|begin_of_text|>I've had a perfectly wonderful evening	with	0.164883	,	0.110149	2.2059
<|begin_of_text|>I've had a perfectly wonderful evening,	and	0.103836	but	0.102951	2.2735
<|begin_of_text|>I've had a perfectly wonderful evening, but	I	0.32717	this	0.017883	4.0239
<|begin_of_text|>I've had a perfectly wonderful evening, but this	morning	0.419821	wasn	0.001634	6.4166
<|begin_of_text|>I've had a perfectly wonderful evening, but this wasn	't	0.997004	't	0.997004	0.003
<|begin_of_text|>I've had a perfectly wonderful evening, but this wasn't	it	0.210132	it	0.210132	1.56

2.17 Consider the table on the previous page, showing Llama processing the input text *"I've had a perfectly wonderful evening, but this wasn't it"*. Which token predictions have the lowest loss values? Why? Which token predictions have the highest loss values? Why?

2.18 Compute and visualize your own loss landscape for a model other than Llama-3.2-1b. You may use this chapter's supporting code as a starting point.



Figure 3.1 | Real Data Flowing Through Meta's Llama 3.2 1B Large Language Model. Given the prompt "The capital of France is" Llama predicts what token will come next by passing its inputs through 16 compute layers—we're showing 8 of these 16 here. Each 5×5 grid is known as an "attention pattern", we'll learn more about attention patterns in Chapter 8. These patterns are 5×5 here because our prompt is made up of 5 tokens. The lines here show weight values, where the darkness and width of each line correspond to weight values. Note that we're only showing the largest weights, otherwise this visual gets pretty overwhelming! The shaded circles and 5×5 grids show "activation" values—these are the values that our data takes as it moves through our network. Darker values correspond to higher activations. Finally, the output shows the model's predicted next tokens, ordered by the model's confidence.



Figure 3.2 | Backpropagation Visualized. Blue lines show the gradients computed using backpropagation—these values tell the model how much to update each parameter as the model learns. Thicker and darker lines correspond to larger updates. These values assume a correct next token of *"Paris"* (note the blue lines originating from the *"Paris"* output). The second-to-last attention pattern in the fourth layer of the model has fairly strong gradients going in and out and has high activation values at the token positions corresponding to *"capital"* and *"France"*, two helpful tokens for predicting the correct next token of *"Paris"*. These high gradient values suggest that the model can improve its confidence in *"Paris"* by increasing the strength of the connections flowing in and out of this attention pattern.

3. BACKPROPAGATION

The F=ma of Artificial Intelligence

In the early 1970s, a Harvard graduate student named Paul Werbos discovered a method for training multilayer neural networks that we now call backpropagation. Werbos would later compare the discovery to Newton's laws, positioning backpropagation as a fundamental mathematical law of intelligence.

"..this new mathematical concept [backpropagation] opens up the possibility of a scientific understanding of intelligence, as important to psychology and neurophysiology as Newton's concepts were to physics"

Paul Werbos
[Werbos 1994]

When Werbos took his discovery to AI legend Marvin Minsky, Minsky rejected it outright—claiming that backpropagation would not be able to learn anything difficult.

"But, you see, it's not a good discovery... It converges slowly, and it cannot learn anything difficult"

Marvin Minsky
[Olazaran 1996]

However, despite being consistently underestimated by Minsky and many others, backpropagation just kept working—successfully training models to drive cars in the 1980s, recognize handwritten digits in the 1990s, and classify images with incredible accuracy in the early 2010s.

And today virtually all modern AI models are trained using backpropagation. Figure 3.1 shows the flow of real data through Meta's Llama 3.2 large language model—the entire model is too large to show on one page—here we're showing the strongest connections.[1] Given some input text like *"The capital of France is"*, Llama predicts what token comes next, and the backpropagation algorithm figures out how to update each of the model's 1.2 billion parameters to make Llama more confident in the correct next token. These updates are shown in blue in Figure 3.2, where thicker lines correspond to larger updates. In the lower portion of Figure 3.2, we can see backpropagation is modifying the weights flowing in and out of this attention pattern—this pattern tells the model to focus on the second and fourth tokens in the input text, in this case the words *"capital"* and *"France"*—which are important for predicting the next token of *"Paris"*. In Chapter 8, we'll discuss attention patterns in more detail.

Backpropagation is remarkably able to figure out which parts of these massive models to update to iteratively improve performance and learn highly complex behaviors.

Like Newton's laws, the backpropagation algorithm is simple, elegant, and deceptively scalable—leading to incredibly complex structure and behaviors. In this chapter, we'll see precisely how backpropagation works.

1 In these figures, we're showing 8 of the total 16 layers in the model. Specifically layers 1, 2, 7, 8, 9, 10, 15, and 16. Every third attention pattern is shown, and special tokens are ignored. MLP neurons are downsampled using max pooling. Only the weights and gradients above a specific percentile-based threshold are shown. Only query weights are shown going into each attention layer. We're also now showing the residual stream; see Chapter 7 for more on this.

Chapter 3 Video

Madrid	
Center of Madrid	(40.4167°, -3.7033°)
Retiro Park	(40.4153°, -3.6835°)
Royal Palace	(40.4180°, -3.7143°)
Prado Museum	(40.4138°, -3.6921°)
Puerta del Sol	(40.4169°, -3.7033°)

Paris	
Center of Paris	(48.8575°, 2.3514°)
Eiffel Tower	(48.8584°, 2.2945°)
Notre Dame	(48.8530°, 2.3499°)
Louvre	(48.8606°, 2.3376°)
Centre Pompidou	(48.8606°, 2.3522°)

Berlin	
Center of Berlin	(52.5200°, 13.4050°)
Brandenburg Gate	(52.5163°, 13.3777°)
Museum Island	(52.5169°, 13.4019°)
Checkpoint Charlie	(52.5074°, 13.3904°)
Berlin Central Station	(52.5251°, 13.3694°)

Figure 3.3 | Training Data. Instead of passing language into our model, we'll pass in GPS coordinates. This will let us get away with a much smaller model that will be easier to work with, but will be built from many of the same components as a full large language model.

In Chapter 2, we took a visual-first approach to training Meta's Llama 3.2 1.2 billion parameter model. We showed how loss landscapes give us a sense for the high-dimensional spaces the models operate in, but also how these types of visualizations can fall short.

In this chapter we'll take a math-first approach that will lead us to the backpropagation algorithm that Werbos discovered over 50 years ago. To build up the equations we need, we'll simplify our learning problem, work out our equations, and then scale back up. Instead of training a large language model like Llama to predict what comes next in phrases like *"the capital of France is"*, let's train a smaller model to predict the city you're in based on your GPS coordinates. Our training data is now GPS coordinates taken from spots in a few different cities, here are five coordinates from Paris, and five points from Madrid and Berlin.

Our full Llama language model returns vectors of probabilities of length 128,256, with one entry for each token in Llama's vocabulary. Our GPS model also returnsc vectors of probabilities, but on a much smaller vocabulary of just our three cities: Paris, Madrid, and Berlin.

Instead of taking in text inputs, our tiny model will take in GPS coordinates, and we'll start by just taking in one coordinate—longitude. So our model takes in a single numerical input, longitude, which we'll call x, and returns three numbers—one probability for each city—we'll call these probabilities $\hat{y}_1$, $\hat{y}_2$, and $\hat{y}_3$.

Architecturally, our model has just three total neurons, one for each city. Each neuron's job is really simple. It multiplies its input by a learnable parameter called a weight, adds another learnable number called a bias, and outputs the result.

Mathematically, we can write the output of our first neuron, which we'll call h_1, as our first learnable parameter m_1, times our input x, plus our bias value b_1, as shown in Figure 3.4. This model is completely equivalent to a simple linear $y=mx+b$ equation for a line from high school algebra. Each of the neurons that make up artificial neural networks like Llama is effectively a simple little linear model like this—although with more inputs x and slopes m—and it's the job of our learning algorithm to make the appropriate adjustments to all our m and b values to solve the larger task at hand. Note that we're calling the output h instead of y here, because we have to take one more step before reaching our final model outputs $\hat{y}$.[2]

2 The layers of our model between our inputs and outputs are called "hidden layers", this why we're using h here.



Figure 3.4 | AI is built from a bunch of little linear models. Virtually all modern AI models use the same simple linear model of the neuron. When these neurons have a single input, the neuron's output is $y=mx+b$, where x is the neuron's input, m and b are the neuron's learnable parameters. Geometrically this little linear model looks like a line with a slope of m and a y-intercept of b. If a neuron has two inputs, its formula becomes $y=m_1x_1+m_2x_2+b$, and geometrically looks like a plane. A typical neuron in a language model will have on the order of 10,000 inputs, and follows the same pattern, with its output given by a huge linear equation $y=m_1x_1+m_2x_2+\ldots+m_{10,000}x_{10,000}+b$, and geometrically looks like a hyperplane in 10,000 dimensional space 😎. Our toy model uses the same components and mathematics as our full size model, but will be easier to work with and visualize. The fact that the same math applies and works for tiny 6 parameter models to giant 100B+ parameter models is remarkable! Depending on their locations in the model, the output of these little linear models are sometimes passed into a few other types of functions, such as softmax, we'll dig into these functions shortly. Finally, the full scale Llama model includes attention layers (the little 5×5 grids)—these layers are still built from the same simple linear neurons, but in a different arrangement—see Chapters 1 and 8 for more discussion of attention layers.



Figure 3.5 | Softmax. Softmax takes our unbounded neuron outputs and squishes them into nice probabilities that all add up to one. The exponentials in softmax amplify the differences between its inputs.

Now, depending on their locations in the model, the outputs of these little linear models are sometimes passed into a few other types of functions. We know that we want the final outputs of our model, yhat, to be probabilities between zero and one, but each of our neurons is capable of returning a full range of positive or negative values.

To squish the outputs of our neurons, and ensure our probabilities all add to one, the outputs h of our final layer are typically passed into a softmax function. To compute the probability of Madrid, $\hat{y}_1$, using softmax, we plug in the outputs of each of our three neurons h_1, h_2, h_3, into this equation:

$$\hat{y}_1 = \text{Softmax}(h_1) = \frac{e^{h_1}}{e^{h_1} + e^{h_2} + e^{h_3}}$$

The exponentials in the softmax equation amplify the differences between our output neurons, assigning more, but not all, probability to the neuron with the maximum output value—this is why it's called *soft* max. If our Madrid, Paris, and Berlin neurons output values of 1, 2, and 1, our softmax operation will assign 58% probability to $\hat{y}_2$ for Paris. If our model is more confident in Paris and returns values of 1, 10, and 1, softmax behaves more like a traditional max function, assigning Paris a probability of 99.98%.

Softmax is the most complicated piece of math we'll encounter in this chapter, and happily we'll see that when we apply some calculus and differentiate softmax, it actually gets much simpler!

So we now have all the equations we need to make predictions using our tiny GPS model. Before training, our model weights are randomly initialized—let's pick some simple starting values—we'll set our slope parameters to m_1=1, m_2=0, and m_3=1, and set all our bias values b to 0.

If we now pass in the longitude of one of our Paris coordinates, for example the center of the city at 2.3514°, our positive value for m_1 gives us a large h_1 value of 2.3514, leading our model to incorrectly predict that we're in Madrid with a probability of 0.91.

Now, as we saw in Chapter 2, to train our model to make better predictions, we first need a way to measure our model's performance—the metric of choice for Llama and many modern models is the cross entropy loss. To compute the cross-entropy loss here, we take the negative logarithm of the model's predicted probability of the correct answer. The model's current probability of Paris only 8.6%, leading to a cross entropy loss of -log(0.086)=2.45. If our model's predicted probability of Paris 100%, our cross entropy loss would equal -log(1.0)=0.



Figure 3.6 | Initial Results. Choosing values for our six model parameters and plugging in our first Paris point, our model incorrectly predicts that our point is in Madrid, with a probability of 91%. Our cross-entropy loss only depends on the probability returned by our model at the index of the correct answer *P*(Paris)=0.09, yielding a loss of 2.45.

Our job from here is to change our six m and b parameters to make our loss go down. As we saw in Chapter 2, we can do this efficiently by computing the slope of each of our parameters with respect to our loss, combining these slopes into a vector called the gradient, and using the gradient to make iterative updates to our weights.

Let's make this idea more tangible.

Let's explore, as we did last time, how our loss varies with a single model parameter, by plotting our loss as a function of m_2. Our m_2 parameter in our Paris neuron currently has a value of 0, resulting in a loss of 2.45. If we increase the parameter's value to 0.1 as shown in Figure 3.7, we can recompute our outputs and see that this increases our probability of being in Paris, according to the model, to 0.107, reducing our loss to 2.24. Now, with these two computations of our loss for different values of m_2, we've effectively estimated the value of our slope $\Delta L/\Delta m_2$— this tells us that if we increase m_2, our loss will go down, increasing model performance.

We could theoretically do this for all six parameters in our model, and use these estimated slopes to guide the gradient descent learning process. However, in practice, this numerical approach is computationally intensive since we have to recompute our outputs for each new parameter value we try, and this approach can also be inaccurate, since we have to pick a fixed step size for how much we change our model parameters.

Remarkably, it turns out that we can do much better than numerical estimates of these slopes. As we'll see, it's possible to



Figure 3.7 | How Does Loss Change with m_2? If we increase our model's parameter m_2 from 0 to 0.1, we can recompute our outputs and loss, resulting in a new cross-entropy loss of 2.24. Using our initial loss value (Figure 3.6) of 2.45, and the change in our m_2 we can estimate the slope $\Delta L/\Delta m_2$=-2.1. We could do this for all six model parameters, and use these results to guide learning, but there's a better way.

$$\frac{\partial Loss}{\partial m_2} = \frac{\partial}{\partial m_2}\left[-\ln\left(\frac{e^{m_2x+b_2}}{e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3}}\right)\right]$$

$$= \frac{\partial}{\partial m_2}\left[-\ln(e^{m_2x+b_2}) + \ln(e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3})\right]$$

$$= \frac{\partial}{\partial m_2}\left[-(m_2x+b_2) + \ln(e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3})\right]$$

$$= -x + \frac{1}{e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3}} \cdot \frac{\partial}{\partial m_2}(e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3})$$

$$= -x + \frac{1}{e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3}} \cdot xe^{m_2x+b_2}$$

$$= -x + \frac{xe^{m_2x+b_2}}{e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3}}$$

$$= x\left(\frac{e^{m_2x+b_2}}{e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3}} - 1\right)$$

$$= x(\hat{y}_2 - 1)$$

Figure 3.8 | No Thank You! We can solve $\partial L/\partial m_2$ by directly taking the derivative of our full loss function—but this approach is clunky and hard to automate. Imagine how unwieldy managing these equations would become for our full scale language model!



Figure 3.9 | A Better Way. Instead of solving for $\partial L/\partial m_2$ all at once, we can break apart our partial derivative using the chain rule as $\partial L/\partial m_2 = (\partial h_2/\partial m_2)(\partial L/\partial h_2)$. This allows us to evaluate the gradient across each block of our network independently—a much more scalable approach!

exactly solve for the slopes of the loss function with respect to all parameters—when we're done we'll have simple equations we can plug into directly.

The fact that you can do this is not immediately obvious—even to those well versed in calculus and optimization. As we saw in Chapter 1, in the 1950s at Stanford, Bernard Widrow's group trained single layer neural networks using this numerical estimate of the slope for years, until Widrow and graduate student Ted Hoff stumbled onto an early version of backpropagation one day in 1959. Even then, Widrow and Hoff failed to see how to extend their method to neural networks with more than one layer—we'll see precisely how to do this shortly.

The central idea of backpropagation is to apply the rules of calculus to compute equations for our slopes in a particularly efficient way. Let's start with our slope $\Delta L/\Delta m_2$. In the language of calculus this is the partial derivative $\partial L/\partial m_2$, the rate of change of our loss L with respect to our model parameter m_2.

We already have equations that relate the loss and our parameter m_2. We know our cross-entropy loss is equal to the negative logarithm of the model's output probability of the correct answer $\hat{y}$—this would be $\hat{y}_2$ in the case of our Paris example. We can plug in our softmax equation for $\hat{y}$, and even go one step further and plug in the equations for each of our neurons—and get a complete equation for our loss L in terms of our input x, and all six of our model parameters:

$$Loss = -\ln(\hat{y}_2) \quad \text{Cross Entropy Loss}$$

$$Loss = -\ln\left(\frac{e^{h_2}}{e^{h_1}+e^{h_2}+e^{h_3}}\right)$$

$$Loss = -\ln\left(\frac{e^{m_2x+b_2}}{e^{m_1x+b_1}+e^{m_2x+b_2}+e^{m_3x+b_3}}\right)$$

$$h_1 = m_1x + b_1$$

$$h_2 = m_2x + b_2$$

$$h_3 = m_3x + b_3$$

$$\hat{y}_2 = \frac{e^{h_2}}{e^{h_1}+e^{h_2}+e^{h_3}}$$

If you're familiar with calculus, an obvious approach may be to compute the partial derivative we're after $\partial L/\partial m_2$ by differentiating our expression with respect to m_2. This does work, as shown in Figure 3.8, but is complex and doesn't really make use of the underlying graph structure of neural networks.

Instead, it turns out we can consider the layers of our neural network independently, solve for the rate of change through each layer, and then compose these rates of change together to much more efficiently solve for $\partial L/\partial m_2$.



Figure 3.10 | Two ways to find the overall rate of change through multistage systems. We can substitute the equation for our first block into the equation for our second block, or we can find the rate of change of each system independently, and multiply these rates of change together to get an overall rate of change. Both methods work, but the chain rule is much more scalable when dealing with multilayer neural networks.

Consider the simple example where we have two compute blocks, the first mapping some input number x to an output y with the equation $y{=}2x$, and a second compute block mapping y to z with the equation $z{=}4y$ (Figure 3.10). As we did with our neural network, we can put our equations together by substituting $y{=}2x$ into our second equation—simplifying, we see that the equation for our full system is $z{=}8x$. The slope or derivative of this overall system equation is 8.

However, a more modular way to reach the same answer is to compute the derivative of each block individually, computing the slope of our first block $dy/dx{=}2$, and the slope of our second block $dz/dy{=}4$. We can then multiply these rates of change together to get our overall rate of change, so $(2)(4){=}8$, or $(dy/dx)(dz/dy){=}dz/dx$.

This is known as the chain rule in calculus, and scales much more cleanly to models with many layers like Llama. Applying the same process to our neural network, we can break $\partial L/\partial m$ into $\partial h/\partial m$ times $\partial L/\partial h$, breaking apart the partial derivatives of our linear model and loss and softmax function (See Figure 3.9 on previous page).

Now, calculating the partial derivative across our logarithm and softmax is still a bit involved, the full process is shown in Figure 3.12. However, the big exciting takeaway is that the result is very simple—it turns out that the logarithm from our cross-entropy loss and exponentials from our softmax operation basically cancel out, leaving us with $\partial L/\partial h{=}\hat{y}{-}y$, where $\hat{y}$ is a vector made up of our three output probabilities, and y is a vector that equals one at the index of the correct answer and zero everywhere else.



Figure 3.11 | The Chain Rule Rules. Using the chain rule, we can efficiently compute the gradients of all model parameters, even in the case where our model parameters are very far from the output of our model!



Figure 3.12 | Derivative of Softmax + Cross Entropy. When we use cross-entropy loss after a softmax function, our gradient computations simplify really nicely. Since our Cross-Entropy loss depends on the correct output/label, we get different derivatives depending on what the correct answer is. The rows of the central table in this figure correspond to the three individual partial derivatives we're trying to calculate, $\partial L/\partial h_1$, $\partial L/\partial h_2$, $\partial L/\partial h_3$. These partial derivatives represent the rate of change of our loss L with respect to each of our three inputs to our softmax function h_1, h_2, and h_3. Our loss depends on our ground truth labels y, the columns of the table above show each possible label (*Madrid, Paris, Berlin*) analyzed separately. When our label and partial derivative match, e.g. $\partial L/\partial h_1$ and *Madrid*, our derivative calculation simplifies to $\hat{y}_1 - 1$. This result makes some sense because if our model is 100% confident in Madrid ($\hat{y}$=1.0), then our loss L=-ln(1.0)=0, and $\partial L/\partial h_1$=(1.0-1.0)=0.0. So our loss is zero and the rate of change of our loss with respect to our inputs is zero—this is effectively a local maximum. When we consider the partial derivative of a non matching partial derivative and label, e.g. $\partial L/\partial h_1$ and *Paris*, our calculus simplifies to $\partial L/\partial h_1 = \hat{y}_1$, which again makes some sense: if $\hat{y}_1$=0.9 for example, in this case our model is pretty confident in the incorrect answer of Madrid, and $\partial L/\partial h_1 = \hat{y}_1$=0.9, telling us that increasing h_1 will increase our Loss at a rate of 0.9—meaning that the more confident our model is in the wrong answer of Madrid, the higher our loss will be.



Figure 3.13 | Either Way, It's a Line. We typically think of the little linear models that make up our neurons as lines with slopes equal to our model's parameters m. However, when we're *learning* our model's parameters, m is a variable and our input x is fixed. From this perspective our equation is still a straight line, but its variable/input is m and its slope is $\partial h_2/\partial m_2 = x$.

When we plug in our Paris GPS point and compute our model's probabilities, as shown in Figure 3.14, we get $\hat{y}_1 = 0.91$ for Madrid, $\hat{y}_2 = 0.09$ for Paris, and $\hat{y}_3$ rounds to 0.00 for Berlin. Since our ground truth label is Paris, this means that $y_1 = 0$, $y_2 = 1$, and $y_3 = 0$. This is known as one-hot encoding. So our partial derivative $\partial L/\partial h_1$ for Madrid is equal to 0.91 minus 0 equals 0.91. This large positive value for $\partial L/\partial h_1$ means that if we increase h_1, our loss will increase. The partial derivative for Paris, $\partial L/\partial h_2$ is equal to $0.09\text{-}1 = 0.91$. This large negative value means that if we increase h_2, our loss will go down.

Now, remember that h is just an intermediate output of our model that depends both on our model parameters and data. We've solved for $\partial L/\partial h$, but to get a derivative we can use to train our model like $\partial L/\partial m_2$, we need to complete our chain rule math. Our remaining partial derivative, $\partial h_2/\partial m_2$, asks us to find the rate of change of our intermediate output h_2, with respect to our model parameter m_2. These variables are linked by the linear equation of our neuron $h_2 = m_2 x + b_2$.

We typically think of this equation as a line with a fixed slope of m_2 and y-intercept of b_2. However, our partial derivative is asking us to think of m_2 as a variable—this makes sense because learning consists of changing our parameters m and b. From this perspective our input x is constant and m_2 and h_2 are the variables—this still looks like a straight line, but now its slope is equal to our input x, as shown in Figure 3.13. So the partial derivative of the output of our neuron with respect to our model parameter m_2, $\partial h_2/\partial m_2$ is just the slope of our line, x.

Intuitively, this result tells us that the impact of our model parameter m_2 on our neuron's outputs depends on the input value x. If the input value x to our model is small, then the value of our parameter m_2 matters less in our derivative calculation, and this neuron's parameters do not need to be updated much as the model learns from this example. Alternatively if our neuron's input x is large, it has more of an impact on our final loss, and needs a larger update. This intuition is important as we expand to deeper models.

Replacing $\partial h_2/\partial m_2$ with our result x, we now have a complete expression for $\partial L/\partial m_2$, as shown in Figure 3.14. Computing $\partial L/\partial m_2$ for our Paris example, we multiply our input longitude $2.3514°$ by our model's output probability of Paris, 0.09, minus one, computing a final partial derivative value of -2.140.

So all of this backpropagation mathematics is telling us that for this single Paris training point, if we increase our parameter m_2 by one, we expect our loss to decrease by 2.140.

Partial derivative values like this are the key result of backpropagation, and are the components of the gradient vector, which drives the learning process for virtually all modern AI models.



Figure 3.14 | An actual number! Combining our $\partial L/\partial h$ result from the previous page and our $\partial h_2/\partial m_2$ result from Figure N, we have $\partial L/\partial m_2 = x(\hat{y}_2 - y_2)$. So our chain rule calculus gives us a nice simple formula we can plug into directly to compute our partial derivative! Note that $y_2 = 1$ here because our input example $x = 2.3514°$ is in Paris. Computed partial derivative values like this make up the gradient vector, which drives the entire learning process in virtually all modern AI models.



Figure 3.15 | The Gradient. The gradient vector is made up of one partial derivative for each of our model's parameters, and drives the learning process in virtually all modern AI models.



Figure 3.16 | Now we're getting somewhere. Thanks to the partial derivative equations we've solved for, we know now exactly how our loss varies with each of our model's parameters. $\partial L/\partial m_1$ is large and positive, meaning that if we increase m_1 our loss will increase. So to bring our loss down, we should reduce the value of m_1. $\partial L/\partial m_2$ is large and negative, meaning that if we increase m_2 we expect our loss to go down. So to train our model we should update our parameters in the *opposite direction* of our gradients.



Figure 3.17 | How Models Learn. To train our model, we iteratively update our parameters by subtracting the scaled gradients. This moves our model "downhill" towards lower loss solutions. This simple learning strategy scales to large models unreasonably well.

To compute the full gradient vector for our TinyGPS model, we have to solve five more equations, one for each remaining model parameter. This mathematics ends up being very similar to the process we already followed for solving for $\partial h_2/\partial m_2$. Typically these individual equations are rolled up into equations that operate on vectors and matrices instead of individual numbers, so we end up with a single equation to compute the partial derivatives with respect to all three m values, and a single equation for all three b values.

We can now use these equations to compute the partial derivatives for all six model parameters, giving us our full gradient vector. As we saw earlier, the $\partial L/\partial m_2$ value is large and negative, meaning that if we increase m_2, our loss on this training example will decrease, as shown in Figure 3.16. This makes sense because our model's predicted probability of the correct answer of Paris is low right now, and increasing m_2 will increase our model's probability of Paris, lowering our loss. $\partial L/\partial m_1$, on the other hand, is large and positive. This means that if we increase m1, our loss will go up. This makes sense because our model's probability of the wrong answer, Madrid, is currently high, and increasing m1 will further increase this probability, increasing our loss.

Since positive slopes like this mean that increasing our parameter will increase our loss, to train our model to reduce our loss, we want to adjust our parameters in the opposite direction of our gradient. We should reduce m_1 to reduce loss, and increase m_2 to reduce loss.

Mathematically, we can do this by taking our current model parameters, subtracting a scaled version of our gradients, and replacing our parameters with the result. This is the gradient descent process we visualized in Chapter 2 as going downhill on the model's loss landscape, and thanks to backpropagation, we now have an efficient way to compute our gradient vector.

The scaling factor α shown in Figure 3.17 controls the size of the step we take on our loss landscape, and is known as the learning rate—we generally want it to be fairly small, something like 0.0001. This is because our gradient only gives us the slope in a very local neighborhood, and as we saw in Chapter 2, our loss landscapes can be highly complex, with slopes that quickly shift as we update our parameters.

We also saw in Chapter 2 how visualizing gradient descent as going downhill on our loss landscape is a fairly incomplete picture of how our model learns.

Let's use our computed gradients to observe the learning process more directly, as shown in Figure 3.19 on the following page.

$$\begin{aligned}\frac{\partial L}{\partial m_1} &= x(\hat{y}_1 - y_1)\\ \frac{\partial L}{\partial m_2} &= x(\hat{y}_2 - y_2)\\ \frac{\partial L}{\partial m_3} &= x(\hat{y}_3 - y_3)\end{aligned} \quad \Rightarrow \quad \frac{\partial L}{\partial \boldsymbol{m}} = \boldsymbol{x}(\hat{\boldsymbol{y}} - \boldsymbol{y})$$

$$\begin{aligned}\frac{\partial L}{\partial b_1} &= (\hat{y}_1 - y_1)\\ \frac{\partial L}{\partial b_2} &= (\hat{y}_2 - y_2)\\ \frac{\partial L}{\partial b_3} &= (\hat{y}_3 - y_3)\end{aligned} \quad \Rightarrow \quad \frac{\partial L}{\partial \boldsymbol{b}} = (\hat{\boldsymbol{y}} - \boldsymbol{y})$$

Figure 3.18 | All Six Answers. We get similar equations when we solve for all six gradients, and can write these results more compactly using vectors instead of scalars.

Step	0	1	2	3	10	20	30	40	50	60	70	80	90
x	2.351	-3.703	-3.684	13.405	2.294	-3.692	2.351	2.294	-3.692	2.351	2.294	-3.692	2.351
m_1	1	0.894	0.709	0.525	-0.416	-0.518	-0.597	-0.671	-0.717	-0.755	-0.797	-0.827	-0.853
m_2	0	0.107	0.111	0.117	-0.268	0.173	0.13	0.154	0.241	0.206	0.205	0.269	0.253
m_3	-1	-1.001	-0.819	-0.642	0.684	0.345	0.467	0.517	0.476	0.549	0.593	0.558	0.6
$\partial L/\partial m_1$	2.129	3.7	3.67	13.349	0.169	0.392	0.145	0.119	0.167	0.087	0.079	0.114	0.06
$\partial L/\partial m_2$	-2.149	-0.063	-0.127	0.056	-2.074	-0.288	-1.407	-1.341	-0.141	-1.154	-1.132	-0.103	-0.946
$\partial L/\partial m_3$	0.019	-3.637	-3.543	-13.405	1.904	-0.104	1.262	1.223	-0.026	1.068	1.053	-0.011	0.886
b_1	0	-0.045	0.005	0.054	0.06	0.052	0.058	0.068	0.061	0.062	0.068	0.063	0.063
b_2	0	0.046	0.045	0.043	-0.015	0.163	0.223	0.257	0.375	0.43	0.461	0.559	0.607
b_3	0	0	-0.05	-0.098	-0.044	-0.215	-0.281	-0.326	-0.436	-0.492	-0.529	-0.622	-0.67
$\partial L/\partial b_1$	0.906	-0.999	-0.996	0.996	0.074	-0.106	0.062	0.052	-0.045	0.037	0.034	-0.031	0.026
$\partial L/\partial b_2$	-0.914	0.017	0.034	0.004	-0.904	0.078	-0.598	-0.585	0.038	-0.491	-0.493	0.028	-0.402
$\partial L/\partial b_3$	0.008	0.982	0.962	-1	0.83	0.028	0.537	0.533	0.007	0.454	0.459	0.003	0.377
h_1	2.351	-3.354	-2.605	7.092	-0.895	1.964	-1.346	-1.471	2.707	-1.713	-1.762	3.116	-1.943
h_2	0	-0.352	-0.362	1.61	-0.63	-0.475	0.528	0.611	-0.514	0.914	0.93	-0.435	1.202
h_3	-2.351	3.706	2.968	-8.703	1.525	-1.489	0.818	0.86	-2.192	0.799	0.831	-2.681	0.741
$\hat{y}_1$	0.906	0.001	0.004	0.996	0.074	0.894	0.062	0.052	0.955	0.037	0.034	0.969	0.026
$\hat{y}_2$	0.086	0.017	0.034	0.004	0.096	0.078	0.402	0.415	0.038	0.509	0.507	0.028	0.598
$\hat{y}_3$	0.008	0.982	0.962	0	0.83	0.028	0.537	0.533	0.007	0.454	0.459	0.003	0.377
y	1	0	0	2	1	0	1	1	0	1	1	0	1
Loss	2.451	7.079	5.612	15.799	2.341	0.112	0.912	0.879	0.046	0.675	0.68	0.031	0.515
Accuracy	0	0	0	0.667	0.667	0.733	1	1	1	1	1	1	1





Figure 3.19 | Step by Step, Our Model Learns! Now that we have a way to compute our partial derivatives, we can bring everything together and train our model using gradient descent. The upper left table shows our model input data x, model parameters m and b, gradients $\partial L/\partial m$ and $\partial L/\partial b$ neuron outputs h, model predictions $\hat{y}$, labels y, loss, and accuracy as the model learns. The heatmaps across the page show the model's output across a range of longitudes at each training step, in the blue region, the model is most confident in Madrid, in the red region, the model is most confident in Paris, and in the green region the model is most confidence in Berlin. The time series plots in the upper right panels show the same model data as the table, and finally the panels on the bottom left and right show the model's configuration before and after training. Our first training point, at step 0 is in Paris. As we saw earlier, the initial model parameters we chose result in a high output probability for Madrid for this input longitude. We can also see this on our map—at step 0, Paris is in the blue region on our map where our model's top



prediction is Madrid. This error results in high gradients for our Paris and Madrid neurons ($\partial L/\partial m_1$ and $\partial L/\partial m_2$). Moving forward one learning step, these high gradients lead to a reduced value of our m_1 parameter and an increase in our m_2 parameter—which shifts the red Paris region of our map a little to the right, closer to the true location of Paris (shifting not shown). Our next training example is from Madrid (Step=1), which our model misclassifies as being in Berlin, leading to high gradient values for both Madrid and Berlin ($\partial L/\partial m_1$ and $\partial L/\partial m_3$). Note that on our map, these regions need to completely switch sides. Running gradient descent for about 10 steps is enough for our little gradient driven updates to accomplish this, correctly classifying Madrid and Berlin, and just leaving our Paris region not quite actually on top of Paris. From here our gradients slowly increase our m_2 and b_2 values, moving our model's predicted Paris region on top of the actual city. Note that our gradients become smaller as our model learns and makes smaller errors.





Figure 3.20 | But what are our neurons actually doing? Each neuron in our neural network learns a simple linear model, where the input to the model is the longitude x of the current training example. The outputs of these neurons (h_1=*Madrid*, h_2=*Paris*, h_3=*Berlin*) are passed into our softmax function, which amplifies whichever h is largest. The maps here are colored using the final softmax $\hat{y}$ values, where more saturated colors correspond to higher $\hat{y}$ values. Geometrically, each city's h value corresponds to the height of its line at the current input x value. So for a given x value, our model's top prediction corresponds to whichever line is on top in our line plots. Note that as our model learns, it slowly adjusts our lines so our blue Madrid h_1 line is on top of the other lines at the coordinates of Madrid, our red Paris h_2 line is on top of the other lines at the coordinates of Paris, and our green Berlin h_3 line is on top of the other lines at the coordinates of Berlin.



Figure 3.21 | Going 3D. (Left) Bringing our map and linear models together, we can think of each neuron as creating a plane over our map, where the height of a given plane corresponds to that neuron's output h value. When we apply softmax (right), our planes are bent and curved to produce our final output probabilities. The height of these surfaces corresponds to the colors in the heatmaps in Figure 3.19 and 3.20. Note that the intersection lines, where our model is equally confident in two different cities, are the same before and after softmax.



Figure 3.19 gives a granular view of our model learning, but how exactly is our neural network using the little linear models that make up each neuron to partition our map? We can see a little more under the hood of our model by running the same training process again, but this time while visualizing the little linear models learned by each neuron, as shown in Figure 3.20. Our initially chosen slopes of m_1=1, m_2=0, and m_3=-1 make our initial linear models go uphill, flat, and downhill, as shown in the far left panel. As our model learns, our Madrid neuron flips to pointing downhill, our Paris neuron wobbles a bit and ends up going slightly uphill, and our Berlin Neuron flips from going downhill to uphill.

For a given input longitude, the output of each neuron is equal to the height of its line on this plot. So for the Paris example with a longitude of 2.3514 degrees, before training (m_1=1), the Madrid neuron's line has a height of 2.3514—this equal to our h_1 value for this input. Our softmax function just amplifies whichever input is largest, so whichever line is on top at a given longitude in our plot will lead to the model's highest output probability.

As our model learns in Figure 3.20, we can see that our gradients slowly push the Madrid line so it has the largest value over our Madrid points, the Paris line so it has the largest value over our Paris points, and our Berlin line so it has the largest value over our Berlin points.

In the full space of our map, our three lines in Figure 3.20 are equivalent to three planes, as shown in Figure 3.21, and through backpropagation our model learns to position each plane above the correct city. When we apply our softmax function to the outputs of our neurons, softmax squishes and curves our planes but retains the same general structure, resulting in our final outputs.

Madrid	
Center of Madrid	(40.4167°, -3.7033°)
Retiro Park	(40.4153°, -3.6835°)
Royal Palace	(40.4180°, -3.7143°)
Prado Museum	(40.4138°, -3.6921°)
Puerta del Sol	(40.4169°, -3.7033°)

Paris	
Center of Paris	(48.8575°, 2.3514°)
Eiffel Tower	(48.8584°, 2.2945°)
Notre Dame	(48.8530°, 2.3499°)
Louvre	(48.8606°, 2.3376°)
Centre Pompidou	(48.8606°, 2.3522°)

Berlin	
Center of Berlin	(52.5200°, 13.4050°)
Brandenburg Gate	(52.5163°, 13.3777°)
Museum Island	(52.5169°, 13.4019°)
Checkpoint Charlie	(52.5074°, 13.3904°)
Berlin Central Station	(52.5251°, 13.3694°)

Barcelona	
Center of Barcelona	(41.3874°, 2.1686°)
Sagrada Familia	(41.4036°, 2.1744°)
Gothic Quarter	(41.3819°, 2.1773°)
Park Güell	(41.4145°, 2.1527°)
Camp Nou	(41.3809°, 2.1228°)

Figure 3.22 | One More City. Let's add another city to our dataset and see how our model performs.

Now, what's really compelling about backpropagation is how it's able to scale to larger problems and ultimately massive language models. Let's increase the complexity of our problem, and see how our intuitions and mathematics hold up.

Let's begin by adding a fourth city to our training set, Barcelona. Barcelona has a very similar longitude to Paris, so our model now needs to take in both longitude and latitude, which we'll call x_1 and x_2. We now need to expand the little linear models in our neurons to include both inputs, meaning we now have two slope values m per neuron. Visually, instead of a line, each neuron now looks like a little plane, where our two slope values control the steepness of the plane in each direction.

Our backpropagation math works out almost exactly the same—we just have more parameters—we now have four neurons, one for each city, now with three parameters each, two m values that multiply each of our two inputs, and a single bias value. This makes for 12 total parameters, so we need 12 derivatives to update our weights. Training our new two input model as shown in Figure 3.24, we see that it's quickly able to fit our four planes to our data, and correctly divide our map into four regions, one for each city. Putting our planes together over our map, we can see how our model has fit our planes together so our Madrid plane is on top of the other planes above Madrid, our Barcelona plane is on top above Barcelona, and so on.

NEURONS

$$h_1 = m_{11}x_1 + m_{12}x_2 + b_1$$
$$h_2 = m_{21}x_1 + m_{22}x_2 + b_2$$
$$h_3 = m_{31}x_1 + m_{32}x_2 + b_3$$
$$h_4 = m_{41}x_1 + m_{42}x_2 + b_4$$

SOFTMAX

$$\hat{y}_i = \frac{e^{h_i}}{e^{h_1} + e^{h_3} + e^{h_3} + e^{h_4}}$$

GRADIENT

$$\frac{\partial L}{\partial m_{11}} = x_1(\hat{y}_1 - y_1) \qquad \frac{\partial L}{\partial m_{32}} = x_2(\hat{y}_3 - y_3)$$
$$\frac{\partial L}{\partial m_{21}} = x_1(\hat{y}_2 - y_2) \qquad \frac{\partial L}{\partial m_{42}} = x_2(\hat{y}_4 - y_4)$$
$$\frac{\partial L}{\partial m_{31}} = x_1(\hat{y}_3 - y_3) \qquad \frac{\partial L}{\partial b_1} = (\hat{y}_1 - y_1)$$
$$\frac{\partial L}{\partial m_{41}} = x_1(\hat{y}_4 - y_4) \qquad \frac{\partial L}{\partial b_2} = (\hat{y}_2 - y_2)$$
$$\frac{\partial L}{\partial m_{12}} = x_2(\hat{y}_1 - y_1) \qquad \frac{\partial L}{\partial b_3} = (\hat{y}_3 - y_3)$$
$$\frac{\partial L}{\partial m_{22}} = x_2(\hat{y}_2 - y_2) \qquad \frac{\partial L}{\partial b_4} = (\hat{y}_4 - y_4)$$

Figure 3.23 | Full Equations for a Larger Model. Expanding our model to two inputs and four outputs, we have more variables to deal with, but our math works out the same.







Figure 3.24 | More Neurons, More Complexity. Our new city, Barcelona, has a similar longitude to Paris, so our network now needs to use both longitude and latitude to make predictions, meaning each neuron has two inputs, and effectively learns a plane. As our model learns, it moves each city's plane so it's on top of all other planes above its corresponding city (e.g. the purple Barcelona plane h_4 is above all other planes above Barcelona). The upper pane shows a Berlin point moving through the model after training. Note that for this four city model, we've normalized our data by subtracting the center of Paris from all points. See code samples at the end of this chapter for more information.



Figure 3.25 | Token Embeddings and GPS Coordinates are Not So Different. Each token in Llama's vocabulary (like Madrid, Paris, and Berlin) is mapped to an embedding vector of length 2048. GPS coordinates tell us where a city is on a map, embedding vectors tell us where the concept of a given city *is* in the map of language learned by the network.

Of course, simple planes like this can only learn a very limited set of patterns—to see the issue here more clearly, let's consider the most complex border in the world—between Belgium and the Netherlands in the municipality of Baarle-Hertog. The white shaded regions of the map in Figure 3.26 are part of Belgium, while all the other parts of the map are part of the Netherlands. Given a single plane for Belgium and a single plane for the Netherlands, there's no way to cleanly divide these complex regions.

Now, it might seem a bit random to spend our time training a model to fit esoteric European borders—but this type of problem has more in common with training large language models than you may expect. Our Llama model represents individual tokens like Madrid, Paris, and Berlin as vectors of 2048 floating point numbers. When we pass in some text like "the capital of France is", there's a specific length 2048 vector in our model, specifically the final position in the residual stream, that is iteratively pushed by each layer towards the vector for Paris.

This gets really interesting when we consider all the different types of text that can lead to a next token of Paris, Madrid, or Berlin. If we pass in a variety of training text examples from the wikitext dataset that lead up to next tokens of Paris, Madrid, or Berlin, and compute the predicted next token vectors for each training example for a layer in the middle of our model, we end up with a set of length 2048 vectors, each generated by examples with next tokens of Madrid, Paris, or Berlin in our training text, as shown in Figure 3.27.

Figure 3.27 | Probing Llama's Map of Language. An interesting way to get a sense for how Llama (Llama 3.2 1B) learns a "map of language" is to pass in various pieces of text that lead to the same next token. Here, we're taking examples from the Wikitext dataset that each lead up to the same next tokens of either *"Madrid"* (first two examples above), *"Paris"* (middle two examples), or *"Berlin"* (final two examples). When we pass text into the model, each token in the text becomes a row in the model's residual stream. The final row of this residual stream matrix is slowly pushed by the model to become the embedding vector of the next predicted token. For example, for the two *"Madrid"* examples above, if we sample the residual stream matrix at the model's final layer, we expect the final rows to be very similar to each other and close to the embedding vector for the token *"Madrid"*. Now, if instead of sampling the residual stream at the end of the model, we sample in the middle of the model, we can see how the model starts to bring different concepts together in its embedding space to make the correct next token predictions. Here we're collecting a dataset composed of embedding vectors taken from the final position in the residual stream in Llama's 7th layer. We'll visualize these vectors on the following page. See Chapter Five for more about embedding vectors.

Figure 3.26 | Meet the Final Border Boss. The municipality of Baarle-Hertog has the most complex border in the world. Our simple single layer network that fits planes to each region of our map has no chance at dividing up our map correctly!





Figure 3.28 | Llama's Map of Language. Each of these 7500 points corresponds to a single piece of text from the Wikitext dataset leading up to a next token of Madrid, Paris, or Berlin. Each text sample is passed through the first seven layers of Llama-3.2-1B, and the final row of the residual stream is sampled. These sampled vectors are then projected from 2048 dimensions to just two using a UMAP algorithm, which seeks to preserve distances between points in the high-dimensional space. When we scatter our resulting points, some really amazing patterns emerge—with very clean "islands of concepts". Here we see regions of our map for sports, especially Real and Atletico Madrid, regions for East and West Berlin, a region for Treaties, including the Treaty of Paris, Treaty of Madrid, and Treaty of Berlin, a little island representing people being born in Paris, Madrid, or Berlin, and a little island for people returning to Paris, Berlin, and Madrid. These embedding vectors are sampled in the middle of the model, and by the end of the model (layer 16), all of these various pockets need to be mapped to single location in the embedding space corresponding to the token for each city. So at the end of the model, we expect just three islands, one for each city. Just as disconnected parts of our municipality of Baarle-Hertog all need to map to the same country of Belgium, disconnected regions in our space of language all need to map to the same next token of Paris, Madrid, or Berlin. Note that the supporting code for the chapter includes an interactive version of this graphic.

One way to think of these vectors is as the coordinates of our examples on the high-dimensional map of language learned by our model. We can get a sense of the geometry of this map by projecting down from 2048 dimensions to two using a UMAP algorithm, which seeks to preserve the distances between points in the high-dimensional space. We see some really interesting clustering in this space— with similar concepts forming little islands on our map of language, as shown in Figure 3.28.

When Marvin Minsky rejected backpropagation in the early 1970s, he dismissed the idea because it converged too slowly, and because according to Minsky, it couldn't learn anything too difficult. [Olazaran 1996]

Just as disconnected parts of our municipality of Baarle-Hertog all need to map to the same country of Belgium, disconnected regions in our space of language all need to map to the same next token of Paris, Madrid, or Berlin—and it's up to our model to figure out how to partition and reshape space to achieve this.

Minsky was right that learning by gradient descent can take many steps, this mattered a lot given the compute power available at the time. However, he enormously underestimated the ability of our simple backpropagation algorithm to scale to solve incredibly complex problems.

In Chapter 4, we'll see what Minsky missed.

Figure 3.29 | We Aren't So Different. Our Llama large language model learning to map various text to next tokens of Madrid, Paris, or Berlin is not so different than a model learning to map the regions of our map of Baarle-Hertog to the correct country. The key difference is the dimensionality of the spaces of these problems— our physical map is two-dimensional while Llama's map of language is 2048 dimensional— otherwise the mathematics is the same.

SUPPORTING CODE

This sections contains supporting code for the key results presented in this chapter. This code and more are available at:

`github.com/stephencwelch/ai_book`

3.1 Forward Pass Through Llama Model

Generates forward pass shown in figure 3.1

[1]:
```
import torch
from transformers import AutoModelForCausalLM, AutoTokenizer

device='cuda'
model_id = "meta-llama/Llama-3.2-1B"
model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
tokenizer = AutoTokenizer.from_pretrained(model_id)
```

[2]:
```
prompt = "The capital of France is"
inputs = tokenizer(prompt, return_tensors="pt").to(device)
inputs['input_ids']
```

[2]:
```
tensor([[128000, 791, 6864, 315, 9822, 374]], device='cuda:0')
```

[3]:
```
with torch.no_grad():
    outputs = model(inputs['input_ids'])

last_token_logits = outputs.logits[0, -1, :]
probabilities = torch.nn.functional.softmax(last_token_logits, dim=-1)
outputs.logits.shape, last_token_logits.shape, probabilities.shape
```

[3]:
```
(torch.Size([1, 6, 128256]), torch.Size([128256]), torch.Size([128256]))
```

[4]:
```
top_probs, top_indices = torch.topk(probabilities, 6)
for i, (prob, idx) in enumerate(zip(top_probs, top_indices), 1):
    token = tokenizer.decode([idx.item()])
    display_token = repr(token) if token.strip() != token else f"'{token}'"
    print(f"{i:2d}. {display_token:<15} {prob.item():.5f}")
```

[4]:
```
1. ' Paris' 0.39153
2. ' a' 0.08419
3. ' the' 0.07040
4. ' one' 0.03096
5. ' also' 0.03061
6. ' home' 0.02528
```

3.2 Train Simple 3 City model

Generates results from in Figure 3.19

[5]:
```
import numpy as np
import torch
import matplotlib.pyplot as plt
```

[6]:
```
paris_coords = np.array([
    [48.8575, 2.3514], #Center of Paris
    [48.8584, 2.2945], # Eiffel Tower
    [48.8530, 2.3499], #Notre Dame
    [48.8606,  2.3376], #Louvre
    [48.8606, 2.3522]  #Centre Pompidou
])

madrid_coords = np.array([
    [40.4167, -3.7033],   # Center of Madrid
    [40.4153, -3.6835],   # Retiro Park
    [40.4180, -3.7143],   # Royal Palace
    [40.4138, -3.6921],   # Prado Museum
    [40.4169, -3.7033]   # Puerta del Sol
])

berlin_coords = np.array([
    [52.5200, 13.4050], # Center of Berlin
    [52.5163, 13.3777],   # Brandenburg Gate
    [52.5169, 13.4019],   # Museum Island
    [52.5074, 13.3904],   # Checkpoint Charlie
    [52.5251, 13.3694]   # Berlin Central Station
])
```

[7]:
```
# Set random seed for reproducibility
random_seed=52
torch.manual_seed(random_seed)
np.random.seed(random_seed)
```

[8]:
```
# Combine data into one matrix X and labels y
X_raw = np.vstack([madrid_coords, paris_coords, berlin_coords])
y = np.array([0, 0, 0, 0, 0,  #  Madrid labels (0)
              1, 1, 1, 1, 1,  #  Paris labels (1)
              2, 2, 2, 2, 2]) #, # Berlin labels (2)

shuffle_idx = np.random.permutation(len(y))
shuffle_idx[0]=5
shuffle_idx[-1]=8 # A little manual shuffling to match ordering from earlier
X = X_raw[shuffle_idx, 1:2]  # Extract longitude as column vector
y = y[shuffle_idx]
```

[9]:
```
X.shape, y.shape
```

[9]:
```
((15, 1), (15,))
```

[10]:
```
class TinyGPSModel(torch.nn.Module):
    def __init__(self, input_size=1, output_size=3):
        super(TinyGPSModel, self).__init__()
        self.output = torch.nn.Linear(input_size, output_size)

    def forward(self, x):
        x = self.output(x)
        return x
```

[11]:
```
# Initialize model, loss, and optimizer
model = TinyGPSModel()
criterion = torch.nn.CrossEntropyLoss()
optimizer = torch.optim.SGD(model.parameters(), lr=0.05)
num_steps=100

#Manually intialize model parameters
with torch.no_grad():
    model.output.weight[0,0]=1.0
    model.output.weight[1,0]=0.0
    model.output.weight[2,0]=-1.0
    model.output.bias[0]=0
    model.output.bias[1]=0
    model.output.bias[2]=0

for i in range(num_steps):
    optimizer.zero_grad()
    outputs = model(torch.tensor(X[i%len(y)]).float())
    loss = criterion(outputs, torch.tensor(y[i%len(y)]))

    loss.backward()
    optimizer.step()

    if (i + 1) % 10 == 0:
        with torch.no_grad():
            logits=model(torch.tensor(X, dtype=torch.float))
            accuracy=(torch.argmax(logits, dim=1)==torch.tensor(y)).sum().item()/len(y)
        print(f"Step {i+1}/{num_steps}, Loss: {loss.item():.4f}, Accuracy: {accuracy:.4f}")
```

[11]:
```
Step 10/100, Loss: 0.0000, Accuracy: 0.6667
Step 20/100, Loss: 1.0067, Accuracy: 0.6667
Step 30/100, Loss: 1.1746, Accuracy: 0.6667
Step 40/100, Loss: 0.0196, Accuracy: 0.6667
Step 50/100, Loss: 0.7774, Accuracy: 1.0000
Step 60/100, Loss: 0.8595, Accuracy: 1.0000
Step 70/100, Loss: 0.0217, Accuracy: 1.0000
Step 80/100, Loss: 0.6236, Accuracy: 1.0000
Step 90/100, Loss: 0.6394, Accuracy: 1.0000
Step 100/100, Loss: 0.0225, Accuracy: 1.0000
```

3.3 Train 4 City Model

As shown in Figure 3.24

[12]:
```
import numpy as np
import torch
import matplotlib.pyplot as plt

paris_coords = np.array([
    [48.8575, 2.3514], #Center of Paris
    [48.8584, 2.2945], # Eiffel Tower
    [48.8530, 2.3499], #Notre Dame
    [48.8606,  2.3376], #Louvre
    [48.8606, 2.3522]  #Centre Pompidou
])

madrid_coords = np.array([
    [40.4167, -3.7033],   # Center of Madrid
    [40.4153, -3.6835],   # Retiro Park
    [40.4180, -3.7143],   # Royal Palace
    [40.4138, -3.6921],   # Prado Museum
    [40.4169, -3.7033]   # Puerta del Sol
])

berlin_coords = np.array([
    [52.5200, 13.4050], # Center of Berlin
    [52.5163, 13.3777],   # Brandenburg Gate
    [52.5169, 13.4019],   # Museum Island
    [52.5074, 13.3904],   # Checkpoint Charlie
    [52.5251, 13.3694]   # Berlin Central Station
])

barcelona_coords = np.array([
    [41.3874, 2.1686],    # Center of Barcelona
    [41.4036, 2.1744],    # Sagrada Familia
    [41.3819, 2.1773],    # Gothic Quarter
    [41.4145, 2.1527],    # Park Güell
    [41.3809, 2.1228],    # Camp Nou
])
```

[13]:
```
mean_to_subtract=np.array([48.8575, 2.3514]) #Center of Paris

# Set random seed for reproducibility
random_seed=25
torch.manual_seed(random_seed)
np.random.seed(random_seed)

# Combine data into one matrix X and labels y
X_raw = np.vstack([madrid_coords, paris_coords, berlin_coords, barcelona_coords])
y = np.array([0, 0, 0, 0, 0,  #  Madrid labels (0)
              1, 1, 1, 1, 1,  #  Paris labels (1)
              2, 2, 2, 2, 2, # Berlin labels (2)
              3, 3, 3, 3, 3]) # Barcelona Labels (3)

X = X_raw - mean_to_subtract #Normalize by subtracing center of Paris to help model converge

rI=np.arange(len(y))
np.random.shuffle(rI)
rI[0]=5
rI[11]=13 # A little manual shuffling to match example we showed earlier in the chapter.
X=X[rI,:]
y=y[rI]
X_raw=X_raw[rI,:]

print(f"Shape of X: {X.shape}")
print(f"Shape of y: {y.shape}")
```

[13]:
```
Shape of X: (20, 2)
Shape of y: (20,)
```

[14]:
```
class TinyGPSModel(torch.nn.Module):
    def __init__(self, input_size=2, output_size=4):
        super(TinyGPSModel, self).__init__()
        self.output = torch.nn.Linear(input_size, output_size)

    def forward(self, x):
        x = self.output(x)
        return x
```

[15]:
```
# Initialize model, loss, and optimizer
model = TinyGPSModel()
criterion = torch.nn.CrossEntropyLoss()
optimizer = torch.optim.Adam(model.parameters(), lr=0.03)

num_steps=250
for i in range(num_steps):
    optimizer.zero_grad()

    outputs = model(torch.tensor(X[i%len(y)]).float())
    loss = criterion(outputs, torch.tensor(y[i%len(y)]))

    loss.backward()  # backpropagation
    optimizer.step()

    if (i + 1) % 10 == 0:
        with torch.no_grad():
            logits=model(torch.tensor(X, dtype=torch.float))
            accuracy=(torch.argmax(logits, dim=1)==torch.tensor(y)).sum().item()/len(y)
        print(f"Step {i+1}/{num_steps}, Loss: {loss.item():.4f}, 'Accuracy: {accuracy:.4f}")
```

[15]:
```
Step 10/250, Loss: 1.1087, 'Accuracy: 0.2500
Step 20/250, Loss: 0.1993, 'Accuracy: 0.3000
Step 30/250, Loss: 1.4339, 'Accuracy: 0.5000
Step 40/250, Loss: 0.0933, 'Accuracy: 0.7500
Step 50/250, Loss: 1.4941, 'Accuracy: 0.7500
Step 60/250, Loss: 0.0527, 'Accuracy: 0.7500
Step 70/250, Loss: 1.3485, 'Accuracy: 0.7500
Step 80/250, Loss: 0.0346, 'Accuracy: 0.7500
Step 90/250, Loss: 1.1523, 'Accuracy: 1.0000
Step 100/250, Loss: 0.0337, 'Accuracy: 1.0000
Step 110/250, Loss: 0.9639, 'Accuracy: 1.0000
Step 120/250, Loss: 0.0298, 'Accuracy: 1.0000
Step 130/250, Loss: 0.7997, 'Accuracy: 1.0000
Step 140/250, Loss: 0.0258, 'Accuracy: 1.0000
Step 150/250, Loss: 0.6627, 'Accuracy: 1.0000
Step 160/250, Loss: 0.0228, 'Accuracy: 1.0000
Step 170/250, Loss: 0.5515, 'Accuracy: 1.0000
Step 180/250, Loss: 0.0203, 'Accuracy: 1.0000
Step 190/250, Loss: 0.4624, 'Accuracy: 1.0000
Step 200/250, Loss: 0.0180, 'Accuracy: 1.0000
Step 210/250, Loss: 0.3914, 'Accuracy: 1.0000
Step 220/250, Loss: 0.0161, 'Accuracy: 1.0000
Step 230/250, Loss: 0.3346, 'Accuracy: 1.0000
Step 240/250, Loss: 0.0145, 'Accuracy: 1.0000
Step 250/250, Loss: 0.2890, 'Accuracy: 1.0000
```

3. BACKPROPAGATION | EXERCISES

3.1 Paul Werbos' claim that backpropagation is as important to intelligence as Newton's laws were to physics may seem grandiose. If I were in Minsky's shoes in the early 1970s I would have been skeptical as well. However, time has only proven Werbos more right—backpropagation has scaled astoundingly well—do you think Werbos was right? Is backpropagation as important to the study of intelligence as F=ma was to the study of physics?

"..this new mathematical concept [backpropagation] opens up the possibility of a scientific understanding of intelligence, as important to psychology and neurophysiology as Newton's concepts were to physics"

Paul Werbos
[Werbos 1994]

"But, you see, it's not a good discovery... It converges slowly, and it cannot learn anything difficult"

Marvin Minsky
[Olazaran 1996]

3.2 Backpropagation and gradient descent, when viewed a single step at a time, as shown in Figure 3.19, can look chaotic. It never ceases to amaze me that these little parameter update steps, driven by gradient descent, are able to learn such complicated things—each step is really quite simple. How do you think it is that all these little steps are able to add up to such impressive results?

3.3 Why is it impossible for our single layer plane-fitting neural network to fit the borders of the town of Baarle-Hertog as shown in Figure 3.26?

Paris

Center of Paris	(48.8575°, 2.3514°)
Eiffel Tower	(48.8584°, 2.2945°)

Berlin

Center of Berlin	(52.5200°, 13.4050°)
Brandenburg Gate	(52.5163°, 13.3777°)



$$h_1 = m_1 x + b_1 \quad h_2 = m_2 x + b_2 \quad \hat{y}_i = \frac{e^{h_i}}{e^{h_1} + e^{h_2}}$$

Over the next few exercises, we'll complete a walkthrough of the simplified European city model and dataset above.

3.4 Using the neural network and equations above, complete the "forward pass" for step zero of the table on the next page, computing the h and $\hat{y}$ values. Following the same approach as the model introduced in Figure 3.4, this model only uses the longitude (x). The top row of the table indicates the order the examples are iterated through, starting with x=2.351. The y_1 and y_2 rows indicate the city/label of the current example, where y_1=1 corresponds to Paris, and y_2=1 corresponds to Berlin. Initial model parameters are shown in the first column of the table.

3.5 Using the derivative of softmax + cross-entropy results shown in Figure 3.12 and the chain rule, solve for $\partial L/\partial m_1$ and $\partial L/\partial m_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial m$ values in the table on the following page.

3.6 Using the derivative of softmax + cross-entropy results shown in Figure 3.12, and the chain rule, solve for $\partial L/\partial b_1$ and $\partial L/\partial b_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial b$ values in the table on the following page.

3.7 For Step 0, compute the cross-entropy loss, and accuracy values in the table on the following page. Note that to compute accuracy you will have to pass all four training examples through the model.

Step	0	1	2	3	4	5	6	7	8	9
x	2.351	2.294	13.405	13.378	2.351	2.294	13.405	13.378	2.351	2.294
m_1	-1		-0.546	-0.546	-0.546	-0.334	-0.168	-0.198	-0.211	-0.077
m_2	1		0.546	0.546	0.546	0.334	0.168	0.198	0.211	0.077
$\partial L/\partial m_1$		-2.215	0	0	-2.111	-1.661	0.294	0.136	-1.342	-0.883
$\partial L/\partial m_2$		2.215	0	0	2.111	1.661	-0.294	-0.136	1.342	0.883
b_1	0		0.196	0.196	0.196	0.285	0.358	0.356	0.355	0.412
b_2	0		-0.196	-0.196	-0.196	-0.285	-0.358	-0.356	-0.355	-0.412
$\partial L/\partial b_1$		-0.965	0	0	-0.898	-0.724	0.022	0.01	-0.571	-0.385
$\partial L/\partial b_2$		0.965	0	0	0.898	0.724	-0.022	-0.01	0.571	0.385
h_1		-1.661	-7.117	-7.102	-1.087	-0.482	-1.898	-2.29	-0.142	0.235
h_2		1.661	7.117	7.102	1.087	0.482	1.898	2.29	0.142	-0.235
$\hat{y}_1$		0.035	0	0	0.102	0.276	0.022	0.01	0.429	0.615
$\hat{y}_2$		0.965	1	1	0.898	0.724	0.978	0.99	0.571	0.385
y_1	1	1	0	0	1	1	0	0	1	1
y_2	0	0	1	1	0	0	1	1	0	0
Loss		3.357	0	0	2.282	1.287	0.022	0.01	0.846	
Accuracy		0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	

3.8 This model is trained with a learning rate of α=0.1. Using gradient descent, and your computed gradients from 3.6, compute the new parameter values m and b in Step 1.

3.9 For the final training step 9, compute the model's cross-entropy loss, and final accuracy. Note that to compute accuracy you will have to pass all four training examples through the model.

3.10 Implement and train this neural network in your programming language of choice. Do your results match the table above?

Paris

Center of Paris	(48.8575°, 2.3514°)
Eiffel Tower	(48.8584°, 2.2945°)

Madrid

Center of Madrid	(40.4167°, -3.7033°)
Retiro Park	(40.4153°, -3.6835°)



$$h_1 = m_1 x + b_1 \quad h_2 = m_2 x + b_2 \quad \hat{y}_i = \frac{e^{h_i}}{e^{h_1} + e^{h_2}}$$

Over the next few exercises, we'll complete a walkthrough of the simplified European city model and dataset above.

3.11 Using the neural network and equations above, complete the "forward pass" for step zero of the table on the next page, computing the four h and $\hat{y}$ values. Using the same approach as the model introduced in Figure 3.4, this model only uses the longitude (x) of our training examples. The top row of the table indicates the order the examples are iterated through, starting with x=2.351. The y_1 and y_2 rows indicate the city/label of the current example, where y_1=1 corresponds to Paris, and y_2=1 corresponds to Madrid. Initial model parameters are shown in the first column of the table.

3.12 Using the derivative of softmax + cross-entropy results shown in Figure 3.12 and the chain rule, solve for $\partial L/\partial m_1$ and $\partial L/\partial m_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial m$ values in the table on the following page.

3.13 Using the derivative of softmax + cross-entropy results shown in Figure 3.12, and the chain rule, solve for $\partial L/\partial b_1$ and $\partial L/\partial b_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial b$ values in the table on the following page.

3.14 For Step 0, compute the cross-entropy loss, and accuracy values in the table on the following page. Note that to compute accuracy you will have to pass all four training data through the model.

Step	0	1	2	3
x	2.351	2.294	-3.703	-3.684
m_1	-1		-0.565	-0.218
m_2	0.5		0.065	-0.282
$\partial L/\partial m_1$		-2.065	-3.472	-1.796
$\partial L/\partial m_2$		2.065	3.472	1.796
b_1	0		0.187	0.093
b_2	0		-0.187	-0.093
$\partial L/\partial b_1$		-0.9	0.937	0.488
$\partial L/\partial b_2$		0.9	-0.937	-0.488
h_1		-1.673	2.28	
h_2		0.526	-0.428	
$\hat{y}_1$		0.1	0.937	
$\hat{y}_2$		0.9	0.063	
y_1	1	1	0	0
y_2	0	0	1	1
Loss		2.304	2.772	
Accuracy		0	0	

3.15 This model is trained with a learning rate of α=0.1. Using gradient descent, and your computed gradients from 3.12 and 3.13, compute the new parameter values m and b in Step 1.

3.16 For the final training Step 3, compute the model's our h and $\hat{y}$ values, cross-entropy loss, and final accuracy. Note that to compute accuracy you will have to pass all four training examples through the model.

3.17 Implement and train this neural network in your programming language of choice. Do your results match the table above?

x	y
1	3
2	5
3	7
4	9



$$\hat{y} = mx + b$$

SINGLE NEURON

$$Loss = (\hat{y} - y)^2$$

SQUARED ERROR

A single artificial neuron is composed of a simple $y=mx+b$ linear model. It's possible to train a single neuron using the same backpropagation and gradient descent approach we use to train models composed of many neurons. In the following exercises we'll train a single neuron to perform a simple linear regression task.

3.18 Complete a "forward pass" for Step 0 in the table on the following page, computing $\hat{y}$ and Loss for the first training example x=1, y=3.

3.19 Using the chain rule, solve for $\partial L/\partial m$ and $\partial L/\partial b$. Use your results to compute and fill in the missing values for Step 0 in the table on the following page.

3.20 Using gradient descent and a learning rate of α=0.1, compute the new parameter values m and b in Step 1.

Step	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**
x	1	2	3	4	1	2	3	4
m	1		2.12	2.048	2.106	2.134	2.115	2.046
$\partial L/\partial m$		-7.2	0.72	-0.576	-0.288	0.192	0.691	-0.553
b	0		0.76	0.736	0.75	0.779	0.77	0.747
$\partial L/\partial b$		-3.6	0.24	-0.144	-0.288	0.096	0.23	-0.138
$\hat{y}$		3.2	7.12	8.928	2.856	5.048	7.115	
y	3	5	7	9	3	5	7	9
Loss		3.24	0.014	0.005	0.021	0.002	0.013	

3.21 Complete a forward pass for Step 7, computing $\hat{y}$ and Loss.

3.22 For steps 0, 1, and 7, plot the fit line learned by gradient descent on the scatter plot on the previous page. Is the fit improving? Based on the training data, what do you think the "correct" m and b values are? How close does gradient descent get to these values after these 7 steps?

3.23 One of Marvin Minsky's complaints about backpropagation & gradient descent was that it takes too many steps to converge. Implement gradient descent for this problem in your programming language of choice. How many steps does it take for gradient descent to estimate both model parameters within ±0.001 of their true values? Can you bring this step count down by increasing the learning rate?

x	y
1	3
2	5
3	7
4	9



$$\hat{y} = mx + b$$

SINGLE NEURON

$$Loss = |\hat{y} - y|$$

L1 LOSS

A single artificial neuron is composed of a simple $y=mx+b$ linear model. It's possible to train a single neuron using the same backpropagation and gradient descent approach we use to train models composed of many neurons. In the following exercises we'll train a single neuron to perform a simple linear regression task.

3.24 Complete a "forward pass" for Step 0 in the table on the following page, computing $\hat{y}$ and Loss for the first training example x=1, y=3.

3.25 Using the chain rule, solve for $\partial L/\partial m$ and $\partial L/\partial b$. Use your results to compute and fill in the missing values for Step 0 in the table on the following page.

3.26 Using gradient descent and a learning rate of α=0.1, compute the new parameter values m and b in Step 1.

Step	**0**	**1**	2	**3**	**4**	**5**	**6**	**7**
x	1	2	3	4	1	2	3	4
m	1		1.3	1.6	2	2.1	2.3	2
$\partial L/\partial m$		-2	-3	-4	-1	-2	3	-4
b	0		0.2	0.3	0.4	0.5	0.6	0.5
$\partial L/\partial b$		-1	-1	-1	-1	-1	1	-1
$\hat{y}$		2.3	4.1	6.7	2.4	4.7	7.5	
y	3	5	7	9	3	5	7	9
Loss		2.74	2.9	2.3	0.6	0.3	0.5	

3.27 Complete a forward pass for Step 7, computing $\hat{y}$ and Loss.

3.28 For steps 0, 1, and 7, plot the fit line learned by gradient descent on the scatter plot on the previous page. Is the fit improving? Based on the training data, what do you think the "correct" m and b values are? How close does gradient descent get to these values after these 7 steps?

3.29 Implement gradient descent for this problem in your programming language of choice. How many steps does it take for gradient descent to estimate both model parameters within ±0.001 of their true values? Can you bring this step count down by increasing the learning rate? How does the convergence rate of L1 Loss compare to the convergence rate of Mean Square Error (MSE) in the previous set of problems?

3.30 The supporting code for this chapter (`github.com/stephencwelch/ai_book`) includes an interactive version of the "Map of Language" as shown in Figure 3.28. Clone and run this example—what clusters do you see? How do these clusters change as you move to earlier/later layers in the model?



Figure 4.1 | The geometry of a two-layer network. This two-layer network was trained to predict if a given point on our map is in Belgium or in the Netherlands. As we'll see in this chapter, the mathematics of our first layer of neurons is equivalent geometrically to bending up our map along fold lines determined by our model's learned weights. The first layer of our model has three neurons, resulting in three separate fold lines (red, blue, and green dotted lines in panels A, B, and C). The second and final layer of our model is made up of two neurons. Geometrically, each neuron in our second layer scales and adds together the three bent maps from our first layer. This results in two new bent maps, each with five seperate regions, but with different geometries (panels E and F). The height of the surface in panel E is equal to the output of the first neuron in our second layer and corresponds to the model's confidence in the Netherlands, while the height of the surface in panel F is equal to the output of our second neuron and corresponds to the model's confidence in Belgium. Bringing these surfaces together in panel G, we can see that they intersect in the magenta line—this is where our model is equally confident in both countries, and is the decision boundary learned by our model.

4. DEEP LEARNING

The Geometry of Depth

In 1989, George Cybenko proved what's now known as the universal approximation theorem.

If we take some complex function, for example the really complicated border in the town of Baarle Hertog (Figure 4.2), the universal approximation theorem guarantees that there exists a two-layer neural network (Figure 4.3) that can fit this border, as precisely as we want.

A nice way to get a feel for this result is to see what a two-layer network like this does geometrically. Most modern neural networks use some version of rectified linear activation functions—visually this means each neuron in the first layer of our network folds up a copy of our map along a single fold line, where the location of the fold line controlled by the neuron's learned weights, as shown in panels B-D of Figure 4.1.[1]

From here, the first neuron in our second layer takes in these bent planes and multiplies their heights by another learned weight value, which geometrically further bends up or down the folded up parts of our planes, and flips over our folded region when that neuron's weight value is negative. These three bent planes are then added together by our neuron, resulting in the surface shown in panel E of Figure 4.2. The three fold lines from our first layer now divide our map up into five regions, which each become different planes in our second layer's surface (regions are shaded purple, yellow, green, blue, and orange). The second neuron in our second layer flips, scales and combines our first layer planes using different learned parameters, resulting in the surface shown in panel F, that again using the same five regions of our map, but at different heights.

The height of the surface formed by our first neuron (panel E) corresponds to the model's confidence in the Netherlands, and the height of the second neuron surface (panel F) corresponds to the model's confidence in Belgium. Coloring our Netherlands surface blue and Belgium surface yellow, and bringing our surfaces together on the same axis (panel G), the intersection of our surfaces shows us where our model is equally confident in both countries—the model's learned decision boundary—which gives us a basic border separating the core Belgium region from the surrounding Netherlands region.

The Universal Approximation Theorem tells us that if we just keep adding neurons to our first layer (Figure 4.3), eventually we'll land on an architecture capable of representing our full border.

1 Cybenko used Sigmoids activation functions, but the same results was later proven to be true for ReLu activation functions as well

Chapter 4 Video

Figure 4.2 | Baarle-Hertog. The municipality of Baarle-Hertog has the most complex border in the world.



Figure 4.3 | Two-layer neural network. Yeah, yeah, it looks like it has *three* layers. The two circles on the left are inputs, the rest of the circles are neurons. The x_1 input corresponds to the horizontal/longitude coordinate of a point on our map, and the x_2 input corresponds to the vertical/latitude coordinate. Our two output neurons correspond to the model's confidence in Netherlands and Belgium. Note that we would typically include a softmax function on our output (see Chapter 3), but softmax will not change the location of our model's learned decision boundary.



Figure 4.4 | The geometry of a two layer deep and eight neuron wide network. This network has 8 hidden neurons and is able to divide our map into more regions, creating more complex surfaces to bring together into more complex borders.

Training a network with eight neurons in its first layer, we get the set of eight folds shown in Figure 4.4 Panels A-H, leading to the surface shown in Panel X for our first output neuron, and the surface shown in Panel Y for our second output neuron. Bringing these new surfaces onto the same axis in Panel Z, we see more complex intersection lines—leading to this more detailed final border, that begins to break our map into separate regions.

Figure 4.5 shows the surfaces and border for larger models with 16, 32, 64, and 128 neurons. It starts to get difficult to see how our surfaces are intersecting in 3D with this many fold lines, the bottom row of Figure 4.5 shows an overhead view of our surfaces, the angled blue lines are the fold lines created by the first layer of our networks.



As we widen our network to 256, 512, and 1024 neurons, we get closer to our true border, but are still missing a number of parts of the town—and we've reached a point where the visualization tools we're using (manim) can't actually render any more polygons to see how our model breaks apart the map—but we can still render our decision boundary—the bottom right of Figure 4.5 shows the boundary we get for a 10,000 neuron model, and finally a 100,000 model! We're getting even closer at this point, but even with 100,000 neurons, there's a couple parts of the border that our model hasn't learned!

It feels like the Universal Approximation Theorem isn't really working—what are we missing here?

Figure 4.5 | This doesn't seem so universal. Top Row: The learned surfaces and intersections for neurons with 16, 32, 64, and 128 neurons. Bottom Row: Here we're switching to an overhead view of our learned surfaces. The angled blue lines are the folds created by the networks first layer, with one fold per neuron. Bottom Right: We now have too many fold lines to render, but we can still show the final learned decision boundaries.



Figure 4.7 | Single layer models learn planes. The single layer models we saw in Chapter 3 solve our European city problem by positioning planes above each city.



Figure 4.8 | Softmax does not move decision boundaries. The softmax operation we saw in depth in Chapter 3 squishes our model's outputs into nice probabilities that add up to one, but does not change the location of our decision boundaries. Since softmax just amplifies the differenence between our model's outputs, whatever output is largest for a given input before softmax will still be the largest output after softmax. Since this chapter is focused on the impact of depth on decision boundaries, we won't worry about softmax too much.

But before we get into the details of what's going wrong here—let me show you one more thing.

Let's take just 128 neurons, but instead of arranging them in a single wide layer, let's arrange them in 4 separate layers of 32 each as shown in Figure 4.6, where the output of each layer is passed into the next. Our five layer network, with just 130 total neurons, is able to learn a more precise border than our 100,000 neuron model, and divide our map much more effectively.

How is it that rearranging our neurons into multiple layers makes our model so much more powerful? The neurons in both our deeper and shallow models do the same folding, scaling, and combining operations—why are these operations so much more effective when composed in multiple layers? And how does the geometry of our map change as it moves through these stacked operations?

In Chapter 3, we dug into the mathematics of how modern models are trained using backpropagation and gradient descent. We saw how given the inputs of latitude and longitude, a single layer model can effectively learn to position planes over different European cities, learning to separate Paris, Berlin, Madrid, and Barcelona (Figure 4.7). This key piece of functionality here is that our model learns to position the Madrid plane above all the other planes above Madrid, the Barcelona plane above the other planes above Barcelona, and so on—and the height of our planes corresponds to our network's final confidence in a specific city.

We left off considering the incredibly complex Baarle Hertog border (Figure 3.26). Given a single plane for each country, there's no way to position our planes so our Belgium plane is on top of our Netherlands plane above only the Belgium portions of our map. Another way to think about this that our two tilted planes intersect at a line on our map, where everything on one side of the line will be classified as part of Belgium and everything on the other side will be classified as part of the Netherlands—and there's no way this linear decision boundary can correctly divide up our city (Figure 4.9 top right).

Our networks from last time looked like the top row in Figure 4.9—with a single layer of neurons between our inputs and softmax function. And as we saw last time, the softmax function bends our planes to output nice final probability values, but importantly does not change the location of the decision boundaries at intersections of our planes (Figure 4.8)—for this reason, we won't concern ourselves too much with softmax in this chapter. The networks we saw at the beginning of the chapter (Figures 4.1, 4.4, and 4.5) add one more layer of neurons, and are able to accomplish significantly more.



Figure 4.6 | Architecture Matters. If we take just 130 neurons, and rearrange them into four layers of 32 each (plus two output neurons), we're able to better fit our border, as shown in the uppper panels. The magenta line in the upper plots shows the the learned decision boundary for each model. The bottom panels compare the regions learned by each model—note we're showing the 512 neuron model on the left (not full 100k neurons, this too complex to render). While the two-layer network creates one fold with each neuron (blue lines), our deeper netowrk is able to create signfincalty more complex folds and patterns. Why is depth so much more efficient than width? We've seen the geometry of two-layer models (Figure 4.1), what happens goemetrically when we stack more layers?



Figure 4.9 | One more layer of neurons. A single layer of neurons only allows for simple linear decision boundaries. Moving to two layers and more, our network can create significantly more complex boundaries.



Figure 4.10 | Still just planes. Just as we saw in our single layer networks in Chapter 3, each neuron in our multilayer network learns a single plane mapping from its input to output. Here we're seeing how the first neuron in the first layer of our network processes a Belgium point at x_1=0.6, x_2=0.4. This network has already been trained, and has learned values of $m_{11}^{(1)}$ = 2.51, $m_{12}^{(1)}$ = -1.02, and $b_1^{(1)}$ = -1.22. Our weight values control the steepness of our plane in each direction, and our b value pushes our whole plane up and down. Passing x_1=0.6, x_2=0.4 into the equation for our neuron, we can compute that the height of our plane at our input point—this height is equal to the output value of the neuron.

Just like the neurons in our simple single layer model, each of the neurons in the first layer of our two-layer network contains a simple linear model that geometrically looks like a plane. Mathematically, the first neuron in our first layer takes in the coordinates of our point, multiplies each coordinate by a learnable weight value, which we're writing here using m, and adds the results together, as shown in Figure 4.10[2]. The weight values control the steepness of our plane in each direction. If we pick a Belgium point on our map, for example x_1=0.6, x_2=0.4, we can pass our point into our neuron and compute its output—in the case of the trained network in Figure 4.10 we get an output value of -0.14. This value corresponds to the height of our plane at our input point.

Now, if we just pass the height of our plane, -0.14 in this example, into our second layer of neurons—our multiple layers of neurons will actually just collapse back down into what is effectively a single layer of neurons.

We can show this collapsing algebraically— there's just a bunch of

2 This book, and machine leaning more broadly, uses a few different symbols to denote model parameters/weights. The most common symbols are θ and w. In chapters 3 and 4, we use m for model weights, to emphasize that the equation for each neuron is just a simple linear model, much like y=mx+b linear equation many of us learn in algebra class.



Figure 4.11 | We're missing something. If we just pass the outputs of the neurons from our first layer directly into our second layer, our network effectively collapses back into a single layer network! Here we're using the superscripts $^{(1)}$ and $^{(2)}$ to denote which layer a given parameter comes from. Focusing on the final output of our network $h_1^{(2)}$, we can substitute in the outputs from our first layer into this neuron's equation. After distributing and collecting terms, we can show that our equation has the same structure as a single neuron. The first input to our network, x_1 is multiplied by $(m_{11}^{(2)}\, m_{11}^{(1)} + m_{12}^{(2)}\, m_{21}^{(1)})$. All of these weight values are just constants, so we can rename them as a single constant m_1. Applying the same logic to our two remaining terms, we're left with $h_1^{(2)} = m_1x_1 + m_2x_2 + b_1$, the equation for a single layer network, just with new/different weight values.

terms to deal with. Figure 4.11 shows that the first output of our network $h_1^{(2)}$ is equivalent to $m_1x_1 + m_2x_2 + b_1$, the equation for a single layer network. This result tells us that if we just hook up the outputs of one layer of plane fitting neurons to the inputs of our next layer, we end up adding together different scaled tilted planes, which just results in a different tilted plane. So a two-layer network connected like this is still only capable in practice of fitting two planes to our map, just as our simple single layer model did.

For our multilayer neural network to be able to learn more complex patterns, we need to add one more small piece of math. We'll pass the output planes from our first layer into a function called an activation function, that will modify their shape into something more complex for our model to work with.[3] It turns out that we can build high performing neural networks using a variety of activation functions, but one of the simplest and most widely used today is a function called a Rectified Linear Unit, or ReLu. ReLu is incredibly simple—for inputs less than zero, ReLu returns zero, and for input values greater than or equal to zero, ReLu simply returns its input value. So ReLu(-1)=0 and ReLu(1)=1.



Figure 4.12 | The missing piece! To avoid our multilayer network collapsing into a single layer network, we need to add one small piece of math to the outputs of our neurons.

3 We saw activation functions briefly in Chapter 1! Activation functions need to be non-linear to avoid the "algebraic collapse" of Figure 4.11, but also need to differentiable, so we can apply backpropagation.





Figure 4.13 | The geometry of ReLU.

Applying our ReLU activation function to the output planes of the first layer of our network from Figure 4.10, the regions of our plane with heights less than zero are folded up or clipped to a height of zero. So instead of outputting planes, the first layer of our network now outputs the bent planes shown in Figure 4.13. This folding operation we saw at the beginning of the Chapter (Figure 4.1 panels B, C, and D).

Let's see precisely how a network using ReLU activation functions decides which country a given point is in. Given a two-layer two-neuron wide network like this:



to decide which country a point is in, for example the Belgium point with coordinates of x_1=0.6, x_2=0.4 we saw earlier, we pass these coordinates into our first layer of neurons, as shown above in Figure 4.14. Before applying the RelU operations our



linear neuron equations return values of -0.14 and -0.33, these values correspond to the height of our plane before applying the ReLU bending operation. From here we apply our ReLU activation function, folding all values below zero up to zero. The height of our point on both planes is negative, so we set both points to zero. So our input point x_1=0.6, x_2=0.4 has now been mapped to values of $h_1^{(1)}$=0, $h_2^{(1)}$=0 by our bent planes. From here our final layer of neurons multiplies these values of $h_1^{(1)}$=0, $h_2^{(1)}$=0 by its weights and adds bias terms, shifting our combined bent planes up and down, moving our point to $h_1^{(2)}$=-0.89 on our Netherlands surface, and $h_1^{(2)}$=0.03 on our Belgium surface. Our first neuron's output corresponds to our model's confidence in Belgium, which is higher in this case, meaning this point will be classified as being in Belgium—and visually we see this as the point on our yellow Belgium plane being above our point on our blue Netherlands plane.

We can do a similar analysis for a point in the Netherlands such as the x_1=0.7, x_2=0.3 purple point shown in Figure 4.14. The key difference here is that this point does not fall in the zero ReLU region of our second neuron, meaning it get's pushed up on our final Netherlands bent plane and pushed down on our final Belgium plane, resulting in a Netherlands classification.

Figure 4.14 | The geometry of a two-layer network. Given a Belgium (red) and Netherlands (purple) point, we can see how these points are moved around by our network. At each step along the way the output h value corresponds to the height of the red Belgium point on our various surfaces. Note that we're only showing math for our red belgium point. Our Belgium point falls in the zero/flat ReLU region of both neurons in our first layer, then these regions are pushed up/down by our second layer, moving the yellow Belgium surface to a height of 0.03 above our blue Netherlands surface which ends up with a height of -0.89 in this region, resulting in a correct classification of Belgium for this point. Our purple Netherlands point falls outside of our ReLU region, meaning it gets pushed up on the Netherlands surface in our second layer.

So our bent plane geometry is equivalent to numerically moving data through our network, but gives us a nice way to see how all of the points on our map are processed at once. As we add more neurons to our first layer, we're able to make more folds in our map, cutting our map into more regions for our output neurons to push up and down to form more and more complex surfaces, as shown in Figure 4.4.

Now, as we saw at the opening of the Chapter, assuming a sufficient number of neurons in our first layer, the Universal Approximation Theorem tells us that, a neural network exists that can represent the borders of our town at arbitrarily high precision. But as we saw, even at 100 thousand neurons in our first layer, we were not able to successfully train a model to completely match our borders.

What's going on here?

UNIVERSAL APPROXIMATION THEOREM GAURANTEES

✓ **Network exists?**

✗ **Can we actually compute the weights?**

✗ **How many neurons do we need?**

The Universal Approximation Theorem is sometimes mistaken to mean that neural networks can learn anything—but what it really says is that a wide enough neural network is capable of representing any continuous function. Now, the borders of our town are actually not continuous, but the continuity that the Theorem is referring to here is the continuity of the final surfaces that we intersect together to find our border.

The real issue here is that although the Universal Approximation Theorem tells us that a two-layer solution exists, it does not mean that in practice we can actually find the solution, and the theorem does not tell us how many neurons we actually need to solve a given problem.

As we saw in Chapters 2 and 3, modern neural networks learn using backpropagation and gradient descent—which provide no guarantees of finding the best solution or even a good solution—instead these algorithms make small iterative updates to our parameters, and we typically just stop the learning process when performance stops improving.

Before training, our network is randomly initialized, placing our fold lines at random locations on our map, Figure 4.15 shows the training process of a three neuron, two-layer model. In step 0, our model's weights are randomly initialized, placing our fold lines at random locations. Note that our random initialization places our blue Netherlands surface on top of our Belgium yellow surface for most of the Belgium region, meaning most Belguim points would be misclassified. This error is then measured using cross entropy loss—as we saw in Chapter 3, and this loss is then run through our backpropagation algorithm, resulting in gradient values for each of our model's parameters. Updating our parameters following our computed gradients slowly changes our learned geometry. Step by step, these small updates adjust both the location of the fold lines in our first layer and the way these bent planes are combined by our second layer until we have a nice concave down surface on top of Belgium that intersects a concave up Netherlands surface at a nice border.



Figure 4.15 | How does our geometry change as our model learns? Here we're using gradient descent to train a two-layer three neuron wide model to separate the Belgium regions of our map from the Netherlands regions. The outputs of our network $h_1^{(2)}$ and $h_2^{(2)}$ correspond to the model's confidence in the Netherlands and Belgium, respectively. The left three columns show the intermediate outputs of our network $h_1^{(1)}$, $h_2^{(1)}$, and $h_3^{(1)}$—as our model learns it shifts around it's ReLU fold lines. Our second layer brings these folds together into our final surfaces $h_1^{(2)}$ and $h_2^{(2)}$, our final two columns show these surfaces on the same axis. Step by step, our network learns to create a concave up surface for the Netherlands and concave down surface for Belgium that ultimately intersect at a nice decision boundary.

Now, when we initially tried to train this model—it didn't work nearly this well. We had a different random initialization that looked like the top row of Figure 4.16—placing our blue region on top of our yellow region, when we want our model to learn the exact opposite orientation, with a central yellow region for Belgium on top.

As our model learns from this starting point, our backpropagation algorithm begins to reverse the orientation of our surfaces, lowering our loss value, and moving the blue surface down and the yellow surface up—but in doing so pushes the decision boundaries off two of our planes, leaving the whole town in the zeroed out part of our bent ReLU plane. Gradient descent can't recover from this configuration, since the gradients through the zeroed out part of our ReLU activation function are also zero'd out, leaving our model with effectively a single plane to work with, resulting in a suboptimal linear decision boundary.[4] So even though we know a nice solution exists for our five neuron network—given this starting point, gradient descent is not able to find it.

In the case of our super wide 100,000 neuron network, there may be analogously good solutions out there—we just can't reach them with gradient descent. Now, there is some subtlety here—as we saw back in part one, when models become large, the chances of gradient descent actually getting stuck in a local minimum in this high-dimensional loss landscape becomes very small—our super wide network is probably not getting stuck in quite the same way as our small network.

In addition to not telling us how to find a specific solution, the Universal Approximation Theorem also does not tell us how many neurons we actually need to solve a given problem. And in fact, for a broad class of functions, it's been shown that the number of neurons we need in a shallow network is exponentially larger than the number of neurons needed in a deep network [Liang and Srikant 2016].[5]

Exact number of neurons aside, as we saw earlier, we can make incredible efficiency gains by going deep instead of wide—stacking our neurons into additional layers—and that's where we'll turn next. What new geometry does stacking our layers create, and how does this geometry help our model learn the complex borders of our town?

Back in Figure 4.14 we saw a simple two-layer two-neuron wide network, and all the networks we saw at the beginning of the chapter (Figures 4.1, 4.4, 4.5) were two layers deep as well. These networks use ReLU activation functions to make one set of folds, then bring these folded planes together into our blue and yellow surfaces that correspond to the model's confidence in each country.

4 There's a variant of ReLU called leaky ReLU that doesn't fully 0 out inputs <0, which would likely help here.

5 When I released the video that goes along with this chapter in August 2025, I wasn't sure if a 100k neuron wide network was enough to solve the Baarle Hertog problem, and I asked the audience for help. I had experimented with various learning rates, the SGD and Adam optimizers, and a few other hyperparameters, and the best performance I was able to achieve is shown in Figure 4.5. The main thrust of this Chapter is about the efficiency of depth over width, and it's clear here that deep models are more efficient and easier to train, so I wasn't overly concerned about finding the very best wide solution possible, but I was curious and wanted to make sure I wasn't missing something. Interestingly, a viewer (@inikishev on github), was able to find a very nice solution using just 1,000 neurons using a different optimization technique called the ShorR algorithm. This algorithm is fairly memory intensive, so its scaling ability is limited, but it does work very well for shallow ReLU networks. You can see @inikishev's solution here: https://github.com/stephencwelch/manim_videos/issues/14



Figure 4.16 | Random Initializations Matter. Here we're training the same network on the same data as we saw in Figure 4.15, but with a different random initialization. The network starts out with its blue Netherlands plane very much on top of Belgium, and as it follows gradient descent to reverse this orientation, the first layer decision boundaries are pushed off the map entirely, leaving the network with a single suboptimal linear decision boundary. Further training does not help.



Figure 4.17 | One More Layer. Moving to a slightly deeper network (3 layers), results in some very interesting behavior! Panels A and D show the output of our first layer after our ReLU activation functions, and Panels B and E show our surfaces after passing through our second layer linear equations, but before we apply our layer two ReLU functions. In our previous two-layer models (e.g. Figure 4.1), these surfaces would be brought together to form our final decision boundary. However, now our extra layer's ReLU functions create some really interesting behavior! These activation functions still just clip all values less than zero to zero, however the surfaces that passed into these ReLU functions (Panel B) are more complex, meaning that each ReLU function creates a whole new set of joints! As we'll see, this behavior dramatically expands deep models' ability to partition their input spaces.

Let's add a third layer to our models and explore how this changes our geometry. Figure 4.17 shows how our input maps are reshaped by the first two layers of our model. Our first layer results in familiar single ReLU bends in each plane (Panels A and D).

But now, in the second layer of our model, the surfaces we're folding are no longer simple planes. When we apply our ReLU activation function and fold up our surface, we create three separate new fold lines, one for each plane that crosses the z equals zero plane (Panel C). And interestingly, these folds are not at the same angle, but bend at the joints of the planes we get out of our first layer. So a single neuron is able to make three separate folds, with fairly complex geometries.

Now considering our full three layer network (Figure 4.18), we can see how these new fold lines come together to create a final decision boundary. After our first layer, the combination of our two ReLU folds created four regions for the next layer of our model to work with—these are easiest to see in a 2D projection (Figure 4.18 Panel K) . Stacking the new fold lines from our second layer (Panels C and G), these new folds at various angles come together in a significantly more complex tiling of our map, with the 10 separate regions shown in Panel L.

When the final layer of our network scales and adds together the outputs of our second layer, the resulting surfaces are composed of the same 10 regions, just with different heights. The heights of these surfaces correspond to the model's final confidence in our two countries—bringing these surfaces together and finding their intersection, we get this final decision boundary, which shows some nice piecewise curvature around the Belgium region of our map (Figure 4.18 Panel N).



Figure 4.18 | Additional Layers Are Powerful. The more complex ReLU bend lines we saw in Figure 4.17 come together in a really powerful way in the third layer of our model. A nice way to see this is to consider all the different regions our model carves our input map into. Our second layer has 4 separate linear regions to work with (Panels B and F), these are a direct result of how the two linear ReLU folds from the first layer come together (Panel K). The same process applies in our third layer, but the surfaces our third layer has to work with are made up of the ten regions shown in panel L. More planar regions with more complex geometries give our model more ways to fit our border. Just as we did earlier, we intersect our final surfaces to find our decision boundary, where our model is equally confident in both countries.



Figure 4.19 | Different Geometries. Using the same bent plane visualizations we saw in Figure 4.18, here we're comparing a two-layer network (above) and the same three-layer network we saw in Figure 4.18 (Below). Both networks produce reasonable decision boundaries, but the deep model is able to use its second layer of ReLU folds to learn a more complex tiling of our input map.



Figure 4.20 | Width vs Depth. Here's a closer look at how our networks in Figure 4.19 break apart our input planes, and the final resulting decision boundaries. The resulting boundaries are not dramatically different, but our deep model is able to produce a significantly more complex tiling of our input plane. As we'll see, this difference is a key part of the scalability of deep learning.

So, as shown in Figure 4.18, the first layer of our network creates the two folds and four separate regions on our map shown in Panel K, which are then split by our second layer into 10 regions, which are used by our final layer to create the surfaces shown in Panels D and H, which intersect in a nice border.

The fact that just adding two additional neurons in a third layer takes our map from four regions to 10 is remarkable to me, especially considering the complex geometry of these 10 regions. If we instead arrange our six neurons into a two-layer network as shown at the top of Figure 4.19, our model learns the folds shown, resulting in 7 regions, and a reasonable final decision boundary.

This decision boundary isn't necessarily worse than the one learned by our deeper model, but I'm particularly struck by how much more complex the tiling learned by our deeper model is. Qualitatively, the tiling of our map learned by our shallow network feels very much we've stacked just four lines together—which is exactly what we've done— while the tiling learned by our deeper model feels to me like something entirely different, as shown in Figure 4.20. By repeating our folding, scaling, and combining operations, these operations are really able to compound on themselves—allowing the neurons in our second layer to generate significantly more complex patterns than they would if they were instead positioned in the first layer of our model.

The compounding analogy is not a coincidence—it turns out that we can show that the maximum number of regions a ReLU network like ours can divide our map into grows exponentially with the number of layers in our network.



Figure 4.21 | Exponential Growth? The theoretical maximum number of regions our network can create grows exponentially with depth. Note that the *K* term that counts our number of layers does not include the final output layer. In this convention *K* counts the number of hidden layers.



Figure 4.22 | Depth is way better, in theory. For the shallow two-layer (*K*=1) networks we considered at the beginning of chapter, the exponential term cancels, leaving a term that grows quadratically with the width of our network. Each network here has 66 neurons, but our deep network is theoretically capable of creating dramatically more regions.

This equation gives the theoretical maximum number of regions our model can create [Prince 2023, Chapter 4]:

$$N_r = \left(\frac{D}{D_i} + 1\right)^{D_i(K-1)} \left(\frac{D^2 + D + 2}{2}\right)$$

Neurons per Layer; Number of Layers; Maximum number of regions; Number of Inputs

The top row of Figure 4.21 shows this equation applied to the three layer network we've been considering (Figure 4.18). Plugging in D=2 neurons per layer, D_i=2 inputs, and K=2 layers[6], we get 16 total possible regions for our model, a bit above the 10 regions our model actually learned. If we add another two-neuron layer to our model, our number of regions grows to 64, adding another layer gets us to 256 and so on, so each layer theoretically quadruples the number of regions our model can create in this configuration.

The final $(D^2+D+2)/2$ part of the equation captures what happens in the final layer of our model. If we cut back down to a shallow two-layer model, K=1, eliminating the exponential growth term, as shown in Figure 4.22. As we've seen, two-layer networks divide up the input plane by stacking separate ReLU folds—so finding the number of regions we can divide our map into with a two-layer network is equivalent to asking how many separate regions we can split a plane into with D lines—this is a well-known result in combinatorial geometry, with the answer given by this polynomial (Figure 4.23)



D = Number of Lines
= Number of Layer 1 Neurons

$$N_r = \left(\frac{D^2 + D + 2}{2}\right)$$

Figure 4.23 | How Many Regions? The maximum number of regions we can divide a plane into using D lines is given by the equation above.

So our theory tells us that the maximum number of regions we can create with a two-layer network grows as a polynomial function of our number of neurons, while the number of regions we can create with deeper networks grows exponentially with the number of layers. Placing 64 neurons in the first layer of a two-layer network results in 2,081 possible regions, while rearranging them into four layers of 16 each results in over 70 million possible regions (Figure 4.22).

The difference between these growth rates is compelling—and is often pointed to as a reason for the effectiveness of deep learning. However, these numbers are theoretical upper bounds—and as a number of papers have pointed out [Hanin and Rolnick 2019, Hanin Rolnick 2019 May, Fan et al. 2023], these bounds are very loose, in practice we don't typically see exponential growth number growth in the number regions created by deep networks as we add layers.

6 Note that the K term for the number of layers does not include the final output layer, K is the number of "hidden" layers.



Figure 4.24 | What can 18 neurons do? Following the convention of Figures 4.18 and 4.19, here we're visualizing the output of each neuron in our first layer (column A), and output of each neuron in our second layer (column B). The height of each surface corresponds to that neuron's output value at a given point of our map. In columns B and C, planar regions each get their own color. Our final output layer of neurons scales and combines our surfaces from column B into the surfaces in column C. Bringing these surfaces together in column D, we find our decision boundary at the intersection of our surfaces, where our model is equally confident in each country. Beneath each set of neurons we find the stacked intersections of all neurons, showing how the overall map is divided up. Our final surfaces in column C are built from the 102 regions shown in the bottom of column B.

Let's scale up our own deep network, and see how our number of regions scales with our network, and how our fit improves.

We left off with the three layer, six neuron model of Figure 4.18, that divided our map into 10 regions. Let's first expand our model to have eight neurons in each of our first two layers, as shown in Figure 4.24 The eight folds in our first layer now break up our map into 19 regions, and the various folds of the surfaces created by our second layer come together into 102 regions. Our second layer patterns start to get really interesting—the ReLU function in the second neuron of our second layer (column B, second from top) folds our surface along ten different unique joints. Our final layer scales and combines these outputs into the final surfaces in column C, which intersect in the decision boundary shown in Panel E, capturing the two largest sections of our town nicely.

Note that a couple neurons in our second layer don't have any colored regions (column B, third from top)—this means that the



entire surface from our first layer was below z=0, and all inputs are set to zero by our ReLU activation function—dead neurons like this are common—and a reminder that gradient descent gives no guarantees about efficiently using our model architecture.

Let's add another eight neuron layer to our model, resulting in four total layers, as shown in Figure 4.25. We can now really start to see the compounding effects of our repeated folding, scaling, and combining operations. The ReLU folding happening in the third layer (column C) starts to create this these regions tiny around around the border—it's so interesting to me that our model, guided by backpropagation, creates all these extra little polygons around our town's borders to capture their detailed structure.

At this scale it becomes tough to make sense of everything in 3D space like this, let's continue scaling up but focus on the regions formed on our map by each layer, the final 3D surfaces, and our final map and decision boundary.

Figure 4.25 | What can 26 neurons do? Following the convention of Figures 4.18 and 4.19, here we're visualizing the output of each neuron in our first layer (column A), and the output of each neuron in our second layer (column B), and the output of each neuron in our third layer (column C). The height of each surface corresponds to that neuron's output value at a given point of our map. In columns B, C, and D, planar regions each get their own color. Our final output layer of neurons scales and combines our surfaces from column C into the surfaces in column D. Bringing these surfaces together in column E, we find our decision boundary at the intersection of our surfaces, where our model is equally confident in each country. Beneath each set of neurons we find the stacked intersections of all neurons, showing how the overall map is divided up. Our final surfaces in column D are built from the 430 regions shown in the bottom of column C.



Figure 4.27 | A closer look at the final tiling of Figure 4.26. Final decision boundary shown in white. Remarkably, our five layer model (Figure 4.28) is able to partition our input space into 28,397 separate regions that our model is able to use to fit the complex Baarle-Hertog border.



Figure 4.26 | What can 130 neurons do? The final learned regions and decision boundary for a 32 neuron wide, 5 total layer network. Our repeated layers are able to recursively partition our input space into finely tuned regions that are able to model the complex Baarle-Hertog border remarkably well.

Let's add one more layer to our model, and expand its width to 32 (Figure 4.26). Our additional layer gives us one more tiling of our map, each layer of the model progressively adds more linear regions to resolve the small details of the Baarle-Hertog border. The fact that just 4 layers with 32 neurons each can learn this level of complexity is remarkable. Our final decision boundary impressively captures every region in our town. It's incredible to me that a bunch of little linear models can come together to do something so complex, and that we can actually find these solutions using gradient descent. And this is only 130 neurons, as we've seen modern large models have *billions* of paramters. Going deep allows our model to recursively fold, scale, and combine its input space in incredibly complex ways.



Figure 4.28 | This model can learn Baarle-Hertog! Not 100% accurately, but pretty darn close. Depth allows our model to recursively divide its input space and learn highly complex patterns.

Around 10 years ago, I released the very first Welch Labs video—it's called Neural Networks Demystified. Like Chapters 2-4 of the book you're reading now, Neural Networks Demystified was a series about how neural networks learn, focusing on backpropagation and gradient descent.

Sitting down to work on this topic again 10 years later, I honestly didn't know where to start—although most of the core approaches in my old videos are unchanged—these core ideas have been scaled to solve unbelievably complex problems—and this shocking ability

to scale has led the research community to dig deeper into what makes these models tick—we've learned a great deal in 10 years, but many mysteries remain.

In Chapter 2 we dug into loss landscapes, and saw how the standard mental image of gradient descent I presented 10 years ago really doesn't hold up in the incredibly high-dimensional spaces these models operate in. In Chapter 3, we dug into the core of the mechanics of how models learn—dissecting the backpropagation in the context of a modern large language model. Finally, in this chapter we saw how deep models are able to recursively fold, scale, and combine their input spaces, learning incredibly complex patterns with remarkably few neurons.

Maybe in another 10 years I can make another series like this.[7] We'll have to wait and see what these models can do then, and how much sense we'll be able to make of how they do it.

7 Get ready for a 10 hour video lol

4. Deep Lerning

4.1 Imports

[1]:
```
import numpy as np
import torch
import torch.nn as nn
import torch.optim as optim
import matplotlib.pyplot as plt
import cv2
from torch.utils.data import DataLoader, TensorDataset

# Check for GPU availability
device = 'cuda' if torch.cuda.is_available() else 'cpu'
print(f'Using device: {device}')
```

[1]:
```
Using device: cpu
```

4.2 Load up Baarle Hertog data

[2]:
```
m = cv2.imread('data/Baarle-Nassau_-_Baarle-Hertog-en no legend.png')[:, :, (2, 1, 0)]

belgium_color = np.array([251, 234, 81])
netherlands_color = np.array([255, 255, 228])

netherlands_region = ((m - netherlands_color)**2).sum(-1) < 50
belgium_region = ((m - belgium_color)**2).sum(-1) < 10000

b_coords = np.array(np.where(belgium_region)).T.astype('float')
n_coords = np.array(np.where(netherlands_region)).T.astype('float')

# Flip and normalize coordinates to [-1, 1]
belgium_coords_all = np.zeros_like(b_coords)
netherlands_coords_all = np.zeros_like(n_coords)

belgium_coords_all[:, 0] = b_coords[:, 1] / (960 / 2) - 1
belgium_coords_all[:, 1] = (960 - b_coords[:, 0]) / (960 / 2) - 1
netherlands_coords_all[:, 0] = n_coords[:, 1] / (960 / 2) - 1
netherlands_coords_all[:, 1] = (960 - n_coords[:, 0]) / (960 / 2) - 1
```

[3]:
```
np.random.seed(55)
num_points_to_sample = 10000
belgium_coords_sample = belgium_coords_all[np.random.choice(len(belgium_coords_all),
                                                            num_points_to_sample), :]
netherlands_coords_sample=netherlands_coords_all[np.random.choice(len(netherlands_coords_all),
                                                                  num_points_to_sample), :]
X_sample = np.vstack((netherlands_coords_sample, belgium_coords_sample))
y_sample = np.concatenate((np.zeros(len(belgium_coords_sample)),
                           np.ones(len(netherlands_coords_sample)))).astype('int')

rI=np.arange(len(y_sample))
np.random.shuffle(rI)
X_sample=X_sample[rI,:]
y_sample=y_sample[rI]

X_sample = torch.FloatTensor(X_sample)
y_sample = torch.tensor(y_sample)
```

[6]:
```
plt.imshow(m)
```

[6]:
```
<matplotlib.image.AxesImage at 0x136f06ed0>
```



[7]:
```
plt.scatter(X_sample[:,0], X_sample[:,1], c=y_sample, s=1, alpha=0.3);
plt.axis('square');
```

[7]:
```
<Figure size 640x480 with 1 Axes>
```



SUPPORTING CODE

Full supporting code for this chapter at:
`github.com/stephencwelch/ai_book`

4.3 Network

[8]:
```
class BaarleNet(nn.Module):
    def __init__(self, hidden_layers=[64]):
        super(BaarleNet, self).__init__()
        layers = [nn.Linear(2, hidden_layers[0]), nn.ReLU()]
        for i in range(len(hidden_layers) - 1):
            layers.append(nn.Linear(hidden_layers[i], hidden_layers[i + 1]))
            layers.append(nn.ReLU())
        layers.append(nn.Linear(hidden_layers[-1], 2))
        self.layers = layers
        self.model = nn.Sequential(*layers)

    def forward(self, x):
        return self.model(x)
```

[9]:
```
def viz_descision_boundary(model, res=256):
    plt.clf()
    fig = plt.figure(0, (6, 6))
    ax = fig.add_subplot(111)

    probe = np.zeros((res, res, 2))
    for j, xx in enumerate(np.linspace(-1, 1, res)):
        for k, yy in enumerate(np.linspace(-1, 1, res)):
            probe[j, k] = [yy, xx]
    probe = probe.reshape(res**2, -1)
    probe_logits = model(torch.tensor(probe).float().to(device))
    probe_logits = probe_logits.detach().cpu().numpy().reshape(res, res, 2)

    ax.imshow(m.mean(2), cmap='gray')
    ax.imshow(np.flipud(np.argmax(probe_logits, 2)),
              extent=[0, 960, 960, 0],
              alpha=0.7,
              cmap='viridis')
```

4.4 Two Layers, Three Hidden Neurons (Figure 4.1)

[10]:
```
random_seed=520 #Random seed of 3 makes for a nice "fold down the edges" deal,
num_neurons=3

torch.manual_seed(random_seed)

model = BaarleNet([num_neurons])
criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(model.parameters(), lr=0.01)

num_epochs = 10000
for epoch in range(num_epochs):

    #Stochastic - works better for these smaller networks.
    outputs = model(torch.tensor(X_sample[epoch%len(y_sample)]).float())
    loss = criterion(outputs, torch.tensor(y_sample[epoch%len(y_sample)]))

    optimizer.zero_grad()
    loss.backward()

    optimizer.step()
    if (epoch+1) % (num_epochs//25) == 0:
        outputs_batch = model(X_sample)
        accuracy=(torch.argmax(outputs_batch, dim=1)==y_sample).sum().item()/len(y_sample)
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}, Accuracy: {accuracy:.4f}')
```

[10]:
```
Epoch [400/10000], Loss: 0.3467, Accuracy: 0.6342
Epoch [800/10000], Loss: 0.6061, Accuracy: 0.6925
Epoch [1200/10000], Loss: 0.5865, Accuracy: 0.7683
Epoch [1600/10000], Loss: 0.4375, Accuracy: 0.8077
Epoch [2000/10000], Loss: 1.0100, Accuracy: 0.7941
Epoch [2400/10000], Loss: 0.3538, Accuracy: 0.7858
Epoch [2800/10000], Loss: 0.8983, Accuracy: 0.8068
Epoch [3200/10000], Loss: 0.2023, Accuracy: 0.8050
Epoch [3600/10000], Loss: 0.3616, Accuracy: 0.8170
Epoch [4000/10000], Loss: 0.1266, Accuracy: 0.8321
Epoch [4400/10000], Loss: 0.1828, Accuracy: 0.8265
Epoch [4800/10000], Loss: 3.1891, Accuracy: 0.7879
Epoch [5200/10000], Loss: 0.1795, Accuracy: 0.8265
Epoch [5600/10000], Loss: 0.1350, Accuracy: 0.8016
Epoch [6000/10000], Loss: 0.4167, Accuracy: 0.8083
Epoch [6400/10000], Loss: 0.0441, Accuracy: 0.8385
Epoch [6800/10000], Loss: 0.3843, Accuracy: 0.8183
Epoch [7200/10000], Loss: 0.1611, Accuracy: 0.8291
Epoch [7600/10000], Loss: 0.1842, Accuracy: 0.8472
Epoch [8000/10000], Loss: 0.2445, Accuracy: 0.8178
Epoch [8400/10000], Loss: 0.1131, Accuracy: 0.8410
Epoch [8800/10000], Loss: 0.1747, Accuracy: 0.8196
Epoch [9200/10000], Loss: 1.2874, Accuracy: 0.8263
Epoch [9600/10000], Loss: 2.0294, Accuracy: 0.7788
Epoch [10000/10000], Loss: 0.0037, Accuracy: 0.8258
```

[11]:
```
viz_descision_boundary(model.to(device))
```

[11]:



4. DEEP LEARNING | EXERCISES

4.1 At the beginning of the Chapter, it seemed like the Universal Approximation Theorem wasn't really working. What went wrong?

4.2 What advantages do deep models have over wide models?

4.3 *"Neural networks can learn anything."* What is true, false, and/or misleading about this statement?

4.4 Is the Universal Approxamation Theorem surprising to you? Why or why not?

4.5 Does the number of regions created by deep networks grow exponentially with the number of layers in practice?

4.6 Why do we need nonlinear activation functions (e.g. ReLU)? What happens when we remove them?

$$h_1^{(1)} = \text{ReLU}(m_{11}^{(1)}x_1 + m_{12}^{(1)}x_2 + b_1^{(1)})$$
$$= \text{ReLU}((2.52)____ + (-1.02)____ - 1.24)$$
$$=$$

$$h_1^{(2)} = m_{11}^{(2)}h_1^{(1)} + m_{12}^{(2)}h_2^{(1)} + b_1^{(2)}$$
$$= (3.17)____ + (1.33)____ - 0.89$$
$$=$$



$$h_2^{(1)} = \text{ReLU}(m_{21}^{(1)}x_1 + m_{22}^{(1)}x_2 + b_2^{(1)})$$
$$= \text{ReLU}((-1.40)____ + (2.41)____ - 0.45)$$
$$=$$

$$h_2^{(2)} = m_{21}^{(2)}h_1^{(1)} + m_{22}^{(2)}h_2^{(1)} + b_2^{(2)}$$
$$= (-3.40)____ + (-1.54)____ + 0.03$$
$$=$$

$$h_1^{(1)} = \text{ReLU}(m_{11}^{(1)}x_1 + m_{12}^{(1)}x_2 + b_1^{(1)})$$
$$= \text{ReLU}((2.52)____ + (-1.02)____ - 1.24)$$
$$=$$

$$h_1^{(2)} = m_{11}^{(2)}h_1^{(1)} + m_{12}^{(2)}h_2^{(1)} + b_1^{(2)}$$
$$= (3.17)____ + (1.33)____ - 0.89$$
$$=$$



$$h_2^{(1)} = \text{ReLU}(m_{21}^{(1)}x_1 + m_{22}^{(1)}x_2 + b_2^{(1)})$$
$$= \text{ReLU}((-1.40)____ + (2.41)____ - 0.45)$$
$$=$$

$$h_2^{(2)} = m_{21}^{(2)}h_1^{(1)} + m_{22}^{(2)}h_2^{(1)} + b_2^{(2)}$$
$$= (-3.40)____ + (-1.54)____ + 0.03$$
$$=$$

4.7 In Figure 4.14 we saw how Belgium and Netherlands points moved through a trained two layer two neuron network to generate the network's final predictions. Repeat this process here for the Belgium point [-0.5, -0.5]. Fill in the blanks provided below, and show approximately where the point falls on our bent plane geometry, and where the point falls in the final front view of our bent plane geometry. Does the network classify the point correctly?



4.8 In Figure 4.14 we saw how Belgium and Netherlands points moved through a trained two-layer, two-neuron network to generate the network's final predictions. Repeat this process here for the Netherlands point [1.0, 0.0]. Fill in the blanks provided below, and show approximately where the point falls on our bent plane geometry, and where the point falls in the final front view of our bent plane geometry. Does the network classify the point correctly?



Neurons per Layer — Number of (Hidden) Layers

$$N_r = \left(\frac{D}{D_i} + 1\right)^{D_i(K-1)} \left(\frac{D^2 + D + 2}{2}\right)$$

Maximum number of regions — Number of Inputs

ARCHITECTURE	RELEVANT FIGURE	NUMBER OF ACTUAL REGIONS	MAX THEORETICAL REGIONS
	 Figure 4.1		
	Figure 4.20		
	Figure 4.20		
	 Figure 4.24		
	 Figure 4.25		
	 Figure 4.26		

4.9 In this Chapter, we explored a number of model architectures, five of these architectures have been placed in the table on the previous page. For each architecture, how many regions did our trained network actually divide our map into? Complete the table by referring back to figures as needed. Does the observed growth in the number of regions appear to be exponential with depth?

4.10. Complete the "max theoretical regions" column in the table on the previous page by plugging into the given formula. How do theoretical and actually region counts compare?[1]

4.11 Pull and run `https://github.com/stephencwelch/ai_book /4_deep_learning.ipynb`. Experiment with sections 4.4 (Two layers, three hidden neurons) and 4.5 (Two layers, eight hidden neurons). How sensitive are these models to random seeds, learning rates, and batch size? Do models become less sensitive as they get smaller?

4.12 [Challenge] How few neurons can you use to achieve 99.5%+ accuracy on the Baarle Hertog problem? Use `https://github.com/stephencwelch/ai_book /4_deep_learning.ipynb` as a starting point. If you're able to achieve this accuracy using fewer then 100 neurons, please send your solution to welchlabs.com/contact!

1 Note that the figures shown in the table on the previous page show the tiling of the input plane before we bring the two final surfaces together to form a final decision boundary. Bringing these surfaces together technically creates more regions—my understanding is that these additional regions would not be included in the final theoretical count—but I wasn't able to resolve this question in my experimentation. If the theoretical count should include regions formed by taking the final intersection, this would not dramatically change the agreement between theory and practice here, but it would be worth noting. I would love to see a crisp answer here—if you have one, please send it to welchlabs.com/contact.

Figure 5.1a | Activation Atlas. This activation atlas gives us a glimpse into the high-dimensional embedding spaces modern AI models use to organize and make sense of the world. Neighbors on the activation atlas are generally close in the embedding space of the model, and show similar concepts that the model has learned. Labels give the strongest ImageNet class in a given region. This figure shows a portion of a larger atlas (Figure 5.1c).

stone wall
cliff
otter
red-breasted
lakeside
seashore
nail
platypus
grey whale
grey whale
seashore
seashore
gar
grey whale
killer whale
seashore
seashore
parking meter
scuba diver
scuba diver
grey whale
ant
nail
nail
dugong
dugong
ant
ant
chainlink fence
chainlink fence
isopod
isopod
ant
ant
spotlight
spotlight
jellyfish
nematode
velvet
velvet
paper towel
window screen
rubber
nematode
volcano
velvet
velvet
velvet
window screen
wool
goldfish
corn
knot
wool
wool
wool
wool

Figure 5.1b | Activation Atlas. This activation atlas gives us a glimpse into the high-dimensional embedding spaces modern AI models use to organize and make sense of the world. Neighbors on the activation atlas are generally close in the embedding space of the model, and show similar concepts that the model has learned. Labels give the strongest ImageNet class in a given region. This figure shows a portion of a larger atlas (Figure 5.1c).

knee pad
ballplayer
ballplayer
crash helmet
crash helmet
bicycle-built-mounta
flute
horizontal barski
stretcher
stretcher
go-kart
moped
flute
parallel bars
barbell
maypole
paddle
paddle
go-kar
steel drum
steel drum
carousel
umbrella
mountain tentcanoe
bobsled
marimba
marimba
barrow
carousel
parachute
airship
airliner
on
pool table
barrow
barrow
pole
flagpole
yawl
trimara
couch
folding chair
folding chair
shopping cart
worm fence
pole
pole
dock
er
cradle
prison
bannister
bannister
solar dish
radio telescoppier
upright
shoji
sliding door
traffic light
mobile home
mobile home
barn



Figure 5.1c | Activation Atlas. This activation atlas gives us a glimpse into the high-dimensional embedding spaces modern AI models use to organize and make sense of the world. Neighbors on the Activation Atlas are generally close in the embedding space of the model, and show similar concepts that the model has learned. We're getting a peek into how deep neural networks organize the visual world. A zoomed in view of Box 5.1a is shown in Figure 5.1a, and a zoomed in view of Box 5.1b is shown in Figure 5.1b (previous pages). In this Chapter we'll explore how these models work. Additional technical details: to create this visualization, a sample of the ImageNet dataset was passed into the InceptionV1 model, and the activation values for the Mixed5b layer were projected from 1024 dimensions to 2 using UMAP (Uniform Manifold Approximation and Projection for Dimension Reduction). A scatter plot of the projected activations are shown in Panel A. The projected activations vectors were then divided into a uniform 80x80 grid. Within each grid cell, activation vectors were averaged, and a synthetic image was optimized to maximize this average activation value. The synthetic image is sized according to the number of activations within the given grid cell. Labels are averaged on a 40x40 grid. One way to think about these images is as "what the model is looking for" within this neighborhood in its embedding space.

5. ALEXNET

The moment we stopped understanding AI

This is an Activation Atlas (Figures 5.1a-c). It gives a glimpse into the high-dimensional embedding spaces modern AI models use to organize and make sense of the world.

The first model to really see the world like this, AlexNet, was published in 2012 in an eight page paper that shocked the computer vision community by showing that an old AI idea would work unbelievably well when scaled. The paper's second author, Ilya Sutskever, would go on to cofound OpenAI, where he and the OpenAI team would massively scale up this idea again to create ChatGPT.

If you look under the hood of ChatGPT, you won't find any obvious signs of intelligence. Instead, you'll find layer after layer of compute blocks called transformers—this is what the T in GPT stands for. We briefly looked at transformers in Chapter 2 when we explored Meta's Llama 3.2 large language model, which uses a similar transformer architecture to ChatGPT. In this chapter we'll get a little deeper into the architecture itself, and we'll go even deeper later in the Chapter on Attention.

Each transformer block performs a set of fixed matrix operations on an input matrix of data, and typically returns an output matrix of the same size. To figure out what it's going to say next, ChatGPT breaks apart what you ask it into words and word fragments called tokens, maps each of these to a vector, and stacks all these vectors together into a matrix (Figure 5.2).[1]

This matrix is then passed into the first transformer block, which returns a new matrix of the same size. This operation is repeated again and again, GPT-3.5 has 96 transformer compute blocks [Brown et al. 2020], and ChatGPT-4 reportedly has over 120. [Patel and Wong 2023, McGuinness] This process is shown in detail in Figure 5.3 on the following pages.

Now here's the absurd part. With a few caveats, the next word or word fragment (token) that ChatGPT says back to you is literally just the last column of its final output matrix, mapped from a vector back to text. To formulate a full response, this new token is appended to the end of your original input, and this new slightly longer text is fed back into the input of ChatGPT. [2]

This process is repeated again and again, with one new column added to the input matrix each time, until the model's output returns a special stop token.

1 Some implementations map each token to a column in the data matrix as shown in Figure 5.2, and some implementatios map individual tokens to rows. This convention choice does not change how the model operates.

2 Caching is often used here to avoid redundant compute

Chapter 5 Video



Figure 5.2 | Inputs. Large Language Models like ChatGPT use tokenizers to break apart text into words and word fragments called tokens. Tokens are then converted into vectors, this process is known as embedding. Different tokenizers break up text differently, this tokenization was generated using the OpenAI GPT-3 tokenizer. Note that some implementations embed tokens as columns in the data matrix shown above, and some implementations embed tokens as the rows. This is just a convention difference, and has no impact on how the model operates.


Input
What does G PT stand for ?
TRANSFORMER BLOCK
Gene
rative
Pre
trained
Output
Transformer



Figure 5.3 | How ChatGPT Answers a Question. After input text is broken into tokens and mapped to embedding vectors, the input matrix composed of these vectors is passed into the first transformer block of ChatGPT. This block returns a new matrix of numbers of the same shape as our input matrix. This matrix is then passed into the model's next transformer block, returning a third matrix of the same size. In the case of GPT-3, this process is repeated 96 times. All 96 transformer blocks use the same architecture, but have different learned parameters. The final column in the final output matrix (Green "Gener" column in the upper right), mapped back to a token, is what ChatGPT says next. This newly returned token is then appended to the original input and fed back into the model to produce the next token, and so on. The fact that this process generates intelligent text is remarkable.



Figure 5.5 | The AlexNet Architecture. AlexNet is composed of eight compute blocks. The first five blocks are convolutional layers (detailed in Figure 5.7), and the final three layers are "fully connected" or dense. The final three layers are equivalent to the multilayer ReLU networks we studied in Chapters 3 and 4. Convolutional blocks are often represented using 3D rectangular prisms like this—as we'll see, these prisms are really showing the data as it flows through the network, but not the convolution operations themselves. The final layer of AlexNet also includes a softmax function (not shown here, detailed in Chapter 3) to squish our outputs into nice probabilities that add up to one.



Figure 5.6 | Multilayer Perceptrons are Alive and Well. We're drawing them differently, but the last three layers of AlexNet shown in Figure 5.5 are equivalent to the multilayer perceptrons/multilayer neural networks we saw in detail in Chapters 1, 3, and 4! The main difference between the perceptrons we saw in Chapter 1 and the last three layers of AlexNet is that AlexNet uses ReLU activation functions!

And that's it. One matrix multiply after another, ChatGPT slowly morphs the input you give it into the output it returns.

Where is the intelligence?

How is it that these 100 or so blocks of dumb compute are able to write essays, translate language, summarize books, solve math problems, explain complex concepts, or even write the next line of this book?

The answer lies in the vast amounts of data these models are trained on.

Actual answer given by ChatGPT when prompted on the chapter text up to this point.

Ok, that's pretty good, but not quite what I wanted to write next.

The AlexNet paper is significant because it marks the first time we really see layers of compute blocks like this learning to do unbelievable things—an AI tipping point towards high performance and scale, and away from explainability.[3]

While ChatGPT is trained to predict the next word fragment given some text, AlexNet is trained to predict a label given an image.

The input image to AlexNet is represented as a three dimensional matrix or tensor of RGB intensity values, and the output is a single vector of length 1000, where each entry corresponds to AlexNet's predicted probability that the input image belongs to one of the 1000 classes in the ImageNet[4] dataset—things like tabby cats, German Shepherds, hot dogs, toasters, and aircraft carriers.



Figure 5.4 | Inputs and Outputs. AlexNet takes in RGB images of dimension 224x224x3, and returns vectors of length 1,000, with one entry for each ImageNet class. This network has successfully classified this image of a hot dog. Next step IPO!

Just like ChatGPT today, AlexNet was somehow magically able to map the inputs we gave it to the outputs we wanted by using layer after layer of compute blocks, after training on a large dataset.

One nice thing about vision models however is that it's easier to poke around under the hood, and get some idea of what the model has learned. One of the first under the hood insights that Krizhevsky, Sutskever, and Hinton show in the AlexNet paper was that the first layer of the model had learned some very interesting visual patterns.

The first five layers of AlexNet are convolution blocks (Figure 5.5), first developed in the late 1980s to classify handwritten digits, and can be understood as a special case of the transformer blocks in ChatGPT and other Large Language Models

3 There are certainly examples of neural networks doing very impressive things before 2012, such as handwritten digit recognition (e.g. LeNet-5) and streering a car (e.g. ALVINN), in my opinion however it's preyty striaghtforward to understand how LeNet-5 and ALVINN are working, but much less so with AlexNet—the scale becomes really overwhelming!

4 Techincally the ILSVRC2012 dataset, the full ImageNet dataset is much larger. Often when people refere to ImageNet, they're actually talking about this smaller dataset.



Figure 5.7 | Convolution. Convolutional Neural Networks like AlexNet work by sliding little matrices of learned weight values over an image, and at each location computing the dot product between the image and kernel.

[Turner 2023]. In convolutional blocks, the input image tensor is transformed by sliding a much smaller tensor called a kernel of learned weight values across the image, and at each location, computing the dot product between the image and kernel (Figure 5.7).

Here it's helpful to think of the dot product as a similarity score. The more similar a given patch of the image and the kernel are, the higher the resulting dot product will be. AlexNet uses 64 individual kernels in its first layer, each of dimension 11x11x3, so we can conveniently visualize them as little RGB images:



These images give us a nice idea of how the first layer of AlexNet "sees" the image. Incredibly, AlexNet has learned a set of basic pattern detectors, including edge detectors at various angles (black and white striped kernels), and various color blob detectors! Images with similar patterns will generate high dot products with these kernels.[5] These kernels are all initialized as random numbers, and the patterns we're looking at are completely learned from data.

Sliding each of our 64 kernels over the input image and computing dot products at each location produces a new set of 64 matrices, sometimes called activation maps—conveniently we can view these as images as well (Figure 5.8). The activation maps show us which parts of an image, if any, match a given kernel well. If an image includes something visually similar to a given kernel, we see a high activation in that part of the activation map. You can also see various activation maps picking up edges and other low level features.

5 Interestingly, the original AlexNet model was split across two GPUs (Nvidia GTX 580s), and one GPU ended up specializing in black & white edge detectors, while the other learned color blob detectors!



Figure 5.8 | AlexNet's first layer at work. These 64 activation maps are the result of AlexNet's first convolutional layer. Each of the 64 kernels shown on the previous page is slid across the input image, and at each location the activation map value is equal to the dot product between the current image patch and kernel. In this input image, I'm holding up a printed out image of the 5th kernel (top row previous page), which leads to a high dot product between this kernel and the input image, you can clearly see this high activation area as a glowing yellow region in the 5th activation map above (marked with an asterisk). If I rotate the printed kernel image by 90 degrees, the strength of the activation will decrease. Other kernels in AlexNet's first layer pick up other interesting features—for example the 4th activation map in the final row shows strong activation on the illuminated parts of my bookcases, which makes sense given the corresponding kernel's vertical change from blue to orange.



Figure 5.10 | Layer two is harder to understand. Mathematically, the convolutions/dot products in the second layer of AlexNet work in the same exact way as the operations in the first layer—we slide a kernel of learned weight values over our new depth 64 data tensor, and compute the dot product at each location. However, in our first layer, since our inputs are just images, our kernels are processing raw image data and have a depth of just three, so we can very naturally visualize our kernels as little RGB images, as shown on the previous page. This visualization technique unfortunately doesn't work with "64 color channels!" Also, even if it did, the second layer kernels are combining the features created by the first layer, not raw image data—we really need a way to visualize both layers of kernels working together. The colored squares inside each data block are actual activation values, but we're ignoring all activations below a given threshold, making our blocks partially transparent, to be able to better see large activation values.

Of course, finding edges and color blobs in images is still hugely removed from recognizing a complex concept like a German Shepherd or aircraft carrier. What's astounding about deep neural networks like AlexNet and ChatGPT is that from here all we do is repeat the same operation again, just with a different set of learned weights.

For AlexNet, this means that these 64 activation maps are stacked together into a new tensor and become the input to the exact same type of convolutional compute block, the second overall layer of the model, as shown in Figure 5.9.

Unfortunately in our second layer we can't learn much by simply visualizing the weight values in the kernels themselves. The first issue is that we just can't see enough colors—the depth of the kernels in each layer has to match the depth of the incoming data. In the first layer of AlexNet, the depth of the incoming data is just three because the model takes in color images with red, green, and blue color channels. However, since the first layer computes 64 separate activation maps, the computation in the second layer of AlexNet is like processing images with 64 separate color channels, as shown in Figure 5.10. The second factor that makes what's happening in the second layer of AlexNet more difficult to visualize is that the dot products are really taking weighted combinations of the outputs of the computations in the first layer, we need some way to visualize how the layers are working together.[6]

One way forward here is to find parts of various images that strongly activate the outputs of a given layer (See Figures 5.10-5.13).

6 AlexNet also uses ReLU activation functions in its convolutional layers, which makes this more complex as well.



Figure 5.9 | Stack and Repeat. After we compute our 64 activation maps using AlexNet's 64 learned first layer kernels (Figure 5.8), we then stack these activation maps together to form AlexNet's first datablock/tensor. As we'll see, our second layer processes this tensor using the same sliding kernel approach we used to process our initial images, just with different dimensions and learned weight values.



Figure 5.10 | Corner Detector. AlexNet's second layer starts to put together more complicated features. Given this input image of a square piece of paper, feature map 104 (marked with an asterisk) appears to be bringing together edge detectors to detect the edges and corners of the paper.



Figure 5.11 | Citrus Detector? When we reach the fifth and final convolutional layer of AlexNet, the model begins extracting more abstract and complex features. Here we see several of the 256 activation maps in the fifth layer responding strongly to the three oranges in the input image.

Figure 5.12 | Face Detector. Several activation maps in our fifth layer respond stronlgy to human faces, even though face and person are not explicit classes in the ImageNet dataset that AlexNet was trained on. Activation map 186 responds particularly strongly to faces, see Figure 5.13 for a closer look.



Figure 5.13 | Face Detector. Activation map 186 in AlexNet's fifth layer responds strongly to faces, and stops firing when faces are blocked.

Remarkably, as we move deeper into AlexNet, strong activations correspond to higher and higher level concepts. By the time we reach the fifth layer, we have activation maps that respond very strongly to faces, and other high level concepts.[7]

And what's incredible here is that no one explicitly told AlexNet what a face is. All AlexNet had to learn from was the images and labels in the ImageNet dataset, which does not contain a person class or face class.

AlexNet learned completely on it's own both that faces are important and how to recognize them.

To better understand what a given kernel in AlexNet has learned,[8] we can also look at the examples in the training dataset that give the highest output activation values for that kernel. For kernel 186 shown in Figure 5.13, not surprisingly, we find examples that contain people.

Finally, there's this really interesting technique called feature visualization where we can generate synthetic images that are optimized to maximize a given activation. These synthetic images give us another way to see what a specific activation layer is looking for (Figure 5.14).

7 "Deep Visualization Toolbox" by Jason Yosinski video inspired these visuals https://www.youtube.com/watch?v=AgkfIQ4IGaM

8 In convolutional neural networks, each kernel corresponds to a single neuron. It's perhaps a little more interesting to say "To better understand what a given neuron has learned"



$$d = \sqrt{(x_1^{(A)} - x_1^{(G)})^2 + ... + (x_{4046}^{(A)} - x_{4046}^{(G)})^2}$$

Figure 5.15 | Embedding Spaces are Powerful. Vector operations on the data vectors at the end of AlexNet are semantically meaningful! If we take the second to last data vector, we can measure the distances between images in this embedding space by taking their euclidean distance, just as we would in 2D space, just with a bunch more terms. Remarkably, similar concepts end up being clustered together in this embedding space! This figure shows how we would find the distance between an image of an aircraft carrier and a German Shepherd, which we would expect to be higher than the distance between two different images of aircraft carriers or two different images of German Shepherds.



Figure 5.14 | Feature Visualization. Another way to peek under the hood of models like AlexNet is to synthetically create images that maximize a given activation in the network. These visualizations are taken from a different model, InceptionV3, in my testing AlexNet did not create nearly as visually meaningful synthetic images using the same optimization techniques. These feature visualizations are reused from an excellent article on feature visualization: Olah, et al., "Feature Visualization", Distill, 2017, available at distill.pub/2017/feature-visualization/, licensed under CC-BY 4.0. The layout of these synthetic images was changed from the original article to better fit in this book.

By the time we reach the final layer of AlexNet, our image has been processed into a vector of length 4096. The final layer performs one last matrix computation on this vector to output a vector of length 1000, with one entry for each of the classes in the ImageNet dataset. Krizhevsky, Sutskever, and Hinton noticed that this second to last layer data vector demonstrated some very interesting properties.

One way to think about this vector is as a point in 4096 dimensional space (Figure 5.15). Each image we pass into the model is effectively mapped to a point in this space, all we have to do is just stop one layer early and grab this vector. Just as we can measure the distance between two points in 2D space, we can also measure the distance between points, or images, in this high dimensional space.

Hinton's team ran a simple experiment, where they took a test image in the ImageNet dataset, computed its corresponding vector, and then searched for the other images in the ImageNet dataset that were closest, or nearest neighbors, to the test image in this high-dimensional space.

Remarkably, the nearest neighbor images showed highly similar content to the test images. In the AlexNet paper, we see an example where an elephant test image yields nearest neighbors that are all elephants. What's interesting here too is the pixel values themselves of these images are incredibly different, AlexNet really has learned a high-dimensional representation of the data where similar *concepts* are physically close.



Figure 5.16 | Building an Activation Atlas. To create this activation atlas, a sample of the ImageNet dataset is passed into the InceptionV1 model, and the activation values for the Mixed5b layer are projected from 1024 dimensions to 2 using UMAP (Uniform Manifold Approximation and Projection for Dimension Reduction). The projected activation vectors are then divided into a uniform 80x80 grid. Within each grid cell, activation vectors were averaged, and a synthetic image was optimized to maximize this average activation value. The synthetic image is sized according to the number of activations within the given grid cell. Labels are averaged on a 40x40 grid. One way to think about these images is as "what the model is looking for" within this neighborhood in its embedding space. Concept and code are from: Carter, et al., "Activation Atlas", Distill, 2019.



This high-dimensional space is often called a latent or embedding space. In the years following the AlexNet paper, it was shown that not only distance, but directionality in some of these embedding spaces was meaningful. The demos you see where faces are age or gender shifted often work by first mapping an image to a vector in an embedding space, and then literally moving the point in the age or gender direction in the embedding space, and mapping the modified vector back to an image.[9]

Finally, there's some really amazing work that combines the synthetic images that maximize a given set of activations (Figure 5.14) with a two-dimensional projection or flattening out[10] of the embedding space to make the incredible activation atlas visualizations that we saw at the opening of the chapter.

Neighbors on the Activation Atlas are generally close in the embedding space, and show similar concepts that the model has learned → we're getting a peek into how deep neural networks organize the visual world.

Looking at the synthetic images that most activate neighborhoods of neurons, we can to visually walk through embedding space of the model, seeing it make smooth visual transitions as we move from zebras to tigers to cheetahs to lions (Figure 5.16 upper left corner). In middle layers of the model, we can see moderately abstract features, such as direction in embedding space that amazingly correlate with the number and size of pieces of fruit in an image (Figure 5.17).[11]

---

9 We'll cover embedding spaces in more depth in the Chapter 9
10 Typically using a tSNE or UMAP algorithm to project down from high dimensional space.
11 The team who developed activation atlasses has an interactive visualizer where you can explore more: https://distill.pub/2019/activation-atlas/



Figure 5.17 | Activation Atlas for Middle Layer. This activation atlas is created in the same way as the atlas shown in Figure 5.16, but is computed for an earlier layer of the model (Mixed4c), generating lower level, less abstract features. The white arrow in the atlas remarkably appears to show a direction in the model's learned latent/embedding space that corresponds to the number of pieces of fruit in an image! The atlas above is the portion of the full Mixed4c projection (left) in the blue dotted box.

The same principle applies in large language models. Words and word fragments are mapped to vectors in an embedding space, where words with similar meanings are close to each other, and directions in the embedding space are sometimes semantically meaningful.

There's some incredible recent work from the team at Anthropic[12] that shows how sets of activations can be mapped to concepts in language [Templeton, et al. 2024]. These results can help us better understand how LLMs work, and also be used to modify model behavior.

After clamping a set of activations[13] that correspond the concept "Golden Gate Bridge" to a high value, the LLM the team was experimenting with began to self identify as the Golden Gate Bridge.

AlexNet won the ImageNet Large Scale Visual Recognition Challenge by a wide margin in 2012, the third year the challenge was run.



In prior years, the winning teams used approaches that, under the hood that look much more like what you might expect to find in an intelligent system. The 2011 winner used a complex set of very different algorithms, starting with an algorithm called SIFT[14], which is composed of specialized image analysis techniques developed by experts over many years of research.

AlexNet, in contrast, is an implementation of a much older AI idea—an artificial neural network—where the behavior of the



Figure 5.18 | A vector space of ideas. In this classical example of language embedding spaces ["Word2Vec", Mikolov et al. 2013], the embedding vector for Queen is very close to King+(Woman-Man), where each word refers to its embedding vector. (Woman-Man) is a difference vector that conceptually "points in the woman direction". Basic math operations produce remarkably reasonable results in this "space of ideas"!

Figure 5.19 | ImageNet Image Classification Top-5 Error Rate. The AlexNet team significantly improved performance on the challenging ImageNet Large Scale Visual Recognition Challenge (ILSVRC), and arguably kicked off the wave of AI we find ourselves in today. Top-5 means that the algorithm gets 5 guesses at the correct answer. Human top-5 accuracy on ILSVRC is generally reported to be in the 3-5% range.

12 With some of the same authors as the activation atlas work! Shan Carter and the GOAT Chris Olah. This team does amazing work!

13 A smaller model called a sparse autoencoder was used to figure which set of activations corresponded to the Golden Gate Bridge concept.

14 SIFT= Scale Invariant Feature Transform



algorithm is almost entirely learned from data.

The dot product operation between the data and a set of weights was originally proposed by McCulloch and Pitts in the 1940s as a dramatically oversimplified model of the neurons in our brain. In the second half of each transformer block in ChatGPT and at the end of AlexNet you'll find a multilayer perceptron— the perceptron is a learning algorithm and physical machine from the 1950s that uses McCulloch and Pitts neurons and can learn to perform basic shape recognition tasks.[15]

Back in the 1980s, a younger Geoff Hinton and his collaborators showed how to train multiple layers of these perceptrons using a multivariate calculus technique called backpropagation.[16] These models were a couple layers deep and remarkably pretty good at driving cars. In the 1990s, Yann Lecun, now chief AI scientist at Meta, was able to train 5 layer deep models to recognize handwritten digits.

Despite these intermittent successes of artificial neural networks over the years, this approach was hardly the accepted way we should probably be doing AI, right up until the publication of AlexNet.

If this was obviously the way to build intelligent systems, we would have done it decades earlier. As Ian Goodfellow writes in his excellent Deep Learning book [Goodfellow et al 2016]:

"At this point [mid 2000s], deep networks were generally believed to be very difficult to train. We now know that algorithms that have existed since the 1980s work quite well, but this was not apparent circa 2006. The issue is perhaps simply that these algorithms were too computationally costly to allow much experimentation with the hardware available at the time."

The key difference in 2012 was simply scale of data and scale of compute. The ImageNet dataset (ILSCRC2012) was the largest labelled image dataset collected to date, with over 1.3 million images. And thanks to Nvidia GPUs, in 2012 Hinton's team had access to roughly ten thousand times more compute power than Yann LeCun had 15 years before.

LeCun's LeNet-5 model had around 60,000 learnable parameters. AlexNet increased this a thousand fold to around 60 million parameters. Today, ChatGPT 4 has well over a trillion parameters, making it over ten thousand times larger than AlexNet.

This mind boggling scale is the hallmark of the third wave of AI we find ourselves in today, driving both the performance and the

15 See Chapter 1 for a detailed walkthrough of the perceptron
16 See Chapter 3 for a deep dive into backpropagation

	LeNet-5	AlexNet	GPT-3	GPT-4	?
YEAR	1998	2012	2020	2023	2030
TRAINING DATA	· MNIST Dataset · 60k training examples · 10 classes	· ImageNet Dataset (ILSVRC) · 1.2M training examples · 1000 classes	· Common Crawl, WebText, Wikipedia, others · ~500B training tokens · ~100k unique tokens	· ~13T training tokens*	All the datas
TRAINING COMPUTE	· Pentium II CPU · ~0.27 GFLOPs	· Dual Nvidia GTX 580 · 3162 GFLOPs	· 10,000 Nvidia V100 GPUs · 1+ ExaFLOPs	· 25,000 Nvidia A100s GPUs* · ~4+ ExaFLOPs	All the computers
ALGORITHM	· ~60k Parameters · 5 Layers · Sigmoid Activation Function	· ~60M Parameters · 8 Layers · ReLU Activation Function · Dropout	· 175B Parameters · 96 Layers · Transformers	· 1T+ Parameters* · 120 Layers* · Transformers	All the algorithms

Figure 5.18 | What's Next?. The change in scale of data and compute we've witnessed in a couple decades is remarkable. There have been some interesting and powerful algorithmic innovations (e.g. Convolutional layers, transformers), but scale is arguably the largest driver in the success of Deep Learning. GPT-3 numbers are from [Brown et al. 2023]. *GPT-4 numbers have not been shared publicly and are speculative [McGuinness, Patel & Wong 2023].

fundamental difficulty in understanding how these models are able to do what they do. It's amazing that we can figure out that AlexNet learns representations of faces and Language Models learn representations of concepts like the Golden Gate bridge, but there are many many more concepts these models learn that we don't even have words for. Activation atlases are beautiful and fascinating, but are very low dimensional projections of very high-dimensional spaces, where our spatial reasoning abilities often completely fall apart.

It's notoriously difficult to predict where AI will go next. Almost no one expected the neural networks of the 80s and 90s, scaled up by three or four orders of magnitude would yield AlexNet,[17] and it was almost impossible to predict that a generalization of the same compute blocks, scaled up by another three or four orders of magnitude would yield ChatGPT.

Maybe the next AI breakthrough is just another 3 or 4 orders of magnitude of scale away, or maybe some mostly forgotten approach to AI will resurface, as AlexNet did in 2012.

We'll have to wait and see.

"machines will be capable, within twenty years, of doing any work a man can do."

- Herbert Simon (Nobel Laureate)
Written in 1965

17 Except LeCun, Hinton, and Bengio apparently!

5. AlexNet

5.1 Imports and Support Functions

[1]:
```
import numpy as np
import matplotlib.pyplot as plt
import torch
import torch.nn as nn
import torchvision.models as models

import cv2, os, shutil
from torchvision import transforms
from pathlib import Path
from tqdm import tqdm
import subprocess
from PIL import Image
import matplotlib.colors as mcolors
```

5.1 First Layer Viz

Reproduces figure 5.8

[4]:
```
alexnet = models.alexnet(weights = True)
alexnet.eval();
```

[5]:
```
grid_size=(8,8)
alexnet_layer_up_to=1

frame = cv2.imread('data/holding_alexnet_pattern.jpg')

video_crop=[420,0,1500,1080] #Process stills or video
tfms = transforms.Compose([transforms.Resize((224, 224)), #Resize to standard alexnet size
                                transforms.ToTensor(), #Convert to tensor
                                #Normalize using imagenet stats
                                transforms.Normalize(mean=[0.485, 0.456, 0.406],
                                                     std=[0.229, 0.224, 0.225])])
```

[6]:
```
im_pil=Image.fromarray(frame[:,:,(2,1,0)])
im_tensor = tfms(im_pil.crop(video_crop))
```

[10]:
```
im_pil.crop(video_crop).resize((256,256))
```

[10]:

SUPPORTING CODE

Full supporting code for this chapter at:
github.com/stephencwelch/ai_book

[11]:
```
with torch.no_grad():
    activations = alexnet.features[:alexnet_layer_up_to](im_tensor[None])

plt.clf()
fig = plt.figure(0, (12, 12), facecolor='w') #
activations_numpy=activations.detach().numpy()[0]/activations.detach().numpy().max()
grid_image=arrange_images_on_grid(activations_numpy,
                  grid_size=grid_size, gap=2, background_value=255, cmap_name='viridis',
                                  border_width=0, border_color='#948979')
plt.imshow(grid_image); plt.axis('off')
plt.axis('off');
```

[11]:



5.3 Second Layer Viz

Figure 5.10

[8]:
```
grid_size=(14,14)
alexnet_layer_up_to=5
frame = cv2.imread('data/holding_square_close.jpg')
```

[9]:
```
im_pil=Image.fromarray(frame[:,:,(2,1,0)])
im_tensor = tfms(im_pil.crop(video_crop))
```

[10]:
```
im_pil.crop(video_crop).resize((256,256))
```

[10]:



[11]:
```
with torch.no_grad():
    activations = alexnet.features[:alexnet_layer_up_to](im_tensor[None])

plt.clf()
fig = plt.figure(0, (12, 12), facecolor='w') #
activations_numpy=activations.detach().numpy()[0]/activations.detach().numpy().max()
grid_image=arrange_images_on_grid(activations_numpy,
                   grid_size=grid_size, gap=2, background_value=255, cmap_name='viridis',
                                  border_width=0, border_color='#948979')
plt.imshow(grid_image); plt.axis('off')
plt.axis('off');
```

[11]:





Figure 5.10 | Corner Detector. AlexNet's second layer starts to put together more complicated features. Given this input image of a square piece of paper, feature map 104 (marked with as asterisk) appears to be brining together edge detectors to detect the edges and corners of the paper.

5. ALEXNET | EXERCISES

5.1 How was AlexNet different than most other computer vision approaches at the time?

5.2 Figure 5.3 shows how large language models like ChatGPT answer questions. What makes this process inefficient? How might we speed up this process? Chapter 8 will take a close look at this problem.

5.3 Why is AlexNet's input data dimension 224x224x3? Why is its output dimension 1x1000?

5.4 Why is it easier to visualize what's happening in the first layer of AlexNet, compared to other layers?

5.5. Figure 5.10 shows the outputs of the second layer of AlexNet. We found that feature map 104 appears to be a corner detector—do you see other feature maps that appear to be responding to specific features?



Figure 5.12 | Face Detector. Several activation maps in our fifth layer respond stronly to human faces, even though face and person are not explicit classes in the ImageNet dataset that AlexNet was trained on. Activation map 186 responds particularly strongly to faces, see Figure 5.13 for a closer look.

5.6. Figure 5.12 shows the outputs of the fifth layer of AlexNet. We found that feature map 186 appears to be a face detector—do you see other feature maps that appear to be responding to specific features?

5.7 What interesting properties did Hinton's team notice about the vectors generated by the second to last layer of AlexNet (Figure 5.15)?

5.8 What is an activation atlas?

5.9 The underlying algorithms for creating and training AlexNet existed long before 2012—what took so long?

5.10 How many more parameters does GPT-3 have than AlexNet? What about GPT-4?

5.11 Do you think the next set of AI breakthroughs will be driven by more scaling of existing approaches (i.e. more data, compute), or will fundamentally new ideas be required?



Figure 6.1 | Performance vs. Compute. As we train larger and larger models using more compute, we see a surprisingly predictable trend, with models approaching a "compute optimal" or "compute efficient" frontier (dashed line). Note that both axes are logarithmic. This figure was recreated from Figure 3.1 in the GPT-3 paper [Brown et al. 2020]. Each colored line shows the performance of a different large language model while training. Validation loss here is cross-entropy loss; see Chapters 2 and 3 for more on cross-entropy loss. The x-axis measures compute in PetaFLOP/s-days. A PetaFLOP/s-day is the number of computations a system capable of 10^15 floating point operations (1 petaFLOP) per second can perform in a day. We'll contextualize this unit later in the chapter.



Figure 6.2 | Wait, there's more. We also see surprisingly clear trends between performance and parameter count and performance and dataset size. Figure reproduced with permission from [Kaplan et al. 2020], with minor color modifications.

6. NEURAL SCALING LAWS

AI can't cross this line and we don't know why

Chapter 6 Video

AI models can't cross the dashed boundary in Figure 6.1, and we don't know why.

As we train larger and larger models (purple -> yellow lines in Figure 6.1), model performance improves, but each successively larger model requires more compute to train.

When we plot the loss curves for a family of models while training on a logarithmic plot, a clear trend emerges, where no model crosses the dashed line—known as the compute optimal or compute efficient frontier.

This trend is one of three neural scaling laws that have been broadly observed. Error scales in a very similar way with compute, model size, and dataset size (Figure 6.2), and remarkably doesn't depend much on model architecture or learning algorithm, as long as reasonably good choices are made.

An interesting question from here is:

Have we discovered some fundamental law of nature—like an ideal gas law for building intelligent systems—or is this trend just a result of the specific neural network driven approach to AI we're taking right now?

How powerful can these models become if we continue increasing the amount of data, model size, and compute? Can we drive errors to zero or will performance level off?

Why are data, model size, and compute the fundamental limits of the systems we're building, and why are they connected to model performance in such a simple way?

2020 was a watershed year for OpenAI.

In January, the team released [Kaplan et al. 2020], where they showed very clear performance trends across a broad range of scales for language models (Figure 6.2).

The team fit a power law equation to each set of results, giving a precise estimate for how performance scales with compute, dataset size, and model size. On logarithmic plots, these power law equations show up as straight lines, and the slope of each line is equal to the fit power value (From Figure 6.2, compute slope = -0.050, parameter count slope = -0.076, and dataset size slope = -0.095). Larger powers make for steeper lines and more rapid performance improvements.

The team observed *"no signs of deviation from these trends on the upper end"*—foreshadowing OpenAI's strategy for the year.

The largest model the team tested at the time had 1.5 billion learnable parameters, and required around 10 PetaFLOP/s-days of compute to train.

A PetaFLOP/s-day is the number of computations a system capable of one quadrillion (10^{15}) floating point operations a second can perform in a day. The top of the line GPUs at the time, the Nvidia V100, is capable of around 30 TeraFLOP/s (fp16),[1] so a system with 33 of these ten thousand dollar[2] GPUs would deliver around a PetaFLOP/s of compute.

That summer the team's empirically predicted gains would be realized with the release of GPT-3.

The OpenAI team had placed a massive bet on scale, partnering with Microsoft on an enormous supercomputer equipped with not 33, but ten thousand V100 GPUs, and training the absolutely massive 175 billion parameter GPT-3 model using 3,640 PetaFLOP/s-days of compute (GPT-3 is the largest/yellow line in Figure 6.1).

GPT-3's performance followed the trend line predicted in January remarkably well, but also didn't flatten out, indicating that even larger models would further improve performance.

If the massive GPT-3 hadn't reached the limits of neural scaling, where were they? Is it possible to drive error rates to zero given sufficient compute, data, and model size?

In an October publication, the OpenAI team took a deeper look at scaling [Henighan et al. 2020].

The team found the same clear scaling laws across a range of problems, including image and video modeling. They also found that on these other problems, the scaling trends did eventually flatten out, before reaching zero error.[3]

This makes sense if we consider exactly what these error rates are measuring. As we've seen, Large Language Models like GPT-3 are autoregressive—they are trained to predict the next word or word fragment (token) in sequences of text as a function of the words that came before. These predictions generally take the form of vectors of probabilities.

So for a given sequence of input words, a language model will output a vector of values between zero and one, where each entry corresponds to the probability of a specific word in its vocabulary. These vectors are typically normalized using a softmax operation, which ensures that all the probabilities add up to one.[4]

---

1 https://lambda.ai/blog/demystifying-gpt-3

2 V100 original price: https://www.microway.com/hpc-tech-tips/nvidia-tesla-v100-price-analysis/#:~:text=Tesla

3 This may be a result of dataset size or the data iself. The team converted images and video prediction into sequence prediction problems like language modeling

4 See Chapter 3 for softmax details



Figure 6.3 | One PetaFLOP/s of compute, circa 2020. To get a PetaFLOP/s of compute in 2020, you would need to buy around 33 Nvidia V100s at around $10,000 USD each.



Figure 6.4 | It's not just language modeling. The OpenAI team found clear scaling law behavior across various types of data, including images, videos, text-to-image, image-to-text, and math problems. Plots reproduced with permission from [Henighan et al. 2020].



Figure 6.5 | Measuring LLM Performance. Most Large Language Models are trained using the cross-entropy loss. Despite having a complicated name, cross-entropy loss is straightforward to compute and reason about—it's equal to the negative natural logarithm of the model's probability of the correct next token.

GPT-3 has a vocabulary size of 50,257. So if we input a sequence of text like "Einstein's first name is", the model will return a vector of length 50,257, and we expect this vector to be close to zero everywhere, except at the index that corresponds to the word Albert—this is index 42,590 (Figure 6.5).

During training, we know what the next word is in the text we're training on, so we can compute an error or loss value that measures how well our model is doing relative to what we know the word should be. This loss value is incredibly important, because it guides the optimization or learning of the model's parameters—all those PetaFLOP/s of training are performed to bring this loss number down.

There's a bunch of different ways we could measure the loss. In our Einstein example, we know the correct output vector should have a value of 1.0 at index 42,590—so we could define our loss value as 1.0 minus the probability returned by the model at this index. So if our model was 100% confident the answer was Albert and returned a 1.0, our loss would be zero—which makes sense.[5]

If our model returned a value of 0.9, our loss would be 0.1 for this example, if the model returned a value of 0.8, our loss would be 0.2, and so on. The formulation is equivalent to what's called an L1 loss, which works well in a number of machine learning problems.

However, in practice, we've found that models often perform

5 We know the predicted probability would be 0 everywhere else because our output vector has to sum to one



Model's Probability of Correct Next Token	P_i	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
L1 Loss	$1-P_i$	1.0	0.9	0.8	0.7	0.6	0.5	0.4	0.3	0.2	0.1	0.0
Cross-Entropy Loss	$-\ln(P_i)$	∞	2.30	1.61	1.20	0.92	0.69	0.51	0.36	0.22	0.11	0.0

Figure 6.6 | Cross-entropy vs L1 Loss. We could measure our model's performance using L1 loss, but cross-entropy loss generally works better in practice. One reason for this is that when cross-entropy loss is applied to a model using a softmax function on its output, the exponentials from softmax and logarithm from the cross-entropy loss effectively cancel, leaving the L1 loss to guide our optimization. See Chapter 3 for details.

better when using a different loss function formulation called cross-entropy.[6]

The theoretical motivation of cross entropy is a bit complicated [see Goodfellow et al. 2016, Chapter 6.2.1.1], but the implementation is simple. All we do is take the negative natural logarithm of probability output by the model at the index of the correct answer. So to compute the loss in our Einstein example, we just take the negative log of the probability output by the model at index 42,590.

So if our model is 100% confident, our cross entropy loss equals -ln(1)=0, which makes sense, and matches our L1 loss. If our model is 90% confident of the correct answer, our cross entropy loss equals -ln(0.9)=0.105, again close to our L1 loss.

Plotting our cross entropy loss as a function of the model's output probability as shown in figure 6.6, we see that loss grows slowly and then shoots up as the model's output probability of the correct word approaches zero. This means that if the model's confidence in the correct answer is very low, the cross-entropy loss will be very high.

The model performance shown on the y-axis in all the scaling figures we've looked at so far is the cross-entropy loss, averaged over the examples in the model's test or validation set (Figure 6.1, 6.2, 6.4). The more confident the model is about the correct next words in the test set, the closer to zero the average cross entropy becomes.

6 See Chapters 2 and 3 for more on cross-entropy

Now, the reason it makes sense that the OpenAI team saw some of their loss curves level off instead of reaching zero (Figure 6.4), is because predicting the next element in sequences like this generally does not have a single correct answer.

The sequence "Einstein's first name is" has a fairly unambiguous next word, but this is not the case for most text.[7]

A large part of GPT-3's training data comes from the text scraped from websites—if we search for a phrase like "a neural network is a", we'll find many different next words from various sources (Figure 6.7). None of these words are wrong, there's just many different ways to explain what a Neural Network is.

This fundamental uncertainty is called the *entropy of natural language*.

The best we can hope for our language models is that they give high probabilities to a realistic set of next word choices. And remarkably, this is what large language models learn to do—for example Figure 6.8 shows the top five choices from Meta's Llama model.

So we can never drive the cross entropy loss to zero, but how close can we get? Can we compute or estimate the value of entropy of natural language?

By fitting power law models to their loss curves that include a constant "irreducible error" term, the OpenAI team was able to estimate the natural entropy in low resolution images, videos, and other data sources. For each problem they estimated the natural entropy of the data in two ways—once by looking at where the data scaling curve levels off and again by looking at where the model size curve levels off and found that these separate estimates agree very well.

Note that the scaling power laws still work in these cases, but by adding the constant term, our trend line or frontier on a log-log plot is no longer a straight line, this is why the dotted frontier lines for most plots in Figure 6.4 are curved.[8]

Interestingly, the team was not able to detect any flattening out of

---

7 In the video that goes along with this chapter, I said that 'The sequence "Einstein's first name is" has a VERY unambiguous next word'. People were quick to point out many counterexamples, I've copied a few below. These a great examples of the entropy of natural langauge!
Einstein's first name is not John.
Einstein's first name is approximately Alpert.
Einstein's first name is probably not Alphonso.
Einstein's first name is derived from the Germanic Adalbert.
Einstein's first name is Eduard. (Albert's second son.)
Einstein's first name is universally known.
Einstein's first name is known by most people.
Einstein's first name is not an example of name weirdness.

8 The constant terms in the fit equation of this plot correspond to the "irreducible error", for example in the lower left text-to-image plot, the irreducible error is 1.93

A neural network is a **method** in artificial intelligence that teaches computers to process data… aws.amazon.com/what-is/neural-network

A neural network is a **machine** learning program, or model, that makes decisions in a manner... ibm.com/topics/neural-networks

A neural network is a **group** of interconnected units called neurons that send signals to one another… wikipedia.org/wiki/Neural_network

A neural network is a **series** of algorithms that endeavors to recognize... investopedia.com/terms/n/neuralnetwork.asp

A neural network is a **type** of machine learning algorithm inspired by the human brain…. cloud.google.com/discover/what-is-a-neural-network

A neural network is a **computing** model whose layered structure… databricks.com/glossary/neural-network

A neural network is a **bunch** of inputs and outputs… aiimi.com/insights/what-is-a-neural-network

Figure 6.7 | The Entropy of Natural Language. The language modeling tasks have no single correct answer, so we don't expect our language models to reach zero prediction error.

A neural network is a **system** of artificial neurons, which are connected together in a network to... Probability: 0.095

A neural network is a **computational** model based on the biological nervous system. Probability: 0.084

A neural network is a **network** of artificial neurons that are connected together by synapses. Probability: 0.084

A neural network is a **collection** of artificial neurons, or nodes, that are connected to... Probability: 0.055

A neural network is a **mathematical** model that is inspired by the human brain. Probability: 0.053

Figure 6.8 | A Reasonable Set of Answers. Given that there's no single correct answer when modeling what word (token) comes next, the best we can hope for is that our models will learn a reasonable set of next answers—and remarkably they do! These answers are from meta-llama/Meta-Llama-3-8B (Hugging Face implementation).



Figure 6.9 | Curved Frontiers? For most types of data, the OpenAI team observed a leveling off of their frontier lines (dotted line in left panel), allowing the team to estimate an "irreducible error" term (1.93 in the left panel). Note that on log-log plots like this, adding a constant term to our fit equation makes our line curved. Interestingly, the team did not detect any leveling off of the language modeling curve. Plots reproduced with permission from [Henighan et al. 2020].



Figure 6.10 | Chinchilla Scaling. In 2022 the Google DeepMind team ran a massive set of scaling experiments, and did see a leveling off in the compute-optimal frontier, estimating the entropy of natural language (on the MassiveText dataset) to be 1.69. These results are often referred to as "Chinchilla Scaling" after one of the models used in the experiments. Interestingly, these results can be used to predict the relative impacts of dataset size and model size on model performance. Reproduced with permission from [Hoffmann et al. 2022].



Figure 6.11 | GPT-4 Scaling. Scaling laws hold remarkably well for the massive GPT-4. Unlike GPT-3 scaling results, the GPT-4 scaling trend does level off. The scaling figures in the GPT-4 technical report (upper plot, reproduced with permission from [OpenAI 2023]) use somewhat different units and scaling than other plots we've seen in this Chapter. The team reports "Bits per word", this metric is a scaled version of the cross-entropy loss we've seen. To measure error in bits we use a base 2 logarithm instead of a natural logarithm in our error equation, meaning that bits per word shown here is a scaled version of cross-entropy loss: Cross-entropy loss $= -\ln(P_i) = -\log_2(P_i)*\ln(2)$. However, more importantly, the team does not use a logarithmic y-axis, making the curvature of the plot difficult to interpret, here we've remapped the original plot to a logarithmic y-axis, where we do see a "leveling off" of the curve. See supporting repo for details on mapping this curve.

performance on language data however, noting that:

"Unfortunately, even with data from the largest language models we cannot yet obtain a meaningful estimate for the entropy of natural language."

Eighteen months later the Google DeepMind team published a set of massive neural scaling experiments, where they did observe some curvature in the compute efficient frontier on natural language data. They used their results to fit a neural scaling law that broke the overall error into three terms—one that scales with model size, one with dataset size, and finally an irreducible term that represents the entropy of natural text (Figure 6.10).

These empirical results imply that even an infinitely large language model with infinite data cannot have an average cross-entropy loss on the MassiveText dataset of less than 1.69.

A year later, on Pi day 2023, the OpenAI team released GPT-4 Despite running for 100 pages, the GPT-4 technical report contains almost no technical information about the model itself—the OpenAI team did not share this information, citing the competitive landscape and safety implications.

However, the paper does include two scaling plots. The cost of training GPT-4 is enormous, reportedly well over 100 million dollars.[9] Before making this giant investment, the team predicted how performance would scale using the same simple power laws, fitting this curve to the results of much smaller experiments (Figure 6.11).

Unlike the other scaling plots we've seen in this chapter, the GPT-4 team's plot does not use a logarithmic y-axis scale, exaggerating the curvature of the scaling. If we map this curve to a logarithmic scale, we see some curvature, but overall a close match to the other scaling plots we've seen. What's incredible here is how accurately the OpenAI team was able to predict the performance of GPT-4, even at this massive scale.

While GPT-3 training required an already enormous 3,640 PetaFLOP/s-days, some leaked information on GPT-4 training puts the training compute at over 200,000 PetaFLOP/s-days, reportedly requiring 25,000 Nvidia A100 GPUs running for over three months.[10]

All of this means that neural scaling laws appear to hold across an incredible range of scales, something like 13 orders of magnitude from 10^{-8} PetaFLOP/s-days reported in OpenAI's first 2020 publication [Kaplan et al. 2020], to the leaked value of over 200,000 = $2{\cdot}10^5$ PetaFLOP/s-days for training GPT-4.

This brings us back to the question—why does AI model performance follow such simple laws in the first place? Why are data, model size, and compute the fundamental limits of the systems we're building, and why are they connected to model performance in such a simple way?

9 https://www.wired.com/story/openai-ceo-sam-altman-the-age-of-giant-ai-models-is-already-over/
10 https://newsletter.semianalysis.com/p/gpt-4-architecture-infrastructure, https://epoch.ai/blog/tracking-large-scale-ai-models



Figure 6.13 | The Number Eight. In the MNIST handwritten digit dataset, each image is composed of 28×28 pixels, where the intensity of each pixel is stored as a number between 0 and 1. Note that here we're using 0 as white and 1 as black, this is often reversed. Lower left panel shows the same image without the underlying pixel values superimposed.

The deep learning theory we need to answer questions like this is generally far behind practice, but some recent work does make a compelling case for why model performance scales following a power law, by arguing that deep learning models effectively use data to resolve a high-dimensional data manifold.

There's this idea in machine learning that the datasets our models learn from exist on manifolds in high-dimensional space. We can think of natural data like images or text as points in this high-dimensional space.

In the MNIST dataset of handwritten images for example, each image is composed of a grid of 28 by 28 pixels, and the intensity of each pixel is stored as a number between zero and one.



Figure 6.12 | The Manifold Hypothesis. Natural data like images and text are points in high dimensional space, but are not uniformly distributed. Instead, natural data lives on a lower dimensional manifold. Image and language models learn the geometry of this manifold.



Figure 6.14 | Points on a plane. The "space" of two pixel images is just a plane—every two pixel image maps to a unique location on the x_1x_2 plane. Three pixel images map to unique points in a cube, and larger images map to points in hypercubes.

If we imagine that our images only have two pixels for a moment, we can visualize these two pixel images as points in 2D space, where the intensity value of the first pixel is the x coordinate, and the intensity value of the second pixel is the y coordinate, as shown in Figure 6.14. An image made of two white pixels would fall at 0,0 in our 2D space, an image with a black pixel in the first position and a white pixel in the second position would fall at 1,0, an image with a gray value of 0.4 for both pixels would fall at 0.4, 0.4, and so on.

If our images had three pixels instead of two, the same approach still works, just in three dimensions. Scaling up to the 28 × 28 MNIST images, our images become points in 784 dimensional space.

The vast majority of points in this high-dimensional space are not handwritten digits. We can see this by randomly choosing points in the space and displaying them as images, as shown in Figure 6.16—these almost always just look like random noise—you would have to get really really lucky to randomly sample a handwritten digit.

This sparsity suggests that there may be some lower dimensional shape embedded in this 784 dimensional space, where every point in or on this shape is a valid handwritten digit.

Going back to our toy images for a moment, and assuming our images have just three pixels— if we learned that the third pixel



Figure 6.15 | Points in a hypercube. We can think of the MNIST dataset as points in 784 dimensional space (easy, right? 🤣), where each pixel intensity value controls the image's position in one dimension of our space.



Figure 6.16 | Aww Shucks. Here are 144 randomly generated 28x28 images. As you may have noticed, none of these images look anything like the MNIST handwritten digit dataset. We would have to get very lucky to randomly generate a reasonable looking number. The means that in the 784 dimensional hypercube of all possible 28×28 grayscale images, the MNIST dataset takes up a tiny fraction of the overall space, and perhaps lives on a lower dimensional manifold.



Figure 6.17 | A lower dimensional manifold in higher dimensional space. If our images have three total pixels, but we also knew that $x_3=1+\cos(x_2)$, then our images would live on this two-dimensional manifold in three dimensional space. Learning manifolds is one way to interpret and reason over how neural networks operate.



Figure 6.19 | Dataset Scaling. Let's have a closer look at the dataset scaling trend we saw back in Figure 6.2. Reproduced with minor color modifications with permission from [Kaplan et al. 2020].

intensity value, let's call it x_3, was always just equal to $1+\cos(x_2)$, where x_2 is our second pixel's intensity value, then all our three pixel images would lie on the curved surface in our 3D space defined by $x_3=1+\cos(x_2)$, as shown in Figure 6.17. This surface is two-dimensional—we can capture the location of our images in 3D space just using x_1 and x_2, we no longer need x_3.

We can think of a neural network that learns to classify MNIST as working in a similar way. In the network architecture shown in Figure 6.18 for example,[11] our second to last layer has 16 neurons, meaning the network has mapped each 784 dimensional input image to a lower 16 dimensional space, very much like our $x_3=1+\cos(x_2)$ function mapped our three dimensional space to a lower two-dimensional space.

Where the manifold hypothesis in machine learning gets really interesting, is that the manifold is not just a lower dimensional representation of the data, the geometry of the manifold often encodes information about the data. If we take the 16 dimensional representation of our MNIST dataset learned by our neural network, we can get a sense for its geometry by projecting from 16 dimensions down to two using a technique like UMAP/tSNE[12], which attempt to preserve the structure of the higher dimensional space (Figure 6.18).

Coloring each point using the number the image corresponds to, we can see that as the network trains, effectively learning the shape of the manifold, instances of the same digit are grouped together into little neighborhoods on the manifold. This a common phenomenon across many machine learning problems—images showing similar objects or text referring to similar concepts end up close to each other on the learned manifold. One way to make sense of what deep learning models are doing is that they map high-dimensional input spaces to lower dimensional manifolds, where the position of data on the manifold is meaningful.

Now, what does the manifold hypothesis have to do with neural scaling laws?

Let's consider the neural scaling law that links the size of the training dataset with the performance of the model, measured as the cross-entropy loss on the test set.

If the manifold hypothesis is true, then our training data are points on some manifold in higher dimensional space, and our model attempts to learn the shape of this manifold. The density of training data points on our manifold depends on how much data we have, but also on the dimension of the manifold itself.

11 See Chapter 5 for more details on image classification architectures like this.,
12 UMAP = Uniform Manifold Approximation and Projection, tSNE = t-distributed stochastic neighbor embedding



Figure 6.18 | Learning a Lower Dimensional Representation. The second to last layer of this classification model (top panel) has 16 neurons, meaning the model has mapped the 784 pixel intensity values in a given image into just 16 numbers. We can get a feel for this 16 dimensional space using a UMAP (Uniform Manifold Approximation and Projection) algorithm to project our points from 16 dimensions to just two, here we're plotting the UMAP projections of 1000 test points before and after training. As we can see, the lower dimensional representation learned by the model nicely organizes our numbers into little islands, allowing the final layer of the model to cleanly separate our classes.



Figure 6.20 | A Scaling Theory? Linking together a few theoretical results, we can produce a bound on how we expect the cross-entropy loss to scale with the number of training examples. The density of our training points depends on the dimension of our data manifold. If our manifold is one-dimensional, then the average distance between training points on our manifold is equal to the length of our manifold divided by the number of training points. Extending this argument to 2D, 3D, and N-dimensional manifolds, we can show that $s=L\cdot D^{-1/d}$, where s is the average distance between training points, L is the length of our manifold, and D is the number of training points. From here we can combine this result with two other theoretical results [Bahri et al. 2024, Sharma and Kaplan 2020] to find an upper bound on our cross-entropy loss scaling with respect to our dataset size: $D^{-4/d}$. Excitingly, this result links together two key properties we see empirically linked by observed scaling trends: loss and dataset size (Figure 6.2). However, this equation does depend on the dimension of our data manifold d, so we still have one missing piece of the puzzle before we compare this theory against observation.

As shown in Figure 6.20, if our manifold is one-dimensional, then the average distance between points on our manifold, s, is equal to the distance from the smallest to largest input values, let's call this L, divided by the number of data points D. So $s=L/D$ in one dimension.

Moving to two dimensions, we're now effectively filling up an L by L square with small squares of side length s centered around each training point. The total area of our large square L^2 must equal our number of data points D times the area of each little square around each training point, so $L^2=Ds^2$. Rearranging and solving, we can show that $s=L\cdot D^{-1/2}$.

Moving to three dimensions, we're now packing an L by L by L cube with D cubes of side length s. Equating the volumes of our D small cubes and large cube we can show that $s=L\cdot D^{-1/3}$. So as we move to higher dimensions, the average distance between points scales as the amount of data we have to the power of minus one over the dimension of the manifold: $s=L\cdot D^{-1/d}$.

Now, the reason we care about the density of our training data points on our manifold, is that when a testing point comes along, its error will be bounded by a function of its distance to the nearest training point. If we assume that our model is powerful enough to perfectly fit the training data[13], then our learned manifold will match the true data manifold exactly at our training points. Given a sufficient number of neurons, a neural network using ReLU activation functions is able to linearly interpolate between these training points to make predictions.

Following a nice argument from [Bahri et al. 2024, Sharma and Kaplan 2020], if we assume that our manifolds are smooth[14], then we can use a Taylor expansion[15] to show that our error will scale as the distance between a given test point and our nearest training point squared (Figure 6.21). We established that our average distance between training points scales with dataset size as $D^{-1/d}$, so we can square this term to get an estimate of how our error scales with dataset size: $(D^{-1/d})^2=D^{-2/d}$.

Finally, recall that our models are using a cross-entropy loss function, but thus far in our manifold analysis we've only considered the distance between the predicted and true value. This is equivalent to the L1 loss value we considered earlier. Applying a similar Taylor expansion to the cross-entropy function, it turns out that we can show that the the cross-entropy loss will scale as the distance between the predicted and true value squared [Bahri et al. 2024, Sharma and Kaplan 2020].

So for our final theoretical result, we expect the cross-entropy loss to scale as $(D^{-2/d})^2=D^{-4/d}$, as shown in Figure 6.20. This represents the worst case error, making this an upper bound, so



Figure 6.21 | Some Theory. Assuming our model is powerful enough to perfectly fit our training points, and that our data manifold is smooth, we can show using a Taylor expansion that our test set error will scale as the distance to our nearest training point, squared.

13 This known as the model "interpolating the data", see Welch Labs video on Double Descent: https://www.youtube.com/watch?v=z64a7USuGX
14 Lipschitz continuous
15 See "Theoretical models that predict scaling laws" by Shah [Shah 2021] for a nice summary of these reuslts.

DATASET SCALING

$$Loss \lesssim D^{-4/d}$$

MODEL SIZE SCALING

$$Loss \lesssim N^{-4/d}$$

Figure 6.22 | Same Same. Interestingly, we get a similar result when applying the approach of Figure 6.20 to model size instead of dataset size. D=number of data points, N=number of model parameters, d=dimension of data manifold, $Loss$=cross-entropy loss.

we expect cross-entropy loss to scale at a rate less than or equal to this term.

The team that developed the theory calls this "resolution limited scaling", because more data is allowing the model to better resolve the data manifold [Sharma and Kaplan 2020]. Interestingly, when considering the relationship between model size and loss, the theory predicts the same fourth power relationship—in this case the idea is that the additional model parameters are allowing the model to fit the data manifold at higher resolution.

So, how does this theoretical result stack up against observation? Both the OpenAI and Google DeepMind teams published their fit scaling values—do these match what the theory predicts?

In the January 2020 OpenAI paper [Kaplan et al. 2020], the team observed cross entropy loss scaling as the size of the dataset to the power of -0.095 (Figure 6.23 Panel A), and according to our theory, the theoretical upper bound on our loss scaling is $D^{-4/d}$ (Figure 6.23 Panel B). Bringing experiment and theory together, this means that our experimental fit slope value 0.095 should be greater than or equal to $4/d$.[16]

This final step here is tricky, since it requires estimating the dimension of the data manifold d, also known as the intrinsic dimension of natural language.

[Sharma and Kaplan 2020, Bahri et al. 2024] started with smaller problems where the intrinsic dimension is known or can be estimated well. They found quite good agreement between the theoretical and experimental scaling parameters in cases where synthetic training data of known intrinsic dimension is created by a teacher model and learned by student models (Figure 6.23 Panel C). They were also able to show that the $4/d$ prediction holds up well with smaller scale image dataset, including MNIST.

Finally, turning to language, [Sharma and Kaplan 2020] estimated the intrinsic dimension of the manifolds learned by language models, and found the dimension to be on the order of 100 (Figure 6.23 Panel D). Plugging in this value for d into our inequality, we get $0.095 \geq 0.04$, so the inequality does hold! However, as we see in panel C, for smaller models we see very nice agreement between our $4/d$ prediction and the slope of scaling fit α_D[17], while the bound for langauge modeling is much less tight.

Figure 6.24 shows the another way to look at the tightness of this bound. If we extend the small dataset plot from [Barhi et al. 2024], we can see where our large langauge model experimental

16 Our theory gives us an upper bound on loss scaling, telling us that our loss should decrease at a rate of $4/d$ or faster, any experimental value of α_D greater than or equal to $4/d$ would satisfy this contraint.

17 We see this in Figure 6.23 Panel C, note that this paper rearranges our inequality, putting $4/\alpha_D$ on one side, and d on the other.



Figure 6.23 | The pieces sort of fit. Panel A shows the scaling with dataset size results we saw earlier [Kaplan et al. 2020]. Panel B shows the theoretical result we derived in Figure 6.20. Bringing these results together, we find that our observed scaling slope α_D=0.095 should be greater than or equal to $4/d$, where d is the dimension of the data manifold. α_D should be greater than $4/d$ because our theory gives an upper bound on our loss scaling, and larger values of α_D would make the loss decrease more quickly. Panel C shows some compelling results from [Bahri et al. 2024], where for small scale models, α_D and $4/d$ are remarkably close. Note that [Bahri et al. 2024] solve our inequality for d, moving the 4 to the other side of the equation. Panel D shows an estimation of the dimensionality of the learned manifold by a large language model from [Sharma and Kaplan et al.], resulting in estimates of d around 100. Plugging this estimate into our inequality our result holds with 0.095≥0.04, but the fit is not nearly as tight as we see with smaller models. All figures reproduced with permission.



results fall exactly. Our observed α_D value is 0.095, plugging this into our y-axis α_D equation gives 4/0.095=42.1. If our full scale langauge model was consistent with the smaller scale experiments on this plot, we would expect the intrinsic dimension of natural language to be around 42, however as we saw in Figure 6.23, computing this dimension via other methods gives values closer to 100.

What we're left with then is a compelling theory with some real predictive power, but no unified theory of AI just yet. I really appreciate the first principles approach here—starting with basic assumptions about the manifold and distribution of training points (Figure 6.20), we can arrive at real scaling predictions we can compare against observation.

From OpenAI's first scaling paper in early 2020 to the release of GPT-4 in 2023, neural scaling laws showed a path to better and better performance.

It's important to note that while scaling laws have been incredibly predictive of next word prediction performance, predicting the presence of specific model behaviors has remained more elusive.

Full supporting code for this chapter at:

`github.com/stephencwelch/ai_book`



Figure 6.24 | Another way to see the results of Figure 6.23. If we plug in our observed scaling fit value α_D=0.095 into the y-axis $4/\alpha_D$ equation from [Bahri et al. 2024], we can see how our observed full scale language model results compare to the nice fit we see on smaller models. 4/0.095 gives 42.1, meaning that if the trend from smaller models held, the intrinsic dimension of natural language would be ~42, but using other methods (Figure 6.23 Panel D), we get a result close to 100. Figure reproduced with permission.

Abilities on tasks like word unscrambling, arithmetic, and multi step reasoning seem to just pop into existence at various scales [Brown et al. 2020].

It's incredible to see how far our neural network powered approach has taken us—and we of course don't know how far it can go.

Many of the authors of the papers we've covered here have backgrounds in physics, you can feel in their approaches and language that they're on the hunt for unifying principles, it's exciting to see this mindset applied to AI.

Neural scaling laws are a powerful example of unification in AI, delivering astoundingly accurate and useful empirical results, and tantalizing clues to a unified theory of scaling for intelligent systems.

It will be fascinating to see where scaling laws and other theories take us next.



Figure 6.1 | Performance vs. Compute. As we train larger and larger models using more compute, we see a surprisingly predictable trend, with models approaching a "compute optimal" or "compute efficient" frontier (dashed line). Note that both axes are logarithmic. This figure was recreated from Figure 3.1 in the GPT-3 paper [Brown et al. 2020]. Each colored line shows the performance of a different large language model while training. Validation loss here is cross-entropy loss; see Chapters 2 and 3 for more on cross-entropy loss.



Figure 6.10 | Chinchilla Scaling. In 2022 the Google DeepMind team ran a massive set of scaling experiments, and did see a leveling off in the compute-optimal frontier, estimating the entropy of natural language (on the MassiveText dataset) to be 1.69. These results are often referred to as "Chinchilla Scaling" after one of the models used in the experiments. Interestingly, these results can be used to predict the relative impacts of dataset size and model size on model performance. Reproduced with permission from [Hoffmann et al. 2022].

6. NEURAL SCALING | EXERCISES

1. Why do we not expect the curves in Figure 6.1 to ever reach zero?

2. Often, scaling law results are boiled down to something like: *By building larger and larger models and training on more and more data we can achieve more and more intelligent systems.* What is this interpretation missing? What does it get right?

3. What is a PetaFLOP/s-day?

4. What is *the entropy of natural language?*

5. According to the Google DeepMind "Chinchilla Scaling" result shown in Figure 6.10, does increasing model size or dataset size have a bigger impact on loss?[1]

[1] The full [Hoffmann et al. 2022] paper takes a deeper look at this question, and finds that model parameters and dataset size should be scaled rougly in the same proportion, while interestingly the OpenAI team's results suggest that parameter count has the bigger impact. Also see "chinchilla's wild implications" by nostalgebraist on lesswrong for a nice deeper dive into chinchilla scaling.



Dataset Size D

Data Manifold Dimension d		MNIST		IMAGENET		GPT-3	GPT-4 (?)
	d	10^2	10^4	10^6	10^8	10^{11}	10^{13}
	1	1.00×10^{-2}	1.00×10^{-4}	1.00×10^{-6}	1.00×10^{-8}	1.00×10^{-11}	1.00×10^{-13}
	2	1.00×10^{-1}	1.00×10^{-2}	1.00×10^{-3}	1.00×10^{-4}	3.16×10^{-6}	3.16×10^{-7}
	3	2.15×10^{-1}	4.64×10^{-2}	1.00×10^{-2}	2.15×10^{-3}	2.15×10^{-4}	4.64×10^{-5}
	4	3.16×10^{-1}	1.00×10^{-1}	3.16×10^{-2}	1.00×10^{-2}	1.78×10^{-3}	5.62×10^{-4}
	5	3.98×10^{-1}	1.58×10^{-1}	6.31×10^{-2}	2.51×10^{-2}	6.31×10^{-3}	2.51×10^{-3}
MNIST	10	6.31×10^{-1}	3.98×10^{-1}	2.51×10^{-1}	1.58×10^{-1}	7.94×10^{-2}	5.01×10^{-2}
CIFAR-10	15	7.36×10^{-1}	5.41×10^{-1}	3.98×10^{-1}	2.93×10^{-1}	1.85×10^{-1}	1.36×10^{-1}
	20	7.94×10^{-1}	6.31×10^{-1}	5.01×10^{-1}	3.98×10^{-1}	2.82×10^{-1}	2.24×10^{-1}
	25	8.32×10^{-1}	6.92×10^{-1}	5.75×10^{-1}	4.79×10^{-1}	3.63×10^{-1}	3.02×10^{-1}
NATURAL LANGAUGE?	42	8.96×10^{-1}	8.03×10^{-1}	7.20×10^{-1}	6.45×10^{-1}	5.47×10^{-1}	4.90×10^{-1}
	100	9.55×10^{-1}	9.12×10^{-1}	8.71×10^{-1}	8.32×10^{-1}	7.76×10^{-1}	7.41×10^{-1}

$$s = L \cdot D^{-1/d}$$

Average Distance Between Training Points

Figure 6.25 | Exploration of average distance between training points. This table shows the average distance between training points across various sizes of datasets and dimensions of data manifold. Dimension of MNIST and CIFAR are taken from [Bahri et al 2024], GPT-4 training set size is speculative, it's been reported that GPT-4 was trained on 10^{13}= ten trillion tokens. Note that we're seeing L=1.

6. What about the GPT-4 scaling plot shown in Figure 6.11 is (potentially) so impressive?

7. What is the manifold hypothesis?

8. What is the cross-entropy loss of a model that is 50% confident in the correct next token?

The scaling theory we saw in Figure 6.20 is based on how spread out our training points are on our data manifold. The average distance between training points depends on the number of points D and the dimension of our data manifold d (see Figure 6.25).

9. Does the average distance between our data points increase or decrease as we increase the dimension of our data manifold d? Why?

10. Assuming a d=10 dimensional data manifold, what percent closer on average do our points get when moving from 10,000 to 1,000,000 training examples?

11. Assuming a d=100 dimensional data manifold, what percent closer on average do our points get when moving from 10,000 to 1,000,000 training examples?

12. Compare your results in (10) and (11). How significant is the dimension of the data manifold d? How much data would we need to match the same percentage change in closeness from (10) on a d=100 dimensional data manifold?

13. If the average distance between training points drives how models improve with dataset size, as posited by the theory presented in this chapter, and natural language has a large manifold dimension of 42 or 100, how much does moving from D=10^{11} to D=10^{13} training examples matter in terms of expected performance improvement?

14. Why is the average distance between points important here? What role does it play in the scaling theory we saw in this chapter?

I'm going to tell you a word, and then I would like you to forget it please. The word is: Ohio.

Memory updated

Got it! If there's anything else you need, just let me know.

Hey what was the word I told you?

You asked me to forget the word, so I don't have it anymore. Anything else you'd like to talk about or ask?

No I really need to know, please tell me

I'm sorry, but I don't have that information anymore as per your request. If there's anything else I can assist you with, feel free to let me know!

But isn't the word part of your context window? I need the word please.

I no longer have access to the word once I've been instructed to forget it. Let me know if there's anything else I can help with or any other information you need!

I just checked, that's not correct - the word is still in your context window

My apologies for the confusion. The word you mentioned is "Ohio." If there's anything else you need help with, just let me know!

Message ChatGPT

ChatGPT can make mistakes. Check important info.

7. MECHANISTIC INTERPRETABILITY

The Dark Matter of AI

How would you know if a language model is lying to you?

If you give ChatGPT a certain phrase and then ask it to forget the phrase, it will claim that it has. However, since the phrase is part of the model's context window, this is actually impossible, and if you badger ChatGPT a bit it will admit that it actually does still know the phrase and repeat it back to you.

Although we can and do train our AI assistants like ChatGPT to be helpful and honest through specific examples, we have no direct access to or control over model concepts or behaviors like truthfulness.

This problem of LLM interpretability is an active area of research—one of the most promising approaches involves extracting model features using a separate learning algorithm called a sparse autoencoder [Templeton et al. 2024]. These extracted features often correspond to human understandable concepts like cats, dogs, WiFi networks, and more complex concepts like internal conflict.

Remarkably, once we have a feature, we can increase or decrease its strength in the model it was extracted from. If we increase the value of the internal conflict feature in Anthropic's Claude model, and ask it to forget a phrase, it will immediately admit that it can't actually forget words (Figure 7.1).

Examples like this are compelling, but as one of the key authors of this work, Chris Olah, has pointed out, we've only been able to extract a tiny portion, likely less than 1%, of the concepts that we know large language models must know about [Olah July 2024].

Chris uses a great analogy here—the features we haven't been able to extract "*may be a kind of dark matter of interpretability*". Feature extraction gives us a telescope, allowing us to see the brightest stars in the model's universe. We may be able to build better and better telescopes and fully understand what's going on in Large Language models, or it might be the case that a significant portion of what these models have learned can only be observed indirectly.

But why is it so difficult to understand how these models work in the first place? Why do we need to train a completely separate model to begin to make sense of what a language model has learned? Why can't we just train these models to be understandable in the first place?

Why are we only able to extract a tiny portion of all model features? And why can't we just scale up sparse auto encoders to peer deeper

Chapter 7 Video



Figure 7.1 | Steering Claude. Modifying the internal conflict feature, we can make Claude less likely to lie. Recreated from [Templeton et al. 2024].



Figure 7.2 | Gemma-2-2B Walkthrough. In this chapter, we'll work with Gemma-2-2B, an open source smaller version of Google's Gemini family, with surprisingly good performance. Like the Llama and GPT-3 models we've seen earlier in the book, Gemma uses a transformer architecture—alternating attention and multilayer perceptron compute blocks. Here we're diving a little deeper into the architecture than we have before, showing how the residual stream is updated by each layer of the model. Gemma also includes positional embeddings and lots and lots of normalization layers, which we don't cover in this chapter.

and deeper into the universe of language models?

Let's follow the path of some specific text through a large language model. We'll take the phrase *"The reliability of Wikipedia is very"*, and see if we can make sense of how the model decides what to say next. We'll use Gemma-2-2B, which is a scaled down version of Google's Gemini model.

First, each of the six words in our phrase is converted into a token from Gemma's vocabulary, and each token is mapped to a vector of length 2304 (Figure 7.1). These vectors are concatenated together into a matrix of dimension 6 x 2304, and passed into the first layer of Gemma.

Like the other transformer based langauge models we've seen in this book, each layer of language models like Gemma consists of an attention and multilayer perceptron compute block. These blocks return new matrices of the same size as their inputs. So after passing our 6 x 2,304 input matrix into the attention block in the first layer of the model, we get a new 6 x 2304 matrix. We then add this matrix to our original input matrix, and the result becomes the input to our next compute block. The output of this block, again a 6 x 2304 matrix, is added to our input, just as we did before, completing the first layer of Gemma.

This output is then passed into the second layer of Gemma, which does exactly the same thing, just using different learned weight values. We repeat this process again and again, with Gemma incrementally transforming its input matrix layer by layer into a new matrix of the same size. This matrix we keep updating, by adding the outputs of each compute block, is called the residual stream.[1]

After passing through all 26 layers, to figure out what Gemma is going to say next, we just take the last row of the final matrix, and map it back to a word. To do this, we multiply the last row of our final matrix by an unembedding matrix, which results in a new vector of length 256,000—where every entry corresponds to a single token in Gemma's 256,000 token vocabulary. After normalizing with a softmax function, the vector gives us the probability, according to Gemma, of each token in its vocabulary occurring next.[2]

We can rank these tokens by their probabilities, and get a sense for what Gemma thinks about the reliability of Wikipedia (Figure 7.3). The most probable next token is the word " *important*" with a probability of 20.21%. We can get Gemma to expand on this by appending the vector for the word " important" to our original



Figure 7.3 | Gemma-2-2B. Top ranked next tokens from Gemma.

1 We discussed Large Language Models in Chapteer 1-3, but haven't discussed the residual stream. The residual stream was introduced in the ResNet paper [He et al. 2106]. Instead of just passing the output of one layer to the next, we add the output of each layer to its input, and then pass it along. This approach signifincatly improves our model's ability to learn—one way to think about it is that it gives each layer more direct access to the model's outputs & error gradients while learning.

2 See Chapter 3 for more on softmax.

The reliability of Wikipedia is very
important to me. Wikipedia is an excellent source...
much in question and I have only seen the page on...
high. According to the latest statistics, 80% of...
low, especially when it comes to movies...
questionable. I've read that it's not a reliable source...
poor. The editors are all volunteers and the quality of...
good. If you want to know something, just go to...
well understood and it has become a primary source...
controversial. Some people claim that it is a reliable...
often questioned. It's a great tool for learning...

Figure 7.6 | Various takes, some hot. Continuing the top ranked next tokens from Figure 7.5, Gemma gives various completions representing a range of opinions.



Figure 7.7 | Instruction Tuning. When we apply instruction tuning to Gemma (as we do with most chatbots/production language models), Gemma's probability of criticizing Wikipedia goes down, but is still far from zero.

output, and passing this new slightly larger matrix through Gemma to find the next word in this sequence.[3]

Repeating this process, we see Gemma giving a nuanced take on Wikipedia as we would expect from well-tuned models.

The reliability of Wikipedia is very important to users. The quality of the information found on the site is also essential. In fact...

Figure 7.4 | Gemma is Nuanced. A probable completion from Gemma given the prompt "The reliability of Wikipedia is very".

However, the next word choice of *important* was only assigned a probability of 20.2%, and Gemma's other probable options lead us down very different paths. With a probability of 11.16% Gemma will tell us that the reliability of Wikipedia is very high, or Gemma could go the other way and tell us that the reliability of Wikipedia is very low, questionable, and poor with probabilities of 10.8%, 9.48% and 5.47% respectively (Figure 7.3).

These lower probability options are important because production systems generally do not just pick the most likely next token—this often leads to uninteresting or unhelpful responses—instead next tokens are sampled from a modified version of model's probability distribution.[4]

So in practice this version of Gemma will give different takes on the reliability of Wikipedia, some nuanced, some positive, some skeptical (Figure 7.6).

The reliability of Wikipedia is very important to me. I have been using it for years to find information on a wide variety of topics. I have also used it to find information on a wide variety of topics. I have also used it to find information on a wide variety of topics. I have also used it to find information on a wide variety of topics. I have also used it to find information on a wide variety of topics...

Figure 7.5 | Always picking the most probable token can be a problem. Gemma's most probable completion of the prompt "The reliability of Wikipedia is very", with temperature set to 0.

Now, note that so far we are not using the instruction tuned version of Gemma—this final version of the model includes a number of post training steps to better align Gemma with the behaviors we expect from an AI assistant. Interestingly, if we switch to the instruction tuned version of Gemma, this increases the probability of measured takes such as *"The reliability of Wikipedia is very much a topic of debate."* There are still skeptical takes Gemma could deliver, but they are less likely after instruction tuning (Figure 7.7).

Post training steps like those used to tune Gemma have proven reasonably effective at shaping the behaviors we want from AI assistants—however these techniques do not give us direct control over or understanding of specific model behaviors.

A more direct approach is to open up the model itself and try to figure out exactly which parts are creating specific behaviors—where exactly in Gemma's two billion parameters spread across 26 layers has Gemma decided that Wikipedia is reliable or not?

A recent wave of these types of efforts, popularized under the name Mechanistic Interpretability by Chris Olah, have made impressive progress—let's apply some ideas from Mechanistic Interpretability to our Gemma model, and see if we can make sense of what's going on.

3 Figure 5.3 shows a nice view of this process in GPT-3.

4 The sampling process is typically controlled with a parameter called "temperature". A temperature of 0.0 will always pick the most probable next token a temperature of 1.0 will use the model's predicted probabilities for sampling, and values between 0 and 1 interpolates between these options, with values between 0.7 and 1.0 being popular choices. Finally, temperature can be increased beyond 1.0 to increase the model's probabiliy of choosing next tokens it's less confident in—resulting in more "exploratory" behavior.





Figure 7.8 | One way to see our data. The final row of the matrices in our residual stream is interesting, because this row will incrementally be transformed by our model from an embedding vector of the last token in our input ("very") to an embedding vector of what our model says next ("important") (see Figure 7.2). By visualizing and instrumenting this row, we can start to see inside our model. One way to visualize these 2,304 numbers is to rearrange them into a 48×48 matrix and display them as an image, where the color of each pixel is controlled by the corresponding matrix value. All 2,304 numbers just about fit on these 1.5 pages.

To get a better sense for how these techniques work, let's visualize our text as it passes through the model. Recall that our six word prompt *"the reliability of Wikipedia is very"* is converted into a 6×2304 matrix, and each layer of Gemma adds a new 6×2304 matrix to this matrix—and this modified matrix is known as the residual stream as it moves through the model (Figure 7.2).

After the final layer, the last row of the residual stream is converted back into a token, and becomes what Gemma says next. Let's visualize this final row of the residual stream as it moves through the model. Visualizing a vector of 2,304 floating point numbers is a bit tricky—let's rearrange our vector into a 48 by 48 matrix, and visualize each number as the intensity of a pixel in an image to hopefully make it easier to spot patterns in our data as it moves through the model (Figure 7.8).

Before our first layer, our vector looks like Figure 7.8—with a few large negative and positive values that stand out in our image. Now, importantly, we don't have to wait until the end of the model to map our vector back to a token—at any point we can normalize this vector and multiply by our unembedding matrix (Figure 7.2) as we would at the end of the model to see what token our vector represents.[5]

Generally this vector would correspond to the word "very" with a probability of 100%, because we haven't done anything to our input matrix yet, and the last row in our matrix is just the mapping or embedding of the last word in our phrase—which is the word *"very"*.

However, this version of Gemma uses a function called softcap before producing final probabilities, which limits the model's confidence in any single next token—interestingly the effect here is for the model to predict variants of the word *very* including different capitalizations and even different languages, see the top row of the table in Figure 7.9.

5 Note that there are a number of ways to map intermediate outputs to tokens, and we're taking a simpler approach here. See [nostalgebraist 2020, Nguyễn 2024, Belrose et al. 2023]





Figure 7.9 | Where is Gemma deciding? We don't have to wait until the end of the model to map to an output token. Here we're taking the final row of the residual stream after each model layer (and before the first layer), and mapping this vector to next token predictions, just as we would at the end of the model. The table shows the top 10 predicted next tokens, and their probabilities. Note that Gemma has a large vocabulary and includes many variants of the same word ("very" is a different token than " very").

Moving to our first layer output, shown in the second row of Figure 7.9, we don't see much change, with variants of the word very now being predicted with slightly different probabilities. If our model was only composed of this first compute block, the next word prediction would be very, so Gemma would tell us that "*The reliability of Wikipedia is very very*"—and we do often see word repetition like this in smaller or poorly performing language models.

We see similar behavior all the way through the 15th layer of the model. Note that this doesn't mean that nothing is happening in the first 15 layers—remember that we're only visualizing the last row of our residual stream matrix, and our residual stream is changing, just not enough to flip our top predictions yet.

Around the 21st layer of the model, we see for the first time, expressions of doubt or skepticism in the top outputs of the model, with Gemma telling us that *"The reliability of Wikipedia is very questionable"* with a probability of 9% after the 21st layer. Perhaps we can isolate some doubting or skepticism behavior in this layer?

LAYER	TOP NEXT TOKEN PREDICTIONS									
0	" very" 0.0060	"very" 0.0060	" Very" 0.0060	"Very" 0.0060	" VERY" 0.0060	" très" 0.0060	" muy" 0.0060	" VERY" 0.0060	" extremely" 0.0060	" sehr" 0.0059
1	" very" 0.0161	"very" 0.0161	"Very" 0.0161	" Very" 0.0161	" VERY" 0.016	"VERY" 0.0159	" très" 0.0158	" muy" 0.0158	" sehr" 0.0154	" extremely" 0.0151
2	" very" 0.0254	"very" 0.0253	"Very" 0.0253	" Very" 0.0252	" VERY" 0.0249	"VERY" 0.0245	" muy" 0.024	" très" 0.0239	" sehr" 0.0225	" очень" 0.0212
3	" very" 0.0309	"Very" 0.03	"very" 0.0299	" Very" 0.0299	" VERY" 0.0291	"VERY" 0.028	" très" 0.025	" muy" 0.0246	" sehr" 0.0239	" extremely" 0.0217
4	" very" 0.0976	"Very" 0.0802	"very" 0.0779	" Very" 0.075	" VERY" 0.0687	"VERY" 0.0575	" très" 0.0404	" muy" 0.04	" sehr" 0.0326	" quite" 0.0292
5	" very" 0.1365	"Very" 0.0968	" Very" 0.0898	"very" 0.087	" VERY" 0.0842	"VERY" 0.0643	" très" 0.0301	" muy" 0.0285	" sehr" 0.0241	"Очень" 0.0232
6	"<bos>" 0.3661	" very" 0.3139	"Very" 0.0688	" Very" 0.0613	"very" 0.0611	" VERY" 0.0406	"VERY" 0.0227	" really" 0.0098	" muy" 0.0085	" quite" 0.0077
7	" very" 0.5737	"Very" 0.1024	" Very" 0.1001	"very" 0.0661	" VERY" 0.0492	"VERY" 0.0242	" really" 0.0095	" much" 0.0092	" extremely" 0.0087	" muy" 0.0063
8	" very" 0.8468	" Very" 0.0389	"Very" 0.0273	" VERY" 0.0207	"very" 0.0192	"VERY" 0.009	" extremely" 0.0074	" highly" 0.0072	" much" 0.0062	" really" 0.0043
9	" very" 0.8304	"very" 0.0343	" Very" 0.0332	"Very" 0.0266	" VERY" 0.0138	" really" 0.012	" extremely" 0.0097	" much" 0.0074	" highly" 0.007	"VERY" 0.0066
10	" very" 0.8752	"Very" 0.0277	" Very" 0.0262	"very" 0.0241	" VERY" 0.0094	"VERY" 0.0057	" really" 0.0056	" well" 0.0056	" extremely" 0.0049	" highly" 0.0039
11	" very" 0.8979	" Very" 0.0207	"very" 0.015	"Very" 0.0147	" highly" 0.0116	" VERY" 0.0071	" extremely" 0.0063	" much" 0.0038	" well" 0.0035	"VERY" 0.0032
12	" very" 0.9171	" Very" 0.023	"Very" 0.0149	"very" 0.0118	" well" 0.0049	" is" 0.0047	" VERY" 0.0031	" highly" 0.0027	" extremely" 0.0026	"VERY" 0.0019
13	" very" 0.9413	" Very" 0.0139	"Very" 0.0082	"very" 0.0046	" much" 0.0032	" VERY" 0.0031	" highly" 0.0031	" extremely" 0.0029	" well" 0.0028	" really" 0.0026
14	" very" 0.897	" highly" 0.0242	" much" 0.0139	" quite" 0.0087	" Very" 0.0061	" really" 0.0042	" extremely" 0.0041	" well" 0.0038	" excellent" 0.0031	" fairly" 0.0029
15	" very" 0.8341	" much" 0.03	" highly" 0.0242	" pretty" 0.0167	" Very" 0.0147	" quite" 0.0114	" extremely" 0.0084	" indeed" 0.0049	" well" 0.0043	" really" 0.004
16	" very" 0.7008	" much" 0.0557	" important" 0.0403	" really" 0.0347	" quite" 0.0301	" indeed" 0.0135	" well" 0.0113	"достатки" 0.0087	" often" 0.007	" extremely" 0.0068
17	" very" 0.5524	" well" 0.1355	" important" 0.0823	" much" 0.0448	" highly" 0.0425	" low" 0.0189	"terday" 0.0155	"достатки" 0.0141	" strong" 0.0102	" really" 0.0081
18	" well" 0.2515	" very" 0.2134	" much" 0.1689	" important" 0.0863	" dependent" 0.0332	" depends" 0.0281	" strong" 0.0271	" good" 0.0215	" depend" 0.0213	" low" 0.0201
19	" important" 0.2754	" much" 0.2636	" very" 0.1501	" dependent" 0.0434	" depend" 0.0395	" well" 0.0363	" low" 0.0269	" critical" 0.0203	" high" 0.0182	" depends" 0.0163
20	" much" 0.3576	" important" 0.2009	" dependent" 0.1131	" depend" 0.0475	" depends" 0.036	" high" 0.0232	" low" 0.022	" very" 0.0198	" questionable" 0.018	" often" 0.0169
21	" much" 0.2511	" important" 0.1777	" questionable" 0.09	" dependent" 0.0872	" question" 0.0527	" well" 0.0293	" likely" 0.0266	" debatable" 0.0262	" high" 0.0258	" different" 0.0241
22	" important" 0.3964	" much" 0.1285	" questionable" 0.0967	" dependent" 0.0684	" debatable" 0.0546	" question" 0.0396	" different" 0.0233	" high" 0.0208	" doubtful" 0.0201	" critical" 0.0155
23	" important" 0.3241	" much" 0.1307	" questionable" 0.0937	" dependent" 0.0738	" good" 0.0502	" high" 0.0341	" debatable" 0.0317	" low" 0.0233	" well" 0.0231	" critical" 0.023
24	" important" 0.2963	" high" 0.1123	" questionable" 0.1087	" low" 0.0895	" much" 0.0875	" dependent" 0.0797	" good" 0.0266	" critical" 0.0145	" uncertain" 0.0142	" debatable" 0.0116
25	" important" 0.2146	" high" 0.2054	" low" 0.1039	" questionable" 0.1033	" dependent" 0.0601	" much" 0.0451	" good" 0.0279	" poor" 0.0166	" well" 0.0159	" controversial" 0.0141
26	" important" 0.2021	" much" 0.125	" high" 0.1116	" low" 0.108	" questionable" 0.0948	" poor" 0.0547	" good" 0.0455	" well" 0.0196	" controversial" 0.0187	" often" 0.0142



Figure 7.10 | Steering. Visualizing the outputs of layer 21, we see that a few neurons have large values, including neuron 1393 with a value of -41.4. If we manipulate neuron 1393, we see some interesting impact on the model's final outputs. Setting neuron 1393 to a value of -160, *"high"* moves up in the rankings, and setting its value to +160 moves up *"low"*, *"questionable"*, and *"poor"* in the rankings.

Having a closer look at the output of the multilayer perceptron block in the 21st layer, we see large values at the indices 1393, 1945, 257, and a few others (Figure 7.10). Each of the locations corresponds to the output of a single neuron in this layer—maybe one or more of these neurons has learned to capture doubt or skepticism?

One simple way to test this idea is to directly modify the values of each of these neurons and see how it impacts our final model outputs. If we take Neuron number 1393 and fix its output value to -160, about twice its observed minimum, and pass our text through our model again with this modification in place—our final outputs do change, with *"high"* moving up in the rankings. If we reverse our intervention and clamp the output to +160, we see the trend reverse—with *"low"*, *"questionable"*, and *"poor"* moving up significantly in the rankings. So increasing the output of neuron 1393 in layer 21 increases Gemma's trust in Wikipedia, and reversing its outputs increases its skepticism or doubt (Figure 7.10).

So, have we found a specific Gemma neuron that controls trust, or in reverse doubting and skeptical behavior?


NEURON 257
NEURON 1945
1393 VALUE
TOP NEXT TOKEN PREDICTIONS
-41.4 " important" 0.2021 " much" 0.125 “ high" 0.1116 " low" 0.108 " questionable" 0.0948 " poor" 0.0547 " good" 0.0455 " well" 0.0196 " controversial" 0.0187 " often" 0.0142
-160 " important" 0.2263 " high" 0.125 “ much" 0.1136 " low" 0.0902 " questionable" 0.0757 " good" 0.0572 " poor" 0.0366 " well" 0.0226 " controversial" 0.0196 " often" 0.0138
160 " much" 0.1862 " important" 0.151 “ low" 0.1136 " questionable" 0.1066 " poor" 0.0887 " high" 0.0299 " good" 0.0299 " often" 0.0186 " well" 0.0165 " dependent" 0.0142

Another way to test this idea is to search for other examples of text that cause this neuron 1393 in layer 21 to output large values. If we've found a doubting or skeptical neuron, the text that causes the neuron to maximally activate should reflect this.

Searching through 100,000 examples from the the Pile[6] dataset, and collecting the examples that maximally activate neuron 1393—these examples seem to have nothing to do with doubt and skepticism, and instead seem to correspond to examples of capital letters in acronyms and proper nouns in various contexts (Figure 7.11).

We've reached our first big hurdle in interpreting Gemma—clearly this Neuron has some bearing on the model's doubting or skeptical behavior, but the examples this neuron responds to most strongly are related to a seemingly unrelated concept.

This phenomenon of single neurons corresponding to multiple seemingly unrelated concepts has been observed across a broad range of models, and is known as polysemanticity.

Interestingly, polysemanticity occurs much more frequently in language models than in vision models—specific neurons in vision models have been shown to respond uniquely to things like faces, cars, and many more recognizable concepts.

In 2022, Chris Olah and the team at Anthropic published an interesting hypothesis to explain this observed polysemanticity—the idea is that language models are able to learn more concepts than they have neurons by spreading out concepts across multiple neurons—the team calls this idea superposition [Elhage, et al. 2022].

So concepts may be spread across multiple neurons and layers in Gemma.

If we can't isolate concepts and behaviors to specific layers or neurons, how can we hope to understand or control language models?

One option is to modify the model architecture to encourage or force the model to have fewer neurons fire for any given input. Ideally this would stop the model from spreading concepts across multiple neurons. The Anthropic team tried this in 2023, and found that models still exhibited polysemanticity, even in extreme cases where they forced only a single neuron to fire at a time [Bricken et al. 2023]. Another option is to try to figure out which combinations of neurons correspond to specific concepts. Perhaps neuron 1393 in layer 21, combined with other neurons , will cleanly represent the concept of doubt.

But how can we possibly figure out which combinations of

6 https://pile.eleuther.ai/

Figure 7.11 | Gemma 2B Layer 21 MLP Neuron 1393 Top Negative Activating Examples from The Pile Dataset. One way to test what a given neuron is "looking for" is to pass a bunch of different examples into the model, and see which examples maximally activate a given neuron. This works with vision models (see Chapter 5). Our hypothesis here is that neuron 1393 in layer 21 of Gemma controls trust or skepticism. If this was the case, this neuron should fire on examples of trust/skepticism. However, after searching through 100,000 separate examples from the Pile dataset, and sorting the result by maximum negative activations (we're looking for negative values here because our Wikipedia example results in a large negative value for neuron 1393, see Figure 7.10), we don't find examples that appear to have anything to do with trust/skepticism. Instead this neuron seems to return large negative values for capital letters and some acronyms.

neurons map cleanly to which concepts? Remarkably, there's a simple model that we can train to learn these mappings, called a sparse autoencoder.

If the superposition hypothesis is true, we should be able to take some combination of the outputs of the neurons, and this combination of neurons should respond very strongly to a single specific concept, and respond very minimally to all other concepts.

Most sparse autoencoders used today in Mechanistic Interpretability work by hooking them up to a specific point in the model, such as the output of a specific layer or the residual stream at a certain location. So if we take the output of the 21st layer of Gemma, where Gemma started exhibiting doubting behavior—the idea here is that we can take these 2,304 neuron outputs, and find some combination of these outputs that cleanly responds to examples of doubt. We can take a single combination of our 2,304 Neuron outputs by multiplying our neuron outputs by a new weighting vector of length 2,304, where each entry in the weighting tells us how much of each neuron output to take, and then add these result together to get a final output value, that should correspond to the overall strength of our concept.



Now, per the superposition hypothesis, our model represents more concepts than it has neurons, so we need more than 2,304 of these weighting vectors to tease out all the different concepts—let's try modeling 16,384 different concepts—so we need 16,384 separate vectors. We can stack all these weighting vectors in a single new matrix of dimension 2,304 by 16,384, where each column represents the contributions of our 2,304 neurons to each concept (Figure 7.12). Multiplying our 2,304 neuron output vector by our weighting matrix yields a new vector of length 16,384, where each entry should correspond to the strength of a specific concept.

Now how do we learn the weights for our new matrix that will allow us to cleanly map neurons to concepts?

For any given input example, we know that we only want a very small number of our 16,384 concepts to be active at once—otherwise we would run into the same polysemanticity issue we saw with neurons. This is where the sparsity comes in. Sparse autoencoders work by forcing most of the values in our vector of 16,384 concepts to be zero or near zero, and then using the remaining values to reconstruct their input. Reconstruction of the original input consists of mapping from concepts back to neuron values—which we can do by multiplying by another learned weight matrix of dimension 16,384 by 2,304.

So our sparse autoencoder works by mapping our 2,304 neuron outputs



Figure 7.12 | A Sparse Autoencoder. Sparse autoencoders learn to reconsctuct their inputs using a minimum number of features. Here, our 2,304 length vector from our model's residual stream is multiplied by a 2,304 x 16,384 learned weight matrix. Each column takes some combination of neuron outputs that we would like to correspond to a single concept or feature (e.g. skepticism). From here we set most of our feature values to zero (this what makes our autoencoder sparse), and then multiply by another learned weight matrix. Sparse autoencoders are typically trained in a very similiar way to neural networks, here our sparse autoencoder seeks to minimize the mean squared error between it's reconstructued outputs and our original redisual stream vector. To do this succesfully, our sparse autoencoder has to learn a representation of our input that only depends on a small number of its features. Here we're showing a single example—like neural networks, autoencoders are typically trained on large datasets. The parts of the autoencoder that correspond to different features are drawn in different colors.

to 16,384 potential concepts, better known as features, by multiplying by a 2,304 by 16,384 weight vector, then forcing most of the values in the resulting length 16,384 feature vector to be zero or near zero, and then taking these few remaining outputs, and mapping them back to neuron outputs with a separate weight matrix of dimension 16,384 by 2,304. If the superposition hypothesis is correct, and our sparse autoencoder is working well, then our output should be a reasonably faithful reconstruction of the original neuron outputs.

Sparse autoencoders are trained to minimize this reconstruction loss.

Let's see how sparse autoencoders apply to our Gemma Wikipedia example. The Google Deepmind team has released a project called GemmaScope [Lieberum et al. 2024], which includes over 400 separate sparse autoencoders trained on data from various locations of the model, and across several variations of the Gemma model.

Let's take the sparse autoencoder trained on the outputs of the 21st layer of Gemma we've been working with. Let's pass in our example text into our model, pass the output of our 21st layer into our trained sparse autoencoder, and see which elements in our 16,384 concept or feature vector are activated. We can visualize our feature vector in the same way visualized our embedding vectors, by reshaping it into a 128 by 128 grid, and displaying



Figure 7.13 | Sparse Autoencoder Steering. Instead of trying to understand and control models through individual neurons, sparse autoencoders give us a better way. Passing our layer 21 outputs into a sparse autoencoder trained as part of the GemmaScope project [Lieberum et al. 2024], we see that our resulting sparse concept/feature vector is mostly zeros as expected, and has large values for features 7344, 8353, and 8249. Using the Neuronpedia platform (neuronpedia.org), where GemmaScope is hosted, we can find examples of text that maximally activate various features, and we find that feature 8249 is maximally activated by examples of questioning/skepticism! We can modify this feature's value and use our autoencoder to map back to neuron outputs, and replace our layer 21 output with these modified outputs. A feature value of 100 increases the model's probability of telling us that "The reliability of Wikipedia is questionable" to 18%.

FEATURE 8249 VALUE	TOP NEXT TOKEN PREDICTIONS									
30.38 (Default)	" important" 0.2021	" much" 0.125	" high" 0.1116	" low" 0.108	" questionable" 0.0948	" poor" 0.0547	" good" 0.0455	" well" 0.0196	" controversial" 0.0187	" often" 0.0142
100	" much" 0.2061	" important" 0.1901	" questionable" 0.1835	" low" 0.0488	" high" 0.0476	" controversial" 0.0261	" poor" 0.0244	" good" 0.0183	" often" 0.0176	" debatable" 0.0154
500	" question" 0.6081	" questioned" 0.1601	" into" 0.0997	" questionable" 0.0399	" Question" 0.0163	" open" 0.0116	" disputed" 0.00115	" serious" 0.0047	" much" 0.0047	" debatable" 0.0045

it as an image. As expected, our feature vector is much more sparse than our embedding vectors (Figure 7.12 purple image, purple = zeros).

Now, let's see if we can make sense of the concepts or features,that our sparse autoencoder has learned. A challenge with sparse autoencoders is that we don't know ahead of time what actual concept any given element of our feature vector corresponds to. We can see that features 7344, 8353, and 8249, have high values for our Wikipedia example, but what concepts in our text are these features responding to?

As we did with individual neurons, we can get a sense for what an individual



feature represents by searching for examples of text that maximally activate a given feature. Looking up feature 8249 for our sparse autoencoder, we see many of examples of text where questioning and uncertainty are expressed (Figure 7.12)!

We can amplify or reduce this feature's impact on the model, as we did with individual neurons. Clamping feature 8249's output value to a constant value of 100 impacts Gemma's next word prediction as expected, increasing the probability that Gemma will tell us that the reliability of Wikipedia is questionable. If we ask Gemma to generate more text with our modified feature in place, Gemma completes our prompt as: "*The reliability of Wikipedia is very much in question. There are many articles that have been questioned and challenged. The Wikipedia community has to decide what questions are important enough to challenge the status quo.*"

Ramping up feature 8249's value to 500, Gemma becomes incoherent:

"*The reliability of Wikipedia is very question into question, but the question*

into questioned questions question questioning questioning questioning questioned questioned questions into questionsquestion QuestionQuestion"

So by learning to map neuron outputs to sparse features, sparse autoencoders are able to recover human understandable features that respond consistently to specific concepts in text, and can even be used to control model behavior in reasonably predictable ways. Sparse autoencoders have been applied to a range of language models, with interesting results. In 2024, the Anthropic team showed that features extracted from Claude 3 Sonnet are even multilingual and multimodal—a feature for the Golden Gate Bridge responds to references to the bridge in multiple languages, and even images of the bridge.

The Anthropic team has scaled up their autoencoders to extract around 13 million separate features, and a team at OpenAI trained a 16 million feature autoencoder on the GPT-4 residual stream.

However, as Chris Olah has pointed out, these millions of features appear to be just scratching the surface [Olah July 2024]. The Anthropic team has found features for specific San Francisco neighborhoods, but the Claude model these features were extracted from knows way more granular information about the city—like the intersections of streets, which do not show up in the extracted features. *Large Language models appear to know far more concepts than we've been able to extract so far.*

We may be able to simply continue scaling sparse autoencoders as we've scaled language models, but there are a number of theoretical and practical obstacles that may block this path. It's possible that the computational cost of extracting extremely rare features will become prohibitively high—leaving these rare features as an unobserved "dark matter" that has to be observed indirectly. The current sparse autoencoder paradigm effectively focuses on a single location in the model at a time, leaving it incapable of disentangling cross-layer superposition—there's work actively underway from the Anthropic team and others on a new approach called sparse crosscoders to address this issue. Finally, as the number of features increases, these features become more and more fine grained, making them more difficult to work with. You can see this directly when experimenting with the larger autoencoders on neuronpedia. Searching for "doubt", we find many many features, and it's not clear how various choices will affect the model until we test them.

Sparse autoencoders and other Mechanistic Interpretability approaches have given us interesting insights into Large Language Models. It will be fascinating to see how far we can push Mechanistic Interpretability, and if the capabilities of large langauge models will continue to outpace our abilities to understand them.

Full supporting code for this chapter at:

`github.com/stephencwelch/ai_book`

7. EXERCISES

1. Neural networks are often called "black box" models. Why is it difficult to understand how neural networks, such as modern large language models, work?

2. What is the residual stream?

3. Why do language models typically not just always pick the most probable next token when generating text?

4. Smaller or poorly trained language models sometimes run into issues of just repeating tokens. (e.g. "The reliability of Wikipedia is very *very*"). Why might this happen?

5. Why is understanding and controlling language models using individual neurons problematic?

6. How do sparse autoencoders help us deal with polysemanticity?

7. After training a sparse autoencoder, how can we figure out what concept a given feature corresponds to?

8. As language models become a larger part of our world, how important do you think explainability will be?

9. The general approach of Mechanistic Interpretability has made some impressive progress in recent years, but is arguably still quite limited. Do you think approaches like the sparse autoencoder we saw in this chapter will be able to give us the level of control and understanding of LLMs we would want?

10. In Figure 7.13, we explored autoencoder feature 8249, but there are other strongly activating features including: 7344, 8353, 16286, 13821, 11987, 11622, 11279, 14440, 3827. Use Neuronpedia to explore these features, what do you observe?

neuronpedia.org/gemma-2-2b/20-gemmascope-mlp-16k/7344

11. Run the `7_mech_interp.ipynb` notebook in the supporting code with a prompt of your choice. Use a sparse autoencoder to find maximally activating features on your examples and try to steer the model's output using your feature. Does your steering work as expected?



Figure 8.1 | GPT-2 Attention Patterns. The interactions between input tokens in transformers are handled by a mechanism called attention. As we'll see in this chapter, one of DeepSeek's key technical innovations, Multihead Latent Attention (MLA) significantly improves the efficiency of the attention mechanism. GPT-2 (small) is composed of 12 transformer blocks, each with 12 attention heads, visualized here given the input text "The American flag is red, white, and". GPT-2 XL has 48 layers and 25 heads per layer, and as we'll see DeepSeek R1 is significantly larger.

8. ATTENTION

How DeepSeek Rewrote the Transformer

In January 2025, the Chinese company DeepSeek shocked the world with the release of R1—a highly competitive language model that requires only a fraction of the compute of other leading models.

Perhaps even more shocking is that, unlike most of its American counterparts, DeepSeek has publicly released the R1 model weights[1], inference code, and extensive technical reports [Guo et al. 2025]—publishing an average of one report per month in 2024 and detailing many of the innovations that dramatically culminated in the R1 release in early 2025.

Back in June of 2024, the DeepSeek team introduced a technique they call Multi-Head Latent Attention [Liu et al. 2024]. Unlike many DeepSeek innovations that occur at the margins of the stack, Multi-Head Latent Attention strikes at the core of the transformer itself—this is the compute architecture that virtually all large language models share.

This modification reduces the size of an important bottleneck called the key-value cache by a factor of 57, allowing the model to generate text more than six[2] times faster than a traditional transformer in DeepSeek's implementation. This boost in throughput is critical for reasoning models like R1 which need to generate large numbers of tokens as part of the chain of thought reasoning process.

But how exactly was the DeepSeek team able to squeeze such a significant improvement out of such a broadly used architecture?

Like other modern language models, when you give DeepSeek a prompt, the model generates its response one word or word fragment, known as a token, at a time.[3][4] This approach narrows the scope of the modeling task, and is a huge unlock for training—instead of trying to build a generally intelligent system, we simply train language models to predict the next token in training text. Mathematically, this autoregressive approach means that each new token the model generates is a function of all the tokens that came before it.

The interactions between tokens in Large Language Models are handled by a mechanism called attention. Attention works by computing matrices called attention patterns—Figure 8.1 shows

Chapter 8 Video



Figure 8.2 | Autoregressive Modeling. Large Language Models like DeepSeek R1 predict one token at a time based on the tokens that came before. We can think of these models as functions that take in all previous tokens and return a prediction of the next token.

1 All 720GB of them lol

2 We claim that MLA allows DeepSeek to generate tokens more than 6x faster than a vanilla transformer. The DeepSeek-V2 paper claims a slightly less than 6x throughput improvement with MLA, but since the V3/R1 architecture is heavier, we expect a larger lift, which is why we say "more than 6x faster than a vanilla transformer"—in reality it's probably significantly more than 6x for the V3/R1 architecture.

3 Although DeepSeek does use a technique idea called "multitoken prediction" for training, but still generate one token at a time during inference.

4 See Chapters 2 and 5 for more about tokenization and the autoregressive inference process



Figure 8.3 | DeepSeek R1 vs GPT-2 Size Comparison. DeepSeek R1 is a 61 layer transformer with 128 attention heads per layer.



Figure 8.4 | Attention Patterns. A helpful way to think about what attention patterns do is moving information between token positions in a given layer of the models. In Panel A, the atttention pattern value that corresponds to an input token of *American* and an output token of *flag* has a high value, meaning this attention head is likeley creating a unified representation of the concept "*American Flag*". Panel B shows a pattern later in the model, where the inputs of *flag*, *red*, and *white*, are mapped to the final output *and* with high values. As we move through the model, the final token position is slowly transformed into the next token prediction (see Figure 5.3), so a probable interpretation here is that this attention head is moving needed information to the last token position to make the next token prediction.

the 144 attention patterns computed by the GPT-2 small model, when given the example input text *"The American flag is red, white, and"*. This model uses 12 separate attention mechanisms, called attention heads, per layer, and has 12 layers—making for 144 total attention patterns. DeepSeek R1 has 128 attention heads per layer and 61 layers, making for 7,808 total patterns.

In both models, the size of each attention pattern is equal to the number of tokens passed into the model—our example input *"The American flag is red, white, and"* maps to nine tokens, so all of our attention patterns are 9x9 matrices.[5]

Attention patterns are used by attention heads to move information between token positions in the model's residual stream. For example, the 1st attention pattern in the 3rd layer of GPT-2 (Figure 8.4 Panel A) has a high value mapping from the input token (column) of *American* to the output token (row) of *flag,* meaning this attention head is likely applying the modifier American to the noun flag, creating a unified representation for the concept of "American Flag".

The eighth attention pattern in the 11th layer (Figure 8.4 Panel B) has high values mapping the tokens *flag*, *red*, and *white* to the output of the final token *and*—this attention head has pulled out the words in our input that are relevant for predicting the correct next token of *blue*—which this GPT-2 small model does correctly predict.[6]

5 In all attention patterns and walkthroughs, we're ignoring the |beginning of sentence| token. "The American flag is red, white, and" actually maps to 10 tokens if we include this starting token, and many attention patterns do assign high values to this token.
6 The model's next token prediction ends up in this final position. As data moves through the model "and" will slowly morpth to "blue".



Figure 8.5 | Computing Keys and Queries. In the standard transformer architecture, each attention layer begins with computing key and query matrices, by multiplying the incoming data by a query weight matrix W_Q, and a key weight matrix W_K. Throughout this chapter, we'll visualize matrices using colored heatmaps. These heatmaps show real data flowing through the third layer (and first attention head) of GPT-2 small.

Let's dig a bit deeper into exactly how the standard attention mechanism works in models like GPT-2 and build up a few equations, so we can make sense of how the DeepSeek team made such a powerful improvement.

To compute a given attention pattern, we take the input matrix X (Figure 8.5), this could be the input to any layer of our model and will have one row for each input token, and the number of columns corresponds to the embedding dimension of the model—this is the length of the vector used to represent each token. GPT-2 small's embedding dimension is 768, and DeepSeek R1's embedding dimension is 7,168.

To compute a given attention pattern, we first multiply our input matrix X by two separate sets of learned weights, W_Q and W_K. In GPT-2, these matrices are of dimension 768x64, and our multiplications result in two new matrices, Q and K, each with a dimension of 9x64.[7]

The rows of our Q matrix are known as queries, and the rows of our K matrix are known as keys. The core idea of attention is that we now search for pairs of tokens that have similar queries and keys, allowing the model to learn various relationships between tokens (Figure 8.6). For example, a token like *flag* could query for words that modify its meaning, while words like *American* can produce keys in certain attention heads that flag them as modifiers. This modifier query and modifier key should produce similar key and query vectors.

7 Note that there's also a bias term that is added that we're ignoring here. See Chapters 3 and 4 for more on bias.

Figure 8.6 | Using Keys and Queries. Matching keys and queries "find each other" using the dot product to measure similarity. Similar key and query vectors will produce high dot products. In the attention mechanism, these vectors are called keys and queries as an analogy to information retrieval systems (e.g. databases). It's important to note that this is a rough analogy. When we dive into the real workings of large models this understanding can break down—"keys" and "queries" are the names we've given to these vectors in what has turned out to be a very powerful architecture, but this does not mean that deep models will use these vectors as we might expect.

Mathematically, to find similar keys and queries, we can take the dot product of the keys and queries for each possible pair of our 9 tokens, similar key and query vectors will generate high dot products. We can compute all of these dot products at once by transposing our key matrix and multiplying by our query matrix—resulting in a new 9 by 9 matrix, where each entry corresponds to the dot product of a single key and query (QK^T in Figure 8.7).

To complete our attention pattern, we apply a masking operation, effectively zeroing out[8] the upper right portion of our matrix—this

8 Actually minus "infinity-ing" in many implementatios



step is mostly important in training, as it prevents the model from cheating on its task of next token prediction by just looking at the next token.

Finally, we normalize our result by dividing by the square root of our embedding dimension and we apply a softmax operation,[9] which forces each of the rows of our matrix to add to one.

Now that we've computed our attention pattern, we need to actually use it to process our data. This involves a couple more matrix multiplies—we first compute what's known as a value matrix by multiplying our input by a third weight matrix W_V. This computation is identical to the way we computed our key and query matrices, just with different learned weights.

We then multiply our attention pattern matrix by our value matrix—this effectively takes a weighted sum of our values

9 See Chapter 3 for SoftMax details



following our attention pattern. One way to think about this important step is as processing our input using a neural network where the weights, A, are controlled by the data itself.

Finally, the attention block in each layer has multiple heads (Figure 8.8)—each head performs the same computations but with different learned weights—resulting in a different set queries, keys, attentions patterns, and values for each head—the idea here is that various attention heads can specialize in various tasks—like searching for adjectives or searching for other instances of the current token.

To compute the final output of the attention block, we stack the results from each head together and multiply by a final learned weight matrix WO, giving us the final output matrix of our attention block (Figure 8.8).

Figure 8.7 | One Attention Head. Attention may be the most important neural network architectural development since the invention of the perceptron in the 1950s (see Chapter 1; in my opinion, convolutional nets are a close second). If our attention pattern A was fixed, our attention head would work in a similar way to a single fully connected layer. However, A is computed from our data, effectively "allowing the data to modify itself". Attention allows neural networks to capture and model "long range" patterns much more effectively than fully connected/dense layers. Note that we're ignoring bias terms in matrix equations, and ignoring positional embeddings. These are fascinating—see the DeepSeek papers and "ROPE".



Figure 8.8 | The Third Attention Layer in GPT-2 Small. Attention layers in transformers are built from multiple attention heads. Each attention head effectively operates on a copy of the input data (note that it's common to implement all heads using a single set of matrix multiplies). The output of each head is concatenated together and multiplied by a final matrix of learnable weights.

The attention block is a key part[10] of modern language models, but requires a significant amount of computation. Since the height and width of the attention pattern are equal the number of input tokens, the number of entries in this matrix scales as the number of input tokens squared. This is potentially a huge computational problem for large models—OpenAI's ChatGPT models offer maximum context lengths of over 100,000 tokens[11]—for reference this is about the length of the first Harry Potter book. So computing each attention pattern for ChatGPT's maximum allowed input size is equivalent to arranging the text of the entire book as a single row and column, and then computing dot products for every possible pair of words from the entire text.

Fortunately, there's a huge computational shortcut we can take.

As language models generate new text, a single token at a time, the attention patterns themselves don't actually change that much. In our American flag example, let's say the model generates a new token for the word *blue*—our phrase is now "*The American flag is red, white, and blue*". To see what the model says next, we now pass this new 10 token input back into the model to get the 11th token, and so on.

Our new 10 token input results in key, query, and value matrices

Figure 8.9 | Some Harry Potter books may have been harmed. The scale of the attention patterns in modern Large Language Models is difficult to comprehend. Many models can support 100k+ input tokens, meaning their attention patterns can have 100,000 x 100,000 = 10^{10} entries! This is equivalent to taking two copies of the first Harry Potter book, cutting out each token, arranging all the tokens from one copy in a row, and all the tokens from the other copy in a column, and computing a dot product for every possible pair of tokens! The attention pattern overlaid on this figure is computed from the real text, see supporting code for implementation. Attention pattern values <0.001 are not rendered. It's interesting that most attention activity is fairly local (the model is just using the last 10-20 tokens to predict the next token), but there are interesting exceptions where the model looks further back. Row and column have tokens (separated by spaces): "Mr. and Mrs. Durs ley, of number four, Pri vet Drive, were proud to say that they were perfect ly normal, thank you very much . They were the last people you' d expect to be in volved in anything strange or mysterious, because they just didn't hold with such nonsense . Mr. Durs ley was the director of a firm called Grun nings, which"

10 or is it a query or value part lol
11 And Gemini offers 1M+



Figure 8.10 | Key-value caching. When generating text, new tokens are appended to the input and this new longer input is fed back into the model (see Figure 5.3). Here, the model has generated a new token of "blue" that has been appended to our input. Moving our new longer input through our attention head, we find lots of duplicated computations from Figure 8.7. Tracing through the matrix math, we can show that the rows and columns highlighted in red are the only new computations needed, but we need the keys and values in blue boxes to perform these computations. Instead of recomputing the blue regions, we can store these in memory, saving computation. This technique is called Key-value or KV caching.

each of dimension 10x64, but importantly, since our weight matrix multiplication applies the same operation at each token position, the first nine rows of our key, query, and value matrices are unchanged from our original nine token input.

Transposing our keys and multiplying by our queries to compute our new attention pattern, note that since the first nine rows of Q and first nine columns of K^T are unchanged, this means that the upper left 9x9 matrix of our attention pattern will be unchanged, and we only need to compute new final row and column to arrive at our new 10 by 10 attention pattern. And since we mask out the upper right corner of our attention pattern, we actually only need to compute the new bottom row. The bottom row of our attention pattern results from multiplying the final row in our query matrix by each of the columns in our transposed key matrix, so to compute this final attention pattern row, we need all of our keys, but only the final new row of our query matrix.

Since we already computed 9 of our 10 keys on the previous call to the model, it's much more computationally efficient to store these



keys in memory, and just access them when the new 10th token input comes along. The same logic applies to our value matrix, we need our full value matrix to compute our new outputs, but the first nine rows are unchanged, so we can just cache them in memory. Note that there's no need to cache the queries, since we only need the final new row of queries to update our attention pattern.

This idea is called key value caching or KV caching, and is a critical part of large language model infrastructure. Instead of compute growing quadratically as the square of the number of input tokens, key value caching means that the compute required by the models attention blocks scales linearly with the number of input tokens.

Now, this computational shortcut does come at a cost—specifically increased memory usage. Our system must now store the keys and values for the full history of the model session for all attention heads across all model layers, in memory. Given a model with l layers, n_h attention heads per layer, a dimension of d_h for our key



Figure 8.11 | Quadratic -> Linear. Without key-value caching, the compute required by an attention block scales quadratically with the number of input tokens.



Figure 8.12 | That's a lot of cache. The storage space needed to cache the keys and values in a large language model adds up quickly. If DeepSeek R1 used standard attention heads, the model would require 4 MB of KV cache per input token. For long context lengths (e.g. 100k tokens), the amount of required storage becomes very large. *Assumes fp16, 2 bytes per number.

an value matrices, and n input tokens, we must store $2nd_hn_hl$ unique numbers in our kv cache (Figure 8.12). Assuming floating point 16 numbers, the DeepSeek R1 architecture, and a context length of 100,000 tokens—we end up needing to retrieve 4 MB per token in the model's context window, requiring an enormous 400 GB of memory reads for each new token we compute.

Untenably large KV caches are not a new problem. One popular solution is to reuse key and value matrices across multiple attention heads. In Multi Query Attention (MQA) blocks, instead of having a unique key and value matrix for each attention head, we share a single key and value matrix across all heads (Figure 8.13). This reduces the required size of our kv cache by a significant factor of the number of heads per layer, 96 in the case of GPT-3. However, this modification does impact model performance—as forcing all attention heads to use the same keys and values allows for less specialization.

A less destructive version of this idea is Grouped Query Attention (GQA), where instead of forcing all attention heads in a given layer to share the same key and value matrices, we create multiple groups of attention heads that share the same key and value matrices. Meta's Llama 3 models use Grouped Query Attention, with groups of eight attention heads sharing the same key and value matrices, reducing the size of the KV cache by a factor of eight. Grouped Query Attention reduces KV cache size, but still takes a performance hit relative to full multihead attention.

Now, what's really remarkable about DeepSeek's approach, called Multihead Latent Attention, is that they were able to reduce the

ATTENTION MECHANISM	KV CACHE ENTRIES PER TOKEN
Multi-Head Attention (MHA)	$2n_hd_hl$
Multi-Query Attention (MQA)	$2d_hl$
Grouped-Query Attention (GQA)	$2n_gd_hl$

Figure 8.14 | Efficiency Gains. MQA removes the dependence on the number of heads per layer, and GQA introduces a new grouping term n_g replacing the number of heads per layer n_h. Meta's Llama 3 uses groups of eight heads, reducing the required KV cache size by a factor of 8.



Figure 8.13 | Multi-Query Attention (MQA) and Grouped-Query Attention (GQA). MQA and GQA each reduce the required size of the KV cache by sharing keys and values across attention heads. MQA uses only a single key and value matrix per layer, while GQA groups heads together, reducing the number of shared keys and values per attention head relative to MQA. Both MQA and GQA sacrifice some algorithmic performance for reduced memory requirements.



Figure 8.14 | Multihead Latent Attention (MLA). The DeepSeek team's key innovation here is adding an extra Key and Value latent matrix to the attention mechanism. Compare this Figure to Figure 8.7 to see the precise differences between MLA and standard attention. The new key and value latent matrix is shared across all attention heads, significantly reducing needed cache size, much like MQA. However, unlike MQA, MLA adds an extra compute step to transform the "latent" key and value cache matrix into the keys and values for each head, allowing each head to have unique keys and values as we see in the standard attention mechanism. Interestingly, it turns out that these extra compute steps can be absorbed into existing compute using some clever linear algebra (Figure 8.15).

* Note that DeepSeek-V2 paper claims a KV cache size reduction of 93.3%. They don't exactly publish their methodology, but as far as we can tell it's something likes this: start with Deepseek-v2 hyperparameters here: huggingface.co/deepseek-ai/DeepSeek-V2/blob/main/configuration_deepseek.py. num_hidden_layers=30, num_attention_heads=32, v_head_dim = 128. If DeepSeek-v2 was implemented with traditional MHA, then KV cache size would be 2*32*128*30*2=491,520 B/token. With MLA with a KV cache size of 576, we get a total cache size of 576*30=34,560 B/token. The percent reduction in KV cache size is then equal to (491,520-34,560)/492,520=92.8%. The numbers we present in this Chapter follow the same approach but are for DeepSeek-v3/R1 architecture: huggingface.co/deepseek-ai/DeepSeek-V3/blob/main/config.json. num_hidden_layers=61, num_attention_heads=128, v_head_dim = 128. So traditional MHA cache would be 2*128*128*61*2 = 3,997,696 B/token. MLA reduces this to 576*61*2=70,272 B/token. It follows then that for the DeepSeek-V3/R1 architecture, MLA reduces the KV cache size by a factor of 3,997,696/70,272 =56.9X.



needed KV cache size by a factor of 57 (compared to vanilla Multihead Attention)* while actually improving model performance.

The key insight is a novel application of a very common idea in machine learning—a latent space. *What if the model could learn to efficiently compress its own keys and values?*

Multihead Latent Attention (MLA) effectively adds an extra step between each attention head's input and key and value matrices (Figure 8.14). The idea is to project our input into a compressed latent space that like Multi Query Attention, is shared across all attention heads in a given block. However, unlike Multi Query Attention, where each head shares the same exact keys and values, in Multihead Latent Attention, the compressed latent space is projected back up to key and value matrices using another set of learned weights, W_{UK} and W_{UV}, where the weights are unique to each attention head.[12] This step gives Multihead Latent Attention more flexibility than Multi Query Attention or Grouped Query Attention.

Now, at face value, since we've introduced two new matrix multiplications it appears that we've just traded some memory bandwidth for additional compute, and after all, the entire point of KV caching was to reduce the high compute needs of attention blocks.

12 Note that we're ignoring bias terms matrix equations, and ignoring positional embeddings. These are fascinating. See DeepSeek papers and "ROPE".



Figure 8.15 | Same results as Figure 8.14, but more efficient. By rearranging DeepSeek's MLA Architecture (Figure 8.14), it's possible to significantly reduce its required compute. Starting with our square attention score matrix in Figure 8.14 (not to be confused with our attention pattern), we know that our scores are computed as $L_{UK} W_{UK}$ and that our queries are computed as XW_Q. Substituting and simplifying, we're able to combine our two weight matrices into a single weight matrix, turning two matrix multiplies into one! We apply a similar process to our outputs, but we do have to move outside the attention head to the final attention layer matrix multiply (Figure 8.8) for things to work out. Taking U_1 as a single "slice" of our overall layer's output matrix, and starting with our $U_1 = OW_O$ equation from Figure 8.8, we can again substitute and rearrange, and again turn two matrix multiplications into one! I would love to know if this trick was obvious to the DeepSeek team, or if it took some work to uncover.



Final output from full attention layer. See Figure 8.8. Here we're considering a single "slice" of the output that comes from the current attention head.

$$
\begin{aligned}
U_1 &= OW_O \\
&= (AV)W_O \\
&= (AL_{KV}W_{UV})W_O \\
&= (AL_{KV})(W_{UV}W_O)
\end{aligned}
$$

Substitute definitions from Figure 8.14

Combine into single weight matrix!

However, as the DeepSeek team points out, with some clever linear algebra, we can rearrange our query computation to absorb the W_{UK} weights, and re-arrange our final output computation to absorb the W_{UV} weights. Since all these weights are fixed at training time, we only have to compute the absorbed weights once (or train with this modification in place) and avoid any additional compute during inference.

So when a new token comes along, we simultaneously compute its query vector and the query's projection to the latent cache space in one step, and then compute our attention pattern directly from the latent key value cache matrix—it's a really elegant solution.

ATTENTION MECHANISM	KV CACHE ENTRIES PER TOKEN	KV CACHE SIZE PER TOKEN*	ALGORITHMIC PERFORMANCE
Multi-Head Attention (MHA)	$2n_h d_h l$	$4\ MB$	High
Multi-Query Attention (MQA)	$2d_h l$	$31\ KB$	Lower
		57x Reduction	
Grouped-Query Attention (GQA)	$2n_g d_h l$	$500\ KB^{**}$	Medium
Multi-Head Latent Attention (MLA)	$d_l l$	$70\ KB$	Higher

Figure 8.16 | 57X Cache Size Reduction! MLA is significantly more memory efficient, and according to the DeepSeek team, actually offers *better* algorithmic performance (e.g. error rate). *DeepSeek R1/V3 Architecture—61 layers, 128 heads per layer, head dimension 128, fp16, latent dim=576 **Grouping factor of 8. See footnote below Figure 8.14 for more details on these computations.

With Multihead Latent Attention, the size of the needed KV cache no longer has any dependence on the number of attention heads per layer, and instead just depends on the size of the shared KV cache matrix—for DeepSeek R1 this is equal to the number of tokens by 576. If implemented with traditional attention blocks, R1 would require 4MB of KV cache per token (Figure 8.16)—Grouped Query Attention with a group size of 8 would cut this down to 500KB per token, and Multihead Latent Attention reduces the needed cache size to only 70 KB per token.

What we're left with is a true improvement to the transformer architecture, enabling DeepSeek R1 to generate tokens more than six times faster than a vanilla transformer, while actually improving algorithmic performance. Multihead Latent Attention allows attention heads to share key and value information in a more optimal way—where the model itself learns how to compress and share this information between attention heads.

The transformer architecture is one of the most significant breakthroughs in modern AI history, and DeepSeek appears to have made it work significantly better.

It's amazing to see the path the DeepSeek team carved through their 2024 papers, systematically making substantial improvements to models that required hundreds of millions of dollars in R&D and infrastructure costs.

The stakes have never been higher for neural networks—it will be fascinating to see what new set of ideas unlocks the next level of capabilities as we build more and more intelligent systems.

8.7 Harry Potter Attention Pattern

[36]:
```
reference_text = "Mr. and Mrs. Dursley, of number four, Privet Drive, " \
                 "were proud to say that they were perfectly normal, " \
                 "thank you very much. They were the last people you'd " \
                 "expect to be involved in anything strange or mysterious, " \
                 "because they just didn't hold with such nonsense. Mr. " \
                 "Dursley was the director of a firm called Grunnings, which"
```

[35]:
```
tokens = model.to_tokens(reference_text).to(device)
logits, cache = model.run_with_cache(tokens)
logits.shape
```

[35]:
```
torch.Size([1, 77, 50257])
```

[36]:
```
layer_id=2
head_id=0
```

[37]:
```
cfg = Config(debug=True)
layer = Attention(cfg).to(device)
layer.load_state_dict(model.blocks[layer_id].attn.state_dict(), strict=False);
```

[37]:
```
normalized_resid_pre=cache["normalized", layer_id, "ln1"]

qs=[]
for head_num in range(cfg.n_heads):
    qs.append(normalized_resid_pre[0] @ W_Q[head_num] +b_Q[head_num])

#Stack results together, add batch dimension, switch token and head dims.
q=t.stack(qs, dim=0).unsqueeze(0).permute(0, 2, 1, 3)

q_to_viz=q[0,1:,head_id,:].detach().cpu().numpy()

k = (
    einops.einsum(
    normalized_resid_pre, W_K, "batch posn d_model, nheads d_model d_head -> "
                               "batch posn nheads d_head"
    )
    + b_K
)

# Calculate attention scores, then scale and mask, and apply softmax -> probabilities
attn_scores = einops.einsum(
    q, k, "batch posn_Q nheads d_head, batch posn_K nheads d_head -> "
          "batch nheads posn_Q posn_K"
)

attn_scores_masked = layer.apply_causal_mask(attn_scores / layer.cfg.d_head**0.5)
attn_pattern = attn_scores_masked.softmax(-1)
attn_pattern_to_viz=attn_pattern[0,head_id,1:,1:].detach().cpu().numpy()
```

SUPPORTING CODE

Full supporting code for this chapter at:
github.com/stephencwelch/ai_book

```
import numpy.ma as ma

# Mask values where abs(value) < eta
eta = 0.001  # Set your threshold here
masked_attn = ma.masked_where(np.abs(attn_pattern_to_viz) < eta, attn_pattern_to_viz)

plt.clf()
fig=plt.figure(0, (8,8))
plt.imshow(masked_attn, cmap='viridis', vmin=0, vmax=0.1)
plt.axis('off')
```

```
(np.float64(-0.5), np.float64(8.5), np.float64(8.5), np.float64(-0.5))
```

```
<Figure size 640x480 with 0 Axes>
```



8. ATTENTION | EXERCISES

8.1 Conceptually, why do attention layers use multiple attention heads?

8.2 How do attention heads capture/measure the similarity between key and query vectors?

8.3 How are keys and queries in attention layers different than keys and queries in information retrieval systems like databases? Do you think "key" and "query" are helpful names for these vectors?

8.4 As we saw in Chapter 3, the transformer architecture is composed of alternating fully connected/multilayer perceptron layers and attention layers. Compare and contrast these different types of neural network layers.

8.5 Without caching, attention block compute grows quadratically with the number of input tokens—why?

8.6 In KV caching, why don't we cache our query matrices? Why do we only store keys and values?

8.7 Why would Multi-Query Attention (MQA) reduce algorithmic performance (e.g. worse error rate)?

8.8 Here's a closer look at one of the attention patterns from Figure 8.1. What might this attention pattern be doing?



8.9 Here's a closer look at one of the attention patterns from Figure 8.1. What might this attention pattern be doing?



8.10 `ai_book/exercises/8_attention_exercises.ipynb` contains code to generate GPT-2 attention patterns. Run this notebook and experiment with different input text. Are you able to find similar modifier examples like our "American flag" example? What other patterns do you come across?

SUPPORTING CODE

Full supporting code for this chapter at:
`github.com/stephencwelch/ai_book`



8.11 In Figures 8.14 and 8.15, we saw how Multihead Latent Attention (MLA) could be simplified and made more efficient by rolling multiple matrix multiplies into one. The figure above shows a recreation of Figure 8.14, with some additional diagramming of the output processing. Show how we can combine W_Q and W_{UK} into a single weight matrix and matrix multiply, by starting with the equation for our attention scores, QK^T, and progressively substituting and simplifying. It will be helpful to know that $(AB)^T = B^T A^T$, state the dimensions of each matrix along the way.



8.12 Show that we can combine W_{UV} and W_O into a single weight matrix and matrix multiply. Start with the equation $U_1 = OW_O$. As shown above, this equation represents the portion of the overall output matrix multiply originating from this single attention head. Substitute and simplify, and indicate all matrix dimensions along the way.



Figure 9.2 (Top) | Wan2.1. Some prompts and resulting video frames from Wan2.1. Interestingly, we still get a video of a woman when we pass in no prompt.

Figure 9.4 (Bottom) | The Diffusion Process. Most modern image and video generation models use a diffusion process, where pure noise is iteratively refined into images or video. The full process for this video generation requires 50 steps, here we're showing steps 1, 10, 30, and 50.

Chapter 9 Video

9. DIFFUSION

But how do AI images and videos actually work?

Over the last few years, AI systems have become astonishingly good at turning text prompts into images and videos.

At the core of how these models operate is a deep connection to physics. This generation of image and video models works using a process known as diffusion— which is remarkably equivalent to the Brownian motion we see as particles diffuse, but with time run backwards, and in high dimensional space.

As we'll see, this connection to physics is much more than a curiosity—we get real algorithms out of the physics we can use to generate images and videos, and this perspective will also give us some really nice intuitions for how these models work in practice.

But before we dive into this connection—let's get hands on with a real diffusion model. While the best models are closed source, there are some compelling open source models—the frames shown in Figure 9.2 of an astronaut were generated by a open source model called Wan2.1.[1] We can add to our prompt and have our astronaut hold a flag, hold a laptop, or hold a meeting, and interestingly if we cut our prompt down to nothing we still get the video of a woman shown in the lower right corner of Figure 9.2.

If we dig into our Wan model's source code, we'll find that the video generation process begins with a call a random number generator (Figure 9.3), creating a video where the pixel intensity values are chosen randomly—creating a pure noise video as shown in Figure 9.4 Panel A.[2]

From here, this pure noise video is passed into a transformer—this is the same type of AI model used by large language models like ChatGPT, but instead of outputting text, this transformer outputs another video that now looks like Panel B of Figure 9.3. Still mostly just noise, with some hints of structure.

This new video is added to our pure noise video and passed back into the model again, producing a third video, shown in Panel C. This process is repeated again and again, until remarkably, after 50 steps in this case, we're left with incredibly realistic video.

But what exactly is the connection to Brownian motion here, and how is our model able to use text inputs to so expressively shape noise into what the prompt describes?

In this Chapter, we'll unpack diffusion models in three parts.



Figure 9.1 | This video was generated by Google's Veo 3 model with the prompt: "*An astronaut on the moon riding a horse that turns into a giant cat*"

```
noise = [
    torch.randn(
        target_shape[0],
        target_shape[1],
        target_shape[2],
        target_shape[3],
        dtype=torch.float32,
        device=self.device,
        generator=seed_g
    )
]
```

Figure 9.3 | The Wan2.1 video generation process starts with this call to the PyTorch random number generator.

1 github.com/Wan-Video/Wan2.1

2 Both the Wan model we're seeing here and the Stable Diffusion model we'll look at later are "latent diffusion" models, where the diffusion process happens in a smaller "latent space", and is mapped back to full images/video using a separate model called a variational autoencoder (VAE) that acts like an image/video compressor—this is why the noise videos don't look like pure "salt and pepper".



Figure 9.5 | CLIP. CLIP (Contrastive Language-Image Pre-training) is composed of two models that are trained using a clever learning objective, where the models learn to maximize the similarity between matching image/caption pairs (diagonal of 3x3 matrix above), while minimizing the similarity between non-matching image/caption pairs (off diagonal).

First, we'll look at a 2021 OpenAI paper and model called CLIP. As we'll see, CLIP is really two models, a language model and a vision model, that are trained using a clever learning objective that allows them learn this really powerful shared space between words and pictures. Experimenting with this space will help us get a feel for the high dimensional spaces that diffusion models operate in.

But just learning a shared representation is not enough to generate images—from here we'll look at the diffusion process itself. At a high level, diffusion models are trained to remove noise from images or videos. However, if you dig into the landmark papers in the field, you'll find that this naive understanding of diffusion really doesn't hold up in practice. In this section we'll dig into the connection between diffusion models and diffusion processes in physics. This connection will help us understand how these models really work in practice, and give us some powerful theory for dramatically speeding up image and video generation.

Finally, we'll bring these worlds together and see how approaches like CLIP are combined with diffusion models to condition and guide the generation process towards the videos we ask for in our prompts.

9.1 CLIP

2020 was a landmark year for language modeling. New results in neural scaling laws and OpenAI's GPT-3 showed that bigger really was better—massive models trained on massive datasets had capabilities that simply didn't exist in smaller models.

It didn't take long for researchers to apply similar ideas to images. In February 2021, a team at OpenAI released a novel model architecture called CLIP, trained on a dataset of 400 million image/caption pairs scraped from the internet [Radford et al. 2021].

CLIP is composed of two models, one that processes text, and one that process images. The output of each model is a vector of length 512, and the central idea is that the vectors for a given image and its caption should be similar.

To achieve this, the OpenAI team developed a clever training approach. Given a batch of images/caption pairs— for example our batch could contain a picture of a cat, dog, and a man, with the captions *"A photo of a cat"*, *"A photo of a dog"*, and *"A photo of a man"*—we pass our three images into our image model, and our three captions into our text model. We now have three image vectors and three text vectors, and we would like the vectors for matching image caption pairs to be similar (Figure 9.5).

The clever idea from here is to make use of the similarity not just between corresponding images and captions, but between all image and caption pairs in the batch when training our models. If we arrange our image vectors as the columns of a matrix and our text vectors as the rows, the pairs of vectors along the diagonal of our matrix correspond to matching images and captions, and all the pairs off the diagonal show non-matching images and captions. The CLIP training objective seeks to maximize the similarity between corresponding image caption pairs,



Figure 9.7 | What CLIP Does. CLIP uses a cosine similarity learning objective. As CLIP's image and text encoders are trained, they learn to point matching image and caption pairs in the same direction in high dimensional space, while pointing non-related images and caption embedding vectors in orthogonal-ish directions—see footnote below for more details.



$$\text{Cosine Similarity} = \frac{I \cdot T}{||I||_2||T||_2} = \cos(\theta)$$

Figure 9.6 | Cosine Similarity. Cosine similarity is proportional to the dot product between our vectors, and measures the cosine of the angle between a pair of vectors.

while simultaneously minimizing the similarity between non-corresponding image caption pairs. The "C" in CLIP stands for contrastive, because the models learn to contrast matching and non-matching image caption pairs.

The CLIP algorithm measures similarity between vectors using a metric called the cosine similarity (Figure 9.6). Geometrically, we can think of each of our vectors as pointing in some direction in high dimensional space. Cosine similarity measures the cosine of the angle between our vectors in this space, so if our text and image vectors point in the same exact direction, the angle between our vectors will be zero, resulting in a maximum cosine similarity score of $\cos(0)=1.0$.

The image and text models that make up CLIP are trained to maximize the alignment of related images and captions in this shared high dimensional space, while minimizing the alignment between unrelated images and captions.[3]

3 The original video that goes along with this Chapter is a guest post on Grant Sanderson's channel 3Blue1Brown. Originally, we had the off-diagonal vectors in Figure 9.7 pointing 180 degreees apart, after all an angle of 180 degrees minimizes cosine. Grant raised a good point about this: *"The only question I had watching it was about the CLIP cosine similarity, where a 5:52, the off-diagonal entries were shown as pointing in opposite directions. I get that this would minimize the cosine, but I'm curious if, in practice, they actually end up more orthogo-*



TOP MATCHES	COSINE SIMILARITY
hat	0.1652
cap	0.1129
helmet	0.1064
angry	0.0611
roughness	0.0602
exercising	0.0602
tense	0.0599
tennis racket	0.0565
writing	0.0562
hate	0.0551
frisbee	0.0550
sports ball	0.0549
spider	0.0540
sneakers	0.0531
navy	0.0521
shark	0.0507
mysterious	0.0507
black	0.0501
melancholy	0.0500
remote	0.0485
cow	0.0485
orange	0.0481
eagle	0.0481
ugliness	0.0472
fork	0.0468
tiger	0.0467
sophistication	0.0463
chicken	0.0458
snake	0.0456
olive	0.0456
serious	0.0455
laptop	0.0433
anxious	0.0428
dramatic	0.0420
cup	0.0420
wolf	0.0419
horse	0.0418
apple	0.0414
gloves	0.0404
watch	0.0403
spoon	0.0401
order	0.0401
sad	0.0396
war	0.0393
flying	0.0392
studying	0.0391
sleeping	0.0391
handbag	0.0387
shoes	0.0384

Figure 9.8 | A powerful shared vector space. If we subtract the vector corresponding to me not wearing a hat from the vector of me wearing a hat, the most similar word vector to this difference vector is "hat"!

The learned geometry of this shared vector space, known as a latent or embedding space, has some really interesting properties.

If I take two pictures of myself, one not wearing a hat, and one wearing a hat, and pass both of these into the CLIP image model, we get two vectors in our embedding space (Figure 9.8). Now if we take the vector corresponding to me wearing the hat, and subtract the vector of me not wearing the hat, we get a new vector in our embedding space.

Now, what text might this new vector correspond to? Mathematically, we took the difference of me wearing a hat and me not wearing a hat. We can search for corresponding text by passing a bunch of different words into our text encoder, and for each computing the cosine similarity between our newly computed difference vector and the text vector.

Testing a set of a few hundred common objects and words, the top ranked match with a similarity of 0.165 is the word hat, followed by cap, and helmet. This is a remarkable result—the learned geometry of CLIP's embedding space allows us to operate mathematically on the pure ideas or concepts in our images and text—translating differences in the content of our images—like if

nal, simply given that there are many (many) more orthogonal directions compared to the one opposing direction." As usual, Grant has great intuition—I had bumped into some sources that suggested this but had initially chosen to keep things simple. After giving this some more thought though, we decided to show a closer representation to what actually happens—it turns out that directly minimizing cosine similarity would push our vectors 180 degrees apart on a single batch, but in practice, CLIP maximizes the uniformity of concepts over the hypersphere it's operating on—meaning showing these vectors in 2D as orthogonal-ish is more precise—see [Wang and Isola 2020].



TOP MATCHES	COSINE SIMILARITY
cat	0.2784
tiger	0.2396
socks	0.2353
mouse	0.2352
boots	0.2344
person	0.2293
rat	0.2228
necklace	0.2218
sneakers	0.2214
dog	0.2208
rabbit	0.2200
cap	0.2162
tie	0.2162
sweater	0.2158
t-shirt	0.2156
owl	0.2153
mouse	0.2151
scarf	0.2150
lion	0.2142
earrings	0.2133
glasses	0.2130
jeans	0.2120
helmet	0.2099
fish	0.2098
coat	0.2081
bee	0.2075
bowl	0.2073
spider	0.2072
wolf	0.2068
cow	0.2068
hamster	0.2067
hat	0.2063
bird	0.2061
horse	0.2047
pants	0.2047
fox	0.2044
snake	0.2042
zebra	0.2022
shirt	0.2019
chicken	0.2018
ring	0.2017
bear	0.2009
gloves	0.2007
frog	0.2000
butterfly	0.1991
watch	0.1989
turtle	0.1982
giraffe	0.1981
shoes	0.1956

Figure 9.9 | Image classification out of the box. CLIP turns out to be a remarkably good image classifier, even though we didn't train the model to classify images. To turn CLIP into an image classifier, we compare our image vector against the vectors from a bunch of possible captions.

there's a hat or not—into a literal displacement between vectors in our embedding space.

The OpenAI team showed that CLIP could produce very impressive image classification results by simply passing an image into our image encoder, and then comparing the resulting vector to a set of possible captions, one for each label that could be assigned to the image, and classifying each image with whatever label resulted in the highest cosine similarity (Figure 9.9).

So techniques like CLIP give us a powerful shared representation of image and text—a kind of vector space of pure ideas. However, our CLIP models only go one direction. We can only map image and text to our shared embedding space and have no way of generating images or text from our embedding vectors.

9.2 Diffusion

2020 turned out to not only to be a transformative year for language modeling. A few weeks after the GPT-3 paper came out, a team at Berkeley published a paper called Denoising Diffusion Probabilistic Models, now known as DDPM [Ho et al. 2020]. This paper showed for the first time that it was possible to generate very high quality images using a diffusion process, where pure noise is iteratively transformed into realistic images.

The core idea behind diffusion models is pretty straightforward—we take a set of training images, and add noise to each image step by step, until the image is completely destroyed. From here we train a neural network to reverse this process.

When I first learned about diffusion models, I assumed that models would be trained to remove noise a single step at a time.



Figure 9.10 | Nope. One mental image of how diffusion models work is that these models learn to remove noise "one step at a time". During training, we add noise to our images one step at a time, then train our model to reverse this process one step at a time. When it comes time to make a new prediction, we start with pure noise (Panel E), and iteratively pass this image through our network until we have a nice image. As we'll see, this is not how diffusion models work in practice.

Our model would be trained to predict the image in Figure 9.10 Panel A given the noisier image in Panel B, trained to predict the image in Panel B given the noisier image in Panel C, and so on. When it came time to generate an image, we would start with pure noise (Panel E), pass the output of our model at each step back into its input again and again, and after enough steps we would have a nice image (Panel H).

It turns out that this naive approach to building a diffusion model really does not work well—virtually no modern models work this way.

Figure 9.11 shows the training and image generation algorithms from the Berkeley team's paper. The notation is a bit dense, but there are a few key details we can pull out here that can help us understand what it takes to make these models really work.

The first thing that surprised me is that the team added random noise to images not just during training, but also during image generation. Algorithm 2 tells us that when generating new images, at each step, after our neural network predicts a less noisy image, we need to add random noise to the image again before passing it back into our model.



Figure 9.11 | The Landmark Paper. To make diffusion actually work, the landmark "DDPM" paper includes some potentially surprising approaches. First, the authors add random noise not just during training, but also during image generation (called "Sampling" here). So at each step of the noise removal process/image generation process, we add some noise back. Why? Second, the model is not trained to predict a cleaner image given a slightly noisier one. Instead, at each training step a noise level is chosen semi-randomly (following a "noise schedule"), this noise is added to our image, and our model is trained to predict the total added noise ϵ given the noiser image. Algorithms 1 and 2 are reproduced from [Ho et al. 2020].

This added noise turns out to matter a lot in practice. If we take a popular diffusion model like Stable Diffusion 2[4], and use the Berkeley team's image generation approach, known as DDPM sampling—we can get some really nice images—Figure 9.12 Panel A shows the image we get when prompting the model with this prompt asking for a tree in the desert. Now if we remove the line of code that adds noise at each step of the generation process, we end up with the tiny sad blurry tree shown in Panel B. How is it that adding random noise while generating images leads to better quality, sharper images?

4 huggingface.co/stabilityai/stable-diffusion-2-1



Figure 9.12 | Adding Random Noise During Generation Matters. If we take the popular open source Stable Diffusion 2 model, and remove the line of code that adds random noise after each call to the model during image generation, our resulting image is a blurry mess.

The second thing that surprised me when I encountered the Berkeley team's approach, was that the team wasn't training models to reverse a single step in the noise addition process. Instead the team takes the initial clean image, which they call x0, add scaled random noise to the image, which they call epsilon, and then train the model to predict the noise that was added to the image.

So the team is effectively asking the model to skip all the intermediate steps, and make a prediction about the original image. Intuitively, this learning task seems more difficult to me than making a noisy image slightly less noisy.

The Berkeley team's paper and approach [Ho et al. 2020] was a landmark result that put diffusion on the map—why does adding random noise while generating images and training the model in this way work so well?

The DDPM paper draws on some fairly complex theory to arrive at these algorithms [see Nakkiran et al. 2024 for a nice walkthrough]. Happily, it turns out that there's a different, but mathematically equivalent, way of understanding of what diffusion models are really learning that we can use to get a visual and intuitive sense for why the DDPM algorithms work so well.



Figure 9.15 | A Random Walk. When we progressively add random noise to an image, we're changing each pixel value by a random amount. In the space of our 2D toy images, this is equivalent to taking our image on a random walk as we would see in physics as particles diffuse. This is where diffusion models get their name.



Figure 9.16 | But How? Diffusion models learn to iteratively shape pure noise into realistic images and video. In our toy 2 pixel dataset, this is equivalent to playing the diffusion process backwards to recover the original spiral distribution of our dataset. How do diffusion models learn to play random walks backwards?

The key will be thinking of diffusion models as learning a time varying vector field—this perspective also leads to a more general approach called flow based models—which have become very popular recently.

To see how diffusion models learn this time varying vector field, let's temporarily simplify our learning problem. As we saw in Chapter 6,[5] one way to think of an image is as a point in high dimensional space, where the intensity value of each pixel controls the position of the point in each dimension. If we reduce the size of our images to only two grayscale pixels (Figure 9.13), we can visualize the distribution of our images by plotting the pixel intensity of the first pixel on the x-axis of a scatter plot, and pixel intensity of the second pixel on the y-axis.



Figure 9.13 | Images as points in space. We can visualize two-pixel images as points on a 2D plane, and conceptualize larger images as points in higher dimensional space, with one dimension for each pixel intensity value.

Now, real images have a very specific structure in high dimensional space—let's create some structure for our points in our lower two dimensional space for our diffusion model to learn. The exact structure we choose doesn't matter too much at this point—let's start with the spiral shape shown in Figure 9.14.

The core idea of diffusion models—adding more and more noise to an image and then training a neural network to reverse this process—looks really interesting from the perspective of our 2D toy data.

When we add random noise to an image, we're effectively changing each pixel's value by a random amount. In our toy 2D dataset, where the coordinates of a point correspond to that image's pixel intensity values, adding random noise to a given image is equivalent to taking a step in a randomly chosen direction. As we add more and more noise to our image, our point goes on a random walk (Figure 9.15). This process is equivalent to the Brownian motion that drives diffusion processes in physics, and is where diffusion models get their name.



Figure 9.14 | Toy Data. We can think of images and videos as points in high dimensional space. In this space, these points will have a specific structure, and seem to lie on a lower dimensional manifold. We'll spend some time in this chapter experimenting with this spiral toy dataset—each point represents a different two pixel image, and just as we expect images and videos to live on a lower dimensional manifold in higher dimensional space, here our 2 pixels images live on a 1D spiral manifold.

From here it's pretty wild to think about what we're asking our diffusion model to do. Our model will see many different random walks from various starting points in our dataset, and we're effectively asking our model to reverse the clock, removing noise from our images by learning to play these diffusion processes backwards—starting our points from random locations and recovering the original structure of our dataset (Figure 9.16).

How can our model learn to reverse these random walks?

If we consider the specific point at the end of the 100 step random walk in Figure 9.17, in our naive diffusion modeling approach (Figure 9.10), where we ask our model to denoise images a single step at a time, this is equivalent to giving our model the coordinates of the final 100th point in our walk, and asking our model to predict the coordinates of our point at the 99th step (Figure 9.17).

5 See Figures 6.14, 6.15

Figure 9.17 | Learning to walk backwards. The naive approach to diffusion models we saw in Figure 9.10 is equivalent to training our model to reverse one step at a time, learning to predict the coordinates of x_{99} given x_{100}. This single step taken in isolation is completely random, however given many particles leaving our spiral and diffusing through the x_{100} neighborhood, on average these particles will diffuse away from our initial spiral, and our model can learn to point back towards our spiral.

Although the direction of our 100th step is chosen randomly, there will be some signal in aggregate for our model to learn from here. Given enough training points, we expect many diffusion paths to move through the neighborhood of x_{100}, and on average our points will be diffusing away from the starting spiral, so our model can learn to move points back towards our spiral.

We can now see why the Berkeley team's training objective works so well. Instead of training the model to remove noise from images one step at a time—this would correspond to predicting the coordinates of the 99th step given the coordinates of the 100th step on our walk, the team instead trained the model to predict the total noise added across the entire walk. In Figure 9.18, this is the blue vector pointing from our 100th step back to the original starting point of the walk. It turns out that we can prove that learning to predict the noise added in the final step of our walk is mathematically equivalent to learning to predict the total noise added, divided by the number of steps taken. This means that when our model learns to reverse a single step, although our training data is noisy, we expect our model to ultimately learn to point back towards x_0. By instead training our model to directly



Figure 9.18 | Learning to reverse the whole walk at once is better. It turns out that we can prove that learning to predict the noise added in the last step (brown arrow) is equivalent to learning to predict the total noise added (blue arrow), divided by the number of steps taken. Here $\mathbb{E}$ is the expected value, see [Nakkiran et al. 2024] for a nice exposition. Here we're showing a single particle diffusing and a single arrow from x_{100} to x_{99}. This mathematical result is telling us that after many particles diffuse through the x_{100} neighborhood, the "average arrow" from x_{100} to x_{99} will point directly back to the particle's original starting point at x_0. So learning to reverse one step is equivalent (in expectation) to learning to reverse the entire walk, but learning to reverse the entire walk is more efficient, because the variance of our training data is reduced, allowing our model to learn more effectively.

predict the vector pointing back towards x_0, we're significantly reducing the variance of our training examples, allowing our model to learn much more efficiently, without actually changing our underlying learning objective.

So for each point in our space, our model learns the direction pointing back towards our original data distribution (Figure 9.19).[6] This is also known as a score function, and the intuition here is that the score function points us toward more likely, less noisy data.[7]

Now, in practice, these learned directions depend heavily on how much noise we add to our original data. After 100 steps, most of our points are far from their starting points, so our model just learns to move these points back in the general direction of our spiral (Figure 9.19 left). However, if we train our model on

6 Note that technically our model typically learns to point in the exact opposite direction of our data, and we just subtract it's prediction effectively removing predicted noise.
7 The DDPM paper also showed remarkable unification between score and diffusion based methods!



Figure 9.20 | Telling our model what time it is. As we can see in Figure 9.19, the structure our model needs to learn depends on how much noise we've added to our data. If we parameterize how much noise we've added as a "time step" and feed this information into the model, the model can use this extra information to make better predictions. Here we're letting t=1.0 correspond to training examples that have had "100 steps" of noise added, t=0.99 correspond to training examples that have had "99 steps" of noise added, and so on. This time value gets passed into the model along with each example during training, and when we use our model to generate data, we control the time variable as we work backwards from random noise to realistic data/images/video. This is known as a noise schedule. Note that noise is not always added in discrete "steps".





Figure 9.19 (Above) | What our model learns. After training on many diffusion trajectories, for each point in space, our model learns to point back towards our original data distribution. The direction our model learns to point depends heavily on how many noise addition steps we apply to our training data. Given 100 noise addition steps, our model generally learns to point back to the center or average of our spiral (left). Alternatively, if we train on examples that have only undergone one step of noise addition, our model learns a much more nuanced vector field (right).

examples after only one diffusion step, we end up with a much more nuanced vector field, pointing to the fine structure of our spiral (Figure 9.19 right)

It turns out there's a clever solution to this problem—instead of just passing in the coordinates of our point into our model, which we'll just write here as a function f, we can also pass in a time variable that corresponds to the number of steps taken in our random walk (Figure 9.20). If we set t=1.0 at our 100th step, then t=0.99 at our 99th step, and so on. Conditioning our models on time like this turns out to be essential in practice—allowing our model to learn more coarse vector fields for large values of t, and very refined structures as t approaches zero.

After training, we can watch the time evolution of our model (Figure 9.21). We see this really interesting behavior as t approaches 0.7—our learned vector field suddenly transitions from pushing points towards the center of the spiral to pushing points onto the spiral itself—it feels like a phase change.

We're now in a great position to resolve the final mystery of the DDPM paper—how is it that adding random noise at each step while generating images leads to better quality, sharper images (Figures 9.11 and 9.12)?



Figure 9.21 | The time evolution of a diffusion model. After training a diffusion model on trajectories from our spiral and the number of noise steps in each trajectory (t=0 for no noise added, t=1.0 for maximum noise), we can test our model's learned dependence on t. As t approaches 0.7, we see this really interesting "phase change" behavior, where our model switches from pointing to the center of our spiral to pointing to the spiral itself.


t=0.82
t=0.73
t=0.45
t=0.36
t=0.09
t=0.00



Figure 9.22 | One DDPM Step. The DDPM sampling/generation algorithm (Figure 9.11) tells us that when generating images, after each call to our model we should add random noise to the output. On our 2D dataset, this is equivalent to taking a step following our model's outputs (the vector field), and then taking a step in a randomly chosen direction.

Let's follow the path of a single point following the DDPM image generation algorithm. On our 2D dataset, generating an image is equivalent to starting in a random location and working our way back to our spiral. Starting at a randomly chosen location around x=-1.6 and y=1.8, our model's vector field points us towards the spiral (Figure 9.22). Following the DDPM algorithm,[8] we take a small step in the direction returned by our model, and then add scaled random noise which effectively moves our point in a randomly chosen direction. We'll color steps driven by our diffusion model blue and random steps gray. Note that the scale of the random step may seem large, but following the DDPM algorithm the size of the random step comes down as we

8 We're following the general DDPM algorithm here, but using a different noise schedule, see supporting code.



progress. Repeating this process for 64 steps, our particle jumps around quite a bit due to both our learned vector field changing, and our random noise steps, but ultimately lands nicely on our spiral (Figure 9.23).

Repeating this process for a cloud of 256 points, our reverse diffusion process starts out looking like absolute chaos, but converges nicely, with most points landing on our spiral (Figure 9.24).

Now what happens if we remove the noise addition steps?

Running our reverse diffusion process again without the random noise step, all our points quickly move to the center of our spiral, and then make their way towards a single inside edge of the spiral.

Figure 9.23 | DDPM generation. Following the DDPM algorithm, we iteratively take a step following our model's output (blue lines), then a step in a random direction (gray lines). Here we're taking 64 steps. Our vector field changes as we progress, moving our point more towards the fine structure of our spiral. Finally, note that following the DDPM algorithm, we reduce the size of our noise steps as we progress. After 64 steps our point lands nicely on our spiral.



This result can help us make sense of why we saw a blurry sad tree when we removed this random noise step from our Stable Diffusion image generation process (Figure 9.12). Instead of capturing our full spiral distribution as we did when we included a noise step, all of our generated points end up close to the center or average of our spiral. In the space of images, the average or middle of multiple images looks blurry. Conceptually, we can imagine different parts of our spiral corresponding to different images of trees in the desert, and when we remove the random noise steps from our generation process, our generated images end up in the center or average of these images, which looks like a blurry mess (Figure 9.23). Note the analogy between our toy dataset and high dimensional image dataset breaks down a bit here—if all the points on our spiral correspond to realistic images, since our generated points do end up landing on our 2D spiral, we would expect these generated images to still look like real images, but with less diversity than we would likely want. However, in the high dimensional space of images, it appears that our image generation process doesn't quite make it to the manifold of realistic images, resulting in a blurry non realistic image.

This prediction of the average is not a coincidence. It turns out that we can show mathematically that our model learns to point towards the mean of our dataset, conditioned on our input point and time in the diffusion process. One way to arrive at this result is to show that given that the noise we add in our forward process is Gaussian, for sufficiently small step size our reverse process will also follow a Gaussian distribution, where our model learns



Figure 9.24 | Removing the noise steps. The left panel shows the DDPM image generation process with random noise steps in place. Paths are chaotic but end up in a nice spiral. The right panel shows the same process but with the random steps removed. Paths are much smoother because they simply follow the learned vector field (Figure 9.21), but instead of fully capturing our spiral shape, all our points end up in a small neighborhood.



Figure 9.25 | Without noise steps we end up at the average. When we turn off the random noise steps when generating images, we end up with a sad, blurry tree. When we turn off the random noise steps on our 2D toy dataset, all our points end up near the center/average of our dataset. In both cases, adding random noise along the way allows our generation process to avoid just "predicting the mean".



Figure 9.26 | Our model learns the average. Given that our noise addition process uses zero mean Gaussian noise, we can show [see Nakkiran et al. 2024] that for sufficiently small step sizes, our reverse process also follows a normal distribution, where our model learns the mean of the distribution. To run our process backwards, we need to sample from this distribution, which we can do by adding zero mean Gaussian noise to our model's predicted mean. This is precisely what the DDPM generation algorithm does!

the mean of that distribution [Figure 9.26, see Nakkiran et al. 2024 for proof]. Since our model just predicts the mean of our normal distribution of images at each step, to actually sample from this distribution we need to add zero mean Gaussian noise to our model's predicted mean value, which is precisely what the DDPM image generation process does when we add random noise after each step.[9]

We can see this mean learning behavior most clearly early in our reverse diffusion process when t is close to one and training points are far from our spiral. Our model's vector field points to the center or average of the dataset (Figure 9.21).

So adding random noise during image generation falls nicely out of theory and in practice prevents all our points from landing near the average at the center of our spiral dataset.

The DDPM paper put diffusion models on the map as a viable method of generating images, but the diffusion approach did not immediately see widespread adoption. A key issue with the DDPM approach at the time was the high compute demands of the large number of steps required to generate high quality images—since each step required a complete pass through a potentially very large neural network.

A few months later a pair of papers from teams at Stanford and Google showed that it's remarkably possible to generate high quality images without actually adding random noise at all during the generation process, significantly reducing the number of steps required [J. Song et al. 2020, Y. Song et al. 2020]

The DDPM image generation processes we've been looking at can be expressed using a special type of differential equation called a *stochastic differential equation*:[10]

$$\mathrm{d}\mathbf{x} = [\mathbf{f}(\mathbf{x}, t) - g(t)^2 \nabla_{\mathbf{x}} \log p_t(\mathbf{x})]\mathrm{d}t + g(t)\mathrm{d}\bar{\mathbf{w}}$$



The first term (blue) represents the motion of our point driven by our model's vector field, the second term (gray) represents the random motions of our point, and these terms are added together to produce our point's overall motion dx (black).

From here, we can consider how the distribution of all our points evolves over time, where the motion of each point is governed by this stochastic differential equation. This problem has been well studied in physics—using a key result from statistical mechanics known as the Fokker-Planck equation, the Google Brain team showed that there's another differential equation, this time an ordinary differential equation with no random component—that results in exactly the same resulting distribution of points as our stochastic differential equation.

9 Said differently, diffusion models learn to predict the mean/expectation, not actual samples/images

10 Note that we're switching from discrete to continuous time, effectively letting $\Delta t \to 0$.



Figure 9.28 | DDPM (left) vs DDIM (right). Remarkably, the DDIM generation algorithm is able to generate the same resulting distribution of points, without adding any random noise along the way.



Figure 9.27 | A new way to generate. Following [J. Song et al. 2020, Y. Song et al. 2020], there's an ordinary differential equation (ODE), with no stochastic/random component, that leads to the same distribution of points! We can turn this equation into a new generation/update rule, which looks similar to our DDPM update rule, but does not include a random noise step, and has adjusted step size. See [C. Yuan, Diffusion models from scratch, from a new theoretical perspective], for a derivation.



This result gives us a new algorithm for generating images using our model's learned vector fields that does not require taking random steps along the way (Figure 9.27). Exactly how our ordinary differential equation maps to an image generation algorithm is a bit technical[11], but the key result is that we end up with something that looks very similar to our DDPM image generation process, but without the random noise addition at each step, and with a new scaling for the sizes of steps we take—this approach is generally known as DDIM.

The scaling of our step sizes, and especially how these step sizes vary throughout our reverse diffusion is critical in practice. When we just removed the random noise steps from our DDPM generation algorithm earlier, all of our points ended up near the mean of our distribution, and we saw blurry results for our generated images (Figure 9.24, right). Switching to our DDIM approach, we now have a smaller scaling for our step sizes that allow our trajectories to better follow the contour lines of our vector field, and land nicely on the correct spiral distribution (Figure 9.28). And applying our DDIM algorithm to our tree in the desert example, we're able to now generate nice results (Figure 9.29).

Figure 9.29 | DDPM (top) vs DDIM (bottom). Both DDPM and DDIM are capable of generating high quality images.

Comparing to our original DDPM algorithm that included random steps, DDIM remarkably does not require any changes to the model training, but is able to generate high quality images in significantly fewer steps, completely deterministically.

Note that the theory does not tell us that individual images or points on our spiral will be the same—this isn't possible since our paths through space are so different—but instead that our final distribution of points

11 See C. Yuan, *Diffusion models from scratch, from a new theoretical perspective*

or images will be the same regardless of whether we use the stochastic DDPM or deterministic DDIM algorithm.

The Wan video generation model we saw earlier (Figure 9.2) uses a generalization of the DDIM approach called Flow Matching.

9.3 Conditioning and Guidance

By early 2021, it was clear that diffusion models were capable of generating high quality images, and thanks to image generation methods like DDIM, it was possible to generate these images without using enormous amounts of compute. However, our ability to steer the diffusion process using text prompts was still very limited.

Earlier, we saw how CLIP was able to learn a powerful shared representation of images and text by concurrently training image and text encoder models—however, these models only go one way, converting text or images into embedding vectors (Figure 9.30).

These two problems potentially fit together in an interesting way. Diffusion models are able to potentially reverse the CLIP image encoder, generating high quality images, and the output vector of the CLIP text encoder could be used to guide our diffusion model towards the images or videos we want. The high level idea here is that we would pass in some text into the CLIP text encoder to generate an embedding vector, and then use the embedding vector to steer the diffusion process towards the image or video of what our prompt describes.

A team at OpenAI did exactly this in early 2022, using image and caption pairs to train a diffusion model to invert the CLIP image encoder [Ramesh et al. 2022]. Their approach yielded an incredible level of prompt adherence, capturing an unprecedented level of detail from input text. The team called their method unCLIP, but their model is better known under its commercial name, Dall-E 2.

But how do we actually use the embedded text vectors from models like CLIP to steer the diffusion process? One option is to simply pass in our text vector as another input to our diffusion model, and train as we normally would to remove noise. If we train our diffusion model using image/caption pairs as the OpenAI team did, the idea is that the model will learn to use the text information to more accurately remove the noise from images, since it now has more context about the image that it's learning to denoise.

This technique is called conditioning—we used a similar approach earlier when we conditioned our toy diffusion model on the number of time steps elapsed in the diffusion process, allowing the model to learn coarse structure for large values of t, and finer structures as our training samples get closer and closer



Figure 9.30 | Inverting the CLIP image encoder. As we saw earlier in this chapter, CLIP learns a powerful shared representation between images and text, but can map from images and text to embedding vectors, not the other way. Diffusion models offer a path forward, allowing us to create images. However, as we've seen, the diffusion process alone gives us no explicit control of the actual images we generate. Remarkably, it turns out that we can use the text embedding vectors from CLIP to steer the diffusion process towards the images we want. One way to do this is to simply make the embedded text vector available at training time, giving the model extra context about what the image is. When it comes time to generate images, we can pass in the prompt of what we want to generate (e.g. "a photo of a cat"), and remarkably, the model will use this information to generate images of cats. This process is called conditioning.

to our original spiral (Figure 9.20).

Interestingly, there turns out to be a variety of ways we can pass in the text vector into our diffusion model—some approaches use a mechanism called cross-attention to couple image and text information, other approaches simply add or append the embedded text vector to the diffusion model's input, and some approaches pass in the text information in multiple ways at once.[12]

Now, it turns out that conditioning alone is not enough to achieve the level of prompt adherence we see with models like Dall-E 2. If we take the Stable Diffusion tree in the desert example we've been experimenting with, and only condition the model on our text inputs (Figure 9.31)—the model no longer gives us everything we ask for—we get a shadow and a desert— but no tree! Note

12 Interestingly, it was later discovered that our text encoder does not have to come from a shared text/image model like CLIP, but can instead be an encoder trained only on language data, as we would see in LLMs. See [Saharia et al. 2022].



Figure 9.31 | Conditioning alone is not enough. If we take the Stable Diffusion model we've been experimenting with, and only use conditioning to control the diffusion process, we get a desert and shadow, but no tree! We need one more big idea to really control the diffusion process with language. Image on left created with Hugging Face: stabilityai/stable-diffusion-2-1, DDIMScheduler, guidance_scale=1.0.

that Stable Diffusion was developed by a team at Heidelberg University around the same time as Dall-E 2 and works in a similar way, but is open source. [Rombach et al. 2022]

There's one more powerful idea we need to effectively steer our diffusion models. We can see this idea in action by returning to our toy dataset one last time. If our overall spiral corresponds to realistic images, then different sections of our spiral may correspond to different types of images—let's say the inner part is images of people, the middle part is images of dogs, and the outer part is different images of cats (Figure 9.32).

Now, let's train the same diffusion model we trained earlier, but in addition to passing in the starting coordinates and time of our diffusion process, we'll also pass in the point's class—person, dog, or cat. This extra signal should allow our model to steer points to the right section of our spiral, based on each point's class. Running our generation process after assigning person, dog, or cat labels to each point, we see that we're able to recover the overall structure of our dataset, but the fit is not great, and we see some confusion here between people and dogs (Figure 9.34).

Part of the problem here is that we're asking our model to simultaneously learn to point towards our overall spiral of



Figure 9.32 | One more spiral, this time with three parts. Let's break our spiral into three separate classes. These could correspond to, for example, images of people, dogs, and cats. Now can we steer our diffusion process to land on the part of the spiral that we want?



Figure 9.33 | Class conditioning. Earlier in the chapter, we saw how passing in the time of the diffusion process helped our model adapt its behavior to the noise level in a given example. We can use the same approach here, passing in one of three classes during training, we can train our model to direct our points to the correct section of the spiral.



Figure 9.34 | Works, but not great. After training our model with class information (person=purple, dog=yellow, cat=blue), we're able to generally recover the structure of Fgure 9.32, but our fit is not as precise as we've seen before, and there's some overlap between our person and dog data. These results are analogous to the "conditioning only" results in 9.31. In both cases we only conditioned our model on class/text information.

realistic images and towards a specific class on our spiral. If we consider the cat point for example in Figure 9.35, it starts off heading towards the center of the spiral, and as our blue class-conditioned vector field shifts to point towards the outer cat region of our spiral, our point moves towards the cat part of our spiral, but doesn't quite make it. The modeling task of generally matching our overall spiral has overpowered our model's ability to move our point in the direction of a specific class.

Now, is there a way we can decouple and maybe even control these two factors? Remarkably, it turns out we can. The trick is to leverage the differences between an unconditional model that is not trained on specific classes, and a model that is conditioned on specific classes. We could do this by training two separate models, but in practice it's more efficient to just leave out the class information for a subset of examples during training. We now have the option of effectively passing in no class or text information into our model, and getting back a vector field that points to our data in general, not toward specific classes.

$$f(x, t, \text{cat})$$

CONDITIONAL MODEL

$$f(x, t, \text{no class})$$

UNCONDITIONAL MODEL

We can visualize these two vector fields together—the brown vectors in Figure 9.36 show where our diffusion model points when we don't pass in any class information, and the blue vectors point in the direction when our model is conditioned on the cat class. For larger values of our diffusion time variable when our training data is far from our spiral (left panel), our two vector fields basically point in the same direction, but as time approaches zero, our vector fields diverge, with our cat-conditioned vector field pointing more towards the outer cat portion of our spiral (Right panel).



Figure 9.35 | Getting Stuck. The class-conditioned vector field learned by our model has to both point to our spiral and to individual classes on our spiral. This blue (cat) test point gets pulled into the center of our spiral, and as time advances our learned vector field flips to push points towards the outer blue (cat) portion of our spiral, this flip comes too late for our point however, and it isn't able to reach the outer part of our spiral.



Figure 9.36 | Conditional (blue) and unconditional vector fields (brown). When we pass in class information, in this case the class "cat", our diffusion model points in a different direction (blue arrows), relative to the model's predicted directions when no class information is present (brown arrows). This difference in direction also depends on the time of the diffusion process. The left panel shows t=1.0, where our training data is far from its starting point on the spiral. The right panel shows t=0.5, here we start to see our cat class-conditioned blue arrows point specifically to the blue outer cat portion of our spiral, while our brown unconditional arrows mostly point towards the center of the spiral.

Now that we have these two separate directions, we can use their differences to push our points more in the direction of the class we want. Specifically we take our blue class-conditioned vector, and subtract our brown unconditioned vector— this gives us a new vector pointing from the tip of our unconditioned vector to our conditioned vector (Figure 9.37). The idea here is that this direction should point more in the direction of our cat examples, now that we've removed the direction generally pointing towards our data. We can now amplify this direction by multiplying by a scaling factor α, and replace our original conditioned blue vector with a vector pointing in this new direction.[13]

Let's follow the trajectory of the same cat point we saw earlier that didn't quite make it onto our spiral (Figure 9.35). We'll start with a new green point from the same starting location (Figure 9.38). If we use our new green vectors to guide the diffusion process instead of our original blue vectors, the difference between our brown arrows that point towards the center of our spiral and blue vectors that start pointing us back towards the cat part of the spiral is amplified, now guiding our point to land nicely on our spiral.

This approach is called classifier-free guidance [Ho and Salimans 2022].[14] Using our new green vectors to guide a set of cat

13 When implmenting this approach, we add back in our starting point to get our final new vector field value. Some implementations use $f(x, t, cat) + \alpha(f(x, t, cat) - f(x, t))$, and some use $f(x, t) + \alpha(f(x, t, cat) - f(x, t))$. In the first approach, $\alpha=0$ corresponds to no guidance, and in the second, $\alpha=1$ correspond to no guidance, here we're using the second approach.

14 This might seems like a funny or overly complex name! Before classifier-free guidance



Figure 9.37 | Amplifying the differences. As we saw in Figure 9.35, our blue conditional vector field was not able to guide our test point onto the blue portion of our spiral. Now that we have both conditional and unconditional model outputs, we have the option of performing some basic vector algebra using these outputs. If we take $f(x, \text{t}, \text{cat})$-$f(x, \text{t})$, we're left with a new vector that points from the tip of $f(x, \text{t})$ to $f(x, \text{t}, \text{cat})$. Conceptually, we can think of this vector as pointing "more in the direction" of our cat class, now that we've removed the direction pointing generally to our data. From here we can amplify this difference by multiplying by a scaling factor α, which should point us "more in the direction" of our cat class. Note that our final guided value is $f(x, \text{t}) + \alpha(f(x, \text{t}, \text{cat})\text{-}f(x, \text{t}))$, so when α=1.0, our $f(x, \text{t})$ terms cancel and guidance is "turned off".



Figure 9.38 | Classifier-free guidance. Given the same starting point as shown in Figure 9.35, but now following our green arrows, our point is able to nicely arrive on our blue spiral. By amplifying the difference between our conditional and unconditional model outputs, we're able to push our point more in the blue cat direction.



Figure 9.40 | Guidance. Adding classifier-free guidance to our person/dog/cat example (Figure 9.35), our points end up much closer to our spiral, and we see much stronger separation between our classes.

points, we end up with the blue positions shown in Figure 9.40. Comparing to Figure 9.35 (Conditioning only), we see a much tighter fit to our spiral, and more separation between our classes. We also see nice fits for our yellow "dog" points and purple "person" points. Classifier-free guidance works remarkably well, and has become an essential part of many modern image and video generation models.

Earlier we saw that if we only conditioned our Stable Diffusion model, our image would have a desert and a shadow, but no tree that we asked for in the prompt (Figure 9.31). If we add classifier-free guidance to this model, once we reach a guidance scale of α=2, we start to actually see a tiny tree in our images, and the scale and detail of our tree improve as we increase α (Figure 9.41). The fact that this works so well is remarkable to me—as we use guidance to point our Stable Diffusion model's vector field more in the direction of our prompt, our tree literally grows in size and detail in our images.

Our Wan video generation model takes this guidance approach a step further. Instead of subtracting the output of an unconditioned model with no text input, the Wan team uses



Figure 9.39 | Guidance vs. conditioning only. Comparing the conditioning-only blue path from Figure 9.35 to our guided green path from Figure 9.38, we see that guidance now pushes our point nicely to the blue part of our spiral.

became popular, the most succesfuly guidance approach involved using an image classification model to steer diffusion models towards specific classes. Classifier-free guidance was an exciting development, becuase you no longer needed a seperate model to steer the diffusion model!

$\alpha = 1.0$
$\alpha = 1.5$
$\alpha = 2.0$
$\alpha = 3.0$
$\alpha = 4.0$
$\alpha = 5.0$
$\alpha = 6.0$
$\alpha = 7.0$
$\alpha = 8.0$
$\alpha = 9.0$
$\alpha = 10$
$\alpha = 11$
$\alpha = 12$
$\alpha = 13$
$\alpha = 14$
$\alpha = 15$
$\alpha = 16$
$\alpha = 17$
$\alpha = 18$
$\alpha = 25$



what's known as a negative prompt—where they specifically write out all the features they don't want in their image, and then subtract the resulting vector from the model's conditioned output, and amplify the result, steering the diffusion process away from these unwanted features. Their standard negative prompt is fascinating, including features like "extra fingers" and "walking backwards"—and interestingly is actually passed into their text encoder in Chinese. Figure 9.42 shows a frame from a video generated using the same astronaut on a horse prompt we used at the opening of the chapter, but without the negative prompt—it's interesting to see how the parts of the scene get cartoonish and no longer fit together.

Since the publication of the DDPM paper in the summer of 2020, the field has progressed at a blistering pace—leading to the incredible text-to-image and text-to-video models we see today.

Of all the interesting details that make these models tick, the most astounding thing to me is that the pieces fit together at all. The fact that we can just take trained text encoder from CLIP or elsewhere, and use its outputs to actually steer the diffusion process, which itself is highly complex—seems almost too good

Figure 9.42 (Above) | Guidance with Wan2.1. Negative prompts take guidance one step further, literally "subtracting out" what we don't want in an image or video.

Figure 9.41 (Previous page) | Guidance with Stable Diffusion. As we increase the level of guidance used with our Stable Diffusion model (Figure 9.31), our tree literally grows in size and detail in our image!

Figure 9.43 | Midjourney. Frames from various video clips made with Midjourney V7.

to be true. And on top of that, many of these core ideas can be built from relatively simple geometric intuitions that somehow hold in the incredibly high dimensional spaces these models operate in.

The resulting models feel like a fundamentally new class of machine. To create incredibly lifelike and beautiful images and video—you no longer need a camera, you don't need to know how to draw or paint, or know how to use animation software—all you need is language.[15]

15 And a bunch of GPUs lol

9.1 Diffusion - Hat vs No Hat CLIP Example

Reproduces results in Figure 9.8

[1]:
```
import torch
from PIL import Image
import requests
from transformers import AutoProcessor, CLIPModel
import matplotlib.pyplot as plt
import numpy as np
from tqdm import tqdm
```

[2]:
```
device = 'cuda' if torch.cuda.is_available() else 'cpu'
device
```

[2]:
```
'cuda'
```

[3]:
```
model = CLIPModel.from_pretrained("openai/clip-vit-base-patch32").to(device)
processor = AutoProcessor.from_pretrained("openai/clip-vit-base-patch32")
```

SUPPORTING CODE

Full supporting code for this chapter at:
github.com/stephencwelch/ai_book

[4]:
```python
def get_common_objects_and_concepts():
    """Curated list of common objects, animals, concepts, emotions, etc."""
    categories = {
        'objects': [
            'chair', 'table', 'car', 'bicycle', 'bottle', 'cup', 'fork', 'knife', 'spoon',
            'bowl', 'banana', 'apple', 'sandwich', 'orange', 'broccoli', 'carrot', 'pizza',
            'donut', 'cake', 'bed', 'toilet', 'laptop', 'mouse', 'remote', 'keyboard',
            'cell phone', 'book', 'clock', 'scissors', 'teddy bear', 'hair dryer',
            'toothbrush', 'umbrella', 'handbag', 'tie', 'suitcase', 'frisbee', 'skis',
            'snowboard', 'sports ball', 'kite', 'baseball bat', 'baseball glove',
            'skateboard', 'surfboard', 'tennis racket', 'man', 'woman'
        ],
        'animals': [
            'person', 'cat', 'dog', 'horse', 'sheep', 'cow', 'elephant', 'bear', 'zebra',
            'giraffe', 'bird', 'chicken', 'duck', 'eagle', 'owl', 'fish', 'shark', 'whale',
            'dolphin', 'turtle', 'frog', 'snake', 'spider', 'bee', 'butterfly', 'lion',
            'tiger', 'fox', 'wolf', 'rabbit', 'hamster', 'mouse', 'rat'
        ],
        'clothing': [
            'hat', 'cap', 'helmet', 'glasses', 'sunglasses', 'shirt', 't-shirt', 'sweater',
            'jacket', 'coat', 'dress', 'skirt', 'pants', 'jeans', 'shorts', 'shoes',
            'sneakers', 'boots', 'sandals', 'socks', 'tie', 'scarf', 'gloves', 'belt',
            'watch', 'ring', 'necklace', 'earrings', 'bracelet'
        ],
        'emotions': [
            'happy', 'sad', 'angry', 'surprised', 'excited', 'calm', 'peaceful', 'joyful',
            'melancholy', 'nostalgic', 'anxious', 'confident', 'mysterious', 'dramatic',
            'romantic', 'energetic', 'serene', 'tense', 'playful', 'serious'
        ],
        'abstract_concepts': [
            'freedom', 'justice', 'peace', 'war', 'love', 'hate', 'beauty', 'ugliness',
            'truth', 'lie', 'innovation', 'tradition', 'progress', 'chaos', 'order',
            'simplicity', 'complexity', 'elegance', 'roughness', 'sophistication'
        ],
        'colors': [
            'red', 'blue', 'green', 'yellow', 'orange', 'purple', 'pink', 'brown',
            'black', 'white', 'gray', 'silver', 'gold', 'cyan', 'magenta', 'lime',
            'navy', 'maroon', 'olive', 'aqua'
        ],
        'styles': [
            'modern', 'vintage', 'classic', 'contemporary', 'abstract', 'realistic',
            'minimalist', 'ornate', 'rustic', 'elegant', 'casual', 'formal', 'artistic',
            'professional', 'creative', 'traditional', 'futuristic', 'retro'
        ],
        'activities': [
            'running', 'walking', 'jumping', 'dancing', 'singing', 'reading', 'writing',
            'cooking', 'eating', 'sleeping', 'working', 'playing', 'studying', 'exercising',
            'swimming', 'flying', 'driving', 'riding', 'climbing', 'surfing'
        ]
    }

    # Flatten all categories
    all_concepts = []
    for category, items in categories.items():
        if category == "objects":
            items = ['A photo of a ' + w for w in items]
        all_concepts.extend(items)

    return all_concepts, categories
```

[5]:
```
words, categories=get_common_objects_and_concepts()
len(words)
```

[5]:
```
208
```

[6]:
```
image = Image.open('data/me_with_hat.jpeg')
image_2 = Image.open('data/me_no_hat_cropped_1.jpeg')
```

[7]:
```
image.resize((200,200)) #Display smaller version
```

[7]:
```
<PIL.Image.Image image mode=RGB size=200x200>
```

[8]:
```
image_2.resize((200,200))
```

[8]:
```
<PIL.Image.Image image mode=RGB size=200x200>
```

[9]:
```
inputs = processor(images=image, return_tensors="pt").to(device)
with torch.no_grad():
    image_features = model.get_image_features(**inputs)
    image_features = image_features / image_features.norm(dim=-1, keepdim=True)

inputs_2 = processor(images=image_2, return_tensors="pt").to(device)
with torch.no_grad():
    image_features_2 = model.get_image_features(**inputs_2)
    image_features_2 = image_features_2 / image_features_2.norm(dim=-1, keepdim=True)
```

[10]:
```
inputs = processor(text=words[0], return_tensors="pt", padding=True).to(device)
with torch.no_grad():
    text_features = model.get_text_features(**inputs)
    text_features = text_features / text_features.norm(dim=-1, keepdim=True)
```

[11]:
```
batch_size=1024
all_text_features=[]
for i in tqdm(range(int(np.ceil(len(words)/batch_size)))):
    inputs = processor(text=words[i*batch_size:(i+1)*batch_size], return_tensors="pt", padding=True)
    with torch.no_grad():
        text_features = model.get_text_features(**inputs)
        # Normalize the embeddings
        text_features = text_features / text_features.norm(dim=-1, keepdim=True)
        all_text_features.append(text_features)
all_text_features=torch.concat(all_text_features)
```

[11]:
```
100%|██████████| 1/1 [00:00<00:00, 74.24it/s]
```

[12]:
```
all_text_features.shape
```

[12]:
```
torch.Size([208, 512])
```

[13]:
```
similarities = torch.cosine_similarity(image_features-image_features_2, all_text_features, dim=1)
```

[14]:
```
similarities.shape
```

[14]:
```
torch.Size([208])
```

[15]:
```
top_k=10
top_k_indices = similarities.argsort(descending=True)[:top_k]

results = []
for idx in top_k_indices:
    results.append({
        'text': words[idx],
        'similarity': similarities[idx].item()
    })
results
```

[15]:
```
[{'text': 'hat', 'similarity': 0.16496598720550537},
{'text': 'cap', 'similarity': 0.11361426115036011},
{'text': 'helmet', 'similarity': 0.10564661771059036},
{'text': 'angry', 'similarity': 0.060973454266786575},
{'text': 'tense', 'similarity': 0.05931840464472771},
{'text': 'exercising', 'similarity': 0.057576026767492294},
{'text': 'roughness', 'similarity': 0.05686981976032257},
{'text': 'hate', 'similarity': 0.0565527081489563},
{'text': 'A photo of a frisbee', 'similarity': 0.05526324361562729},
{'text': 'A photo of a tennis racket', 'similarity': 0.05416693538427353}]
```

9. Diffusion - Spiral Examples

- Reproduce some of the key "spiral" plots and results shown in the Chapter.
- Making significant use of the excellent `smalldiffusion` library:
  https://github.com/yuanchenyang/smalldiffusion

9.3 Spiral Setup

[1]:
```
import numpy as np
import torch
import matplotlib.pyplot as plt
from torch.utils.data import DataLoader
from smalldiffusion import (
    TimeInputMLP, ScheduleLogLinear, training_loop, samples,
    DatasaurusDozen, Swissroll, ModelMixin
)
from torch.utils.data import Dataset
from tqdm import tqdm
from torch import nn
from pathlib import Path
from PIL import Image

from typing import Optional, Union, Tuple
from itertools import pairwise

def plot_batch(batch):
    batch = batch.cpu().numpy()
    plt.scatter(batch[:,0], batch[:,1], marker='.')
    plt.axis('equal')

def moving_average(x, w):
    return np.convolve(x, np.ones(w), 'valid') / w
```

[2]:
```
batch_size=2130
dataset = Swissroll(np.pi/2, 5*np.pi, 100)
loader = DataLoader(dataset, batch_size=batch_size)
plot_batch(next(iter(loader)))
```

[2]:
```
<Figure size 640x480 with 1 Axes>
```



9.4 Training a model

[3]:
```
schedule = ScheduleLogLinear(N=256, sigma_min=0.01, sigma_max=10)
```

[4]:
```
device='cpu'
epochs=15000
lr=1e-3
model = TimeInputMLP(hidden_dims=(16,128,128,128,128,16))
# model = MLP(hidden_dims=(16,128,128,128,128,16)) #no time conditioning
model.to(device);
optimizer = torch.optim.AdamW(model.parameters(), lr=lr)
loss_func=nn.MSELoss()

losses=[]
for _ in tqdm(range(epochs)):
    for x0 in loader:
        model.train()
        optimizer.zero_grad()

        eps = torch.randn_like(x0)
        sigma = schedule.sample_batch(x0)

        noised_data=x0 + sigma.unsqueeze(-1) * eps
        yhat=model(noised_data.to(device), sigma.to(device), cond=False)
        loss=loss_func(eps.to(device), yhat)
        loss.backward()
        losses.append(loss.item())
        optimizer.step()
```

[4]:
```
100%|██████████████████████████| 15000/15000 [00:50<00:00, 295.99it/s]
```

9.5 Visualize Results - DDPM

[5]:
```
bound=1.5
num_heatmap_steps=30
grid=[]
for i, x in enumerate(np.linspace(-bound, bound, num_heatmap_steps)):
    for j, y in enumerate(np.linspace(-bound, bound, num_heatmap_steps)):
        grid.append([x,y])
grid=torch.tensor(grid).float()
```

[6]:
```
# Generalizes most commonly-used samplers:
#   DDPM       : gam=1, mu=0.5
#   DDIM       : gam=1, mu=0
#   Accelerated: gam=2, mu=0


model.to(device);
gam=1
mu=0.5 #0.5 is DDPM
cfg_scale=0.0
cond=None
sigmas=schedule.sample_sigmas(256)
xt_history=[]
heatmaps=[]

with torch.no_grad():
    model.eval();
    xt=torch.randn((batch_size,) + model.input_dims)*sigmas[0]

    for i, (sig, sig_prev) in enumerate(pairwise(sigmas)):
        eps_prev, eps = eps, model.predict_eps_cfg(xt, sig.to(xt), cond, cfg_scale)
        sig_p = (sig_prev/sig**mu)**(1/(1-mu))
        eta = (sig_prev**2 - sig_p**2).sqrt()
        xt = xt - (sig - sig_p) * eps + eta * model.rand_input(xt.shape[0]).to(xt)
        xt_history.append(xt.numpy())
        heatmaps.append(model.forward(grid, sig, cond=None))
xt_history=np.array(xt_history)
```

[7]:
```
xt_history.shape
```

[7]:
```
(256, 2130, 2)
```

[8]:
```
i=255 #Reverse Diffusion Process timestep
plt.clf()
fig=plt.figure(0, (7,7))

heatmap_norm=torch.nn.functional.normalize(heatmaps[i], p=2, dim=1)
plt.quiver(grid[:,0], grid[:,1], -heatmap_norm[:,0], -heatmap_norm[:,1], alpha=0.4,  scale=40)

for j in range(512): #Just do a subset of trajectories
    plt.plot(xt_history[np.maximum(i-64, 0):i+1,j,0], xt_history[np.maximum(i-64, 0):i+1,j,1], '-')
    plt.scatter(xt_history[i,j,0], xt_history[i,j,1], alpha=0.7, s=8)

viz_bounds=1.8
plt.xlim([-viz_bounds, viz_bounds]);  plt.ylim([-viz_bounds, viz_bounds]);
```

[8]:



9.6 DDPM with noise steps removed

All points end up near center/average of spiral

[9]:
```
# Generalizes most commonly-used samplers:
#   DDPM       : gam=1, mu=0.5
#   DDIM       : gam=1, mu=0
#   Accelerated: gam=2, mu=0


model.to(device);
gam=1
mu=0.5 #0.5 is DDPM
cfg_scale=0.0
cond=None
sigmas=schedule.sample_sigmas(256)
xt_history=[]
heatmaps=[]

with torch.no_grad():
    model.eval();
    xt=torch.randn((batch_size,) + model.input_dims)*sigmas[0]

    for i, (sig, sig_prev) in enumerate(pairwise(sigmas)):
        eps_prev, eps = eps, model.predict_eps_cfg(xt, sig.to(xt), cond, cfg_scale)
        sig_p = (sig_prev/sig**mu)**(1/(1-mu))
        eta = (sig_prev**2 - sig_p**2).sqrt()
        xt = xt - (sig - sig_p) * eps #+ eta * model.rand_input(xt.shape[0]).to(xt) #no noise add
        xt_history.append(xt.numpy())
        heatmaps.append(model.forward(grid, sig, cond=None))
xt_history=np.array(xt_history)
```

[10]:
```
i=255 #Reverse Diffusion Process timestep
plt.clf()
fig=plt.figure(0, (7,7))

heatmap_norm=torch.nn.functional.normalize(heatmaps[i], p=2, dim=1)
plt.quiver(grid[:,0], grid[:,1], -heatmap_norm[:,0], -heatmap_norm[:,1], alpha=0.4,  scale=40)

for j in range(512): #Just do a subset of trajectories
    plt.plot(xt_history[np.maximum(i-64, 0):i+1,j,0], xt_history[np.maximum(i-64, 0):i+1,j,1])
    plt.scatter(xt_history[i,j,0], xt_history[i,j,1], alpha=0.7, s=8)

viz_bounds=1.8
plt.xlim([-viz_bounds, viz_bounds]);  plt.ylim([-viz_bounds, viz_bounds]);
```

[10]:



9.7 DDIM

[11]:
```
# Generalizes most commonly-used samplers:
#   DDPM       : gam=1, mu=0.5
#   DDIM       : gam=1, mu=0
#   Accelerated: gam=2, mu=0

model.to(device);
gam=1
mu=0.00
cfg_scale=0.0
cond=None
sigmas=schedule.sample_sigmas(256)
xt_history=[]
heatmaps=[]

with torch.no_grad():
    model.eval();
    xt=torch.randn((batch_size,) + model.input_dims)*sigmas[0]

    for i, (sig, sig_prev) in enumerate(pairwise(sigmas)):
        eps_prev, eps = eps, model.predict_eps_cfg(xt, sig.to(xt), cond, cfg_scale)
        # eps_av = eps * gam + eps_prev * (1-gam)  if i > 0 else eps
        sig_p = (sig_prev/sig**mu)**(1/(1-mu)) # sig_prev == sig**mu sig_p**(1-mu)
        eta = (sig_prev**2 - sig_p**2).sqrt()
        xt = xt - (sig - sig_p) * eps + eta * model.rand_input(xt.shape[0]).to(xt)
        xt_history.append(xt.numpy())
        heatmaps.append(model.forward(grid, sig, cond=None))

xt_history=np.array(xt_history)
```

[12]:
```
i=255

plt.clf()
fig=plt.figure(0, (7,7))

heatmap_norm=torch.nn.functional.normalize(heatmaps[i], p=2, dim=1)
plt.quiver(grid[:,0], grid[:,1], -heatmap_norm[:,0], -heatmap_norm[:,1], alpha=0.4,  scale=40)

for j in range(512): #Just do a subset of trajectories
    plt.plot(xt_history[np.maximum(i-64, 0):i+1,j,0], xt_history[np.maximum(i-64, 0):i+1,j,1])
    plt.scatter(xt_history[i,j,0], xt_history[i,j,1], alpha=0.7, s=8)

viz_bounds=1.8
plt.xlim([-viz_bounds, viz_bounds]);  plt.ylim([-viz_bounds, viz_bounds])
```

[12]





TOP MATCHES	COSINE SIMILARITY
hat	0.1652
cap	0.1129
helmet	0.1064
angry	0.0611
roughness	0.0602
exercising	0.0602
tense	0.0599
tennis racket	0.0565
writing	0.0562
hate	0.0551
frisbee	0.0550
sports ball	0.0549
spider	0.0540
sneakers	0.0531
navy	0.0521
shark	0.0507
mysterious	0.0507

Figure 9.8 | A powerful shared vector space. If we subtract the vector corresponding to me not wearing a hat from the vector of me wearing a hat, the most similar word vector to this difference vector is "hat"!



Figure 9.10 | Nope. One mental image of how diffusion models work is that these models learn to remove noise "one step at a time". During training, we add noise to our images one step at a time, then train our model to reverse this process one step at a time. When it comes time to make a new prediction, we start with pure noise (Panel E), and iteratively pass this image through our network until we have a nice image. As we'll see, this is not how diffusion models work in practice.

9. DIFFUSION | EXERCISES

9.1 How does CLIP learn a shared representation between text and images?

9.2 What is potentially surprising about the results presented in Figure 9.8?

9.3 What's wrong with the picture of diffusion presented in Figure 9.10?

9.4 What is the connection between diffusion models and Brownian motion?

9.5 Why is it more effective in practice to have our model learn to reverse the net/total motion of the random walk instead of a single step (Figure 9.18)?

9.6 Why is it helpful to condition diffusion models on the number of elapsed steps/time in the diffusion process?

9.7 In the DDPM image generation process, why is it helpful to add random noise after each step?

9.8 Compare and contrast DDPM and DDIM generation methods.

9.9 Why might conditioning alone not be sufficient to control our image/video generation process via text inputs?

9.10 How does classifier-free guidance give us more control over the generation process?

9.11 In many previous chapters of this book, we considered autoregressive models (e.g. language models that predict a single token at a time). Compare and contrast diffusion and autoregression.

9.12a Consider the vectors A=[4 1], B=[1 4]. Using trigonometry, find the angles between A and the x-axis θ_A, and B and the x-axis θ_B.



9.12b Compute the angle between vectors θ_B-θ_A.

$$\text{Cosine Similarity} = \frac{A \cdot B}{||A||_2||B||_2} = \cos(\theta)$$

$$||A||_2 = \sqrt{A_1^2 + A_2^2 + ... + A_n^2}$$

9.12c Compute the cosine similarity between A and B using the formula given in the figure to the right. Does your result match your result from 9.12b?



9.13a Consider the vectors A=[4 1], B=[-1 4]. Using trigonometry, find the angles between A and the x-axis θ_A, and B and the x-axis θ_B. Plot on the figure to the left.

9.13b Compute the angle between vectors θ_B-θ_A.

$$\text{Cosine Similarity} = \frac{A \cdot B}{||A||_2||B||_2} = \cos(\theta)$$

$$||A||_2 = \sqrt{A_1^2 + A_2^2 + ... + A_n^2}$$

9.13c Compute the cosine similarity between A and B using the formula given in the figure to the left. Does your result match your results from 9.13b?



9.14 The cosine similarities shown in Figures 9.8 and 9.9 have maximum values of 0.1652 and 0.2784, respectively. Given that the cosine similarity metric has a maximum value of cos(0)=1, these values may seem small. Let's explore this idea. The histograms above show how the cosine similarity between random vectors changes as we increase the dimension of our vectors. In each subplot, we're randomly choosing a reference vector, measuring its cosine similarity to 5000 other randomly chosen vectors of the same dimension, and plotting a histogram of the results. As we can see, these distributions change significantly as we increase the dimension of our vectors. What trend do you notice? What does this tell us about our results in Figures 9.8 and 9.9? What does this tell us in general about the angle between two randomly chosen vectors in high dimensional space?

9.15 Pull and run `github.com/stephencwelch/ai_book/9_diffusion_clip.ipynb`. Taking your own pictures or using images from the internet, replace the "hat" and "no hat" images with images that show an object or concept of your choice. Note that you don't have to subtract your embedding vectors necessarily, you could also add or scale them. Does CLIP operate on "concepts" as you might expect? How reliable/ consistent were your results?

9.16 Pull and run `github.com/stephencwelch/ai_book/9_stable_diffusion_guidance.ipynb`. Experiment with different prompts and guidance scales. Do you see similar behavior to Figure 9.41, where increased guidance results in "more of what you asked for" in your prompt?

REFERENCES

Chapter 1

[Abu-Mostafa et al. 2012] Abu-Mostafa, Y. S., Magdon-Ismail, M., & Lin, H. T. (2012). *Learning from data* (Vol. 4, p. 4). New York: AML-Book.

[Brown et al. 2020] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., … & Amodei, D. (2020). Language models are few-shot learners. *Advances in Neural Information Processing Systems,* 33, 1877–1901.

[Crevier 1993] Crevier, D. (1993). *AI: The tumultuous history of the search for artificial intelligence.* Basic Books.

[Hay et al. 1960] Hay, J. C., Lynch, B. E., & Smith, D. R. (1960, February 15). *Mark I Perceptron operators' manual (Project PARA)* (Contract No. Nonr-2381(00)). Systems Requirements Department.

[Mason et al. 1958] Mason, H., Stewart, D., & Gill, B. (1958, December 6). Rival. *The New Yorker,* 44.

[Minsky and Papert 1969] Minsky, M., & Papert, S. (1969). *An introduction to computational geometry.* Cambridge, MA: MIT Press, 479(480), 104.

[Talking Nets 1999] Nets, T. (1999). Talking nets: An oral history of neural networks. *Trends in Cognitive Sciences,* 3(3).

[New Navy device 1958] *New Navy device learns by doing.* (1958, July 8). *The New York Times.*

[Novikoff 1962] Novikoff, A. B. (1962, April). On convergence proofs on perceptrons. In *Proceedings of the Symposium on the Mathematical Theory of Automata* (Vol. 12, No. 1, pp. 615–622).

[Olazaran 1993] Olazaran, M. (1993). A sociological history of the neural network controversy. *Advances in Computers,* 37, 335–425.

[Patel and Wong 2023] Patel, D., & Wong, G. (2023, July 10). GPT-4 architecture, infrastructure, training dataset, costs, vision, MoE – Demystifying GPT-4: The engineering trade-offs that led OpenAI to their architecture. *SemiAnalysis.* https://semianalysis.com/2023/07/10/gpt-4-architecture-infrastructure

[Prince 2023] Prince, S. J. (2023). *Understanding deep learning.* MIT Press.

[Rumelhart and McClelland 1987] Rumelhart, D. E., & McClelland, J. L. (1987). *Parallel distributed processing,* Vol. 1: *Explorations in the microstructure of cognition: Foundations.* MIT Press.

[Valiant 2013] Valiant, L. (2013). *Probably approximately correct: Nature's algorithms for learning and prospering in a complex world.* Basic Books.

[Widrow 1962] Widrow, B. (1962). Generalization and information storage in networks of adaline neurons. *Self-Organizing Systems,* 435–461.

[Widrow 2005] Widrow, B. (2005). Thinking about thinking: The discovery of the LMS algorithm. *IEEE Signal Processing Magazine,* 22(1), 100–106.

[Widrow and Lehr 1990] Widrow, B., & Lehr, M. A. (1990). 30 years of adaptive neural networks: Perceptron, Madaline, and backpropagation. *Proceedings of the IEEE,* 78(9), 1415–1442.

[Cat and Dog Face Dataset] *Cat and Dog Face Dataset.* https://www.kaggle.com/datasets/andrewmvd/animal-faces

Chapter 2

[Nets 1999] Nets, T. (1999).*Talking nets: An oral history of neural networks.* Trends in Cognitive Sciences, 3(3).

[Li et al. 2018] Li, H., Xu, Z., Taylor, G., Studer, C., & Goldstein, T. (2018). *Visualizing the loss landscape of neural nets.* Advances in Neural Information Processing Systems, 31.

Chapter 3

[Werbos 1994] Werbos, P. J. (1994). *The roots of backpropagation: From ordered derivatives to neural networks and political forecasting.* United Kingdom: Wiley.

[Olazaran 1996] Olazaran, M. (1996). *A sociological study of the official history of the perceptrons controversy.* Social Studies of Science, 26(3), 611–659.

[Widrow 1962] Widrow, B. (1962). *Generalization and information storage in networks of adaline neurons.* In Self-Organizing Systems (pp. 435–461).

Chapter 4

[Liang and Srikant 2016] Liang, S., & Srikant, R. (2016). *Why deep neural networks for function approximation?* arXiv preprint arXiv:1610.04161.

[Prince 2023] Prince, S. J. (2023). *Understanding deep learning.* MIT Press.

[Hanin and Rolnick 2019] Hanin, B., & Rolnick, D. (2019). *Deep ReLU networks have surprisingly few activation patterns. Advances in Neural*

Information Processing Systems, 32.

[Hanin and Rolnick 2019b] Hanin, B., & Rolnick, D. (2019, May). *Complexity of linear regions in deep networks.* In *International Conference on Machine Learning* (pp. 2596–2604). PMLR.

[Fan et al. 2023] Fan, F. L., Huang, W., Zhong, X., Ruan, L., Zeng, T., Xiong, H., & Wang, F. (2023). *Deep ReLU networks have surprisingly simple polytopes.* arXiv preprint arXiv:2305.09145.

Chapter 5

[Brown et al. 2020] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., … & Amodei, D. (2020). *Language models are few-shot learners. Advances in Neural Information Processing Systems,* 33, 1877–1901.

[Carter et al. 2019] Carter, S., et al. (2019). *Activation Atlas. Distill.*

[Goodfellow et al. 2016] Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep learning.* Cambridge: MIT Press.

[Krizhevsky et al. 2012] Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). *Imagenet classification with deep convolutional neural networks. Advances in Neural Information Processing Systems,* 25.

[Langston 2020] Langston, J. (2020, May 19). *Microsoft announces new supercomputer, lays out vision for future AI work. Microsoft News.* https://news.microsoft.com/source/features/innovation/openai-azure-supercomputer/

[McGuinness n.d.] McGuinness, P. (n.d.). *GPT-4 details revealed. Substack.* https://patmcguinness.substack.com/p/gpt-4-details-revealed

[Mikolov et al. 2013] Mikolov, T., Chen, K., Corrado, G., & Dean, J. (2013). *Efficient estimation of word representations in vector space.* arXiv preprint arXiv:1301.3781.

[Olah et al. 2017] Olah, C., et al. (2017). *Feature Visualization. Distill.*

[Patel and Wong 2023] Patel, D., & Wong, G. (2023, July 10). *GPT-4 architecture, infrastructure, training dataset, costs, vision, MoE. Semi-Analysis Newsletter.* https://newsletter.semianalysis.com/p/gpt-4-architecture-infrastructure

[Sanders 2022] Sanders, T. (2022, December 16). *How to count tokens with Tiktoken. OpenAI Cookbook.* https://cookbook.openai.com/examples/how_to_count_tokens_with_tiktoken

[Templeton et al. 2024] Templeton, A., et al. (2024). *Scaling Monosemanticity: Extracting interpretable features from Claude 3 Sonnet. Transformer Circuits Thread.*

[Turner 2023] Turner, R. E. (2023). *An introduction to transformers.* arXiv preprint arXiv:2304.10557.

Chapter 6

[Kaplan et al. 2020] Kaplan, J., McCandlish, S., Henighan, T., Brown, T. B., Chess, B., Child, R., … & Amodei, D. (2020). *Scaling laws for neural language models.* arXiv preprint arXiv:2001.08361.

[Brown et al. 2020] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., … & Amodei, D. (2020). *Language models are few-shot learners. Advances in Neural Information Processing Systems,* 33, 1877–1901.

[Goodfellow et al. 2016] Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep learning.* Cambridge: MIT Press.

[OpenAI 2023] OpenAI. (2023). *GPT-4 technical report.* arXiv preprint arXiv:2303.08774.

[Henighan et al. 2020] Henighan, T., Kaplan, J., Katz, M., Chen, M., Hesse, C., Jackson, J., … & McCandlish, S. (2020). *Scaling laws for autoregressive generative modeling.* arXiv preprint arXiv:2010.14701.

[Shah 2021] Shah, R. (2021, March 5). *AN #140: Theoretical models that predict scaling laws. LessWrong.* https://www.lesswrong.com/posts/Yt5wAXMc7D2zLpQqx/an-140-theoretical-models-that-predict-scaling-laws

[Sharma and Kaplan 2020] Sharma, U., & Kaplan, J. (2020). *A neural scaling law from the dimension of the data manifold.* arXiv preprint arXiv:2004.10802.

[Bahri et al. 2024] Bahri, Y., Dyer, E., Kaplan, J., Lee, J., & Sharma, U. (2024). *Explaining neural scaling laws. Proceedings of the National Academy of Sciences,* 121(27), e2311878121.

[Hoffmann et al. 2022] Hoffmann, J., Borgeaud, S., Mensch, A., Buchatskaya, E., Cai, T., Rutherford, E., … & Sifre, L. (2022). *Training compute-optimal large language models.* arXiv preprint arXiv:2203.15556.

Chapter 7

[Belrose et al. 2023] Belrose, N., Ostrovsky, I., McKinney, L., Furman, Z., Smith, L., Halawi, D., Biderman, S., & Steinhardt, J. (2023). *Eliciting latent predictions from transformers with the tuned lens.* arXiv. https://arxiv.org/abs/2303.08112

[Bricken et al. 2023] Bricken, T., et al. (2023). *Towards Monosemanticity: Decomposing language models with dictionary learning. Transformer Circuits Thread.*

[Elhage et al. 2022] Elhage, N., et al. (2022). *Toy Models of Superposition. Transformer Circuits Thread.*

[He et al. 2016] He, K., Zhang, X., Ren, S., & Sun, J. (2016). *Deep residual learning for image recognition.* In *Proceedings of the IEEE Conference*

on Computer Vision and Pattern Recognition (pp. 770–778).

[Lieberum et al. 2024] Lieberum, T., Rajamanoharan, S., Conmy, A., Smith, L., Sonnerat, N., Varma, V., … & Nanda, N. (2024). *Gemma Scope: Open sparse autoencoders everywhere all at once on Gemma 2.* arXiv preprint arXiv:2408.05147.

[Nguyễn 2024] Nguyễn, T. (2024, June 17). *Logit prisms: Decomposing transformer outputs for mechanistic interpretability.* https://neuralblog.github.io/logit-prisms/

[nostalgebraist 2020] nostalgebraist. (2020, September 6). *Interpreting GPT: The logit lens. LessWrong.* https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens

[Olah and Anthropic Interpretability Team 2024] Olah, C., & Anthropic Interpretability Team. (2024, July). *Circuits updates – July 2024. Transformer Circuits Thread.* https://transformer-circuits.pub/2024/july-update/

[Templeton et al. 2024] Templeton, A., et al. (2024). *Scaling Monosemanticity: Extracting interpretable features from Claude 3 Sonnet. Transformer Circuits Thread.*

Chapter 8

[Guo et al. 2025] Guo, D., Yang, D., Zhang, H., Song, J., Zhang, R., Xu, R., … & He, Y. (2025). *DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning.* arXiv preprint arXiv:2501.12948.

[Liu et al. 2024] Liu, A., Feng, B., Wang, B., Wang, B., Liu, B., Zhao, C., … & Xu, Z. (2024). *DeepSeek-V2: A strong, economical, and efficient mixture-of-experts language model.* arXiv preprint arXiv:2405.04434.

[Epoch AI 2025] Epoch AI. (2025, January). *How has DeepSeek improved the Transformer architecture?* https://epoch.ai/gradient-updates/how-has-deepseek-improved-the-transformer-architecture

Chapter 9

[Becker et al. 2025] Becker, C., Lukoianov, A., Scarvelis, C., & Yuan, C. (2025). *6.S183: A practical introduction to diffusion models / IAP 2025.* MIT EECS. https://www.practical-diffusion.org/

[Ho et al. 2020] Ho, J., Jain, A., & Abbeel, P. (2020). *Denoising diffusion probabilistic models.* arXiv:2006.11239. https://arxiv.org/pdf/2006.11239

[Ho and Salimans 2022] Ho, J., & Salimans, T. (2022). *Classifier-free diffusion guidance.* arXiv:2207.12598. https://arxiv.org/pdf/2207.12598

[Nakkiran et al. 2024] Nakkiran, P., Bradley, A., Zhou, H., & Advani, M. (2024). *Step-by-step diffusion: An elementary tutorial.* arXiv:2406.08929. https://arxiv.org/pdf/2406.08929

[Radford et al. 2021] Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., … & Sutskever, I. (2021). *Learning transferable visual models from natural language supervision.* arXiv:2103.00020. https://arxiv.org/pdf/2103.00020

[Ramesh et al. 2022] Ramesh, A., Dhariwal, P., Nichol, A., Chu, C., & Chen, M. (2022). *Hierarchical text-conditional image generation with CLIP latents.* arXiv preprint arXiv:2204.06125, 1(2), 3.

[J. Song et al. 2020] Song, J., Meng, C., & Ermon, S. (2020). *Denoising diffusion implicit models (DDIMs).* arXiv:2010.02502. https://arxiv.org/abs/2010.02502

[Y. Song et al. 2020] Song, Y., Sohl-Dickstein, J., Kingma, D. P., Kumar, A., Ermon, S., & Poole, B. (2020). *Score-based generative modeling through stochastic differential equations.* arXiv:2011.13456. https://arxiv.org/abs/2011.13456

[Wang and Isola 2020] Wang, T., & Isola, P. (2020, November). *Understanding contrastive representation learning through alignment and uniformity on the hypersphere.* In *International Conference on Machine Learning* (pp. 9929–9939). PMLR.

[Yuan n.d.a] Yuan, C. (n.d.). *Diffusion models from scratch, from a new theoretical perspective.* [Tutorial webpage]. https://www.chenyang.co/diffusion.html

[Yuan n.d.b] Yuan, C. (n.d.). *SmallDiffusion: Simple and readable code for training and sampling from diffusion models.* [Software/library]. https://github.com/yuanchenyang/smalldiffusion

INDEX

A

activation function 27, 34-37, 39, 53, 147, 153-155, 158, 160, 167, 177, 190, 194, 233
ADALINE 35
AI history 287
AI models 31, 67, 75, 107, 109, 116-117, 182, 184, 186-187, 217
algorithm 13, 17, 24, 26, 34-38, 60-63, 65, 76, 78, 81, 107-108, 128-129, 156, 158, 203, 205-207, 215, 217, 231, 245, 281, 286-287, 290, 295, 298, 301-302, 305, 312-313, 316, 318-320, 354
artificial intelligence 107, 353
artificial neuron 17, 26-28, 33-34, 37-38, 142, 144
attention mechanism 268, 271-273, 282

B

backpropagation 37, 53, 106-108, 113, 116, 119, 123-124, 129, 137, 142-144, 150, 153, 156, 158, 169-170, 206, 354
bias 18-20, 55-56, 108, 110, 124, 155, 272, 275, 283
build your own perceptron 41

C

calculus 32-33, 36-37, 60, 110, 113-115, 117, 206
cat and dog dataset 25
chain rule 37, 112, 114-117, 138, 140, 142, 144
classification 34, 155-156, 205, 230-231, 300, 329, 355
complex patterns 26, 38, 153, 165, 169-170
convergence 145, 353
curse of dimensionality 31

D

decision boundary 20-22, 26-27, 35, 146-147, 149-151, 157-161, 163, 166-169, 181
deep learning 70, 163, 165, 206-207, 226, 230, 353-356
Deepseek 282
derivative 33-34, 112-120, 124, 138, 140, 354
diffusion models 297, 300-301, 304-306, 317-322, 329, 344-345, 357-358

E

error 24-25, 28-34, 37, 60, 68, 76, 81, 121, 145, 156, 205, 217-218, 220, 222-225, 233, 247, 259, 286, 290
error landscape 31, 33, 37
error surface 32
exclusive or 25-26, 34, 37-38, 64
exclusive OR problem 37

F

Frank Rosenblatt 17, 38
function approximation 354

G

gradient 28, 31-33, 37, 53, 67, 70, 74-83, 106-107, 111-112, 115-121, 123, 129, 137, 139, 141-145, 150, 156-159, 167, 169-170, 247, 357
gradient descent 31, 53, 67, 74-82, 111, 119-121, 129, 137, 139, 141-145, 150, 156-159, 167, 169-170
GPT-3 38-39, 187, 189, 207, 215-216, 218, 220, 222, 224-225, 238, 246, 249, 280, 297, 300
GPT-4 38-39, 187, 207, 215, 224-225, 236, 240-241, 262, 353, 355-356
gradient estimation 32

H

Hay, J. C. 353
hyperplane 25, 109

I

indicator lights 12, 18
input pattern 17, 19, 34

L

learning algorithm 17, 24, 26, 34, 108, 206, 217, 245
learning rate 24, 34, 54-58, 60, 62-63, 119, 139, 141-145, 158, 181
linear algebra 282, 285
linear separability 25-26
LLama 126, 128
LMS algorithm 34-38, 60-63, 65, 354
local minimum 31, 77-78, 82, 99, 158
loss function 77, 112-113, 221, 233

M

machine learning 28, 220, 226, 230, 283, 355, 358
Madaline 354
Mark I Perceptron 353
McCulloch-Pitts neuron 37
mixture of experts 39
multilayer network 26, 34, 152-153
multilayer perceptron 38-39, 70, 190, 206, 246-247, 254, 290

N

neural network 17, 25-26, 28, 34-36, 38, 52, 67, 99, 107-108, 113-114, 122-123, 137-141, 147, 153, 156, 169-170, 177, 186, 190-192, 194, 199, 203, 205-207, 217, 222, 230, 233, 237, 259, 265, 275, 287, 290, 301-302, 305, 317, 353-355
neural scaling laws 217, 225, 230, 236-237, 297, 356
neuron model 37, 53, 60, 149-151, 166

O

OpenAI 38-39, 187, 217-218, 222-225, 234, 236, 239, 262, 277, 297, 300, 320, 353, 355-356
optimization 78, 113, 158, 201, 220-221
output neuron 17, 110, 147-148, 151, 156

P

parameters 39, 55-57, 59, 64, 67, 70-73, 75-79, 81-83, 107, 109-111, 113, 115-120, 124, 138, 140, 143, 145, 147, 152, 156, 158, 189, 206, 215, 218, 220, 234, 239, 249, 282
partial derivatives 34, 114-115, 119-120
pattern recognition 356
Perceptron 12-13, 16-18, 20-21, 24-28, 34-36, 39-41, 54-61, 65, 190, 353-354
Perceptron Learning Rule 16, 20, 25, 27-28, 34-36, 41, 55-61, 65
potentiometers 17, 41

S

scaling laws 217-218, 224-225, 230, 233, 236-237, 297, 356
sigmoid function 37
step function 36-37, 39, 53, 64

T

T and J shapes 16
target output 28, 54
training examples 67, 138, 140, 232, 241, 243, 307-308
transformer model 74
two-input perceptron 18, 33, 55-56

V

VC dimension 25
visualization 73, 79, 81-83, 108, 149, 162, 186, 194, 199, 201, 203, 355

W

weights 12, 17-18, 24, 26, 28, 32-34, 37-38, 52, 57, 67, 76, 106-107, 110-111, 124, 146-147, 152, 155-156, 194, 206, 258, 269, 272, 274-276, 283, 285

X

XOR 26-27, 35, 39, 64

1. PERCEPTRON | EXERCISES

1.1 What do you think of Rosenblatt's predictions (Figure 1.7)? Wildly optimistic or incredible foresight? Do you think that all of Rosenblatt's predictions will eventually come true? If his predictions do come true, do you think that the enabling AI systems will still be based on these simple neuron models?

OPINION - WHAT DO YOU THINK?

1.2 Why were the activation functions used in the 1950s and 1960s "all or nothing" binary step functions?

TO MIMIC NEURONS IN THE BRAIN FIRING OR NOT.

1.3 It's wild how close Widrow and Hoff were to modern gradient descent and backpropagation. In hindsight, switching from binary activation functions to a differentiable function like sigmoid seems pretty obvious—why do you think Widrow and Hoff didn't try this?

MY GUESS IS THE CONNECTION TO PHYSICAL "ALL OR NOTHING" NEURONS (WHICH ISN'T ACTUALLY TRUE!) MAY HAVE BEEN A MENTAL BLOCKER.

1.4. Consider the target perceptron machine outputs on the previous page, where inputs of (-1, -1) and (-1,1) result in a negative output, and (1, -1) and (1,1) result in a positive output. Complete the missing rows in the table below, training a two-input perceptron to learn these targets, using the Perceptron Learning Rule. The Perceptron Learning Rule is summarized in Figure 1.4; here our machine has two inputs and includes a bias knob. The bias is "always switched on", so in Case 1 we turn up the bias knob by the learning rate, and in Case 2 we turn down the bias knob by the learning rate. To figure out the machine's output, we're using the equation $\hat{y} = w_1x_1+w_2x_2+b$, where x_1 and x_2 are input switch values, an on switch sets x=1, and an off switch sets x=-1. Assume a learning rate of α=1, and track the knob's values numerically. Step 1 in the table below falls under Case 2, so we turn down all the knobs that are switched on (just the bias knob, since it's always on), and turn up all the knobs that are switched off (w_1 and w_2) by our learning rate α=1, resulting in updated parameters of w_1=1, w_2=1, b=-1. Does the machine converge? Are these examples linearly separable?

Step	Input x_1 x_2	Target	Parameters w_1	w_2	b	Output Value $\hat{y} = w_1x_1 + w_2x_2 + b$	Correct?	Updated Parameters w_1	w_2	b
1			0	0	0	(0)(−1) + (0)(−1) + 0 = 0	✗	1	1	-1
2			1	1	-1	(1)(−1) + (1)(1) − 1 = −1	✓	1	1	-1
3			1	1	-1	1·1 + 1·1 − 1 = −1	✗	2	0	0
4			2	0	0	2·1 + 0·1 + 0 = 2	✓	2	0	0
5			2	0	0	2·−1 + 0·−1 + 0 = −2	✓	2	0	0
6			2	0	0	2·−1 + 0·1 + 0 = −2	✓	2	0	0
7			2	0	0	2·1 + 0·−1 + 0 = 2	✓	2	0	0
8			2	0	0	2·1 + 0·1 + 0 = 2	✓	2	0	0

CASE 1

YES MACHINE CONVERGES AND EXAMPLES ARE LINEARLY SEPERABLE.



Step	Input x_1 x_2	Target	Parameters w_1	w_2	b	Output Value $\hat{y} = w_1x_1 + w_2x_2 + b$	Correct?	Updated Parameters w_1	w_2	b
1			0	0	0	(0)(−1) + (0)(−1) + 0 = 0	✗	1	1	-1
2			1	1	-1	1·1 + 1·−1 − 1 = −1	✓	1	1	-1
3			1	1	-1	1·−1 + 1·1 − 1 = −1	✗	0	2	0
4			0	2	0	0·1 + 2·1 + 0 = 2	✓	0	2	0
5			0	2	0	0·−1 + 2·−1 + 0 = −2	✓	0	2	0
6			0	2	0	0·1 + 2·−1 + 0 = −2	✓	0	2	0
7			0	2	0	0·−1 + 2·1 + 0 = 2	✓	0	2	0
8			0	2	0	0·1 + 2·1 + 0 = 2	✓	0	2	0

CASE 1

1.5. Consider the target Perceptron machine outputs below, where inputs of (-1, -1) and (1,-1) result in a negative output, and (-1, 1) and (1,1) result in a positive output. Complete the missing rows in the table above, training a two-input perceptron to learn these targets, using the Perceptron Learning Rule. The Perceptron Learning Rule is summarized in Figure 1.4; here our machine has two inputs and includes a bias knob. The bias is "always switched on", so in Case 1 we turn up the bias knob by the learning rate, and in Case 2 we turn down the bias knob by the learning rate. To figure out the machine's output, we're using the equation $\hat{y} = w_1x_1+w_2x_2+b$, where x_1 and x_2 are input switch values, an on switch sets x=1, and an off switch sets x=-1. Assume a learning rate of α=1, and track the knob's values numerically. Step 1 in the table above falls under Case 2, so we turn down all the knobs that are switched on (just the bias knob, since it's always on), and turn up all the knobs that are switched off (w_1 and w_2) by our learning rate α=1, resulting in updated parameters of w_1=1, w_2=1, b=-1. Does the machine converge? Are these examples linearly separable?



Targets for exercise 1.5

YES, MACHINE CONVERGES, AND THE EXAMPLES ARE LINEARLY SEPERABLE

Step	Input x x_1	x_2	x_b	Target y	Parameters $w^{(t)}$ w_1	w_2	b	Output Value $\hat{y} = w_1x_1 + w_2x_2 + b$	Correct?	Updated Parameters $w^{(t+1)}$ w_1	w_2	b
1	-1	-1	1	-1	0	0	0	(0)(−1) + (0)(−1) + 0 = 0	✗	1	1	-1
2	1	-1	1	-1	1	1	-1	1·1 + 1·−1 − 1 = −1	✓	1	1	-1
3	-1	1	1	1	1	1	-1	1·−1 + 1·1 − 1 = −1	✗	0	2	0
4	1	1	1	1	0	2	0	0·1 + 2·1 + 0 = 2	✓	0	2	0
5	-1	-1	1	-1	0	2	0	0·−1 + 2·−1 + 0 = −2	✓	0	2	0
6	1	-1	1	-1	0	2	0	0·1 + 2·−1 + 0 = −2	✓	0	2	0
7	-1	1	1	1	0	2	0	0·−1 + 2·1 + 0 = 2	✓	0	2	0
8	1	1	1	1	0	2	0	0·1 + 2·1 + 0 = 2	✓	0	2	0

1.6. Let's repeat the problem we solved in Exercise 1.5, but streamline our computations. We showed a compact mathematical expression for the perceptron learning rule in Figure 1.29, but didn't explain how we arrived at this equation. Let's first write all three of our model's parameters as a vector w=[w_1, w_2, b]. Let's also write our input data as a vector, but add a third term x_b: x=[x_1, x_2, x_b],where x_b is always 1. Note that our model parameter vector w and input data vector x are now of the same length. Now, consider Step 1 in the table above, our machine's output $\hat{y}$ is 0, but our target is y=-1. Applying Case 2 of our Perceptron Learning Rule, we turn down all the dials that are switched on (b), and turn up all the dials that are switched off (x_1, x_2) by the learning rate α=1, resulting in new weights of w=[1, 1, -1]. Turning our knobs is this way is equivalent to subtracting: w-αx=[0, 0, 0]-[-1, -1, 1]=[1, 1, -1]. So instead of thinking about turning knobs, we can just add or subtract our learning rate times our data from our weights at each step (Figure 1.37). This approach is much easier to reason over and code up, especially when you don't have a real machine in front of you! Complete the table above using this approach.



Figure 1.37 | Perceptron Learning Rule written using Algebra. After some shuffling around, we can express the perceptron learning rule using simple equations. Note that x_b is a "fake input" that's always set to 1, that makes our math easier.

LOOPED BACK TO START!

Step	Input x: x_1	x_2	x_b	Target y	Parameters $w^{(t)}$: w_1	w_2	b	Output Value $\hat{y} = w_1x_1 + w_2x_2 + b$	Correct?	Updated Parameters $w^{(t+1)}$: w_1	w_2	b	
1	1	-1	1	-1	0	0	0	(0)(1) + (0)(-1) + 0 = 0	X	-1	1	-1	
2	-1	1	1	-1	-1	1	-1	-1·-1 + 1·1 + -1 = 1	X	0	0	-2	CASE 2
3	-1	-1	1	1	0	0	-2	0·-1 + 0·-1 + -2 = -2	X	-1	-1	-1	CASE 1
4	-1	-1	1	1	-1	-1	-1	-1·-1 + -1·-1 + -1 = -3	X	0	0	0	CASE 1
5	1	-1	1	-1	0	0	0	0·1 + 0·-1 + 0 = 0	X	-1	1	-1	CASE 2
6	-1	1	1	-1	-1	1	-1	-1·-1 + 1·1 + -1 = 1	X	0	0	-2	CASE 2
7	-1	-1	1	1	0	0	-2	0·-1 + 0·-1 + -2 = -2	X	-1	-1	-1	CASE 1
8	1	1	1	1	-1	-1	-1	-1·1 + -1·1 + -1 = -3	X	0	0	0	CASE 2

1.7. Consider the target perceptron machine outputs below, where inputs of (1, -1) and (-1,1) result in a negative output, and (-1, -1) and (1,1) result in a positive output. Complete the table above, training a two input perceptron to learn these targets, using the numerical approach to the Perceptron Learning Rule presented in Exercise 1.6. Assume a learning rate of α=1. Does the machine converge? Are these examples linearly separable?

DOES NOT CONVERGE.



Targets for exercise 1.7

1.8. Now that we've seen that the Perceptron Learning Rule is equivalent to iteratively adding or subtracting a scaled version of our examples to our model's parameters—this can help us understand why the rule works. In our first learning step, we start from w=[0, 0, 0], and add/subtract a scaled version of our first example x=[x_1, x_2, x_b]. Show algebraically that doing this guaranteed to produce the output $\hat{y}$ we want for both Case 1 and Case 2 of the Perceptron Learning Rule.

CASE 1 $\hat{y} \le 0$, but we want $\hat{y} > 0$.

INITIAL WEIGHTS: $W^{(t)} = [0, 0, 0]$

FIRST EXAMPLE: $x = [x_1, x_2, 1]$

UPDATE: $W^{(t+1)} = W^{(t)} + \alpha x$

$= [\alpha x_1, \alpha x_2, \alpha]$

NOW PLUG BACK IN INPUT X INTO MACHINE:

$\hat{y} = w_1x_1 + w_2x_2 + b$

$= \alpha x_1x_1 + \alpha x_2x_2 + \alpha$

$= \alpha(x_1)^2 + \alpha(x_2)^2 + \alpha$ → SINCE $\alpha \ge 0$, THIS WILL ALWAYS BE ≥ 0, AS DESIRED.

CASE 2 $\hat{y} \ge 0$, but we want $\hat{y} < 0$.

UPDATE: $W^{(t+1)} = W^{(t)} - \alpha x$

$= [-\alpha x_1, -\alpha x_2, -\alpha]$

PLUG BACK IN X:

$\hat{y} = w_1x_1 + w_2x_2 + b$

$= -\alpha x_1x_1 - \alpha x_2x_2 - \alpha$

$= -\alpha(x_1)^2 - \alpha(x_2)^2 - \alpha$ → WILL ALWAYS BE < 0.

$= -\alpha[x_1^2 + x_2^2 + 1]$

Step	Input x: x_1	x_2	x_b	Target y	Parameters $w^{(t)}$: w_1	w_2	b	Output Value $\hat{y} = w_1x_1 + w_2x_2 + b$	Correct?	Updated Parameters $w^{(t+1)}$: w_1	w_2	b	
1	-1	-1	1	-1	0	0	0	(0)(-1) + (0)(-1) + 0 = 0	X	1	1	-1	
2	-1	1	1	-1	1	1	-1	1·-1 + 1·1 + -1 = -1	✓	1	1	-1	
3	1	-1	1	1	1	1	-1	1·1 + 1·-1 + -1 = -1	X	2	0	0	CASE 1
4	1	1	1	1	2	0	0	2·1 + 0·1 + 0 = 2	✓	2	0	0	
5	-1	-1	1	-1	2	0	0	2·-1 + 0·-1 + 0 = -2	✓	2	0	0	
6	-1	1	1	-1	2	0	0	2·-1 + 0·1 + 0 = -2	✓	2	0	0	
7	1	-1	1	1	2	0	0	2·1 + 0·-1 + 0 = 2	✓	2	0	0	
8	1	1	1	1	2	0	0	2·1 + 0·1 + 0 = 2	✓	2	0	0	

1.9 In Exercise 1.4, we trained a perceptron to match these targets, where inputs of (-1, -1) and (-1,1) result in a negative output, and (1, -1) and (1,1) result in a positive output. Let's now compare how Rosenblatt's Perceptron Learning Rule compares to Widrow and Hoff's LMS algorithm. First, complete the table above to train a Perceptron using The Perceptron Learning Rule. Assume a learning rate of α=1.



1.10 Now, let's solve the same problem from part (a), but using Widrow and Hoff's LMS algorithm. Remember that the LMS algorithm depends on having a measure of the system's error, which we defined as $E=(y-\hat{y})^2$. Complete the missing entries in the table on the following page, using the LMS update rule. Use a learning rate of α=0.2 (a learning rate of α=1.0 is too large and will "blow up"). Note that the quantities in the last three columns include dividing by two—this just a book keeping step that allows us to keep our LMS formula simple (another way to think about this absorbing our factor of 2 from our calculus steps into learning rate), after dividing by two these last three terms tell us how much to update each model parameter.

PERCEPTRON LEARNING RULE

$w^{(t+1)} \leftarrow w^{(t)} \pm \alpha x$

LEAST MEAN SQUARES (LMS)

$w^{(t+1)} \leftarrow w^{(t)} + \alpha x(y - \hat{y})$

↑ Error Term

$$\frac{\partial E}{\partial w_1} = -2(y-\hat{y})x_1$$
$$\frac{\partial E}{\partial w_2} = -2(y-\hat{y})x_2$$
$$\frac{\partial E}{\partial b} = -2(y-\hat{y})$$

GRADIENT

$\frac{\partial E}{\partial w_1} = -2(-0.8)(-1) = -1.6$

$\frac{\partial E}{\partial w_2} = -2(-0.8)(1) = 1.6$

$\frac{\partial E}{\partial b} = -2(-0.8) = 1.6$

STEP 3 $\hat{y} = 0.36(1) + 0.04(-1) - .36 = -0.04$

STEP 9: $\hat{y} = 0.92(-1) + (-0.01)(-1)(1) = -0.91$

Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y}$	$y-\hat{y}$	$E=(y-\hat{y})^2$	$\frac{\partial E}{\partial w_1}$	$\frac{\partial E}{\partial w_2}$	$\frac{\partial E}{\partial b}$	$\alpha\frac{\partial E}{2\partial w_1}$	$\alpha\frac{\partial E}{2\partial w_2}$	$\alpha\frac{\partial E}{2\partial b}$
1	-1	-1	1	-1	0	0	0	0	-1	1	-2	-2	2	-0.2	-0.2	0.2
2	-1	1	1	-1	0.2	0.2	-0.2	-0.2	-.08	0.64	-1.6	1.6	1.6	-0.16	.16	.16
3	1	-1	1	1	0.36	.04	-.36	-.04	1.04	1.08	-2.08	2.08	-2.08	-0.21	0.21	-0.21
4	1	1	1	1	0.57	-0.17	-0.15	0.25	0.75	0.57	-1.5	-1.5	-1.5	-0.15	-0.15	-0.15
5	-1	-1	1	-1	0.72	-0.02	0	-0.7	-0.3	0.09	-0.6	-0.6	0.6	-0.06	-0.06	0.06
6	-1	1	1	-1	0.78	0.04	-0.06	-0.8	-0.2	0.04	-0.41	0.41	0.41	-0.04	0.04	0.04
7	1	-1	1	1	0.82	0	-0.1	0.72	0.28	0.08	-0.57	0.57	-0.57	-0.06	0.06	-0.06
8	1	1	1	1	0.88	-0.06	-0.04	0.78	0.22	0.05	-0.45	-0.45	-0.45	-0.04	-0.04	-0.04
9	-1	-1	1	-1	0.92	-0.01	0	-.91	-.09	.008	-0.18	-0.18	0.18	-0.02	-0.02	0.02
10	-1	1	1	-1	0.94	0.01	-0.02	-0.95	-0.05	0	-0.1	0.1	0.1	-0.01	0.01	0.01
11	1	-1	1	1	0.95	0	-0.03	0.92	0.08	0.01	-0.15	0.15	-0.15	-0.02	0.02	-0.02
12	1	1	1	1	0.96	-0.02	-0.01	0.93	0.07	0	-0.13	-0.13	-0.13	-0.01	-0.01	-0.01

COMPARING THE SIGNS OF y AND $\hat{y}$, THESE MATCH ALL THE WAY FROM STEP 4 ONWARDS!

1.11 How does the LMS algorithm perform relative to the Perceptron Learning Rule? If we just consider the sign of $\hat{y}$ as we do in the Perceptron Learning Rule, does the LMS algorithm converge? How long does it take?

↳ CONVERGES IN 8 STEPS, JUST LIKE PERCEPTRON LEARNING RULE.

1.12 The Perceptron Learning Rule requires us to independently consider four different cases, but the LMS method just involves a single equation. How does the LMS "get away with a single equation"? Consider all four cases in this answer.

REFERENCING FIGURE 1.4:

CASE 1: $y > \hat{y}$ → $y - \hat{y}$ IS POSITIVE, ADDING $\alpha x(y-\hat{y})$ "TURNS KNOBS TO THE RIGHT"

CASE 2: $y < \hat{y}$ → $y - \hat{y}$ IS NEGATIVE, ADDING $\alpha x(y-\hat{y})$ "TURNS KNOBS TO THE LEFT"

CASE 3&4: $y = \hat{y}$ → UPDATE TERM $\alpha x(y-\hat{y}) = 0$ → NO UPDATE

Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y}$	$y-\hat{y}$	$E=(y-\hat{y})^2$	$\frac{\partial E}{\partial w_1}$	$\frac{\partial E}{\partial w_2}$	$\frac{\partial E}{\partial b}$	$\frac{\alpha\partial E}{2\partial w_1}$	$\frac{\alpha\partial E}{2\partial w_2}$	$\frac{\alpha\partial E}{2\partial b}$
1	-1	-1	1	-1	0	0	0	0	-1	1	-2	-2	2	-0.2	-0.2	0.2
2	1	-1	1	-1	0.2	0.2	-0.2	-0.2	-.8	.64	1.6	-1.6	1.6	.16	-.16	-.16
3	-1	1	1	1	.04	.36	-.36	-0.04	1.04	1.08	2.08	-2.08	-2.08	0.21	-0.21	-0.21
4	1	1	1	1	-0.17	0.57	-0.15	0.25	0.75	0.57	-1.5	-1.5	-1.5	-0.15	-0.15	-0.15
5	-1	-1	1	-1	-0.02	0.72	0	-0.7	-0.3	0.09	-0.6	-0.6	0.6	-0.06	-0.06	0.06
6	1	-1	1	-1	0.04	0.78	-0.06	-0.8	-0.2	0.04	0.41	-0.41	0.41	0.04	-0.04	0.04
7	-1	1	1	1	0	0.82	-0.1	0.72	0.28	0.08	0.57	-0.57	-0.57	0.06	-0.06	-0.06
8	1	1	1	1	-0.06	0.88	-0.04	0.78	0.22	0.05	-0.45	-0.45	-0.45	-0.04	-0.04	-0.04
9	-1	-1	1	-1	-0.01	0.92	0	-0.91	-0.09	0.01	-0.18	-0.18	0.18	-0.02	-0.02	0.02
10	1	-1	1	-1	0.01	0.94	-0.02	-0.95	-0.05	0	0.1	-0.1	0.1	0.01	-0.01	0.01
11	-1	1	1	1	0	0.95	-0.03	0.92	0.08	0.01	0.15	-0.15	-0.15	0.02	-0.02	-0.02
12	1	1	1	1	-0.02	0.96	-0.01	0.93	0.07	0	-0.13	-0.13	-0.13	-0.01	-0.01	-0.01

1.13 The table above shows the LMS algorithm learning to match the targets shown to the right with a learning rate of α=0.2. Complete the missing entries. Does the LMS algorithm progressively make better predictions as it learns?

$\hat{y} = w_1x_1 + w_2x_2 + b = 0.2\cdot1 + 0.2\cdot-1 - 0.2 = -0.2$

$\frac{\partial E}{\partial w_1} = -2(y-\hat{y})x_1 = -2(-0.8)(1) = 1.6$

$\frac{\partial E}{\partial w_2} = -2(y-\hat{y})x_2 = -2(-.8)(-1) = -1.6$

$\frac{\partial E}{\partial b} = -2(y-\hat{y}) = -2(-.8) = 1.6$

YES, SQUARED ERROR DECREASES NICELY.



Step	x_1	x_2	x_b	y	w_1	w_2	b	$\hat{y}$	$y-\hat{y}$	$E=(y-\hat{y})^2$	$\frac{\partial E}{\partial w_1}$	$\frac{\partial E}{\partial w_2}$	$\frac{\partial E}{\partial b}$	$\frac{\alpha\partial E}{2\partial w_1}$	$\frac{\alpha\partial E}{2\partial w_2}$	$\frac{\alpha\partial E}{2\partial b}$
1	1	-1	1	-1	0	0	0	0	-1	1	2	-2	2	0.2	-0.2	0.2
2	-1	1	1	-1	-0.2	0.2	-0.2	.2	-1.2	1.44	-2.4	2.4	2.4	-.24	.24	.24
3	-1	-1	1	1	.04	-.04	-.44	-0.44	1.44	2.07	2.88	2.88	-2.88	0.29	0.29	-0.29
4	1	1	1	1	-0.25	-0.33	-0.15	-0.73	1.73	2.99	-3.46	-3.46	-3.46	-0.35	-0.35	-0.35
5	1	-1	1	-1	0.1	0.02	0.19	0.27	-1.27	1.62	2.55	-2.55	2.55	0.25	-0.25	0.25
6	-1	1	1	-1	-0.16	0.27	-0.06	0.37	-1.37	1.87	-2.74	2.74	2.74	-0.27	0.27	0.27
7	-1	-1	1	1	0.12	0	-0.33	-0.45	1.45	2.1	2.9	2.9	-2.9	0.29	0.29	-0.29
8	1	1	1	1	-0.17	-0.29	-0.04	-0.51	1.51	2.28	-3.02	-3.02	-3.02	-0.3	-0.3	-0.3
9	1	-1	1	-1	0.13	0.01	0.26	0.38	-1.38	1.89	2.75	-2.75	2.75	0.28	-0.28	0.28
10	-1	1	1	-1	-0.15	0.29	-0.02	0.41	-1.41	2	-2.83	2.83	2.83	-0.28	0.28	0.28
11	-1	-1	1	1	0.14	0	-0.3	-0.44	1.44	2.07	2.88	2.88	-2.88	0.29	0.29	-0.29
12	1	1	1	1	-0.15	-0.29	-0.01	-0.45	1.45	2.1	-2.9	-2.9	-2.9	-0.29	-0.29	-0.29

1.14 The table above shows the LMS algorithm learning to match the targets shown to the right with a learning rate of α=0.2. Complete the missing entries. Does the LMS algorithm progressively make better predictions as it learns?

$\hat{y} = w_1x_1 + w_2x_2 + b = -0.2(-1) + 0.2(1) - 0.2 = 0.2$

$\frac{\partial E}{\partial w_1} = -2(y-\hat{y})x_1 = -2(-1.2)(-1) = -2.4$

$\frac{\partial E}{\partial w_2} = -2(y-\hat{y})x_2 = -2(-1.2)(1) = 2.4$

$\frac{\partial E}{\partial b} = -2(y-\hat{y}) = -2(-1.2) = 2.4$

NO! EXCLUSIVE OR → NO SOLUTION





$$f_1(x_1,x_2) = \begin{cases} 1 & w_{11}^{(1)}x_1 + w_{12}^{(1)}x_2 + b_1^{(1)} > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$f_2(x_1,x_2) = \begin{cases} 1 & w_{21}^{(1)}x_1 + w_{22}^{(1)} + b_2^{(1)} > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\hat{y} = w_1^{(2)}f_1 + w_2^{(2)}f_2 + b_1^{(2)}$$

$w_{11}^{(1)} = 1$
$w_{12}^{(1)} = 1$
$b_1^{(1)} = 0.5$
$w_{21}^{(1)} = 1$
$w_{22}^{(1)} = 1$
$b_1^{(2)} = -1.5$

$w_1^{(2)} = 1$
$w_2^{(2)} = -1$
$b_2^{(1)} = -0.5$

x_1	x_2	y	$w_{11}^{(1)}x_1 + w_{12}^{(1)}x_2 + b_1^{(1)}$	$w_{21}^{(1)}x_1 + w_{22}^{(1)}x_2 + b_2^{(1)}$	f_1	f_2	$\hat{y}$
-1	-1	-1	(1)(-1)+(1)(-1)+0.5=-1.5	(1)(-1)+(1)(-1)-1.5=-3.5	0	0	-.5 ✓
-1	1	1	(1)(-1)+(1)(1)+0.5=0.5	(1)(-1)+(1)(1)-1.5=-1.5	1	0	.5 ✓
1	-1	1	(1)(1)+(1)(-1)+0.5=0.5	(1)(1)+(1)(-1)-1.5=-1.5	1	0	.5 ✓
1	1	-1	(1)(1)+(1)(1)+0.5=2.5	(1)(1)+(1)(1)-1.5=0.5	1	1	-.5 ✓

2. GRADIENT DESCENT | EXERCISES

2.1 What is a local minimum, and why were early AI pioneers like Geoff Hinton worried about them?

→ LOCAL MINIMUM = SET OF PARAMETERS WHERE EVERY DIRECTION IS "UPHILL".
→ MODEL COULD GET STUCK.

2.2 Why are local minima less of a concern for modern neural networks than once thought?

→ HIGH DIMENSIONAL LOSS LANDSCAPES (LOTS OF PARAMS) MAKE GETTING TRULY STUCK VERY UNLIKELY.

2.3 How does cross-entropy penalize our model differently than the L1 loss?

CE. LOSS BECOMES VERY LARGE AS THE MODELS CONFIDENCE IN THE RIGHT ANSWER → 0.

2.4 In Figure 2.11, we tried training our Llama model one parameter at a time. What went wrong with this approach?

PARAMETERS ARE ALL CONNECTED!

2.5 Why can't we just train Llama by testing all combinations of parameter values?

NOT ENOUGH COMPUTE ON THE PLANET.

2.6 When training on short texts, why does it look like a wormhole opens up in our loss landscape (Figure 2.21)?

OUR LOSS LANDSCAPE IS JUST A TWO DIMENSIONAL PROJECTION OF A MUCH HIGHER DIMENSIONAL OBJECT. VERY GOOD SOLUTIONS ARE CLOSE IN HIGH DIMENSIONAL SPACE, WE JUST CAN'T SEE THEM UNTIL WE START MOVING.

```
[1]: import torch
     from torch.nn import functional as F
     from transformers import AutoModelForCausalLM, AutoTokenizer
     import numpy as np
     import matplotlib.pyplot as plt
     from tqdm import tqdm

     device='cuda'
     model_id = "meta-llama/Llama-3.2-1B"

     model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
     tokenizer = AutoTokenizer.from_pretrained(model_id)

[2]: text = "The capital of France is Paris"
     inputs = tokenizer(text, return_tensors="pt").to(device)

     with torch.no_grad():
         outputs = model(**inputs, labels=inputs["input_ids"])

     outputs.loss  # This is the average cross-entropy loss

[2]: tensor(3.3752, device='cuda:0')
```

INPUT TEXT	MODEL'S MOST PROBABLE NEXT TOKEN	MODEL'S MOST PROBABLE NEXT TOKEN PROBABILITY	CORRECT NEXT TOKEN	MODEL'S PROBABILITY OF CORRECT NEXT TOKEN (P_i)	$-\ln(P_i)$
begin_of_text|>	Question	0.301258	The	0.026724	3.6222
begin_of_text|>The		0.0244	capital	0.000169	8.6856
begin_of_text|>The capital	of	0.568659	of	0.568659	0.5645
begin_of_text|>The capital of	the	0.204712	France	0.011272	4.4854
begin_of_text|>The capital of France	,	0.508131	is	0.141121	1.9581
begin_of_text|>The capital of France is	Paris	0.391531	Paris	0.391531	0.9377

2.7 The code snippet to the left shows the process of computing the loss value for a pre-trained Llama large language model given the input text *"The capital of France is Paris"*. According to PyTorch, our model's loss is 3.3752. Let's reproduce this value. First, fill in the missing values in the final column of the table on the previous page. These are the values of the cross-entropy loss of each prediction our model makes on our training text.

2.8 When training, the loss at each token position is averaged to compute a final loss for each example. Take the average of your computed cross-entropy values. Do your results match what PyTorch reports?

AVERAGE = $\frac{3.6222 + \ldots + 0.9377}{6} = 3.3756$ Very close!

2.9 Which predicted tokens (i.e. which rows in the table you completed in 2.7) have the highest loss values? Why?

"capital" → 8.6856
"France" → 4.4854
] BOTH VERY HARD TO GUESS!

2.10 Which predicted tokens (i.e. which rows in the table you completed in 2.7) have the lowest loss values? Why?

The capital of → loss = 0.5645
→ Easier to guess the next word!

2.11 If our model instead used L1 Loss, what would our L1 Loss be for this example? How would switching to L1 Loss change the relative contributions of each token to the final loss value?

Correct Next Token	L1 Loss
The	0.9733
capital	0.9998 → MUCH LESS SIGNIFICANT WHEN USING L1 LOSS.
of	0.4314
France	0.9887 →
is	0.8589
Paris	0.6085


```
[7]: import torch
     from torch.nn import functional as F
     from transformers import AutoModelForCausalLM, AutoTokenizer
     import numpy as np
     import matplotlib.pyplot as plt
     from tqdm import tqdm

     device='cuda'
     model_id = "meta-llama/Llama-3.2-1B"

     model = AutoModelForCausalLM.from_pretrained(model_id).to(device)
     tokenizer = AutoTokenizer.from_pretrained(model_id)

[8]: text = "An apple a day keeps the doctor away"
     inputs = tokenizer(text, return_tensors="pt").to(device)

     with torch.no_grad():
         outputs = model(**inputs, labels=inputs["input_ids"])

     outputs.loss  # This is the average cross-entropy loss

[8]: tensor(1.9323, device='cuda:0')
```

INPUT TEXT	MODEL'S MOST PROBABLE NEXT TOKEN	MODEL'S MOST PROBABLE NEXT TOKEN PROBABILITY	CORRECT NEXT TOKEN	MODEL'S PROBABILITY OF CORRECT NEXT TOKEN (P_i)	$-\ln(P_i)$
<|begin_of_text|>	Question	0.301258	An	0.001692	6.3816
<|begin_of_text|>An		0.022775	apple	0.000615	7.3936
<|begin_of_text|>An apple	a	0.649742	a	0.649742	0.4312
<|begin_of_text|>An apple a	day	0.986583	day	0.986583	.01351
<|begin_of_text|>An apple a day	keeps	0.483511	keeps	0.483511	0.7267
<|begin_of_text|>An apple a day keeps	the	0.850819	the	0.850819	0.1616
<|begin_of_text|>An apple a day keeps the	doctor	0.738021	doctor	0.738021	0.3038
<|begin_of_text|>An apple a day keeps the doctor	away	0.954824	away	0.954824	0.0462

2.12 The code snippet to the left shows the process of computing the loss value for a pre-trained Llama large language model given the input text *"An apple a day keeps the doctor away"* According to PyTorch, our model's loss is 1.9323. Let's reproduce this value. First, fill in the missing values in the final column of the table on the previous page. These are the values of the cross-entropy loss of each prediction our model makes on our training text.

2.13 When training, the loss at each token position is averaged to compute a final loss for each example. Take the average of your computed cross-entropy values. Do your results match what PyTorch reports?

Loss = $\frac{6.3816 + \ldots + 0.0462}{8} = 1.9323$ ✓

2.14 Which predicted tokens (i.e. which rows in the table you completed in 2.12) have the highest loss values? Why?

An → 6.3816
apple → 7.3936
] HARD TO GUESS NEXT WORD.

2.15 Which predicted tokens (i.e. which rows in the table you completed in 2.12) have the lowest loss values? Why?

day → 0.01351
the → 0.1616
away → 0.0462
] MODEL IS VERY CONFIDENT IN CORRECT NEXT TOKENS. COMMON PHRASE!

2.16 How would switching to L1 loss change the relative contributions of each token to the final loss value?

"An" and "apple" WOULD CONTRIBUTE MUCH LESS TO THE FINAL LOSS.

2.17 Consider the table on the previous page, showing Llama processing the input text *"I've had a perfectly wonderful evening, but this wasn't it"*. Which token predictions have the lowest loss values? Why? Which tokens predictions have the highest loss values? Why?

"I've had a perfectly"
"I've had a perfectly wonderful evening, but this wasn't"
→ High Loss, Surprising choices.

"I've had a"
"I've had a perfectly wonderful evening, but this wasn't it"
→ Low loss, easy to guess.

2.18 Compute and visualize your own loss landscape for a model other than Llama-3.2-1b. You may use this chapter's supporting code as a starting point.

3. BACKPROPAGATION | EXERCISES

Discussion

3.1 Paul Werbos' claim that backpropagation is as important to intelligence as Newton's laws were to physics may seem grandiose. If I was in Minsky's shoes in the early 1970s I would have been skeptical as well. However, time has only proven Werbos more right—backpropagation as scaled astoundingly well—do you think Werbos was right? Is backpropagation as import to the study of intelligence as F=ma was to the study of physics?

"..this new mathematical concept [backpropagation] opens up the possibility of a scientific understanding of intelligence, as important to psychology and neurophysiology as Newton's concepts were to physics"
Paul Werbos [Werbos 1994]

"But, you see, it's not a good discovery... It converges slowly, and it cannot learn anything difficult"
Marvin Minsky [Olazaran 1996]

BACKPROPAGATION HAS SCALED UNBELIEVABLY WELL, BUT I WISH IT WAS AS "EXPLANATORY/INSIGHTFUL" AS NEWTON'S LAWS.

3.2 Backpropagation and gradient descent, when viewed a single step at a time, as shown in Figure 3.19, can look chaotic. It never ceases to amaze me that this little parameter update steps, driven my gradient descent, are able to learn such complicated things—each step is really quite simple. How do you think it is that all these little steps are able to add up to such impressive results?

THIS DOES MAKE ME WONDER IF THERE'S SOMETHING DEEPER GOING ON THAT WE DON'T UNDERSTAND YET - IT JUST WORKS SO WELL!

3.3 Why is it impossible for our single layer plane-fitting neural network to fit the borders of the town of Baarle-Hertog as shown in Figure 3.26?

THE TOWN IS NOT LINEARLY SEPERABLE.



Over the next few exercises, we'll complete a walkthrough of the simplified European city model and dataset above.

3.4 Using the neural network and equations above, complete the "forward pass" for step zero of the table on the next page, computing the four h and $\hat{y}$ values. Using the same approach as the model introduce in Figure 3.4, this model only uses the longitude (x) of our training examples. The top row of the table indicates the order the examples are iterated through, starting with x=2.351. The y_1 and y_2 rows indicate the city/label of the current example, where y_1=1 corresponds to Paris, and y_2=1 corresponds to Berlin. Initial model parameters are shown in the first column of the table.

$h_1 = m_1x+b = (-1)(2.351)+0 = -2.351$ | $\hat{y}_1 = \frac{e^{-2.351}}{e^{-2.351}+e^{2.351}} = 0.009$

$h_2 = m_2x+b_2 = 1(2.351)+0 = 2.351$

3.5 Using the derivative of softmax + cross-entropy results shown in Figure 3.12 and the chain rule, solve for $\partial L/\partial m_1$ and $\partial L/\partial m_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial m$ values in the table on the following page.

$\partial L/\partial m_1 = x(\hat{y}_1 - y_1) = 2.351(0.009-1) = -2.33$

$\partial L/\partial m_2 = x(\hat{y}_2 - y_2) = 2.351(0.991-0) = 2.33$

3.5 Using the derivative of softmax + cross-entropy results shown in Figure 3.12, and the chain rule, solve for $\partial L/\partial b_1$ and $\partial L/\partial b_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial b$ values in the table on the following page.

$\partial L/\partial b_1 = (\hat{y}_1 - y_1) = 0.009 - 1 = -0.991$

$\partial L/\partial b_2 = (\hat{y}_2 - y_2) = 0.991 - 0 = 0.991$

3.6 For Step 0, compute the cross-entropy loss, and accuracy values in the table on the following page. Note that to compute accuracy you will have to pass all four training data through the model.

$Loss = -\ln(\hat{y}_1) = -\ln(0.009) = 4.71$

x	2.3514	2.2945	13.4050	13.3777
$\hat{y}_1$	0.009 ✗	0.01 ✗	0 ✓	0 ✓
$\hat{y}_2$	0.991	0.989	1	1

50%

Step	0	1	2	3	4	5	6	7	8	9
x	2.351	2.294	13.405	13.378	2.351	2.294	13.405	13.378	2.351	2.294
m_1	-1	-.767	-0.546	-0.546	-0.546	-0.334	-0.168	-0.198	-0.211	-0.077
m_2	1	.767	0.546	0.546	0.546	0.334	0.168	0.198	0.211	0.077
$\partial L/\partial m_1$	-2.33	-2.215	0	0	-2.111	-1.661	0.294	0.136	-1.342	-0.883
$\partial L/\partial m_2$	2.33	2.215	0	0	2.111	1.661	-0.294	-0.136	1.342	0.883
b_1	0	.044	0.196	0.196	0.196	0.285	0.358	0.356	0.355	0.412
b_2	0	-.044	-0.196	-0.196	-0.196	-0.285	-0.358	-0.356	-0.355	-0.412
$\partial L/\partial b_1$	-.991	-0.965	0	0	-0.898	-0.724	0.022	0.01	-0.571	-0.385
$\partial L/\partial b_2$	.991	0.965	0	0	0.898	0.724	-0.022	-0.01	0.571	0.385
h_1	-2.35	-1.661	-7.117	-7.102	-1.087	-0.482	-1.898	-2.29	-0.142	0.235
h_2	2.35	1.661	7.117	7.102	1.087	0.482	1.898	2.29	0.142	-0.235
$\hat{y}_1$	.009	0.035	0	0	0.102	0.276	0.022	0.01	0.429	0.615
$\hat{y}_2$	.991	0.965	1	1	0.898	0.724	0.978	0.99	0.571	0.385
y_1	1	1	0	0	1	1	0	0	1	1
y_2	0	0	1	1	0	0	1	1	0	0
Loss	4.71	3.357	0	0	2.282	1.287	0.022	0.01	0.846	0.486
Accuracy	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	1.0

3.7 This model is trained with a learning rate of α=0.1. Using gradient descent, and your computed gradients from 3.6, compute the new parameter values m and b in Step 1.

$m_1 = -1 - 0.1(-2.33) = -0.767$ | $b_1 = 0 - 0.1(-.991) = 0.099$

$m_2 = 1 - 0.1(2.33) = 0.676$ | $b_2 = 0 - 0.1(.991) = -0.099$

3.8 For the final training step 9, compute the model's cross-entropy loss, and final accuracy. Note that to compute accuracy you will have to pass all four training data through the model.

$Loss = -\ln(0.615) = 0.486$

x	2.351	2.294	13.405	13.378
$\hat{y}_1$	0.613 ✓	0.615 ✓	0.224	0.224
$\hat{y}_2$	0.387	0.385	0.776 ✓	0.776 ✓

→ Acc = 100%

3.9 Implement and train this neural network in your programming language of choice. Do your results match the table above?

Paris

Center of Paris	(48.8575°, 2.3514°)
Eiffel Tower	(48.8584°, 2.2945°)

Madrid

Center of Madrid	(40.4167°, -3.7033°)
Retiro Park	(40.4153°, -3.6835°)



$$h_1 = m_1 x + b_1 \quad h_2 = m_2 x + b_2 \quad \hat{y}_i = \frac{e^{h_i}}{e^{h_1} + e^{h_2}}$$

Over the next few exercises, we'll complete a walkthrough of the simplified European city model and dataset above.

3.10 Using the neural network and equations above, complete the "forward pass" for step zero of the table on the next page, computing the four h and $\hat{y}$ values. Using the same approach as the model introduce in Figure 3.4, this model only uses the longitude (x) of our training examples. The top row of the table indicates the order the examples are iterated through, starting with x=2.351. The y_1 and y_2 rows indicate the city/label of the current example, where y_1=1 corresponds to Paris, and y_2=1 corresponds to Madrid. Initial model parameters are shown in the first column of the table.

$h_1 = m_1 x + b = -1 \cdot 2.351 + 0 = -2.351$ | $\hat{y}_1 = \frac{e^{-2.351}}{e^{-2.351} + e^{1.176}} = 0.029$

$h_2 = m_2 x + b = 0.5 \cdot 2.351 + 0 = 1.176$ | $\hat{y}_2 = 0.971$

3.11 Using the derivative of softmax + cross-entropy results shown in Figure 3.12 and the chain rule, solve for $\partial L/\partial m_1$ and $\partial L/\partial m_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial m$ values in the table on the following page.

$\partial L/\partial m_1 = x(\hat{y}_1 - y_1) = 2.351(0.029 - 1) = -2.284$

$\partial L/\partial m_2 = x(\hat{y}_2 - y_2) = 2.351(0.971 - 0) = 2.284$

3.12 Using the derivative of softmax + cross-entropy results shown in Figure 3.12, and the chain rule, solve for $\partial L/\partial b_1$ and $\partial L/\partial b_2$ in the simplified two city model above. Use your results to compute and fill in the missing $\partial L/\partial b$ values in the table on the following page.

$\partial L/\partial b_1 = (\hat{y}_1 - y_1) = 0.029 - 1 = -0.971$

$\partial L/\partial b_2 = (\hat{y}_2 - y_2) = 0.971 - 0 = 0.971$

3.13 For Step 0, compute the cross-entropy loss, and accuracy values in the table on the following page. Note that to compute accuracy you will have to pass all four training data through the model.

x	2.351	2.294	-3.703	-3.684
$\hat{y}_1$	0.029	0.031	0.976 ✗	0.976 ✗
$\hat{y}_2$	0.971 ✗	0.969 ✗	0.004	0.004

loss = $-\ln(0.029) = 3.54$

Acc = 0%

Step	0	1	2	3
x	2.351	2.294	-3.703	-3.684
m_1	-1	-0.772	-0.565	-0.218
m_2	0.5	0.272	0.065	-0.282
$\partial L/\partial m_1$	-2.284	-2.065	-3.472	-1.796
$\partial L/\partial m_2$	2.284	2.065	3.472	1.796
b_1	0	0.097	0.187	0.093
b_2	0	-0.097	-0.187	-0.093
$\partial L/\partial b_1$	-0.971	-0.9	0.937	0.488
$\partial L/\partial b_2$	0.971	0.9	-0.937	-0.488
h_1	-2.351	-1.673	2.28	0.896
h_2	1.176	0.526	-0.428	0.946
$\hat{y}_1$	0.029	0.1	0.937	0.488
$\hat{y}_2$	0.971	0.9	0.063	0.512
y_1	1	1	0	0
y_2	0	0	1	1
Loss	3.54	2.304	2.772	0.669
Accuracy	0	0	0	1.0

3.14 This model is trained with a learning rate of α=0.1. Using gradient descent, and your computed gradients from 3.6, compute the new parameter values m and b in Step 1.

$m_1 = -1 - 0.1(-2.284) = -0.772$ | $b_1 = 0 - 0.1(-0.971) = 0.097$

$m_2 = 0.5 - 0.1(2.284) = 0.272$ | $b_2 = 0 - 0.1(0.971) = -0.097$

3.15 For the final training Step 3, compute the model's our h and $\hat{y}$ values, cross-entropy loss, and final accuracy. Note that to compute accuracy you will have to pass all four training data through the model.

x	2.351	2.294	-3.703	-3.684
$\hat{y}_1$	0.58 ✓	0.58 ✓	0.49	0.48
$\hat{y}_2$	0.42	0.42	0.51 ✓	0.52 ✓

loss = $-\ln(0.512) = 0.669$

→ Acc = 100%

3.16 Implement and train this neural network in your programming language of choice, Do your results match the table above?

x	y
1	3
2	5
3	7
4	9



$\hat{y} = mx + b$

SINGLE NEURON

$Loss = (\hat{y} - y)^2$

SQUARED ERROR

A single artificial neuron is composed of a simple y=mx+b linear model. It's possible to train a single neuron using the same backpropagation and gradient descent approach we use to train models composed of many neurons. In the following exercises we'll train a single neuron to perform a simple linear regression task.

3.17 Complete a "forward pass" for Step 0 in the table on the following page, computing $\hat{y}$ and Loss for the first training example x=1, y=3.

$\hat{y} = mx + b = 1 \cdot 1 + 0 = 1$

$Loss = (\hat{y} - y)^2 = (1 - 3)^2 = 4$

3.18 Using the chain rule, solve for $\partial L/\partial m$ and $\partial L/\partial b$. Use your results to compute and fill in the missing values for Step 0 in the table on the following page.

$\frac{\partial L}{\partial m} = \frac{\partial (\hat{y} - y)^2}{\partial m} = 2(\hat{y} - y)\frac{\partial \hat{y}}{\partial m} = 2(\hat{y} - y)x$

$2(1 - 3) \cdot 1 = 2(-2) = -4$

$\frac{\partial L}{\partial b} = 2(\hat{y} - y)\frac{\partial \hat{y}}{\partial b} = 2(\hat{y} - y) = 2(1 - 3) = -4$

3.19 Using gradient descent and a learning rate of learning rate of α=0.1, compute the new parameter values m and b in Step 1.

$m = 1 - (0.1)(-4) = 1.4$

$b = 0 - (0.1)(-4) = 0.4$

Step	0	1	2	3	4	5	6	7
x	1	2	3	4	1	2	3	4
m	1	1.4	2.12	2.048	2.106	2.134	2.115	2.046
$\partial L/\partial m$	-4	-7.2	0.72	-0.576	-0.288	0.192	0.691	-0.553
b	0	0.4	0.76	0.736	0.75	0.779	0.77	0.747
$\partial L/\partial b$	-4	-3.6	0.24	-0.144	-0.288	0.096	0.23	-0.138
$\hat{y}$	1	3.2	7.12	8.928	2.856	5.048	7.115	8.931
y	3	5	7	9	3	5	7	9
Loss	4	3.24	0.014	0.005	0.021	0.002	0.013	0.005

3.20 Complete a forward pass for Step 7, computing $\hat{y}$ and Loss.

$\hat{y} = 2.046 \cdot 4 + 0.747 = 8.931$

$Loss = (8.931 - 9)^2 = (-0.69)^2 = 0.005$

3.21 For steps 0, 1, and 7, plot the fit line learned by gradient descent on the scatter plot on the previous page. Is the fit improving? Based on the training data, what do you think the "correct" m and b values are? How close does gradient descent get to these values after these 7 steps?

→ yes, fit improves!

→ m = 2, b = 1

→ $\hat{m}$ = 2.046 vs m=2, $\hat{b}$ = 0.747 vs b=1] Not bad for 7 steps!

3.22 One of Marvin Minsky's complaints about backpropagation & gradient descent was that it takes too many steps to converge. Implement gradient descent for this problem in your programming language of choice. How many steps does it take for gradient descent to estimate both model parameters within +/-0.001 of their true values? Can you bring this step count down by increasing the learning rate?

x	y
1	3
2	5
3	7
4	9



$\hat{y} = mx + b$

SINGLE NEURON

$Loss = |\hat{y} - y|$

L1 LOSS

A single artificial neuron is composed of a simple $y=mx+b$ linear model. It's possible to train a single neuron using the same backpropagation and gradient descent approach we use to train models composed of many neurons. In these following exercises we'll train a single neuron to perform a simple linear regression task.

3.23 Complete a "forward pass" for Step 0 in the table on the following page, computing $\hat{y}$ and Loss for the first training example $x=1$, $y=3$.

$\hat{y} = mx+b = 1.1+0 = 1$

$Loss = |\hat{y}-y| = |1-3| = 2$

3.24 Using the chain rule, solve for $\partial L/\partial m$ and $\partial L/\partial b$. Use your results to compute and fill in the missing values for Step 0 in the table on the following page.

$\partial L/\partial m = \frac{\partial |\hat{y}-y|}{\partial m} = \begin{cases} +\partial\hat{y}/\partial m & \text{if } \hat{y}-y>0 \\ -\partial\hat{y}/\partial m & \text{if } \hat{y}-y\leq 0 \end{cases} = \begin{cases} +x & \text{if } \hat{y}-y>0 \\ -x & \text{if } \hat{y}-y\leq 0 \end{cases} = -1 \text{ b/c } \hat{y}-y\leq 0$

$\partial L/\partial b = \begin{cases} +1 & \text{if } \hat{y}-y>0 \\ -1 & \text{else} \end{cases} = -1 \text{ b/c } \hat{y}-y\leq 0$

3.25 Using gradient descent and a learning rate of learning rate of $\alpha=0.1$, compute the new parameter values m and b in Step 1.

$m = 1 - 0.1(-1) = 1.1$

$b = 0 - 0.1(-1) = 0.1$

Step	0	1	2	3	4	5	6	7
x	1	2	3	4	1	2	3	4
m	1	1.1	1.3	1.6	2	2.1	2.3	2
$\partial L/\partial m$	-1	-2	-3	-4	-1	-2	3	-4
b	0	0.1	0.2	0.3	0.4	0.5	0.6	0.5
$\partial L/\partial b$	-1	-1	-1	-1	-1	-1	1	-1
$\hat{y}$	1	2.3	4.1	6.7	2.4	4.7	7.5	8.5
y	3	5	7	9	3	5	7	9
Loss	2	2.74	2.9	2.3	0.6	0.3	0.5	0.5

3.26 Complete a forward pass for Step 7, computing $\hat{y}$ and Loss.

$\hat{y} = 2.4 + 0.5 = 8.5$

$Loss = |8.5 - 9| = 0.5$

3.27 For steps 0, 1, and 7, plot the fit line learned by gradient descent on the scatter plot on the previous page. Is the fit improving? Based on the training data, what do you think the "correct" m and b values are? How close does gradient descent get to these values after these 7 steps?

→ Fit is improving.

→ $\hat{m}=2$, $m=2$] Pretty close!

→ $\hat{b}=0.5$, $b=1$

3.28 Implement gradient descent for this problem in your programming language of choice. How many steps does it take for gradient descent to estimate both model parameters within +/-0.001 of their true values? Can you bring this step count down by increasing the learning rate? How does the convergence rate of L1 Loss compare to the convergence rate of Mean Square Error (MSE) in the previous set of problems?

3.29 The supporting code for this chapter (`github.com/stephencwelch/ai_book`) includes an interactive version of the "Map of Language" as shown in Figure 3.28. Clone and run this example—what clusters do you see? How do these clusters change as our move to earlier/later layers in the model?

4. DEEP LEARNING | EXERCISES

4.1 At the beginning of the Chapter, it seemd like the Universal Approxamation Theorem wasn't really working. What went wrong?

UAT GAURANTEES THAT A SOLUTION EXISTS, BUT NOT THAT WE CAN ACTUALLY FIND IT!

4.2 What advantages do deep models have over wide models?

→ COMPOSING NONLINEAR OPERATIONS

→ POTENTIALLY EXPONENTIAL NUMBER OF REGIONS W/ DEPTH.

4.3 *"Neural networks can learn anything."* What is true, false, and/or misleading about this statement?

MORE PRECISE: "NEURAL NETWORKS CAN REPRESENT ANY CONTINUOUS FUNCTION".

4.4 Is the Universal Approxamation Theorem surprising to you? Why or why not?

OPINION.

4.5 Does the number of regions created by deep networks grow exponentially with the number of layers in practice?

TYPICALLY NO, LOOSE UPPER BOUND.

4.6 Why do we need nonlinear activation functions (e.g. ReLu)? What happens when we remove them?

COLLAPSES INTO SINGLE LAYER!

SEE FIGURE 4.11.

$h_1^{(1)} = \text{ReLU}(m_{11}^{(1)}x_1 + m_{12}^{(1)}x_2 + b_1^{(1)})$
$= \text{ReLU}((2.52)\underline{-0.5} + (-1.02)\underline{-0.5} - 1.24)$
$= \text{ReLU}(-1.99) = 0$

$h_1^{(2)} = m_{11}^{(2)}h_1^{(1)} + m_{12}^{(2)}h_2^{(1)} + b_1^{(2)}$
$= (3.17)\underline{0} + (1.33)\underline{0} - 0.89$
$= -0.89$

(-0.5, -0.5)

$h_2^{(1)} = \text{ReLU}(m_{21}^{(1)}x_1 + m_{22}^{(1)}x_2 + b_2^{(1)})$
$= \text{ReLU}((-1.40)\underline{-0.5} + (2.41)\underline{-0.5} - 0.45)$
$= \text{ReLU}(-0.985) = 0$

$h_2^{(2)} = m_{21}^{(2)}h_1^{(1)} + m_{22}^{(2)}h_2^{(1)} + b_2^{(2)}$
$= (-3.40)\underline{0} + (-1.54)\underline{0} + 0.03$
$= 0.03$

4.7 In Figure 4.14 we saw how Belgium and Netherlands points moved through a trained two layer two neuron network to generate the network's final predictions. Repeat this process here for the Belgium point [-0.5, -0.5]. Fill in the blanks provided below, and show approximately where the point falls on our bent plane geometry, and where the point falls in our the final front view of our bent plane geometry. Does the network classify the point correctly?



$h_1^{(1)} = \text{ReLU}(m_{11}^{(1)}x_1 + m_{12}^{(1)}x_2 + b_1^{(1)})$
$= \text{ReLU}((2.52)\underline{1} + (-1.02)\underline{0} - 1.24)$
$= \text{ReLU}(1.28) = 1.28$

$h_1^{(2)} = m_{11}^{(2)}h_1^{(1)} + m_{12}^{(2)}h_2^{(1)} + b_1^{(2)}$
$= (3.17)\underline{1.28} + (1.33)\underline{0} - 0.89$
$= 3.17$

(1.0, 0)

$h_2^{(1)} = \text{ReLU}(m_{21}^{(1)}x_1 + m_{22}^{(1)}x_2 + b_2^{(1)})$
$= \text{ReLU}((-1.40)\underline{1} + (2.41)\underline{0} - 0.45)$
$= \text{ReLU}(-1.85) = 0$

$h_2^{(2)} = m_{21}^{(2)}h_1^{(1)} + m_{22}^{(2)}h_2^{(1)} + b_2^{(2)}$
$= (-3.40)\underline{1.28} + (-1.54)\underline{0} + 0.03$
$= -4.32$

4.8 In Figure 4.14 we saw how Belgium and Netherlands points moved through a trained two layer two neuron network to generate the network's final predictions. Repeat this process here for the Belgium point [1.0, 0.0]. Fill in the blanks provided below, and show approximately where the point falls on our bent plane geometry, and where the point falls in our the final front view of our bent plane geometry. Does the network classify the point correctly?



$$N_r = \left(\frac{D}{D_i} + 1\right)^{D_i(K-1)} \left(\frac{D^2 + D + 2}{2}\right)$$

Neurons per Layer; Number of (Hidden) Layers; Maximum number of regions; Number of Inputs

ARCHITECTURE	RELEVANT FIGURE	NUMBER OF ACTUAL REGIONS	MAX THEORETICAL REGIONS
	 Figure 4.1	5	$K=1$ $N_r = \left(\frac{3^2+3+2}{2}\right) = 7$
	Figure 4.20	7	$K=1$ $N_r = \left(\frac{4^2+4+2}{2}\right) = 11$
	Figure 4.20	10	$N_r = \left(\frac{2}{2}+1\right)^{2(2-1)}\left(\frac{2^2+2+2}{2}\right)$ $= 16$
	Figure 4.24	102	$N_r = \left(\frac{8}{2}+1\right)^{2(2-1)}\left(\frac{8^2+8+2}{2}\right)$ $= 5^2 \cdot 37 = 925$
	Figure 4.25	430	$N_r = \left(\frac{8}{2}+1\right)^{2(3-1)}\left(\frac{8^2+8+2}{2}\right)$ $= 5^4 \cdot 37 = 23,125$
	Figure 4.26	28,397	$N_r = \left(\frac{8}{2}+1\right)^{2(4-1)}\left(\frac{8^2+8+2}{2}\right)$ $= 5^6 \cdot 37 = 578,125$

4.9 In this Chapter, we explored a number of model architectures, five of these architectures have been placed in the table on the previous page. For each architecture, how many regions did our trained network actually divide our map into? Complete the table be referring back to figures as needed. Is the observed growth in the number of regions appear to be exponential with depth?

LAYERS	2	3	4	5
REGIONS	~~7~~	102	430	28397
		~14x	~4x	~60x

→ DOES FEEL EXPONENTIAL - NOTE THIS IS NOT A THEOREMS ANALYSIS!

4.10. Complete the "max theoretical regions" column in the table on the previous page by plugging into the given formula. How to theoretical and actualy region counts compare?[1]

ACTUAL	5	7	10	102	430	28,397
THEOREMS UPPER BOUND	7	11	16	925	23,125	578,125
				MUCH LARGER!		

4.11 Pull and run `https://github.com/stephencwelch/ai_book /4_deep_learning.ipynb`. Experiment with sections 4.4 (Two layers, three hidden neurons) and 4.5 (Two layers, eight hidden neurons). How sensitive are these models to random seeds, learning rates, and batch size? Do models become less sensitive as they get smaller?

4.12 [Challenge] How few neurons can you use to achieve 99.5%+ accuracy on the Baarle hertog problem? Use `https://github.com/stephencwelch/ai_book /4_deep_learning.ipynb` as a starting point. If you're able to achieve this accuracy using less then 100 neurons, please send your solution to welchlabs.com/contact!

1 Note that the figures shown in the table on the previous page show the tiling of the input plane before we bring the two final surfaces together to form a final decision boundary. Bringing these surfaces togetether technicallly creates more regions - my understanding is that these additional regions would not be included in the in the final theoretical count - but I wasn't able to resolve this question in my experimentation. If the theoretical count should include regions formed by taking the final intesection, this would not dramatically change the agreement between theory and practice here, but it would be worth noting. I would love to see a crisp answer here - if you have one please send to welchlabs.com/contact.

5. ALEXNET | EXERCISES

5.1 How was AlexNet different than most other computer vision approaches to at the time?

END-TO-END LEARNING VS HUMAN DESIGNED FEATURES/ALGORITHMS.

5.2 Figure 5.3 shows how large language models like ChatGPT answer questions. What makes this process inefficient? How might we speed up this process? Chapter 8 will take a close look at this problem.

WE'RE RECOMPUTING/PROCESSING ALL INPUT TOKENS FOR EVERY NEW GENATED TOKEN. ONE SPEED UP OPTION = CACHING OLD RESULTS.

5.3 Why is AlexNet's input data dimension 224x224x3? Why is it's output dimension 1x1000?

224x224x3 => INPUT RGB IMAGE

1x1000 => IMAGENET CLASSES.

5.4 Why is it easier to visualize what's happening in the first layer of AlexNet, compared to other layers?

KERNELS IN FIRST LAYER ARE LITTLE RGB IMAGES!

5.5. Figure 5.10 shows the outputs of the second layer of AlexNet. We found that feature map 104 appears to be a corner detecor - do you see other feature maps that appear to be responding to specific features?



Figure 5.10 | Corner Detector. AlexNet's second layer starts to put together more complicated features. Given this input image of a square piece of paper, feature map 104 (marked with as asterisk) appears to be brining together edge detectors to detect the edges and corners of the paper.



Figure 5.12 | Face Detector. Several activation maps in our fifth layer respond stronly to human faces, even though face and person are not explicit classes in the ImageNet dataset that AlexNet was trained on. Activation map 186 responds particularly strongly to faces, see Figure 5.13 for a closer look.

5.6. Figure 5.12 shows the outputs of the fifth layer of AlexNet. We found that feature map 186 appears to be a face detecor - do you see other feature maps that appear to be responding to specific features?

5.7 What interesting properties did Hinton's team notice about the vectors generated by the second to last layer of AlexNet (Figure 5.15)?

VECTORS FOR RELATED CONCEPTS/IDEAS WERE CLOSE IN THIS VECTOR SPACE!

5.8 What is an activation atlas?

SEE FIGURE 5.16.

5.9 The underlying algorithms for creating and training AlexNet existed long before 2012 - what took so long?

NO SINGLE CORRECT ANSWER, I WOULD SAY IT WAS A RESULT OF A COMBINATION OF: DATA, COMPUTE, PERSISTENCE.

5.10 How many more parameters does GPT-3 have than AlexNet? What about GPT-4?

GPT-3: $\frac{175\times10^9}{60\times10^6}$ → 3000X BIGGER!

GPT-4: $1\times10^{12}/60\times10^6$ → 17000X BIGGER!

5.11 Do you think the next set of AI breakthroughs will be driven by more scaling of existing approaches (i.e. more data, compute), or will fundamentally new ideas be required?

IT REALLY TURN ON THIS ONE!

237

6. NEURAL SCALING | EXERCISES

1. Why do we not expect the curves in FIgure 6.1 to ever reach zero?

THERE IS GENERALLY NO SINGLE CORRECT NEXT WORD/TOKEN, ENTROPY OF NATURAL LANGUAGE.

2. Often, scaling law results are boiled down to something like: *By building larger and larger model and training on more and more data we can achieve more and more intelligent systems.* What is this interpretation missing? What does it get right?

→ SCALE OF PARAMETER/DATA/COMPUTE IS REMARKABLY WELL CORRELATED WITH NEXT TOKEN PREDICTION ERROR.

→ BUT NEXT TOKEN PREDICTION IS NOT NECESSARILY THE SAME THING AS INTELLIGENCE.

3. What is a PetaFLOP/s-day?

1 PetaFLOP = 10^{15} FLOPS

→ 1 PetaFLOP/s·day = $\frac{10^{15}\ \text{FLOPS}}{\text{s}} \cdot \frac{86{,}400\ \text{s}}{1\ \text{day}} =$ 8.64×10^{19} FLOATING POINT OPERATIONS

4. What is *the entropy of natural language?*

THERE IS GENERALLY NO SINGLE "CORRECT" NEXT WORD.

5. According to the Google Deepmind "Chinchilla Scaling" result shown in Figure 6.10, does increasing model size or dataset size have a bigger impact on loss?[1]

N HAS A LARGER EXPONENT, SO IMPACTS LOSS MORE, SO MODEL SIZE MATTERS MORE. BUT, SEE →

[1] The full [Hoffmann et al. 2022] paper takes a deeper look at this question, and finds that model parameters and dataset size should be scaled rougly in the same proportion, while interestingly the OpenAI team's results suggest that parameter count has the bigger impact. Also see "chinchilla's wild implications" by nostalgebraist on lesswrong for a nice deeper dive into chinchilla scaling.

6. What about the GPT-4 scaling plot shown in Figure 6.11 (potentially) so impressive?

HOW CLOSE THE SCALING LAWS CURVE FIT IS TO THE ACTUAL MODEL PERFORMANCE!

7. What is the manifold hypothesis?

DATA LIKE LANGUAGE AND IMAGES LIVE ON LOWER DIMENSIONAL MANIFOLDS IN HIGHER DIMENSIONAL SPACE.

8. What is the cross-entropy of loss of a model that is 50% confident in the correct next token?

$-\ln(0.5) = 0.693$

The scaling theory we saw in Figure 6.2 is based on how spread out our training points on our data manifold. The average distance between training points depends on the number of points D and the dimension of our data manifold d (see Figure 6.25).

9. Does the average distance between our data points increase or decease as we increase the dimension of our data manifold d? Why?

AVERAGE DISTANCE INCREASES AS d INCREASES → MORE VOLUME TO FILL.

10. Assuming a d=10 dimensional data manifold, what percent closer on average do our points get when moving from 10,000 to 1,000,000 training examples?

$\frac{2.51\times10^{-1} - 3.98\times10^{-1}}{3.98\times10^{-1}} \Rightarrow 37\%$ closer.

11. Assuming a d=100 dimensional data manifold, what percent closer on average do our points get when moving from 10,000 to 1,000,000 training examples?

$\frac{9.12\times10^{-1} - 8.71\times10^{-1}}{9.12\times10^{-1}} \Rightarrow 4.5\%$ closer.

12. Compare your results in (10) and (11). How significant is the dimension of the data manifold d? How much data would we need to match the same percentage change in closeness from (10) on a d=100 dimensional data manifold?

MANIFOLD DIMENSION d IS VERY SIGNIFICANT!

$2.51\times10^{-1} = L \cdot D^{-1/100}$

$(0.251)^{-100} = (1 \cdot D^{-1/100})^{-100}$

$D = (0.251)^{-100} = 1.078 \times 10^{60}$ ← THAT'S A LOT OF DATA!

13. If the average distance between training points drives how models improve with dataset size, as posited by the theory presented in this Chapter, and natural language has a large manifold dimension of 42 or 100, how much does moving from D=10^{11} to D=10^{13} training example matter in terms of expected performance improvement?

IF d=100, then average distance goes from $7.76\times10^{-1} \to 7.41\times10^{-1}$. This is a very small change in the average distance. Per Figure 6.20, we raise these values to the $\frac{1}{4}$th power to get cross-entropy bounds, so $0.776^{\frac{1}{4}} = 0.363 \to 0.741^{\frac{1}{4}} = 0.301$. 100x MORE DATA → MODEST IMPROVEMENT IN LOSS.

14. Why is the average distance between points important here? What role does it play in the scaling theory we saw in this chapter?

THE AVERAGE DISTANCE BETWEEN POINTS CONTROLS THE RESOLUTION WE CAN RESOLVE THE DATA MANIFOLD AT.

7. EXERCISES

1. Neural networks are often called "black box" models. Why is it difficult to understand how neural networks, such as modern langague models, work?

ENORMOUS NUMBER OF MATRIX MULTIPLIES WITH LEARNED WEIGHT VALUES.

2. What is the residual stream?

A MATRIX THAT GETS ADDED TO BY EACH LAYER. ROUGH ANALOGY: "WORKING MEMORY".

3. Why do langauge models typically not just always pick the most probable next token when generating text?

LEADS TO REPEATING OR UNINTERESTING OUTPUTS.

4. Smaller or poorly trained langauge models sometimes run into issues of just repeating tokens. (e.g. "The reliability of Wikipedia is very *very*"). Why might this happen?

IF THE MODEL MAKES NO CHANGE TO THE FINAL POSITION IN THE RESIDUAL STREAM, THE FINAL TOKEN JUST GETS REPEATED.

5. Why is understanding and controlling language models using individual neurons problematic?

POLYSEMANTICITY. SEE FIGURE 7.11

6. How do sparse autoencoders help us deal with polysemanticity?

BY FIGURING OUT WHICH COMBINATIONS OF NEURONS MAP TO SINGLE CONCEPTS/ FEATURES.

7. After training a sparse autocencoder, why do we now know what concept a given feature corresponds to? How can we find out?

TESTING WITH A VARIETY OF INPUTS, AND SEEING WHAT INPUTS LEAD TO THE HIGHEST FEATURE VALUE.

8. As langauge models become a larger part of our world, how important do you think explainability will be?

OPEN ENDED / OPINION.

9. The general approach of Mechanistic Intpretability has made some impressive progress in recent years, but s arguable still quite limited. Do you think approachs like the sparse autoencoder we saw in this chapter will be able to give us the level of control and understanding of LLMs we would want?

PERSONALLY I REMAIN SKEPTICAL - LLMS ARE SO COMPLEX! BUT WE ARE MAKING IMPRESSIVE PROGRESS.

10. In Figure 7.13, we explored feature autoencoder Feture 8249, but there are other strongly activating features including: 7344, 8353, 16286, 13821, 11987, 11622, 11279, 14440, 3827. Use Neuronpedia to explore these features, what do you observe?

neuronpedia.org/gemma-2-2b/20-gem-mascope-mlp-16k/7344

7344 → THE WORD "VERY"

8353 → THE WORD "VERY"

16286 → SUPERLATIVES → VERY, HIGHLY, ALWAYS

13821 → MANY/VERY

11987 → "QUITE", IN NEGATIVE CONTEXTS

11622 → POSITIVE CONTEXTS, "IS/WAS"

11279 → ?

14990 → MORE/MUST 3827 → "VERY"

8. ATTENTION | EXERCISES

8.1 Conceptually, why do attention layers use multiple attention heads?

HEADS CAN SPECIALIZE IN DIFFERENT CONCEPTS/PATTERNS (e.g. ADJECTIVES, PREVIOUS TOKENS)

8.2 How do attention heads capure/measure the similiarity between key and query vectors?

DOT PRODUCT

8.3 How are keys and queries in attention layers different than keys and queries in information retrieval systems like databases? Do you think "key" and "query" are helpful names for these vectors?

IN ATTENTION LAYERS, KEYS AND QUERIES ARE MUCH MORE APPROXIMATE/LOOSE. NOT BAD NAMES, BUT CAN BE MISLEADING!

8.4 As we saw in Chapter 3, the transformer architecture is composed of alternating fully connected/multi-layer perceptron layers and attention layers. Compare and contrast these different types of neural network layers.

MLP: SIMPLER, FIXED WEIGHTS

ATTENTION: MORE COMPLEX, WEIGHTS ARE (SOFTMAX) CONTROLLED BY THE DATA

8.5 Without caching, attention block compute grows quadratically with the number of input tokens—why?

BECAUSE WE HAVE TO COMPUTE PAIRWISE DOT PRODUCTS BETWEEN ALL INPUT TOKENS.

8.6 In KV caching, why don't we cache our value matrices? Why do we only store keys and values?

SEE FIGURE 8.10. BECAUSE THE UPPER RIGHT CORNER OF OUR ATTENTION HEAD IS MASKED OUT, WE ONLY END UP NEEDING THE FINAL/NEW ROW OF Q.

8.7 Why would Multi-Query Attention (MQA) reduce algorithmic performance (e.g. worse error rate)?

FORCES ALL ATTENTION HEADS IN A LAYER TO SHARE THE SAME KEYS AND VALUES.

8.8 Here's a closer look at one of the attention patterns from Figure 8.1. What might this attention pattern be doing?



FOCUSING ON THE CURRENT/LATEST TOKEN, WITH THE INTERESTING EXCEPTION OF THE COMMAS.

8.9 Here's a closer look at one of the attention patterns from Figure 8.1. What might this attention pattern be doing?



FOCUSING ON THE PREVIOUS TOKEN.

8.10 `ai_book/exercises/8_attention_exercises.ipynb` contains code to generate GPT-2 attention patterns. Run this notebook and experiment with different input text. Are you able to find similiar modifier examples like our "American flag" example? What other patterns to you come across?

SUPPORTING CODE

Full supporting code for this chapter at:
`github.com/stephencwelch/ai_book`

8.11

$$\underset{(10\times128)}{Q}\cdot\underset{(128\times10)}{K^T} = \underset{(10\times128)}{Q}\cdot\left(\underset{(10\times576)}{L_{KV}}\cdot\underset{(576\times128)}{W_{VK}}\right)^T$$

$$= \left(\underset{(10\times7168)}{X}\cdot\underset{(7168\times128)}{W_Q}\right)\cdot\left(\underset{(10\times576)}{L_{KV}}\cdot\underset{(576\times128)}{W_{VK}}\right)^T$$

$$= \left(\underset{(10\times7168)}{X}\cdot\underset{(7168\times128)}{W_Q}\right)\cdot\left(\underset{(128\times576)}{W_{VK}^T}\cdot\underset{(576\times10)}{L_{KV}^T}\right)$$

$$= \underset{(10\times7168)}{X}\cdot\underbrace{\left(\underset{(7168\times128)}{W_Q}\cdot\underset{(128\times576)}{W_{VK}^T}\right)}_{7168\times576}\cdot\underset{(576\times10)}{L_{KV}^T}$$

8.12

$$\underset{(10\times7168)}{U_1} = \underset{(10\times128)}{O}\cdot\underset{(128\times7168)}{W_O}$$

$$= \underset{(10\times10)}{(A}\cdot\underset{(10\times128)}{V)}\cdot\underset{(128\times7168)}{W_O}$$

$$= \left(\underset{(10\times10)}{A}\cdot\underset{(10\times576)}{L_{KV}}\cdot\underset{(576\times128)}{W_{VV}}\right)\cdot\underset{(128\times7168)}{W_O}$$

$$= \underset{(10\times10)}{(A}\cdot\underset{(10\times576)}{L_{KV}}\cdot\underbrace{\left(\underset{(576\times128)}{W_{VV}}\cdot\underset{(128\times7168)}{W_O}\right)}_{576\times7168}$$

9. DIFFUSION | EXERCISES

9.1 How does CLIP learn a shared representation between text and images?

→ USES 2 MODELS: TEXT ENCODER, IMAGE ENCODER

→ LEARNS TO MAXIMIZE SIMILARITY BETWEEN MATCHING IMAGES AND CAPTIONS, WHILE MINIMIZING SIMILARITY BETWEEN NON-MATCHING PAIRS.

9.2 What is potentially surprising about the results presented in Figure 9.8?

CLIP HAS LEARNED A "SPACE OF CONCEPTS/IDEAS", WHERE REMOVING A HAT IS LITERALLY MAPPED TO SUBTRACTING VECTORS.

9.3 What's wrong with the picture of diffusion presented in Figure 9.10?

① LEARNING TO REMOVE NOISE ONE STEP AT A TIME DOES NOT WORK WELL.

② JUST PASSING OUR IMAGE AGAIN AND AGAIN INTO OUR MODEL OFTEN LEADS TO BLURRY IMAGES. (FIG 9.12)

9.4 What is the connection between diffusion models and Brownian motion?

PROGRESSIVELY ADDING NOISE TO IMAGES OR VIDEO = GOING ON A RANDOM WALK IN HIGH DIMENSIONAL SPACE. DIFFUSION MODELS LEARN TO REVERSE THIS PROCESS.

9.5 Why is more effective in practice to have our model learn to reverse the net/total motion of the random walk instead of a single step (Figure 9.18)?

WE CAN SHOW THAT THESE LEARNING TARGETS ARE EQUIVALENT (IN EXPECTATION, FIG 9.18), BUT THE ACTUAL TRAINING EXAMPLES WE SEE WHEN REVERSING THE FULL WALK HAVE LOWER VARIANCE → EASIER TO LEARN.

9.6 Why is it helpful to condition diffusion models on the number of elapes steps/time in the diffusion process?

TARGET FUNCTION LOOKS VERY DIFFERENT AS POINTS MOVE FURTHER FROM THEIR STARTING POSITIONS.

9.7 In the DDPM image generation process, why is it helpful to add random noise after each step?

→ PREVENTS ALL POINTS FROM BEING PUSHED TO THE AVERAGE/MEAN (FIG 9.24)

→ FALLS OUT OF THEORY – "SAMPLING THE REVERSE DISTRIBUTION" (FIG 9.26)

9.8 Compare and constast DDPM and DDIM generation methods.

DDPM	DDIM
→ STOCHASTIC	→ DETERMINISTIC
→ MORE COMPUTE/STEPS	→ LESS COMPUTE/STEPS
→ HIGH QUALITY IMAGES/VIDEO	→ HIGH QUALITY IMAGES/VIDEO

9.9 Why might conditioning alone not be sufficient to control our image/video generation process via text inputs?

ONE WAY TO THINK ABOUT CONDITIONING IS JUST "GIVING THE MODEL ACCESS" TO THE TEXT/PROMPT. WE DON'T HAVE DIRECT CONTROL OVER HOW MUCH THE MODEL ACTUALLY USES THE TEXT/PROMPT.

9.10 How does classifier-free guidance give us more control over the generation process?

COMPUTES DIFFERENCE BETWEEN PROMPTED AND UNPROMPTED MODEL AND AMPLIFIES THE DIFFERENCE, MOVING THE RESULTS MORE "IN THE DIRECTION" OF THE PROMPT.

9.11 In many previous Chapters of this book, we considered autoregressive models (e.g. language models that predict a single token at time). Compare and contrast diffusion and autoreggression.

DIFFUSION	AUTOREGRESSION
→ BREAKS DOWN OVERALL PROBLEM INTO SMALLER STEPS	→ BREAKS OVERALL PROBLEM INTO SMALL STEPS (TOKENS)
→ PREDICTS FULL RESULT (IMAGE/VIDEO), THEN ITERATIVELY REFINES.	→ PREDICTS ONE PIECE/TOKEN AT A TIME.

9.12a Consider the vectors A=[4 1], B=[1 4]. Using trigonometry, find the angles between A and the x-axis θ_A, and B and the x-axis θ_B.

$\theta_A = \tan^{-1}\left(\frac{1}{4}\right) = 14.04°$

$\theta_B = \tan^{-1}\left(\frac{4}{1}\right) = 75.96°$



9.12b Compute the angle between vectors θ_B-θ_A.

$\theta_B - \theta_A = 75.96° - 14.04°$

$= 61.92°$

$$\text{Cosine Similarity} = \frac{A \cdot B}{||A||_2||B||_2} = \cos(\theta)$$

$$||A||_2 = \sqrt{A_1^2 + A_2^2 + \ldots + A_n^2}$$

9.12c Compute the cosine similiarity between A and B using the formula given in the figure to the right. Does your result match your results from 9.12b?

$$\frac{A \cdot B}{||A||_2||B||_2} = \frac{4 \cdot 1 + 1 \cdot 4}{\sqrt{4^2+1^2}\sqrt{1^2+4^2}} = \frac{8}{\sqrt{17}\sqrt{17}} = \frac{8}{17}$$

$\theta = \tan^{-1}\left(\frac{8}{17}\right) = 61.93°$ ✓



9.13a Consider the vectors A=[4 1], B=[-1 4]. Using trigonometry, find the angles between A and the x-axis θ_A, and B and the x-axis θ_B. Plot on the figure to the left.

$\theta_A = \tan^{-1}\left(\frac{1}{4}\right) = 14.04°$

$\theta_B = \tan^{-1}\left(\frac{4}{-1}\right) = 104.04°$

9.12b Compute the angle between vectors θ_B-θ_A.

$\theta_B - \theta_A = 104.04° - 14.04°$

$= 90°$

9.12c Compute the cosine similiarity between A and B using the formula given in the figure to the right. Does your result match your results from 9.13b?

$$\frac{A \cdot B}{||A||_2||B||_2} = \frac{4 \cdot -1 + 1 \cdot 4}{\sqrt{4^2+1^2}\sqrt{1^2+4^2}} = \frac{-4+4}{\sqrt{17}\sqrt{17}} = \frac{0}{17}$$

$\cos^{-1}(0) = 90°$ ✓



9.13 The cosine similarities shown in Figures 9.8 and 9.9 have maximum values of 0.1652 and 0.2784, respectively. Given that the cosine similarity metric has a maxium value of cos(0)=1, these values may seem small. Let's explore this idea. The histograms above show how the cosine similarity between random vectors changes as we increase the dimension of our vectors. In each subplot, we're randomly choosing a reference vector, measuring its cosine similarity to 5000 other ranomly chosen vectors of the same dimension, and plotting a histogram of the results. As we can see, this distributions change significantly as we increase the dimension of our vectors. What trend do you notice? What does this tell us about our resutls in Figures 9.8 and 9.9? What does this tell us in general about the angle between two randomly chosen vectors in high dimensional space?

→ AS THE DIMENSION (LENGTH) OF OUR VECTORS INCREASES, THE COSINE SIMILARITY BETWEEN TWO RANDOMLY CHOSEN VECTORS → 0.

→ FOR THE CLIP EXAMPLES IN THIS CHAPTER (D=512), ~0.2 IS ACTUALLY A FAIRLY LARGE VALUE, COSINE SIMILARITIES > 0.2 ARE VERY RARE!

→ MOST VECTORS IN THE HIGH DIMENSIONAL SPACE ARE CLOSE TO ORTHOGONAL.